


# M-VAVE

## USER MANUAL



OVERDRIVE-AMP

- **Website:** [www.m-vave.com](http://www.m-vave.com)
- **CubeSuite for Windows/Mac OS:** <http://www.m-vave.com/appdownload>
- **CubeSuite for Android/iOS:** scan the QR code



## Preface

Thank you for purchasing the OVERDRIVE-AMP. This product is designed for whom like overdrive timbre of vacuum tube AMP. We do our best to develop this pedal, I hope you like it.

## Attentions

### ■ The power supply:

Please use 9V(+/-10%) adapter (negative inside and positive outside), otherwise it may cause equipment damage. Please unplug the power when not in use or during thunderstorm weather.

### ■ The connection:

Be sure to turn off the power of related equipment before connecting or disconnecting the device.

### ■ The electrical interference:

The electromagnetic wave of radio, television and other equipment may cause interference to the equipment, so please try to stay away from radio, television and other equipment.

### ■ The location:


To avoid deformation, discoloration, or other serious damage, do not expose this unit to the following conditions:

- a. Heat sources
- b. Magnetic fields
- c. Sunlight
- d. High temperature or moist district
- e. Excessively dusty or dirty locations
- f. Strong vibrations or shocks

## Features

- This product is a compact metal appearance design.
- The timbre of product will tend to a dynamic vacuum tube AMP.
- Real bypass.
- This pedal will let you get natural timbre, also it has dynamic response.

## Control panel instruction



### ①Power jack

Please use 9V DC adapter (negative inside and positive outside).

### ②USB jack

Support power supply, suggest to use 5V 1A adapter.

### ③LEVEL knob

Adjust the output volume by turning the LEVEL knob.

### ④TONE knob

Adjust the brightness by turning the TONE knob.

### ⑤GAIN knob

Adjust gain by turning the GAIN knob.

### ⑥Output jack

1/4" MONO audio output jack to connect mixer or speaker.

### ⑦LED

The LED lights up when the effect pedal is enabled, or goes out in bypass mode.

### ⑧Input jack

1/4" MONO audio input jack to connect instrument.

### ⑨Footswitch

Enable/bypass the OVERDRIVE-AMP by tap the footswitch.

## Technical parameter

|                |                               |
|----------------|-------------------------------|
| Input          | Standard 1/4" jack-MONO/TS    |
| Output         | Standard 1/4" jack-MONO/TS    |
| Power supply 1 | DC9V≥300mA ⏻⏻⏻                |
| Power supply 2 | USB 5V≥300mA                  |
| Size           | 90mm(L) x 40mm(W) x 34.5mm(H) |
| Weight         | 221g                          |

Disclaimer: Specifications are subject to change without notice.