


USER MANUAL



MINI LOOPER

- **Website:** www.m-vave.com
- **CubeSuite for Windows/Mac OS:** <http://www.m-vave.com/appdownload>
- **CubeSuite for Android/iOS:** scan the QR code



Preface

This Mini Looper Pedal is designed for recording , playback and overdubbing for musical instruments such as guitar, bass, vocal and electric drum,etc.It provides unlimited times overdubbing for up to 5 minutes recording, It can export/import WAV files to computer by USB cable.

Attentions

■ The power supply:

Please use 9V(+/-10%) adapter (negative inside and positive outside), otherwise it may cause equipment damage. Please unplug the power when not in use or during thunderstorm weather.

■ The connection:

Be sure to turn off the power of related equipment before connecting or disconnecting the device.

■ The electrical interference:

The electromagnetic wave of radio, television and other equipment may cause interference to the equipment, so please try to stay away from radio , television and other equipment.

■ The location:


To avoid deformation, discoloration, or other serious damage, do not expose this unit to the following conditions:

- a. Heat sources
- b. Magnetic fields
- c. Sunlight
- d. High temperature or moist district
- e. Excessively dusty or dirty locations
- f. Strong vibrations or shocks

Features

- This product is a compact metal appearance design.
- Unlimited times overdubbing for up to 5 minutes recording.
- It can undo and redo last overdub audio unlimited times.
- One footswitch to control all LOOP functions: record, play, stop, overdub, undo, redo, delete, etc.
- When the power is turned off suddenly,it will store the recording automatically.
- It can export/import WAV files to computer.

Control panel instruction



①Power jack

Please use 9V DC adapter (negative inside and positive outside).

②USB jack

Support USB data transmission; Support power supply; suggest to use 5V 1A adapter.

③LOOP volume knob

Adjust the LOOP playing volume.

④Output jack

1/4" MONO audio output jack to connect mixer or speaker.

⑤LED

It's a loop status indicator; it shows the current operating status of the Looper.

⑥Input jack

1/4" MONO audio input jack to connect instrument.

⑦Footswitch

The footswitch can control functions of the LOOP, please look the list below.

Status and functional operation of the LOOP

Operation (the LOOP footswitch)	Function/ state	LOOP status indicator
Power on(no data)	Empty	None
Power on(with data)	Stop	Green flash
Tap footswitch(no data)	Record	Red light up
Tap footswitch when recording/overdubbing	Play	Green light up,flash once cycle
Tap footswitch when playing	Overdub	Red light up,flash once cycle
Hold footswitch when playing/recording/overdubbing	Undo/ redo(last layer)	Green flash fast
Double tap footswitch when playing/ recording /overdubbing	Stop	Green flash
Hold footswitch when stopping	Delete	None

Technical parameter

Input	Standard 1/4"jack-MONO/TS
Output	Standard 1/4"jack-MONO/TS
Maximum recording duration	5 minutes
Maximum times of overdubbing	Unlimited layers
Sampling rate	48K/24bit
Size	90mm(L) x 40mm(W) x 34.5mm(H)
Power supply 1	DC9V $\geq$ 300mA  
Power supply 2	USB 5V $\geq$ 300mA
USB type	Micro USB

Disclaimer: Specifications are subject to change without notice.