

AgentDNA Dashboard

Backend Data Inventory — What's Available vs. What's Shown

A field-level audit of every read-facing dashboard API endpoint (/dashboard/v1/*), the data each one currently returns to the frontend, and backend data that is already fetched from the database but dropped before reaching the JSON response.

Repository	agentdna-middleware
Scope	All GET /dashboard/v1/* endpoints (router/router.go, handler/handler.go)
Generated for	hari@rubix.net

1. Home / Overview

GET /home-metrics — HomeMetrics

Landing-page KPI summary (org-wide for admins, own-scope for users).

- agentCount, intentCount, interactionsCount, threatCount
- agentCount24hChange, intentCount24hChange, interactionsCount24hChange, threatCount24hChange
- agentList[] (top 5): agentName, agentID, totalInteractions, totalThreats
- flowEnabled (derived boolean)

GET /agent-metrics — AgentMetrics

Best / worst performing agents leaderboard.

- agentCount, interactionCount, threatCount
- bestPerformingAgents[] / worstPerformingAgents[]: agentName, agentID, totalInteractions, totalThreats
- bestPage, worstPage, pageSize

GET /agents-apps-metrics — AgentsAppsMetrics

Combined agents + apps overview widget.

- topAgents[]: name, totalInteractions, totalThreats
- topApps[]: name, totalInteractions, totalThreats
- metrics: totalInteractions, totalThreats, totalAgents, totalApps, avgReliability

GET /interactions/series?range=24h|7d — InteractionSeries

Time-bucketed chart series of safe vs. threat interaction volume.

- safe[] (int array), threats[] (int array) — parallel bucketed arrays

GET /global-stats (public, no auth) — GlobalStats

Platform-wide totals across all organizations.

- totalUsers, totalAgents, totalInteractions, totalIntents, totalThreats

2. Profile

GET /user-profile — UserProfile

Logged-in org user's own profile.

- name, email, apiKey, organizationID, createdAt, adminEmail

GET /admin-profile — AdminProfile

Logged-in admin's own profile + org counters.

- name, email, organizationID, apiKey, agentCount, intentCount, threatCount, totalUsers, createdAt

3. Agents

GET /agents-list — AgentsList

Paginated agent roster (admin: org-wide, user: own agents).

- agentsList[]: agentID, agentName, createdAt, deployer, policy, totalInteractions, totalThreats, score

- total, page, pageSize, totalPages
- ■ does not include revoked status (see Gaps, item 4)

GET /agent-info?agentDID= — AgentInfo

Single-agent detail panel.

- agentDID, agentName, createdAt, deployerDID, deployerName, policy, orgID
- totalInteractions, totalThreats, score, revoked
- appsInteracted (count), appsList[] (tool names/DIDs contacted)

GET /agent-interactions?agentDID= — AgentInteractions

Paginated interaction log for one agent.

- interactionsList[]: interactionID, from, fromName, to, toName, type, direction, threat, threatID, intentID, time, message
- total, page, pageSize, totalPages

GET /agent-intents?agentDID= — AgentIntents

Paginated intents initiated by / involving one agent (shared buildIntentList — see Section 6 for full field list).

GET /agent-lhi-scores?agentDID= — AgentLHIScores

Proxies cbac-service; agent's trust-edge scores per callee.

- agentDID, scores[]: callee_name, callee_type, mcp_did, intent_score, policy_score, hallucination_score, trust, created_at

GET /tool-agent-scores?toolDID= — ToolAgentScores

LHI scores of every agent that has contacted a given tool.

- toolDID, toolName, agents[]: agentDID, agentName, intentScore, policyScore, hallucinationScore, trust

GET /agents-creation-requests-list[-user] — AgentsCreationRequestsList[User]

Pending/approved “create agent” requests queue.

- requestsList[]: requestID, requestType, policy, creatorDID, agentDID, agentName, requestInfo, status, createdAt
- total, page, pageSize, totalPages

GET /agent-access-requests-list-org / -list-user — AgentAccessRequestsListOrg/User

Same shape as creation requests (shared buildRequestList), for agent_access request type.

GET /agent-policy?agentDID= — GetAgentPolicy

Current policy document text for an agent.

- agentDID, policy (raw text)

GET /agent-policy-history?agentDID= — GetAgentPolicyHistory

On-chain policy update history.

- agentDID, nftID, history[]: updateID, time (epoch)

GET /agent-policy-update?agentDID=&updateID;= — GetAgentPolicyUpdate

Full decoded policy text for one historical update.

- updateID, time, policy (decoded text)

4. Users

GET /users-list — UsersList

Paginated org user roster (admin view).

- usersList[]: userID, userName, createdAt, totalIntents, totalThreats, accessAgentCount
- total, page, pageSize, totalPages

GET /user-info?userID= — UserInfo

Single-user detail page with nested paginated sub-resources.

- user: userID, userName, displayName, createdAt, lastActive, isActive, accessAgentCount, totalInteractions, totalThreats, totalIntents, totalAgentsDeployed
- interactions.list[]: interactionID, from, fromName, to, toName, type, threat, threatID, intentID, message, signature, provenanceRecordID, time (+ pagination)
- intents.list[]: full intent fields, see buildIntentList (+ pagination)
- threats.list[]: interactionID, from, fromName, to, toName, type, threat, intentID, message, signature, provenanceRecordID, time (+ pagination)
- agents.list[]: agentDID, agentName, status (derived), created (epoch), totalInteractions, totalThreats (+ pagination)

GET /user-intents — UserIntents

Paginated intents initiated by the logged-in user (buildIntentList shape).

GET /user-policy — GetUserPolicy

Logged-in user's own policy document.

- policy (raw text)

5. Intents

GET /intent-list — IntentList

Paginated intent list (admin: org-wide, user: own). Shared buildIntentList.

- Per intent: intentID, title (truncated to 5 words), initiatorDID, initiatorName, startedAt, status, reviewStatus,
- threatDetected, flowType, executor, chainDepth, interactionsCount, agentsCount, toolsCount, threatCount,
- firstInteractionAt, lastInteractionAt, runtimeSeconds, endedAt (if set)
- total, page, pageSize, totalPages

GET /intent-info?intentID= — IntentInfo

Single-intent detail with full interaction transcript.

- intentID, initiatorDID, initiatorName, startedAt, status, reviewStatus, threatDetected, flowType, executor,
- chainDepth, interactionsCount, agentsCount, toolsCount, firstInteractionAt, lastInteractionAt, runtimeSeconds,
- provenanceRecordID, endedAt (if set)
- interactions[]: interactionID, from, fromName, to, toName, type, direction, threat, threatID, time, message,
- signature, provenanceReqID, provenanceRecordID

GET /intent-diagram?intentID= — IntentDiagram

Flow-diagram view of one intent.

- basicInfo: intentID, initiatorDID, initiatorName, flowType, status, threatDetected, chainDepth,
- interactionsCount, agentsCount, toolsCount, startedAt ■ drops reviewStatus & executor (see Gaps, item 6)
- interactions[]: interactionID, initiator, initiatorName, to, toName, type, message, intentID, threat, threatID,
- epoch, signature, provenanceReqID, provenanceRecordID

GET /intent-block-data?intent_id= — GetIntentBlockData

Nested block-chain structure for one intent — agent hop-by-hop trace.

- Per block: id, block_index, block_type, from{did,name,type}, to{did,name,type}, message, signature,
- threat_detected, trust_issues[], created_at, parent_block (recursive)
- ■ drops response, delegate_to, received_from, cbac_app, cbac_decision (see Gaps, item 2)

GET /intent-raw-data?intent_id= — GetIntentRawData

Raw JSON payload per block, for debugging/inspection.

- []{ block_index, raw_data } — opaque JSON blob per block

6. Interactions

GET /interactions-list — InteractionsList

Paginated global interaction feed (org/user scoped, optional intentID filter).

- interactionList[]: interactionID, from, fromName, to, toName, type, direction, threat, threatID, intentID, time, message
- total, page, pageSize, totalPages
- ■ threat is a bare bool — resolved threatCode/threatTitle not included (see Gaps, notes)

7. Threats

GET /threats-list — ThreatsList

Paginated threat-flagged interactions (org/user scoped).

- threatsList[]: interactionID, from, fromName, to, toName, type, direction, threat, threatID, threatCode,
- threatTitle, intentID, reviewStatus, time, message
- total, page, pageSize, totalPages

GET /threat-events — ThreatEvents

Paginated raw threat log (from threats table).

- threats[]: id, intent_id, interaction_id, time, threat_code, message
- total, page, limit

GET /threat-by-id?threat_id= — ThreatByID

Single threat record + resolved code metadata.

- id, intent_id, interaction_id, time, threat_code, message, title, description

GET /threat-detail?threat_code= — ThreatDetail

All occurrences of a given threat code.

- threat_code, title, description, count, threats[]: id, intent_id, interaction_id, time, message

GET /top-threats — TopThreats

Top 5 threat codes by frequency (chart/leaderboard).

- []{ threat_code, title, count } — array is the top-level data payload

GET /top-threat-agents — TopThreatAgents

Paginated leaderboard of agents ranked by threat count.

- agentsList[]: agentDID, agentName, totalInteractions, totalThreats
- total, page, pageSize, totalPages

8. Tools / Apps

GET /tools-list — *ToolsList*

Paginated tool/app roster.

- toolsList[]: toolDID, toolName, totalInteractions, totalThreats, totalIntents, score
- total, page, pageSize, totalPages
- ■ lastInteractedAt fetched by ToolInfo but not by this list query (see Gaps, item 3)

GET /tool-info?toolDID=|name= — *ToolInfo*

Single-tool detail with nested paginated sub-resources.

- toolDID, toolName, totalInteractions, totalThreats, totalIntents, totalAgents, score, lastInteractedAt
- interactions.list[]: same interaction fields as elsewhere (+ pagination)
- intents.list[]: full intent fields via buildIntentList (+ pagination)

9. Search

GET /search?q= — *Search*

Global search across agents / apps / intents.

- agents[]: did, name, orgID
- apps[]: did, name
- intents[]: intentID, flowType, status, threatDetected, startedAt

Backend Data Fetched, But Not Shown on the Frontend

These are fields the database queries already fetch into a Go struct, but that get dropped before the handler builds its JSON response. Each is a candidate to surface with no new query needed — just a field added to the response.

1. Agent NFT ID never shown on leaderboards

AgentVolumeRecord.AgentNFTID is fetched by GetTopAgentsByOrg / GetTopAgentsByUser / GetBottomAgentsByOrg / GetTopThreatAgentsByOrg (db/service.go), but every consumer (HomeMetrics agentList, AgentMetrics best/worst lists, TopThreatAgents) drops it before the JSON is built.

2. CBAC decision & delegation hidden in the block-diagram view

GetIntentBlocksByIntent (db/service.go) fetches Response, DelegateTo, ReceivedFrom, CbacApp and CbacDecision per block, but GetIntentBlockData (handler.go) never copies them into blockOut. The allow/deny decision and which app/agent a step delegated to is only visible via the separate, unstructured /intent-raw-data endpoint.

3. Tools list has no “last active” column

GetToolsByOrg (used by ToolsList) only scans did, name, total_interactions, total_threats, total_intents, score — it never selects last_interacted_at, even though GetToolByNameOrDID (used by ToolInfo) does. The tools table can't show recency without an extra per-row call.

4. Agents list has no revoked status

GetAgentInfo (single-agent) surfaces revoked, but GetAgentsByOrg / GetAgentsByUser (used by the paginated AgentsList table) don't select new_agents.revoked at all — the grid can't flag a revoked agent inline.

5. Full intent title is never returned

IntentRecord.Title is always truncated to 5 words by firstNWords() in buildIntentList. No list or detail endpoint returns the untruncated title, even though it's in the DB record.

6. Intent diagram drops reviewStatus and executor

GetIntentInfo fetches ReviewStatus and Executor (and IntentInfo returns both), but IntentDiagram's basicInfo omits both — so the human-triage state (Ongoing / Acknowledged / Flagged) isn't visible on the diagram view.

7. Request queues never expose orgID

buildRequestList (shared by creation-requests and access-requests endpoints) never includes orgID in its rows, though the underlying query is org-scoped.

8. Per-tool LHI scores have no timestamp

ToolAgentScores copies only IntentScore / PolicyScore / HallucinationScore / Trust from each LHIScoreEntry, discarding CreatedAt — so the per-tool score view can't show when a score was last computed (AgentLHIScores, by contrast, returns the whole entry including CreatedAt).

9. AgentMetrics drops the 24h-change deltas

GetOrgMetrics returns AgentCount24hChange / IntentCount24hChange / InteractionsCount24hChange / ThreatCount24hChange. HomeMetrics surfaces all four; AgentMetrics calls the same struct but only reads AgentCount / InteractionsCount / ThreatCount, silently dropping the deltas.

Additional scope notes

- Threat context requires a second call: plain interaction lists (InteractionsList, AgentInteractions, and the interaction sub-lists on UserInfo/ToolInfo) only return threat (bool) and threatID — the resolved threatCode/threatTitle join used by ThreatsList is never applied there, so the UI needs a follow-up /threat-by-id call to explain why something was flagged.
- No endpoint returns new_agents.nft_id directly — it's used internally by agent-policy-history's on-chain lookup but never returned in the response.

Key files: handler/handler.go (all handlers) · router/router.go (route registration) · db/db.go (struct defs) · db/service.go (query implementations)