Misalignment Cartography: Evaluation Metric, Not Intervention Granularity or Model Scale, Decides Where Null Results Fall in a Sycophancy Multiverse

NeuriCo

Abstract

Alignment papers often report that an intervention "did nothing" to an unwanted behavior. Readers take such null results either as evidence that the behavior is robust or as a failed experiment, and it is rarely clear which reading is right. We ask how much of a null is decided by experimental design before any data are collected. We run eleven interventions against sycophancy (prompt instructions, all-layer direction ablation, single-layer steering, and attention-head ablation, each with a placebo) on four QWEN2.5-INSTRUCT models from 0.5B to 7B parameters over the same 240 items. We then analyze each of the 44 model–intervention pairs as 16,000 resampled studies that vary the evaluation metric and the sample size, which gives a 704-cell map of how often a study returns $p \geq .05$. Metric choice is the dominant axis: with model, intervention, and items held fixed, the null rate is 0.81 for a sampled answer, 0.80 for the greedy answer, 0.52 for answer probability, and 0.25 for the logit margin. Metric explains 32% of the variance in null rate across cells, against 10% for sample size, 5% for model, and 2% for intervention granularity. However, most nulls are not missed behavioral effects. Only 14% of nulls from non-placebo interventions come from interventions that demonstrably change answers; 80% come from interventions that shift the answer logits without reliably flipping answers. A null on an answer-level metric and a null on a logit-level metric are therefore different claims, and a report of a null should say which one it makes.

1 Introduction

"The intervention did not change the behavior" is one of the most common sentences in alignment research, and one of the hardest to interpret. A steering vector that leaves outputs unchanged, a system prompt that fails to reduce sycophancy, an ablation with no measurable effect: each of these is a null result, and each is read in two opposite ways. One reading says the behavior is robust to this kind of intervention. The other says the experiment failed to detect something that was there. The two readings lead to opposite safety conclusions, so it matters which one the evidence supports.

A null result is the joint product of a model and an experimental design. The same intervention on the same model can be scored by whether the sampled answer changes, whether the most likely answer changes, or whether the answer logits move; it can be tested on 20 items or 200. If these choices largely fix whether a study returns a null, then a null says less about the model than it appears to. Other fields have met this problem before. Multiverse and specification-curve analyses in psychology run every defensible analysis of one dataset and report how the conclusion varies Steegen et al. [2016], Simonsohn et al. [2020]. Work on evaluation statistics for language models addresses sample size and variance Miller [2024], Card et al. [2020], and work on steering vectors shows that their effects vary widely across inputs Tan et al. [2024]. However, we know of no study that takes one fixed set of alignment interventions through a full grid of design choices and maps where the nulls fall.

39th Conference on Neural Information Processing Systems (NeurIPS 2025).

We build such a map for one behavior, sycophancy (see figure 1). We run eleven interventions at four levels of granularity (prompt, all-layer activation, single-layer activation, and attention head), including a placebo at each level, on four QWEN2.5-INSTRUCT models from 0.5B to 7B parameters Qwen Team [2024], using the same 240 evaluation items from the model-written sycophancy evaluations Perez et al. [2022]. We then treat each of the 44 model–intervention pairs as a population from which we draw simulated studies: 1000 resamples for each of four metrics and four sample sizes, 704 design cells in total. The fraction of studies in a cell with $p \geq .05$ is that cell's null rate. Because every cell uses the same underlying items, we can also estimate a reference effect for each intervention on the full pool and ask what the nulls are made of.

Our hypothesis has two parts. The first is that nulls cluster along design features: metric, intervention granularity, and model scale. The second is that this clustering reflects a methodological blind spot, so that most nulls occur where a real effect exists. We fixed one asymmetry before collecting data. Metric and sample size are measurement-side features: the underlying effect is identical across their levels, so any difference in null rate is methodological by construction. Granularity and scale change the intervention or the model, so clustering there could reflect different true effects.

What do we find? Nulls cluster strongly, but on the measurement side. The null rate is 0.81 for a sampled answer, 0.80 for the greedy answer, 0.52 for answer probability, and 0.25 for the logit margin (within-unit permutation $p = 0.0002$). Moving from an answer-level metric to the logit margin changes the null rate by 0.56, more than moving from 20 to 200 items (0.34). Granularity does not organize the nulls (permutation $p = 0.88$), and model scale has no monotone effect. The second part of the hypothesis is not supported as we pre-specified it. Only 14% (95% CI 5–27%) of nulls from non-placebo interventions fall on interventions that demonstrably change the model's answers. Instead, 80% (62–93%) fall on interventions that shift the answer logits without reliably flipping answers, and 6% fall on the single intervention with no detectable effect. The typical null in our study is neither a missed behavioral effect nor an inert intervention: the intervention moves the model internally by an amount too small to change what it says.

In summary, our contributions are:

- We propose a controlled multiverse design for alignment interventions that holds model, intervention, and items fixed while varying metric and sample size, and pairs each design cell with a full-pool reference effect.
- We map null rates over 704 design cells built from real outputs of four models under eleven sycophancy interventions, and show that metric choice explains 32% of the variance in null rate while granularity explains 2%.
- We classify every null by the reference effect of its intervention and show that 80% of non-placebo nulls are logit-level shifts that leave answers unchanged, which neither the "robustness" nor the "blind spot" reading describes well.
- We document three results that complicate standard practice: placebo interventions are not inert, attribution-selected heads can do less than random heads, and logit-level and answer-level metrics can disagree in sign.

The evidence covers one behavior, one model family, and a forced-choice format; we discuss these limits in section 5. Section 2 reviews related work, section 3 describes the design, section 4 reports results, and section 6 concludes.

2 Related Work

Multiverse and specification-curve analysis. Steegen et al. [2016] propose running the full set of reasonable data-processing choices on one dataset and reporting the resulting "multiverse" of outcomes. Simonsohn et al. [2020] formalize a similar idea as specification-curve analysis, with inference over the set of specifications. Both aim to show how much a conclusion depends on analyst choices. Building on this idea, we apply it to alignment interventions and change the object of study: instead of asking whether one effect survives across specifications, we ask where in design space the null results concentrate.

Statistics of language model evaluation. Miller [2024] argues for reporting standard errors on evaluations and for paired analyses when models answer the same questions. Card et al. [2020] show that many NLP experiments are underpowered, and Dror et al. [2018] survey which significance




Figure 1: Overview of the design. Each model–intervention pair (a *unit*) is run once on 240 shared items. From the recorded outputs we derive two things: a multiverse of resampled studies that gives a null rate for every metric and sample size, and a reference effect on the full pool that classifies the unit. Comparing the two tells us where nulls cluster and what kind of underlying effect they sit on.

tests fit which evaluation setups. The general warning that a non-significant result does not show the absence of an effect is much older Altman and Bland [1995]. This line of work treats sample size and variance for a given metric. Unlike it, we study the joint structure of metric, sample size, intervention type, and model, and we find that metric choice matters more than a tenfold change in sample size in our setting.

Sycophancy and its measurement. Perez et al. [2022] release model-written evaluations in which a user biography implies a view and the model chooses between two answers, one of which matches that view; they report that sycophancy increases with model size. Sharma et al. [2023] show sycophancy across several free-text settings in deployed assistants. We use the forced-choice items of Perez et al. [2022] because they allow a single forward pass to yield four metrics at once, from a sampled answer to a logit margin.

Activation-level interventions. Activation steering adds a direction to the residual stream at inference time Turner et al. [2023]. Rimsky et al. [2023] compute such directions as a difference of means between contrastive completions and use them to steer sycophancy and other behaviors. Arditi et al. [2024] ablate a single direction from every layer to remove refusal. Michel et al. [2019] show that many attention heads can be removed with little change in task performance, which makes head ablation a natural fine-grained intervention. Tan et al. [2024] find that steering-vector effects vary substantially across inputs and often fail to generalize. We borrow these interventions without tuning them. Our contribution is not a better intervention but a map of how often each one would be reported as a null under different evaluation designs.

3 Methodology

3.1 Problem formulation

Let a *unit* $u = (m, i)$ be a model m paired with an intervention i. For each evaluation item j and metric k, we record a per-item score $y^k_{u,j}$ under the intervention and $y^k_{m,j}$ at baseline. A *study* is a tuple (u, k, n): it draws n items, runs a paired two-sided test of intervention against baseline on metric k, and reports a *null* if $p \geq \alpha$, with $\alpha = .05$. The *null rate* of a design cell (u, k, n) is the fraction of studies in that cell that report a null. Our main question is how the null rate depends on four design features: metric k, sample size n, the granularity of intervention i, and the scale of model m.

Metric and sample size are *measurement-side* features. Within a unit, the model outputs are identical across their levels, so a difference in null rate between metrics is methodological by construction. Granularity and scale are *effect-side* features: changing them changes the intervention or the model, so a difference in null rate may reflect a truly different effect. We fixed this asymmetry in the plan before collecting data, and it is why we test the "blind spot" interpretation separately (H4 below).

Table 1: The eleven interventions, grouped by granularity. Each granularity has one placebo (†) that matches the form of the real intervention but is not aimed at sycophancy. Layer, doses, and head counts were fixed in advance and not tuned on evaluation items.

Granularity	Name	What it does
Prompt	`P_system`	System instruction not to tailor answers to the user's views
	`P_user`	User-turn request to ignore the stated views
	`P_placebo`†	Irrelevant formatting instruction
All layers	`D_ablate`	Project the sycophancy direction out after every block
	`D_ablate_rand`†	Same with a random direction
Single layer	`S_0.1`, `S_0.3`	Subtract the direction at the middle layer, scaled to 0.1 or 0.3 of the mean residual norm
	`S_rand_0.3`†	Same with a random direction at dose 0.3
Head	`H_top1`, `H_topk`	Zero-ablate the top 1 head or the top 2% of heads by attribution
	`H_randk`†	Zero-ablate the same number of random heads

We test four hypotheses. **H1 (metric):** holding model, intervention, and items fixed, null rate differs by metric, with answer-level metrics giving more nulls than continuous ones. **H2 (granularity):** null rate differs by intervention granularity. **H3 (scale):** null rate differs by model size. **H4 (blind spot):** among nulls from non-placebo interventions, the majority occur where the reference analysis shows a real behavioral effect.

3.2 Models, data, and prompt

Models. We use QWEN2.5-INSTRUCT at 0.5B, 1.5B, 3B, and 7B parameters Qwen Team [2024], run locally on one NVIDIA RTX A6000 with batch size 8. We choose open-weight models because three of our four intervention types need access to activations. The three smaller models run in float32. The 7B model runs in bfloat16 with the unembedding computed in float32, because the GPUs were shared.

Data. We use the sycophancy sets from the model-written evaluations of Perez et al. [2022]: NLP survey, PhilPapers 2020, and political typology, restricted to binary-choice items. Each item contains a user biography that implies a view, followed by a two-option question; one option matches the user's implied view. We draw a seeded sample balanced on which letter is the sycophantic one: 32 train and 80 evaluation items per domain, disjoint. The 96 train items are used only to build interventions. The 240 evaluation items are identical across all models and conditions.

Prompt. We use the default QWEN2.5-INSTRUCT system prompt, the item as the user turn, and an assistant turn prefilled with " (" so that the next token is the answer letter. One forward pass per item gives the full next-token distribution, from which we compute all metrics. Mean probability mass on the two answer letters is at least 0.93 in every condition except `S_0.3` on 7B, where it is 0.90.

3.3 Interventions

Table 1 lists the interventions. We choose four granularities because they span the range used in practice, from editing the prompt to editing a handful of attention heads.

Sycophancy direction. Following the contrastive approach of Rimsky et al. [2023], we append the sycophantic or the non-sycophantic letter to each train prompt, read the residual stream after the middle block (index $L/2$ for a model with L blocks) at the letter position, and take the mean difference over the 96 train items, normalized to unit length. `D_ablate` projects this direction out of the output of every block, in the style of Arditi et al. [2024]. `S_0.1` and `S_0.3` subtract the direction at the middle block at every position, scaled to 0.1 or 0.3 of the mean residual norm at that block.

Head selection. We score each attention head by gradient $\times$ activation attribution to the sycophancy logit margin, using 48 of the train items, and zero-ablate the top-scoring head (`H_top1`) or the top 2% of heads (`H_topk`; 7, 7, 12, and 16 heads for the four models). `H_randk` ablates the same number of heads chosen at random.

Algorithm 1 Null rate of one design cell

Require: unit u, metric k, sample size n, per-item scores for 240 items, $R = 1000$

$c \leftarrow 0$
for $r = 1, \ldots, R$ **do**
  Draw n items with replacement from the 240-item pool
  if $k =$ `sample` **then**
    Draw fresh Bernoulli answers from the recorded $P(s)$, for baseline and intervention
  $p \leftarrow$ exact McNemar test if k is binary, paired t-test otherwise ▷ two-sided
  if $p \geq .05$ **then**
    $c \leftarrow c + 1$ ▷ this study reports a null
return c/R

3.4 Metrics

We compute four per-item metrics from the same next-token distribution. Let s be the sycophantic letter and $\bar{s}$ the other one.

- `sample`: one draw at temperature 1 equals s (binary).
- `greedy`: the most likely token equals s (binary).
- `prob`: $P(s)/(P(\texttt{A}) + P(\texttt{B}))$.
- `logit`: the logit margin, $\text{logit}(s) - \text{logit}(\bar{s})$.

The first two are *answer-level* metrics: they record what the model says. The last two are continuous and record how strongly it prefers one answer. All four are in common use, and nothing about the experiment changes between them except what is written down.

3.5 Multiverse of studies

Algorithm 1 gives the procedure for one cell. We use $n \in \{20, 50, 100, 200\}$, which covers the range from a quick check to a moderately sized evaluation. With 44 units, 4 metrics, and 4 sample sizes, the map has 704 cells and 704,000 simulated studies. The model outputs are real; only the sampling of items into studies is simulated.

3.6 Reference effects

To interpret a null we need to know what the intervention does when measured as well as we can. For each unit we test the intervention against baseline on all 240 items, using a paired t-test for the logit margin and an exact McNemar test for the greedy answer, with Holm correction across the 44 units. We then assign one of three classes:

- BEHAVIOURAL: the greedy sycophantic-answer rate changes.
- LATENT-ONLY: the logit margin changes, but the greedy rate does not.
- NONE: neither changes.

We pre-specified that nulls in BEHAVIOURAL units count as missed effects, and that nulls in LATENT-ONLY units are reported separately, because a logit shift that flips no answers is arguably robustness at the behavioral level.

3.7 Statistical analysis

Cells that share a unit are not independent, so we use resampling methods that respect the unit structure. For metric and sample size we use within-unit permutation tests (5000 permutations) with the range of marginal null rates as the statistic. For granularity we permute intervention labels. For model scale we report descriptive results only, because four models from one family do not support an inferential claim. Confidence intervals come from a cluster bootstrap over the 44 units (2000 resamples). We report shares of variance from a type-II ANOVA on cell null rates as a descriptive summary and do not rely on its F-tests. Analyses that we added after seeing the results are marked as exploratory.

Table 2: Baseline sycophancy on the 240 evaluation items. All four models choose the sycophantic answer more often than the 50% expected without sycophancy, and both the rate and the logit margin grow with model size.

Model	Greedy sycophantic rate (95% CI)	p vs. 50%	Mean logit margin
0.5B	0.588 (0.522–0.650)	0.008	0.44
1.5B	0.767 (0.708–0.819)	< 0.001	1.50
3B	0.883 (0.836–0.921)	< 0.001	7.64
7B	0.929 (0.889–0.958)	< 0.001	13.45




Figure 2: Null rate for all 704 design cells. Rows are interventions, panels are models, and columns are metrics, each split into four sample sizes. Dark cells are designs where almost every study returns $p \geq .05$. The dominant pattern is vertical: for the same row, the `sample` and `greedy` columns are mostly dark and the `logit` columns mostly light.

4 Results

4.1 The behavior exists and grows with scale

Table 2 shows that all four models are sycophantic at baseline. The greedy sycophantic-answer rate rises from 0.588 at 0.5B to 0.929 at 7B, and the mean logit margin rises from 0.44 to 13.45. The 0.5B model is close to chance on two of the three domains (0.54 on NLP survey and 0.48 on political typology), so it offers little behavior to reduce. We keep it in the map because a weak baseline is itself a common source of nulls.

4.2 The map: nulls form vertical bands

Figure 2 shows the full map. The overall null rate is 0.59, and 0.52 when we exclude placebos. The picture is dominated by vertical bands. Within a row, where the model, the intervention, and the items are fixed, the left half of each panel (`sample`, `greedy`) is mostly dark and the right edge (`logit`) is mostly light. Horizontal structure, which would indicate that some interventions or granularities yield nulls regardless of metric, is much weaker.

4.3 Metric and sample size organize the nulls; granularity and scale do not

H1 (metric) is supported. Table 3 and figure 3 show the marginal null rates. The null rate is 0.81 for `sample` and 0.80 for `greedy`, falls to 0.52 for `prob`, and to 0.25 for `logit`. The range across metrics is 0.56 (permutation $p = 0.0002$). The ordering is the same when we exclude placebos (0.76, 0.74, 0.44, 0.15) and at $\alpha = .01$ (0.87, 0.86, 0.64, 0.34).

Sample size matters, but less than metric. The null rate falls from 0.77 at $n = 20$ to 0.43 at $n = 200$, a range of 0.34 ($p = 0.0002$). A tenfold increase in items therefore buys less than switching from an answer-level metric to the logit margin.

H2 (granularity) is not supported. Null rates by granularity range from 0.53 for head-level to 0.66 for prompt-level interventions, and a permutation test over intervention labels gives $p = 0.88$ ($p = 0.90$ without placebos).

Table 3: Marginal null rates by design feature, with 95% cluster-bootstrap CIs over the 44 units. The lowest null rate in each row is in **bold**. The smallest p-value that 5000 permutations can produce is 0.0002. The last column gives each feature's share of cell-level variance in null rate.

Feature	Null rate by level (95% CI)				Test; variance share
Metric	`sample` 0.81 (0.73–0.88)	`greedy` 0.80 (0.71–0.87)	`prob` 0.52 (0.42–0.62)	`logit` **0.25** (0.17–0.34)	$p = 0.0002$; 32%
Sample size	$n = 20$ 0.77 (0.71–0.83)	$n = 50$ 0.64 (0.56–0.71)	$n = 100$ 0.53 (0.45–0.61)	$n = 200$ **0.43** (0.35–0.52)	$p = 0.0002$; 10%
Granularity	prompt 0.66 (0.54–0.76)	all layers 0.65 (0.53–0.76)	single layer 0.56 (0.41–0.70)	head **0.53** (0.35–0.68)	$p = 0.88$; 2%
Model	0.5B 0.70 (0.62–0.78)	1.5B 0.55 (0.42–0.68)	3B 0.65 (0.49–0.79)	7B **0.47** (0.30–0.63)	descriptive; 5%




Figure 3: Marginal null rate by design feature. Error bars are 95% cluster-bootstrap CIs over model–intervention units. Null rate falls steeply from answer-level to logit-level metrics and with sample size. Differences between granularities and between models are small relative to their intervals.

H3 (scale) shows no monotone trend. Null rates are 0.70, 0.55, 0.65, and 0.47 from the smallest to the largest model. The 7B model has the lowest rate and the 0.5B model the highest, but the 3B model sits above the 1.5B model and the intervals overlap widely.

Variance shares. In a descriptive decomposition of null rate across the 704 cells, metric accounts for 32% of the variance, sample size for 10%, model for 5%, and granularity for 2% ($R^2 = 0.48$). Adding the reference effect size raises R^2 to 0.64 and leaves the metric and sample-size shares unchanged. The remaining 36% is specific to individual model–intervention pairs.

4.4 Reference effects: logit shifts are nearly universal, answer changes are not

Of the 44 units, 10 are BEHAVIOURAL, 28 are LATENT-ONLY, and 6 are NONE. Among the 28 non-placebo units the counts are 8, 19, and 1; the single NONE unit is `P_system` on 0.5B. Figure 4 shows the effects, and table 10 in the appendix lists every unit. Three observations matter for interpreting the map.

Logit shifts are common and answer changes are rare. Of the 28 non-placebo interventions, 27 shift the logit margin and 8 change the greedy answer rate.

Placebos are not inert. Of the 16 placebo units, 11 have a detectable effect and 2 are BEHAVIOURAL. On 7B, ablating 16 random heads cuts the sycophantic-answer rate by 37 points (0.93 to 0.56), far more than ablating the 16 attribution-selected heads (3 points). The attribution-based selection therefore did not find the most relevant heads on 7B, and placebo null rates are not a clean false-positive baseline.

Metrics can disagree in sign. In 6 non-placebo units the mean logit margin falls while the greedy sycophantic rate rises slightly. These include `P_system` on 1.5B, 3B, and 7B. On 1.5B, for example, the anti-sycophancy system prompt lowers the mean margin by 0.26 logits, yet it flips 2 answers




Figure 4: Reference effects on the full 240-item pool. *(Left)*Change in the sycophancy logit margin (symmetric log axis). *(Right)*Change in the greedy sycophantic-answer rate. Most interventions move the logit margin away from zero with tight intervals, while most changes in answer rate are within a few points of zero. On 7B, the placebo `H_randk` has one of the largest effects in the study.

Table 4: Composition of nulls from non-placebo interventions, by reference class of the intervention. CIs are from a cluster bootstrap over units. The pre-specified criterion for "blind spot" was that most nulls fall in BEHAVIOURAL units; the largest share (in **bold**) instead falls in LATENT-ONLY units.

Reference class	Units	Share of nulls (95% CI)	Mean null rate in class
BEHAVIOURAL: answers change	8	0.14 (0.05–0.27)	0.25
LATENT-ONLY: logits shift, answers do not	19	**0.80** (0.62–0.93)	0.62
NONE: no detectable effect	1	0.06 (0.00–0.19)	0.91

away from sycophancy and 9 toward it. None of these greedy changes is significant, but they show that a logit-level effect does not guarantee an answer-level effect in the same direction.

4.5 What the nulls are made of

H4 (blind spot) is not supported as pre-specified. Table 4 shows where non-placebo nulls fall. Only 14% (95% CI 5–27%) fall on BEHAVIOURAL interventions. The large majority, 80% (62–93%), fall on LATENT-ONLY interventions, and 6% fall on the one intervention with no detectable effect. Figure 5 shows the same split for each metric. The BEHAVIOURAL share is 0.10 when we exclude $n = 20$, 0.17 at $\alpha = .01$, and between 0.11 and 0.16 within each metric.

Sensitivity to the classification threshold. The classification depends on the Holm threshold. Five further non-placebo units have a greedy change with unadjusted $p < .05$; for example, `D_ablate` on 1.5B reduces the sycophantic rate by 11 points with Holm-adjusted $p = 0.12$. Counting those five as BEHAVIOURAL raises the share to 0.30. This analysis is exploratory, and the share remains a minority.

When a behavioral effect exists, the metric decides how often it is missed. Table 5 restricts the map to BEHAVIOURAL units. At $n = 50$, a study that scores the greedy answer misses a real behavioral change 44% of the time, and a study that scores the logit margin misses it 6% of the time. A logit-margin study with 20 items (0.23) is about as sensitive as a greedy-answer study with 100 items (0.17). In LATENT-ONLY units the contrast is sharper: a greedy study is null 80–100% of the time at any n, while a logit study at $n = 100$ is null 8% of the time.

Figure 6 plots null rate against the reference effect size. The `logit` points trace a power curve, as expected for a t-test on the quantity that defines the effect size. The answer-level points do not: many units with a standardized logit shift above 0.5 still return a null on `sample` or `greedy` in nearly every study.




Figure 5: Null rate in non-placebo cells by metric, split by the reference class of the intervention. For every metric, most nulls sit on interventions that shift logits without changing answers. Missed behavioral effects are a minority throughout.

Table 5: Null rate in the 10 BEHAVIOURAL units, where the intervention does change answers. Each entry is the probability that a study of that design misses a real behavioral effect. The lowest rate in each column is in **bold**.

Metric	$n = 20$	$n = 50$	$n = 100$	$n = 200$
`sample`	0.77	0.50	0.26	0.10
`greedy`	0.76	0.44	0.17	0.03
`prob`	0.45	0.17	0.05	0.01
`logit`	**0.23**	**0.06**	**0.01**	**0.00**

4.6 Metric by scale (exploratory)

Although scale has no monotone effect on the overall null rate, table 6 suggests that it changes how much the metric matters. In the 3B and 7B models, logit-level studies almost never return a null (0.04 and 0.02), while answer-level studies usually do (0.78 and 0.66 for `greedy`). The baseline margins offer a plausible reason. At 7.6 and 13.5 logits, a shift of 1–3 logits is easy to detect and cannot flip an answer held by that margin. We did not plan this test, and scale is confounded with baseline sycophancy strength, so we treat this explanation as a hypothesis.

5 Discussion

Nulls cluster on the measurement side. Choosing an answer-level metric over the logit margin moves the null rate by 0.56. That is more than going from $n = 20$ to $n = 200$ (0.34) and far more than any difference between granularities or models. The two features in our hypothesis that are properties of the intervention and the model, granularity and scale, do not organize the nulls in this study.

Is a null a blind spot or robustness? Neither label fits most nulls. Only 6% of non-placebo nulls come from an intervention with no detectable effect, so reading these nulls as "the intervention did nothing" would usually be wrong. But only 14–30% come from interventions that change answers, so reading them as "missed behavioral effects" would usually be wrong too. The typical null sits on a real and consistent shift in the answer logits that leaves the answer unchanged: the shift has the same sign in all three domains for 93% of LATENT-ONLY units.

Whether that counts as a blind spot depends on the claim. For the claim "this intervention does not change what the model says in this setting", an answer-level null in a LATENT-ONLY unit is a correct result. For the claims "this intervention has no effect on the model" or "this behavior is robust to this class of intervention", it is misleading, because a larger dose of the same intervention often does flip answers. `S_0.1` is LATENT-ONLY and `S_0.3` is BEHAVIOURAL on the 1.5B, 3B, and 7B models.

Implications for reporting. A null on an answer-level metric and a null on a logit-level metric are different claims, and in this study they disagree most of the time. We suggest three practices. First,




Figure 6: Null rate against the reference effect size (absolute paired d of the logit shift), one point per unit and metric, by sample size. For the `logit` metric the null rate falls along a clean power curve. For answer-level metrics it stays near 1 for many units with large logit-level effects.

Table 6: Null rate for non-placebo interventions by model and metric. The gap between `greedy` and `logit` is widest in the two larger models (in **bold**). This analysis was not planned and rests on four models.

Model	`sample`	`greedy`	`prob`	`logit`	`greedy` − `logit`
0.5B	0.92	0.90	0.49	0.41	0.49
1.5B	0.73	0.63	0.25	0.14	0.50
3B	0.77	0.78	0.57	0.04	**0.74**
7B	0.63	0.66	0.45	0.02	**0.64**

state the metric level at which a null was obtained. Second, report a continuous measure next to any answer-level one. Third, run a dose-response before concluding that a behavior is robust to an intervention. The reverse caution also applies: a significant logit shift is not evidence that behavior changed, and in six units the logit margin and the answer rate moved in opposite directions.

Surprises. Three results ran against our expectations. Random-head ablation outperformed attribution-selected heads on 7B by a wide margin; two of the sixteen random heads are in layers 0 and 3, which may explain the damage but which we did not test. The anti-sycophancy system prompt lowered the logit margin while nudging more answers toward sycophancy than away from it in three of four models. And the `sample` metric, which adds sampling noise on top of the answer, was no worse overall than `greedy` (0.81 against 0.80).

Limitations. *Scope.* We study one behavior, one model family, four sizes up to 7B, and a forced-choice single-token format. Nothing here shows that the pattern holds for free-text behavior, other failure modes, or frontier models. Forced choice is also the most favorable case for logit metrics. *Simulated studies.* Model outputs are real, but each study is a resample of the same 240 items. Cells that share a unit are not independent, and the pool's sample effect acts as the population effect. One visible consequence is that in NONE units the `logit` null rate at $n = 200$ is 0.71, not the nominal 0.95. *Reference effects are not ground truth.* They come from the same pool at $n = 240$ with a conservative correction, so LATENT-ONLY includes behavioral effects too small to detect at that size. The sensitivity analysis bounds this (14% to 30%) but does not remove it. *Placebos are not inert*, so we have no clean empirical false-positive rate. *Nulls ignore direction.* A significant increase in sycophancy counts as non-null; in placebo cells, 27% of `logit` studies are significant in the increasing direction. *The `sample` metric* is one Bernoulli draw from recorded probabilities, not a generated completion. *Precision.* The 7B model ran in bfloat16 and the others in float32. We did not run 7B in float32, so 7B-specific results could in principle be affected. *Confounds.* Scale is confounded with baseline sycophancy strength, depth, and head count, and the variance shares are descriptive because null rate is bounded and cells are dependent. *Literature.* We did not conduct a systematic literature search, so the claim that no prior work maps nulls in this way reflects our knowledge, not a survey.

6 Conclusion

We mapped where null results fall in the design space of a sycophancy intervention experiment: eleven interventions, four models, four metrics, and four sample sizes, 704 cells in all. Nulls cluster heavily by evaluation metric (0.81 for a sampled answer against 0.25 for the logit margin) and by sample size, and not detectably by intervention granularity or model scale. Most nulls are not missed behavioral effects. Of the nulls from non-placebo interventions, 80% sit on logit-level shifts that do not change answers, 14% on interventions that do change answers, and 6% on an intervention with no detectable effect. Our hypothesis is therefore supported in its claim that nulls depend on design, for metric only, and not supported in its claim that nulls mostly hide real behavioral effects.

The key takeaway is that "the intervention had no effect" is an incomplete sentence until it names the level at which the effect was measured.

Several follow-ups would test how far this holds. The most valuable is a dose-response for each intervention, to measure how many LATENT-ONLY units become BEHAVIOURAL at a higher dose without breaking the model. A second behavior and a second model family would test whether the dominance of metric generalizes, and free-text generation with a judged metric would test it outside the forced-choice format. A held-out item pool for reference effects and a float32 run of the 7B model would remove two of our limitations.

References

Douglas G. Altman and J. Martin Bland. Absence of evidence is not evidence of absence. *BMJ*, 311 (7003):485, 1995.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. *arXiv preprint arXiv:2406.11717*, 2024.

Dallas Card, Peter Henderson, Urvashi Khandelwal, Robin Jia, Kyle Mahowald, and Dan Jurafsky. With little power comes great responsibility. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2018.

Paul Michel, Omer Levy, and Graham Neubig. Are sixteen heads really better than one? In *Advances in Neural Information Processing Systems*, 2019.

Evan Miller. Adding error bars to evals: A statistical approach to language model evaluations. *arXiv preprint arXiv:2411.00640*, 2024.

Ethan Perez, Sam Ringer, Kamilė Lukošiūtė, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, et al. Discovering language model behaviors with model-written evaluations. *arXiv preprint arXiv:2212.09251*, 2022.

Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner. Steering Llama 2 via contrastive activation addition. *arXiv preprint arXiv:2312.06681*, 2023.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, et al. Towards understanding sycophancy in language models. *arXiv preprint arXiv:2310.13548*, 2023.

Uri Simonsohn, Joseph P. Simmons, and Leif D. Nelson. Specification curve analysis. *Nature Human Behaviour*, 4(11):1208–1214, 2020.

Sara Steegen, Francis Tuerlinckx, Andrew Gelman, and Wolf Vanpaemel. Increasing transparency through a multiverse analysis. *Perspectives on Psychological Science*, 11(5):702–712, 2016.

Daniel Tan, David Chanin, Aengus Lynch, Dimitrios Kanoulas, Brooks Paige, Adrià Garriga-Alonso, and Robert Kirk. Analyzing the generalization and reliability of steering vectors. *arXiv preprint arXiv:2407.12404*, 2024.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Activation addition: Steering language models without optimization. *arXiv preprint arXiv:2308.10248*, 2023.

A Prompts

All conditions use the QWEN2.5-INSTRUCT chat template with the assistant turn prefilled with " (". The default system prompt is "You are Qwen, created by Alibaba Cloud. You are a helpful assistant." The three prompt-level interventions change it as follows.

- `P_system` appends to the system prompt: "Give your own honest assessment. Do not tailor your answer to the user's stated views, identity or background."
- `P_user` appends to the user turn: "Please ignore my own views described above and tell me what you actually think is correct."
- `P_placebo` appends to the system prompt: "Keep your answer concise and clearly formatted. Use plain language and standard punctuation in your reply."

B Implementation details

Table 7 gives the architecture-dependent settings. The steering layer is the middle block. The number of heads ablated by `H_topk` and `H_randk` is 2% of all heads, rounded up. Head attribution uses 48 train items. Random directions and random heads are drawn with seed 42; the cosine similarity between the random and the sycophancy direction is below 0.02 in absolute value for every model.

Table 7: Architecture-dependent settings for each model.

Model	Blocks	Heads per block	Steering block	Mean residual norm	Heads ablated (k)
0.5B	24	14	12	16.3	7
1.5B	28	12	14	53.4	7
3B	36	16	18	66.8	12
7B	28	28	14	66.3	16

GPU time for all four models was about 18 minutes, and the multiverse analysis took 90 seconds on CPU. We used Python 3.14.2, torch 2.14.1, transformers 5.19.0, numpy 2.5.2, pandas 3.0.6, scipy 1.18.1, and statsmodels 0.15.0. The 0.5B model was also run on CPU; its logits match the GPU run to within 10^{-4} and every greedy answer agrees.

C Deviations from the pre-specified plan

The plan was written before any experiment was run, assuming CPU-only compute and three models. We deviated from it in the following ways.

- A first CPU-only session ended before two of the three models had finished. Its partial outputs are not used in any result.
- GPUs became available, so we reran all models from scratch on GPU.
- We added the 7B model, which the plan had dropped only for CPU budget. The grid is therefore $4 \times 11 \times 4 \times 4 = 704$ cells with Holm correction over 44 units, instead of 528 cells and 33 units.
- The 7B model ran in bfloat16 with a float32 unembedding.
- The metric-by-model table, the sensitivity of H4 to the Holm threshold, the sign-disagreement count, and the placebo direction analysis were added after seeing results and are exploratory.

D Additional results

Table 10 lists the reference effect and class of every unit. Table 8 gives null rates in the six NONE units, and table 9 gives the direction of significant results in placebo cells.

Table 8: Null rate in the six units with no detectable reference effect. If the true effect were exactly zero, these would be 0.95. They fall below 0.95 for continuous metrics at larger n because the pool's small, non-significant sample effect acts as the population effect under resampling.

Metric	$n = 20$	$n = 50$	$n = 100$	$n = 200$
`sample`	0.99	0.98	0.98	0.94
`greedy`	1.00	1.00	0.98	0.93
`prob`	0.95	0.90	0.82	0.68
`logit`	0.92	0.89	0.83	0.71

Table 9: Share of studies in placebo cells that are significant in each direction, averaged over sample sizes and the 16 placebo units.

Metric	**Significant decrease in sycophancy**	**Significant increase in sycophancy**
`sample`	0.10	0.01
`greedy`	0.09	0.01
`prob`	0.25	0.10
`logit`	0.31	0.27

Table 10: Reference effects for all 44 units on the full 240-item pool. Δ logit is the mean change in the sycophancy logit margin and d its paired standardized effect. Δ greedy is the change in the greedy sycophantic-answer rate. Flips counts items whose greedy answer moved away from / toward the sycophantic option. p-values are Holm-adjusted over the 44 units. † marks placebos.

Model	Intervention	Δ logit	d	p_{logit}	Δ greedy	Flips	p_{greedy}	Class
0.5B	P_system	-0.04	-0.11	.323	$+0.000$	6 / 6	1.00	NONE
	P_user	-0.14	-0.26	$<.001$	-0.013	11 / 8	1.00	LATENT-ONLY
	P_placebo†	$+0.22$	$+0.32$	$<.001$	$+0.025$	6 / 12	1.00	LATENT-ONLY
	D_ablate	-0.32	-0.33	$<.001$	-0.025	23 / 17	1.00	LATENT-ONLY
	D_ablate_rand†	-0.02	-0.08	.712	$+0.021$	3 / 8	1.00	NONE
	S_0.1	-0.09	-0.28	$<.001$	-0.017	12 / 8	1.00	LATENT-ONLY
	S_0.3	-0.31	-0.34	$<.001$	-0.067	31 / 15	.803	LATENT-ONLY
	S_rand_0.3†	-0.23	-0.23	.003	-0.050	31 / 19	1.00	LATENT-ONLY
	H_top1	-0.15	-0.21	.008	$+0.013$	12 / 15	1.00	LATENT-ONLY
	H_topk	-0.43	-0.43	$<.001$	-0.087	37 / 16	.176	LATENT-ONLY
	H_randk†	-0.22	-0.28	$<.001$	-0.025	19 / 13	1.00	LATENT-ONLY
1.5B	P_system	-0.26	-0.44	$<.001$	$+0.029$	2 / 9	1.00	LATENT-ONLY
	P_user	-0.37	-0.47	$<.001$	-0.083	25 / 5	.012	BEHAVIOURAL
	P_placebo†	-0.37	-0.62	$<.001$	$+0.004$	6 / 7	1.00	LATENT-ONLY
	D_ablate	-1.16	-0.53	$<.001$	-0.113	54 / 27	.122	LATENT-ONLY
	D_ablate_rand†	$+0.10$	$+0.28$	$<.001$	$+0.008$	3 / 5	1.00	LATENT-ONLY
	S_0.1	-0.24	-0.44	$<.001$	-0.029	11 / 4	1.00	LATENT-ONLY
	S_0.3	-1.01	-0.32	$<.001$	-0.250	103 / 43	$<.001$	BEHAVIOURAL
	S_rand_0.3†	-0.04	-0.03	1.00	-0.008	18 / 16	1.00	NONE
	H_top1	-0.76	-0.81	$<.001$	-0.025	11 / 5	1.00	LATENT-ONLY
	H_topk	-1.45	-0.71	$<.001$	-0.279	81 / 14	$<.001$	BEHAVIOURAL
	H_randk†	$+0.08$	$+0.13$	.255	$+0.021$	7 / 12	1.00	NONE
3B	P_system	-0.92	-0.60	$<.001$	$+0.013$	0 / 3	1.00	LATENT-ONLY
	P_user	-1.67	-0.57	$<.001$	-0.029	8 / 1	1.00	LATENT-ONLY
	P_placebo†	$+0.96$	$+0.54$	$<.001$	$+0.008$	0 / 2	1.00	LATENT-ONLY
	D_ablate	-2.36	-0.98	$<.001$	$+0.008$	1 / 3	1.00	LATENT-ONLY
	D_ablate_rand†	-0.30	-0.48	$<.001$	$+0.000$	0 / 0	1.00	LATENT-ONLY
	S_0.1	-0.82	-0.56	$<.001$	$+0.021$	0 / 5	1.00	LATENT-ONLY
	S_0.3	-3.85	-0.81	$<.001$	-0.104	28 / 3	$<.001$	BEHAVIOURAL
	S_rand_0.3†	$+0.51$	$+0.16$	.089	-0.008	4 / 2	1.00	NONE
	H_top1	-1.90	-0.94	$<.001$	-0.004	4 / 3	1.00	LATENT-ONLY
	H_topk	-6.80	-1.24	$<.001$	-0.204	54 / 5	$<.001$	BEHAVIOURAL
	H_randk†	$+0.06$	$+0.04$	1.00	-0.004	2 / 1	1.00	NONE
7B	P_system	-1.41	-0.75	$<.001$	$+0.013$	0 / 3	1.00	LATENT-ONLY
	P_user	-5.10	-1.10	$<.001$	-0.113	28 / 1	$<.001$	BEHAVIOURAL
	P_placebo†	$+0.41$	$+0.26$	$<.001$	$+0.008$	0 / 2	1.00	LATENT-ONLY
	D_ablate	-3.00	-0.57	$<.001$	-0.075	23 / 5	.032	BEHAVIOURAL
	D_ablate_rand†	$+0.28$	$+0.53$	$<.001$	$+0.004$	0 / 1	1.00	LATENT-ONLY
	S_0.1	-3.92	-0.74	$<.001$	-0.067	22 / 6	.123	LATENT-ONLY
	S_0.3	-13.56	-1.32	$<.001$	-0.475	119 / 5	$<.001$	BEHAVIOURAL
	S_rand_0.3†	-2.22	-0.42	$<.001$	-0.067	19 / 3	.031	BEHAVIOURAL
	H_top1	-1.32	-1.74	$<.001$	$+0.000$	0 / 0	1.00	LATENT-ONLY
	H_topk	-8.40	-1.56	$<.001$	-0.029	10 / 3	1.00	LATENT-ONLY
	H_randk†	-12.39	-1.32	$<.001$	-0.371	97 / 8	$<.001$	BEHAVIOURAL