2

Setup, first run and the team files

Junlin Yuan · Spartan Agentic AI Studio

Setup

Demo

Get OpenCode

the desktop app, from opencode.ai only

Add your key

paste it once in settings, never in a file

Open the team

`AgentTeams › clip02 › clip02_01_simple-team`

Check

“Hi! What agents are on this team?”

Demo

First run

`/do` + a topic

Writer → **Checker** → **You**

writes the brief | opens every link | fix or leave?

/do = a saved prompt
Stop: the Stop button, or “1 working” › X

Team files

Team settings	`opencode.json`: the model + what agents may do
Agents	`writer.md, checker.md`
Commands	`do.md`: the prompt behind /do
Rules	`AGENTS.md`: read by every agent

A team: a few plain text files

Demo

Open the files

Hidden folder: `.opencode`

Mac Command + Shift + .

Windows View › Show › Hidden items

Linux Ctrl + H

Then: right-click › Open with › TextEdit, Notepad or Text Editor

Agents

`writer.md`

talks to you
writes the brief
calls the checker

`mode: primary`
→ in the menu

`checker.md`

opens every link
marks DEAD, BLOCKED, WRONG or OK
can't edit

`mode: subagent`
→ the writer starts it

Each file: description, mode, permissions, steps

Slash command

`/do today's 5 biggest news stories`

Saved — a prompt written once, in `do.md`

Dynamic input — words after /do fill `$ARGUMENTS`

AGENTS.md

Always sent — read by every agent, with every message

Keep it short — each line costs tokens on every message

Past mistakes — turn them into rules so they don’t happen again