

PEGA QUICK REFERENCE

Created By

SAI PRAVEEN

INDEX

No.	Topic	Page
1	PEGA OOTB RULES	3
2	PEGA STANDARD OOTB ACTIVITIES	7
3	PEGA INTEGRATION FLOW ERROR HANDLING	9
4	PEGA SLA / SERVICE-LEVEL AGREEMENTS	11
5	PEGA FLOW SHAPES	14
6	PEGA ACTIVITY METHODS	15
7	CONSTELLATION DATA MODELS	22

PEGA OOTB RULES

Strictly OOTB rules ? Properties excluded

Activities

Rule Name	Purpose	Used in
pxAddChildWork	Creates a child case / child work.	Case Management; Create Child Case.
pxCreateTopCase	Creates a top-level case.	Case Management; case creation.
pxMove	Moves work between work contexts.	Case Management; work hierarchy.
Work-.OpenAndLockWork	Opens a work item and obtains its lock.	Cross-work-item processing.
Work-.SetTicket	Sets/raises a ticket used to control flow processing.	Tickets; workflow control; SLA.
Work-.GetNextWork	Retrieves an assignment.	Get Next Work; assignment processing.
Work-.ResumeFlow	Resumes flow processing.	Workflow recovery; SLA.
Work-.StartNewFlow	Starts an additional flow.	Workflow; parallel processing.
Work-.CloseWorkItem	Closes work and releases its lock.	Case Management; closure.

Assignment Activities

Rule Name	Purpose	Used in
Work-.External	Creates an external assignment.	Assignment; Directed Web Access.
Work-.WorkList	Creates a worklist assignment.	Assignment; Worklist.
Work-.WorkBasket	Creates a workbasket assignment.	Assignment; Work Queue.

SAI PRAVEEN

Notify Activities

Rule Name	Purpose	Used in
Work-.Notify	Sends correspondence to a party.	Notification; Correspondence.
Work-.NotifyAll	Sends correspondence to work parties.	Case Management; Work Parties.
Work-.NotifyAssignee	Sends email to assignment recipient.	Assignment notification.
Work-.NotifyAllAssignees	Sends email to relevant operators.	Assignment notification.
Work-.NotifyParty	Sends correspondence based on urgency.	SLA; Notification.

Route Activities

Rule Name	Purpose	Used in
Work-.ToAssignedOperator	Routes to an available assigned operator.	Assignment; operator routing.
Work-.ToCurrentOperator	Routes to the current operator.	Assignment; Worklist.
Work-.ToCustomer	Routes to Customer work party.	Work Parties; Directed Web Access.
Work-.ToDecisionMap	Routes according to a decision map.	Decisioning; routing.
Work-.ToDecisionTree	Routes according to a decision tree.	Decisioning; routing.
Work-.ToDefaultWorkbasket	Routes to the default workbasket.	Work Queue; routing.
Work-.ToLeveledGroup	Routes using skills, availability and load balancing.	Intelligent routing.
Work-.ToNewWorkParty	Routes to a work party/operator.	Work Parties; routing.
Work-.ToOrgUnitManager	Routes to organization-unit manager.	Organizational routing.
Work-.ToSkilledGroup	Routes to a skilled operator.	Skills-based routing.
Work-.ToWorkbasket	Routes to a specified workbasket.	Work Queue; routing.
Work-.ToWorklist	Routes to a specified worklist.	Worklist; routing.
Work-.ToWorkParty	Routes to an available work party.	Work Parties; routing.

SAI PRAVEEN

Utility Activities

Rule Name	Purpose	Used in
Work-.AddHistory	Adds a history entry.	Case Management; audit/history.
Work-.AddNotetoHistory	Adds a history entry using note text.	Case Management; audit/history.
Work-.AddToFolder	Adds work to a folder.	Case Management; Folders.
Work-.CorrAttach	Links correspondence as an attachment.	Correspondence; Attachments.
Work-.CorrCheckForError	Checks correspondence for errors.	Correspondence; error handling.
Work-.CorrCreate	Prepares correspondence and contact information.	Correspondence; contact resolution.
Work-.CorrFail	Records correspondence failure.	Correspondence; error handling.
Work-.CorrNew	Sends correspondence without user interaction.	Correspondence; generation.
Work-.CorrQuickStart	Supports correspondence requiring verification.	Correspondence; verification.
Work-.CorrSend	Queues/sends correspondence.	Correspondence; delivery.
Work-.CorrVerify	Determines whether verification is required.	Correspondence; verification.
Work-.DuplicateSearch	Searches for possible duplicate work.	Case Management; duplicate detection.
Work-.GenerateID	Computes a work-item ID.	Case creation.
Work-.ProblemFlowThrowException	Raises a flow problem.	Workflow/integration error handling.
Work-.Resolve	Updates values needed for resolution.	Case Management; resolution.
Work-.UpdateStatus	Changes work status and records history.	Case Management; status management.
Work-.pxRetrieveReportDefinition	Retrieves the report definition/context required for report processing.	Reporting; Report Definition processing; report-related activity processing.

SAI PRAVEEN

Data Transforms

Rule Name	Purpose	Used in
Work-.pyDefault	Provides defaults for new work.	Case creation; initialization.
Work-.pyCopyDefault	Determines values copied when work is copied.	Copy Case/Work.
Work-Cover-.pyDefault	Provides defaults for cover work.	Cover/parent work.
Work-Folder-.pyDefault	Provides defaults for folder work.	Folder work.
Work-.pyAddChildWorkDefaults	Provides default/propagated data for child work.	Create Case; Create Child Case.

SAI PRAVEEN

PEGA STANDARD OOTB ACTIVITIES

Standard activities and extension-point rules by Applies To class

Work- Standard Activities

Rule Name	Purpose	Used in
Work-.ActionNotifyQuick	Creates simple correspondence.	Work notification/correspondence.
Work-.AddCovered	Creates a cover work item.	Case Management; cover/child processing.
Work-.CopyAttachmentToNewCategory	Copies attachment to another category.	Attachments.
Work-.CorrUpdate	Updates correspondence.	Correspondence.
Work-.DoClose	Runs when operator closes a user form.	Harness/UI close.
Work-.FindFulfillBasket	Finds fulfillment workbasket.	Fulfillment/routing.
Work-.getFlowProblemOperator	Identifies operator for a flow problem.	Flow error handling.
Work-.RandomSelection	Supports random/statistical selection.	Sampling; quality control.
Work-.WorkPartyRetrieve	Refreshes party identity information.	Work Parties.

Work- Standard / Extension-Point Activities

Rule Name	Purpose	Used in
Work-.NewDefaults	Extension point for new work initialization.	Case creation.
Work-.NewCoveredDefaults	Extension point before covered-work creation.	Child/covered work.
Work-.AddCoveredDefaults	Extension point during covered-work creation.	Child/covered work.
Work-.OpenDefaults	Extension point while opening work.	Open/harness processing.
Work-.PerformDefaults	Extension point during assignment processing.	Assignment processing.
Work-.PreClose	Extension point when closing work.	Close processing.
Work-.ReassignDefaults	Extension point during reassignment.	Assignment reassignment.
Work-.ReassigntoWorkBasketDefaults	Extension point for workbasket reassignment.	Work Queue.
Work-.UpdateDefaults	Extension point during work update/open.	Work update.

Assign- Standard / Extension-Point Activities

Rule Name	Purpose	Used in
Assign-.NewDefaults	Extension point when assignment is created.	Assignment creation.
Assign-Service.HandleInterrupt	Handles asynchronous service interruption.	Assignment Service; ticket/SLA.

@baseclass Standard / Extension-Point Activities

Rule Name	Purpose	Used in
@baseclass.ActivityStatus.NoContentHandler	Standard success response.	Activity execution.
@baseclass.ActivityStatus.ExceptionHandler	Standard exception response.	Activity exception handling.
@baseclass.CheckForCustomWarnings	Extension point for custom warnings.	Validation/framework.
@baseclass.PostSaveAs	Extension point for Save As.	Save As/framework.
@baseclass.pyPrepareFrameworkAssetsForGenerationSetup	Prepares assets before generation.	Case-type framework generation.
@baseclass.pyPrepareFrameworkAssetsForGenerationPost	Prepares assets after generation.	Case-type framework generation.

History- Rule Scope

Rule Name	Purpose	Used in
History-	Append-only hierarchy for cumulative history/change records.	Audit/history persistence.
History-* generated classes	History classes associated with concrete application classes.	Audit/history reporting.

SAI PRAVEEN

PEGA INTEGRATION FLOW ERROR HANDLING

Integration failures, predefined handling rules and recovery patterns

Integration / Connector Error Categories

Error Type	Purpose	Typical Example	Handling
Connection Error	External connection cannot be established/maintained.	Network; endpoint unavailable.	Classify; bounded retry if transient; otherwise technical handling.
Timeout Error	External service exceeds configured response time.	REST/SOAP/HTTP timeout.	Retry only when safe/idempotent.
Authentication / Authorization Error	External system rejects access.	401/403; expired credential.	Do not blindly retry; correct access.
HTTP 4xx Error	Request is invalid or rejected.	400/404/409/422.	Usually functional/permanent; validate request.
HTTP 5xx Error	Remote server fails processing.	500/502/503/504.	Often transient; bounded retry if safe.
SOAP Fault	SOAP endpoint returns a fault.	Business or technical SOAP fault.	Classify fault; route appropriately.
Mapping / Parsing Error	Payload cannot map to expected structure.	Invalid JSON/XML; missing field.	Correct schema/mapping; technical handling.
Business / Functional Error	Service responds but rejects business request.	Business rule rejection.	Route to business resolution; no blind retry.
Duplicate / Idempotency Error	Request already processed/conflicts with existing transaction.	Duplicate transaction/conflict.	Reconcile state; use correlation/idempotency.
Rate Limit / Throttling	Remote service limits request rate.	429 Too Many Requests.	Backoff and retry per service policy.
Certificate / TLS Error	Secure connection negotiation fails.	Expired certificate/trust issue.	Technical remediation; avoid blind retry.
Serialization Error	Data cannot be converted between formats/types.	Incompatible JSON/XML/data type.	Correct payload/schema.
Remote Processing Error	Remote application reports processing failure.	Remote exception.	Classify transient/permanent; retry only if safe.
Pega Flow Error	Workflow cannot continue normally.	Flow/assignment/connector problem.	Problem flow, diagnostics and recovery.

SAI PRAVEEN

Predefined / Standard Problem-Handling Rules

Rule Name	Purpose	Used in	How to use / Formula
ConnectionProblem	Standard problem flow for connector/connection failures.	REST/SOAP/connectors.	Controlled problem processing.
FlowProblems	Processes flow problems after normal handling/retry.	Workflow/integration.	Problem-flow routing and remediation.
pyRemoteProblem	Problem-flow context for remote case creation failures.	Remote case creation.	Remote failure recovery.
pzStageProblems	Problem-flow context for stage configuration problems.	Case/stage processing.	Framework problem handling.
pxErrorHandlingTemplate	Reusable Pega error-handling template pattern.	Data Pages/connectors.	Basis for application-specific handling.
Work-.getFlowProblemOperator	Identifies operator for flow-problem processing.	Problem routing.	Use in problem-flow routing.
Work-.ProblemFlowThrowException	Raises a flow problem.	Workflow/integration.	Raise controlled problem.
Work-.ResumeFlow	Resumes along a specified flow connector.	Workflow recovery.	Resume after underlying problem is resolved.

Recommended Error-Handling Flow

Step	Purpose	Used in	Handling
1. Detect	Capture failure/status/messages.	All integrations.	Check response and exception context.
2. Classify	Separate transient, technical and functional failures.	All integrations.	Classification determines retry.
3. Retry safely	Recover temporary failures without duplication.	Transient failures.	Bounded retry/backoff + idempotency.
4. Log / correlate	Preserve diagnostics and correlation.	All failures.	Never log secrets.
5. Route	Send unresolved errors to controlled handling.	Integration/flow errors.	Problem flow/workbasket/business route.
6. Recover / reconcile	Resume or reconcile after correction.	Recoverable failures.	Verify external state before resume.

SAI PRAVEEN

PEGA SLA / SERVICE-LEVEL AGREEMENTS

SLA types, intervals, formulas and PX/PY/PZ SLA-related properties

SLA Types

SLA Type	Purpose	Used in	Configuration
Assignment SLA	Controls target/deadline for assignment.	Assignment; Worklist; Work Queue.	Assignment/step configuration.
Case SLA	Controls overall case resolution time.	Case Type.	Case-level configuration.
Stage SLA	Defines target for a stage.	Case lifecycle stage.	Stage configuration.
Process SLA	Defines target for a process.	Case lifecycle process.	Process configuration.
Step SLA	Defines target for a step.	Case lifecycle step.	Step configuration.

SLA Intervals

Interval	Purpose	Used in	Formula / Rule
Start	Point where SLA timing begins.	All SLA scopes.	Configured start event/time.
Goal	Desired completion milestone.	All SLA scopes.	Start + business duration.
Deadline	Latest configured target before late status.	All SLA scopes.	Start + business duration.
Passed Deadline	Post-deadline escalation interval.	Overdue SLA processing.	Configured passed-deadline interval.

SAI PRAVEEN

Deep SLA Formulas

Calculation	Purpose	Used in	Formula
Goal DateTime	Target timestamp.	SLA engine.	Goal = Start + BusinessDuration(Goal).
Deadline DateTime	Deadline timestamp.	SLA engine.	Deadline = Start + BusinessDuration(Deadline).
Deadline Remaining	Time left until deadline.	Monitoring/prioritization.	Deadline – CurrentTime.
Elapsed Past Deadline	Time elapsed after deadline.	Reporting/escalation.	CurrentTime – Deadline.
Assignment Urgency	Assignment priority contribution.	Assignment prioritization.	Includes SLA urgency and configured adjustment.
Case Urgency	Case priority contribution.	Case/assignment priority.	Combines work and SLA urgency components.

SAI PRAVEEN

PX / PY / PZ SLA Properties

Property	Purpose	Used in	Handling
pxGoalTime	System-derived goal DateTime.	Work/Assignment SLA.	System managed.
pxDeadlineTime	System-derived deadline DateTime.	Work/Assignment SLA.	System managed.
pySLAGoal	Work-item SLA goal.	Work-level SLA.	System derived.
pySLADecline	Work-item SLA deadline.	Work-level SLA.	System derived.
pySLAName	Identifies associated SLA.	SLA context.	SLA configuration.
pyOverallSLA	Overall case SLA context.	Case SLA.	SLA context.
pyElapsedPastGoal	Elapsed time past goal.	SLA reporting.	Derived.
pyElapsedPastDeadline	Elapsed time past deadline.	SLA reporting.	Derived.
pxUrgencyAssign	Computed assignment urgency.	Assignment priority.	System derived.
pxUrgencyAssignSLA	Assignment SLA urgency contribution.	Assignment priority.	System derived.
pxUrgencyWork	Computed case urgency.	Case priority.	System derived.
pxUrgencyWorkSLA	Case SLA urgency contribution.	Case priority.	System derived.
pxUrgencyWorkStageSLA	Stage SLA urgency contribution.	Stage/case prioritization.	System derived.
pxUrgencyWorkStepSLA	Process/step SLA urgency contribution.	Process/step prioritization.	System derived.
pyUrgencyAssignAdjust	Assignment urgency adjustment.	Assignment priority.	Configured adjustment.
pyUrgencyWorkAdjust	Case urgency adjustment.	Case priority.	Configured adjustment.

SAI PRAVEEN

PEGA FLOW SHAPES

Flow Shape	Purpose	Flow Shape	Purpose
Start	Starts a process or flow.	End	Ends a flow path.
Assignment	Creates a human task for an operator.	Decision	Branches processing based on decision logic.
SubProcess	Invokes another reusable process.	Utility	Performs an automated utility action.
Attach content	Attaches content to the case.	Change to a stage	Changes the case to a specified stage.
Change to a next stage	Moves the case to the next stage.	Change to previous stage	Moves the case to the previously visited stage.
Create case	Creates a new case or child case.	Create PDF	Creates a PDF from configured content.
Generate document	Generates a document as part of case processing.	Persist case	Persists a temporary case as a permanent case.
Post to Pulse	Posts a message to the case Pulse stream.	Push notification	Sends a push notification.
Run Data Transform	Runs a selected Data Transform.	Send Email	Sends an email to configured recipients.
Send notification	Sends a notification through the configured channel.	Send a message	Sends a configured message.
Update a Case	Updates case information.	Search duplicate cases	Searches for possible duplicate cases.
Wait	Pauses processing until a condition, event, or time is met.	Questionnaire	Presents a questionnaire for structured information collection.
Question	Asks a user a question and captures the response.	Question Page	Presents a page of questions for user response.
Load Data Page	Loads data from a configured Data Page.	Save Data Page	Persists changes through a savable Data Page.
Run in background	Runs the action asynchronously in the background.	Agent	Runs a Pega Agent for background/agentic processing.
Gen AI Connect	Connects to a Generative AI rule/service.	Conversation Flow	Starts or invokes a conversational flow.
Custom Event	Triggers processing from a configured custom event.	Annotation	Adds design-time notes without affecting runtime processing.
Split for each	Runs a subprocess for each item in a collection.	Split Join	Runs multiple branches and rejoins them.
Integrator	Invokes an integration asynchronously.	Assignment Service	Invokes a service synchronously from the process.
Assign to Robot Queue	Routes work to a robot queue.	Swim lane	Groups flow elements by role, team, or responsibility.
Send via DocuSign	Sends a document for electronic signature through DocuSign.	Cascading approvals	Runs approval steps in a cascading approval sequence.

SAI PRAVEEN

PEGA ACTIVITY METHODS

Activity step methods and instructions grouped by function

Clipboard / Page Methods

Activity Method / Instruction	Purpose	Used in
Page-Change-Class	Changes clipboard page class.	Clipboard processing
Page-Clear-Messages	Clears page messages.	Validation
Page-Copy	Copies a clipboard page.	Clipboard processing
Page-Merge-Into	Merges pages.	Clipboard processing
Page-New	Creates a clipboard page.	Page creation
Page-Remove	Removes a page.	Page cleanup
Page-Rename	Renames a page.	Clipboard processing
Page-Set-Messages	Sets page messages.	Validation
Page-Unlock	Releases page lock.	Lock management
Page-Validate	Validates a page.	Validation
Load-DataPage	Loads a Data Page.	Data access

SAI PRAVEEN

Persistent Object / Database Methods

Activity Method / Instruction	Purpose	Used in
Commit	Commits database changes.	Persistence
Obj-Browse	Retrieves instances by browse criteria.	Database retrieval
Obj-Delete	Deletes a persistent instance.	Persistence
Obj-Delete-By-Handle	Deletes exact instance by handle.	Persistence
Obj-Filter	Filters results.	Database processing
Obj-List	Retrieves instances.	Database retrieval
Obj-List-View	Retrieves/sorts list-view results.	Reporting
Obj-Open	Opens an instance into clipboard.	Database retrieval
Obj-Open-By-Handle	Opens exact instance by handle.	Database retrieval
Obj-Refresh-and-Lock	Refreshes/opens and locks an instance.	Concurrency
Obj-Save	Saves clipboard data.	Persistence
Obj-Save-Cancel	Reverses uncommitted save/delete.	Transactions
Obj-Sort	Sorts a Page List.	Clipboard processing
Obj-Validate	Validates object data.	Validation
Rollback	Cancels uncommitted changes.	Transaction recovery

SAI PRAVEEN

Activity Control / Instructions

Activity Method / Instruction	Purpose	Used in
Activity-Clear-Status	Clears activity status.	Activity control
Activity-Set-Status	Sets activity status.	Activity control
Activity-End	Ends activity.	Activity control
Activity-List-Add	Adds item to activity list.	List processing
Branch	Runs another activity without returning control.	Activity reuse
Call	Runs activity and returns control.	Activity reuse
Call-Async-Activity	Invokes activity asynchronously.	Async processing
Collect	Collects activity results.	Parallel processing
Exit-Activity	Exits activity.	Activity control
Requestor-Stop	Stops requestor.	Session control
Thread-Clear	Clears thread context.	Thread management
Wait	Pauses processing.	Timing
Queue	Queues processing.	Async/background
Rule	Invokes a rule.	Rule execution
Java	Executes Java in activity step.	Advanced/legacy

Flow-Related Methods

Activity Method / Instruction	Purpose	Used in
Flow-End	Ends a flow execution.	Workflow
Flow-New	Starts a flow execution.	Workflow initiation
TaskStatus-Set	Passes activity result to calling flow.	Workflow integration

SAI PRAVEEN

HTML / XML / Stream Methods

Activity Method / Instruction	Purpose	Used in
Show-HTML	Sends assembled HTML.	UI/HTML
Show-Page	Sends XML page representation.	XML/UI
Show-Property	Sends a property value.	UI response
Show-Stream	Processes JSP/HTML/correspondence/XML stream.	UI/correspondence

Property Methods

Activity Method / Instruction	Purpose	Used in
Apply-DataTransform	Applies a Data Transform.	Data transformation
Property-Remove	Removes property/value.	Clipboard
Property-Seek-Value	Searches for property value.	Data lookup
Property-Set	Sets property value.	Data manipulation
Property-Set-Corr	Sets correspondence content.	Correspondence
Property-Set-HTML	Sets HTML content.	HTML
Property-Set-Messages	Sets validation messages.	Validation
Property-Set-Stream	Sets stream content.	Stream
Property-Set-XML	Sets XML content.	XML
Property-Validate	Validates property.	Validation

SAI PRAVEEN

Connector Methods

Activity Method / Instruction	Purpose	Used in
Connect-Cassandra	Invokes Cassandra integration.	Cassandra
Connect-dotNet	Invokes .NET connector.	External integration
Connect-EJB	Invokes EJB connector.	Enterprise integration
Connect-File	Processes file connector.	File integration
Connect-HBase	Connects to HBase.	HBase
Connect-HTTP	Invokes HTTP connector.	HTTP
Connect-Java	Invokes Java connector.	Java
Connect-JCA	Invokes JCA connector.	Enterprise integration
Connect-JMS	Invokes JMS connector.	Messaging
Connect-MQ	Invokes IBM MQ connector.	Messaging
Connect-REST	Invokes REST connector.	REST
Connect-SOAP	Invokes SOAP connector.	SOAP
Connect-Wait	Waits for connector processing.	Connector processing

Relational Database Methods

Activity Method / Instruction	Purpose	Used in
RDB-Delete	Deletes external DB row.	External DB
RDB-List	Retrieves external DB rows.	External DB
RDB-Open	Opens external DB instance.	External DB
RDB-Save	Saves to external DB.	External DB

SAI PRAVEEN

Structured Parsing Methods

Activity Method / Instruction	Purpose	Used in
Apply-Parse-Delimited	Parses delimited input.	File/text
Apply-Parse-Structured	Parses structured input.	Structured data
Apply-Parse-XML	Parses XML.	XML integration
Map-Structured	Maps structured data.	Data transformation
Parse-Byte-Pos	Processes byte positions.	Parsing
Parse-Char-Pos	Processes character positions.	Parsing
Parse-Fixed-Binary	Parses fixed binary.	Binary/file
Parse-Packed-Decimal	Parses packed decimal.	Legacy parsing
Text-Infer	Evaluates Parse Infer.	Text parsing
Text-Normalize	Evaluates Parse Normalize.	Text normalization

Local Variable / StringBuffer Methods

Activity Method / Instruction	Purpose	Used in
StringBuffer-Append	Appends text.	Activity local variables
StringBuffer-Insert	Inserts text.	Activity local variables
StringBuffer-Reset	Resets string buffer.	Activity local variables

SAI PRAVEEN

Other / Background / Security Methods

Activity Method / Instruction	Purpose	Used in
Assert-No-Invocation	Asserts a rule/method is not invoked.	Testing/framework
DataFlow-Execute	Executes a Data Flow.	Data Flow
DataSet-Execute	Executes Data Set operation.	Data access/integration
Link-Objects	Links persistent objects.	Object relationships
Log-Message	Writes to Pega log.	Diagnostics
Privilege-Check	Checks privilege.	Security
Property-Map-DecisionTable	Maps using Decision Table.	Decisioning
Property-Map-DecisionTree	Maps using Decision Tree.	Decisioning
Property-Map-Value	Maps using value map.	Data mapping
Property-Map-ValuePair	Maps a value pair.	Data mapping
Queue-for-Agent	Queues a page for background processing.	Background processing
Start-Validate	Starts validation compilation.	Rule validation
End-Validate	Ends validation processing	

SAI PRAVEEN

CONSTELLATION DATA MODELS

PEGA CONSTELLATION DATA MODEL

Data Types, Purpose and Available Views



User Reference

The purpose of this data type is to utilize pre-built data pages that return operator or user records. Such as trying to transfer assignment to a case or add a specific operator onto an assignment of the case.

Available Views / Fields

Fields

- Search Box
- Dropdown



Case Reference

The purpose of this data type is to utilize pre-built data pages that return records of case types.

Available Views / Fields

Single Select

Editable

- Autocomplete
- Dropdown

Read Only

- Display Field (Text)

Tables (Radio Buttons)

- Table (Search, Filter, Sort)
- Simple Table
- Search

List (Multi-Select)

Editable

- Dropdown
- Checkbox Group

Read Only

- Display Field (Text)
- Maps

Tables (Checkboxes)

- Table (Search, Filter, Sort)
- Simple Table
- Search
- Table (Search, Filter, Sort)
- Simple Table



Data Reference

The purpose of this data type is to utilize internal or external systems of record. The ability to select one or multiple records. Not intended to capture records.

Available Views / Fields

Single Select

Editable

- Autocomplete
- Dropdown

Read Only

- Display Field (Text)

Tables (Radio Buttons)

- Table (Search, Filter, Sort)
- Simple Table
- Search

List (Multi-Select)

Editable

- Dropdown
- Checkbox Group

Read Only

- Display Field (Text)

Tables (Checkboxes)

- Table (Search, Filter, Sort)
- Simple Table
- Search



Embedded Data

The purpose of this data type is to capture records for an internal or external systems of record. You have the ability to capture records in a list form (tables) or form (single or repeating) and display as read only later on in the case.

Available Views / Fields

Single Select

Read Only

- Form

List

Editable

Tables

- Table (Search, Filter, Sort)
- Simple Table

Read Only

Tables

- Table (Search, Filter, Sort)
- Simple Table

Repeating Views

- Form

Repeating Views

- Form



Query (Read Only)

The purpose of this data type is to display read only data from a query. This could be a single record, or query a list of records (tables).

Available Views / Fields

Single Select

- Add Fields from Object

List

Tables

- Table (Search, Filter, Sort)
- Simple Table



Key Takeaway

Choose the right data type in Constellation based on whether you need to reference users, cases, external data, capture data, or display query results.