

# Rendez-vous

One room, one agent, one artifact — many humans, on the surfaces they already use.

THE WEEK

# The sandbox is now a commodity.

- OpenAI's Agents API: nine sandbox partners, one API call (2026-09-10).
- Every one of them is single-principal — one key, one developer, one session.

**The uncontested ground isn't the sandbox. It's the room around it.**

THE PRIMITIVE

# Room

- Code — RDV-7F3K, a durable handle
- Members — many humans, many surfaces
- Tiers — messenger, email, room-web
- One session — the one agent turn-loop
- One artifact URL — stable, public, live

## THE FIDELITY LADDER

# Three tiers, one room

| TIER | SURFACE             | SENDS                     | RECEIVES                               | LATENCY |
|------|---------------------|---------------------------|----------------------------------------|---------|
| 1    | WhatsApp / Telegram | plain text turns          | final reply + artifact URL, terse      | seconds |
| 2    | Email               | reply-to-thread turns     | per-turn digest + artifact link        | minutes |
| 3    | Laptop web room     | turns, permission answers | full transcript + live artifact iframe | live    |

Telegram and laptop are already two real surfaces.

## RUN 3 — WHAT ACTUALLY HAPPENED

# A real phone, a real operator, one artifact

- 0s** Alice's "new" on real Telegram — room created
- 86.5s** Cold boot — session + artifact ready (4th and final boot budget)
- +~20s** Bob joins from the laptop room view
- live** Attribution confirmed in the stream: [Bob · room-web], [6371794295 · messenger]
- ~33s** Agent finds and edits the artifact, unaided

Curl-verified at every step. Delivery to the phone: operator-confirmed.

# One shape, five independent bugs

1

FOUND LIVE, TONIGHT

the liveness check reads `res.ok`, not `status` — a killed session still answers 200, so resume reports success in 0.7s having resumed nothing

2

queue: `true` omitted → a mid-turn prompt is silently dropped

3

the resume cursor stays frozen → every reply after a resume vanishes

4

an account-pinned inbound route → never fires, filtered out silently

5

the agent proposes to rebuild a Gmail capability it already held

**The first four lost data quietly. The fifth reported success while doing nothing — the correct field was already parsed one function over.**

None crash. All look like working code or correct config. This is evidence you only get by running it.

A DESIGNED POSITION

## Credentials are per-member, not per-room

- A shared room holding one key shares it with everyone who has the code.
- Our position: each member attaches their own tools over rendezvous — nothing inherited.
- Revocation is an unpair, not a key rotation — there was never a shared secret to rotate.

## PHASE 2

# Second brain is a parameter

- Same box. Same filesystem. Same public artifact URL.
- 19 installed adapters, all ACP, verified via `adapter_list`.

```
agent_start({  
  adapter: "codex",  
  model:   "gpt-5.2-codex",  
  sandbox: { provider: "e2b" },  
  appServe: { dir: "...", port: 3210 },  
})
```

Pending the codex proof — not yet run live.

IS THIS A CHEAT?

## Built on our own open-source runtime

- Unmodified. Installed from npm. No fork, no vendored copy.
- The room layer is every line that's new — the judged artifact.
- 8 upstream findings, shipped as a maintainer write-up (docs/UPSTREAM.md).

# What was simulated, what was observed

- Runs 1–2: simulated inbound, no phone, no agentpush workspace. Run 3: real Telegram + web, live.
- Paused e2b boxes expire in 20–60 min — and tonight it happened live: box i7jos6lixgkcfrekmi1vl expired mid-rehearsal, and the room kept advertising its now-dead artifact URL.
- Resume-after-kill and the dead artifact link: fixed after rehearsal, re-proof pending. A room-scoped, proxied artifact URL is now being built — ahead of whisper and multimodal.
- We share the default workspace's Telegram routing — its existing responder route can fire alongside ours on the same message, risking a double reply.
- WhatsApp: not provisioned. No number, no key.
- Phase 2 pairing-back: untested — box-to-broker egress, which side mints the token, post-pairing scope.

# The room is the primitive.

The runtime is a detail.