AgenticData: A Universal Data Comprehension Engine with Schema Inference, Lineage Tracking, and Quality Assurance

Omoshola Owolabi
Researcher – AI/ML
Agentra Labs
omoshola.owolabi@agentralabs.tech

March 2026

Abstract

Data processing tools solve individual format problems—CSV parsers read columns, SQL tools query tables, PDF extractors pull text—but none provides unified *comprehension*: understanding what data means across formats, tracking where it came from, and assessing whether it can be trusted. We present AgenticData, a universal data comprehension engine that addresses three fundamental problems in data management: *schema opacity* (not knowing what fields represent), *lineage blindness* (not tracking data provenance), and *quality silence* (not detecting degradation). The system ingests data from 16 formats with automatic detection at 90–95% confidence, infers schemas with 19 semantic field types (detecting emails, dates, currencies, and geospatial coordinates from raw values), tracks field-level lineage with trust scoring through every transformation, and monitors quality continuously with five-dimensional scoring and statistical anomaly detection. We implement AgenticData in 9,196 lines of Rust across four crates (core library, MCP server, CLI, and FFI bindings), exposing 122 MCP tools through the Model Context Protocol. On representative datasets, CSV ingestion processes 10,000 rows in 82 ms, query filtering scans 10,000 records in 1.8 ms, and spatial radius queries over 1,000 points complete in 25 μs. The `.adat` binary format achieves 132.5 bytes/record with full roundtrip fidelity. All 239 tests (unit, integration, edge case, stress) pass with zero failures.

1 Introduction

The data landscape is fragmented. Organizations routinely process CSV files, JSON APIs, SQL databases, PDF reports, XML feeds, log files, email archives, and geospatial datasets—each requiring a different tool with different semantics [5]. The result is a proliferation of point solutions: `pandas` [6] for tabular data, specialized parsers for each format, separate ETL pipelines for transformation, and ad-hoc scripts for quality checking.

This fragmentation creates three critical problems. First, *schema opacity*: when data arrives from an unfamiliar source, understanding what each field represents requires manual inspection—a process that scales linearly with the number of fields and data sources. Second, *lineage blindness*: once data passes through a transformation pipeline, tracing any output value back to its original source becomes impossible without purpose-built provenance infrastructure [3]. Third, *quality silence*: data quality degrades gradually through null accumulation, outlier injection, and schema drift, but most systems provide no continuous monitoring [7, 1].

The core insight of AgenticData is that these problems share a common root: existing tools *process* data without *understanding* it. A CSV parser knows that column 3 contains strings, but not that those strings are email addresses. An ETL pipeline transforms values but doesn't record which input produced which output. A quality check runs once and is forgotten.

We present AgenticData, a system that treats data comprehension as a first-class capability:

1. Automatically detects data format from content analysis (16 formats, 90–95% confidence)
2. Infers schemas with semantic type detection (email, date, currency, URL, IP address, geospatial)
3. Tracks field-level lineage through every transformation with trust scoring
4. Monitors quality continuously with five-dimensional scoring and anomaly detection
5. Provides 122 MCP tools for AI agent integration via the Model Context Protocol [2]
6. Stores everything in a single portable `.adat` binary file

The remainder of this paper is organized as follows. Section 2 surveys existing data processing tools and their limitations. Section 3 presents the AgenticData architecture. Section 4 reports validated benchmark results. Section 5 describes the MCP integration. Section 7 discusses implications and limitations. Section 8 concludes.



Figure 1: Comparison of data processing paradigms. (a) Traditional tools solve one format each with no cross-cutting capabilities. (b) AgenticData provides a unified pipeline: parse any format, infer schema with semantic types, track lineage, score quality, and redact PII—all in one engine.

2 Background and Related Work

pandas [6] provides the de facto tabular data interface in Python. It reads CSV, Excel, and SQL, but infers only primitive types (int64, float64, object). It cannot detect that a string column contains email addresses or that two columns across tables share a foreign-key relationship.

Apache Spark and **dbt** provide transformation pipelines at scale, but neither tracks field-level provenance. When an output value is incorrect, tracing it to the input that produced it requires external lineage tools.

Great Expectations [1] and **Deequ** provide data quality validation, but require manually-written expectations. They do not infer validation rules from the data itself.

Presidio (Microsoft) detects PII using regex and NLP. It handles structured patterns (email, phone, SSN) but misses context-dependent PII where multiple fields together constitute sensitive information.

Data lineage tools (Apache Atlas, OpenLineage, Marquez) track table-level and column-level lineage in warehouse environments. They require integration with specific execution engines and do not operate on arbitrary file formats.

Table 1 summarizes the comparison across key dimensions.

3 Architecture

AgenticData is implemented as a Rust workspace with four crates: a core library (`agentic-data`, 7,600 LOC), an MCP server (`agentic-data-mcp`, 1,400 LOC), a CLI (`agentic-data-cli`), and FFI bindings (`agentic-data-ffi`).



Figure 2: The five-stage schema inference pipeline. Each stage refines understanding: format detection identifies the parser, parsing extracts structure, type inference adds semantic types, relationship discovery links tables, and storage persists everything with indexes.

3.1 Universal Schema

The `UniversalSchema` type represents any data structure—relational tables, nested documents, key-value pairs, and geospatial data—through a common model. Formally, a schema $S = (N, E)$ consists of typed nodes N (tables, collections) and edges E (relationships between fields). Each node contains a set of `SchemaField` definitions with five properties: inferred type τ, nullability ν, confidence $c \in [0, 1]$, sample values, and optional statistics.

We define 19 semantic field types organized into four categories:

- **Primitives:** `Text`, `Integer`, `Float`, `Boolean`, `Binary`
- **Temporal:** `DateTime`, `Date`, `Time`, `Duration`
- **Structured:** `Object`, `Array`, `Map`, `Enum`, `Uuid`
- **Semantic:** `Email`, `Url`, `IpAddress`, `GeoPoint`, `Currency`

Type inference operates on sample values: if all samples in a column parse as integers, the field is typed as `Integer` with confidence $c = 0.85$. If all samples contain `@` and a domain suffix, the field is typed as `Email` with $c = 0.95$. Declared types (from SQL `CREATE TABLE`) receive $c = 1.0$.

3.2 Format Detection

Format detection uses a priority-ordered pipeline: (1) file extension matching ($c = 0.9$), (2) content-based signature detection—JSON brackets, XML declarations, email headers, iCalendar markers—and (3) statistical delimiter analysis for CSV/TSV. The system supports 16 formats: CSV, TSV, JSON, JSON Lines, XML, YAML, TOML, HTML, SQL, log files, email (`.eml`), calendar (`.ics`), GeoJSON, KML, GPX, and Markdown.

GeoJSON is distinguished from generic JSON by checking for `"type": "FeatureCollection"` before the generic JSON test, achieving $c = 0.92$. Extension-based detection achieves 100% accuracy across all 17 tested extensions.

Table 1: Comparison of data processing tools across key comprehension dimensions.

System	Formats	Schema Inference	Lineage	Quality	PII	Dependencies
pandas [6]	∼10	Primitive types	None	None	None	Python
Apache Spark	Many	Primitive types	Table-level	None	None	JVM cluster
Great Expectations	N/A	None (manual rules)	None	Manual rules	None	Python
Presidio	N/A	None	None	None	Regex + NLP	Python + models
OpenLineage	N/A	None	Column-level	None	None	Integration require
AgenticData	**16 (auto)**	**19 semantic types**	**Field-level**	**5-dim continuous**	**5 types + Luhn**	**None**

3.3 Data Lineage

Every record carries a `LineageChain`—an ordered list of entries recording each transformation with input/output hashes, timestamps, and descriptions. Trust scores decay with each transformation step following:

$$\text{trust}(d) = \max(0.1,\ 1.0 - 0.05d) \tag{1}$$

where d is the number of transformation steps from the original source. Direct source data has trust = 1.0; after 18 transformations, trust reaches the floor of 0.1. This enables downstream consumers to assess data reliability quantitatively.

Seven lineage action types are defined: Ingested, Transformed, Merged, Derived, Corrected, Redacted, and Migrated.

3.4 Quality Engine

The quality engine computes five-dimensional scores, each normalized to $[0, 1]$:

- **Completeness** $= \frac{|\text{non-null values}|}{|\text{total values}|}$
- **Uniqueness** $= \frac{|\text{distinct checksums}|}{|\text{total records}|}$
- **Consistency** $= \frac{|\text{records with modal field count}|}{|\text{total records}|}$
- **Freshness** $= \max(0, 1 - \frac{\Delta t}{720\text{h}})$ (degrades over 30 days)
- **Accuracy** — validation rule compliance (configurable)

The overall score is $Q = \lfloor 100 \cdot \frac{1}{5} \sum_{i=1}^{5} d_i \rfloor$ where d_i are the five dimensions.

Anomaly detection identifies two types: *null spikes* (fields with >50% null rate) and *statistical outliers* (values with z-score > 3). The z-score is computed per numeric field: $z = \frac{|x-\mu|}{\sigma}$ where μ and σ are the field mean and standard deviation.

3.5 Binary File Format

The `.adat` file format stores schemas, data sources, records, lineage chains, and indexes in a single file. The 64-byte header contains magic bytes (`0x41444154`, "ADAT"), format version, section counts, and section offsets.

4 Evaluation

We evaluate AgenticData across four dimensions: format detection accuracy, schema inference quality, quality scoring effectiveness, and throughput. All benchmarks are measured on Apple M4, 24 GB RAM, Rust 1.85.0 compiled with `--release`.

4.1 Format Detection Accuracy

Across 16 formats with representative test inputs, content-based auto-detection achieves 90–95% confidence for structured formats (JSON 95%, XML 95%, SQL 90%, email 90%, calendar 95%) and 75%+ for delimiter-dependent formats (CSV, TSV). GeoJSON is distinguished from generic JSON at 92% confidence. Extension-based detection achieves 100% accuracy across 17 tested extensions. All 15 format detection integration tests pass.

4.2 Schema Inference Accuracy

Type detection correctly identifies all tested type categories from sample values. In validated integration tests across 6 test cases: integer columns detected as `Integer`, float as `Float`, boolean as `Boolean`, email as `Email`, URL as `Url`. Zero misclassifications across all 6 validated cases.

4.3 Quality Scoring Validation

Complete data (20 records, 3 fields, zero nulls) receives $Q = 95$. Data with 75% null values receives measurably lower completeness. Outlier detection correctly identifies a value of 999,999 among 5,000 records centered at 50 ± 10 (z-score $\gg 3$). Null spike detection triggers at >50% null rate.

4.4 Throughput Benchmarks

Table 2 reports throughput measurements from automated stress tests.

File format efficiency: the `.adat` format achieves 132.5 bytes per record including LZ4 compression overhead, with full roundtrip fidelity verified.

5 MCP Tool Surface

AgenticData exposes 122 tools through the Model Context Protocol [2], organized into 24 capability groups across six categories (Table 3). Each tool follows the MCP specification: verb-first descriptions, JSON Schema input



Figure 3: Layout of the `.adat` binary file format. The header stores section offsets. All content sections are LZ4-compressed. Records carry BLAKE3 checksums for integrity verification. At 1,000 records, the format achieves 132.5 bytes/record including compression overhead.

Table 2: Throughput benchmarks on Apple M4, 24 GB RAM. All measurements from automated stress tests with `--release` compilation.

Operation	Scale	Time
CSV ingest	10,000 rows	82 ms
JSON ingest	5,000 objects	847 ms
Query filter (eq)	10,000 records	1.8 ms
Full-text search	10,000 records	2.3 ms
Quality score	5,000 records	2.4 ms
Anomaly detection	5,000 records	1.3 ms
PII scan	1,000 records	2.4 ms
Encrypt + decrypt	1,000 cycles	4.5 ms
Spatial radius query	1,000 points	25 μs
`.adat` write	1,000 records	10.8 ms
`.adat` read	1,000 records	5.4 ms



Figure 4: Throughput benchmarks (lower is better). Sub-millisecond spatial queries. All operations complete in under 100 ms at tested scales.

validation, and two-tier error handling (protocol errors via JSON-RPC codes, tool execution errors via `isError: true`).

6 Security

6.1 Field-Level Encryption

AgenticData supports field-level encryption using per-field key derivation. A master key K is processed through BLAKE3 keyed hashing with the field name f as context: $K_f = \text{BLAKE3}_K(f)$, producing a unique encryption key per field. This enables encrypting sensitive columns (e.g., SSN) while leaving non-sensitive columns (e.g., city) queryable.

Category	Groups	Tools
Comprehension	4	21
Transformation	3	16
Quality	3	16
Intelligence	4	20
Security	2	10
Spatial + Other	5	39
Total	**24**	**122**

Table 3: MCP tool distribution across capability categories.

6.2 PII Detection and Redaction

The redaction engine detects five PII categories: email addresses (pattern: `@` + domain), phone numbers (10–15 digits), Social Security Numbers (NNN-NN-NNNN format), credit card numbers (13–19 digits validated by Luhn algorithm [4]), and IP addresses (N.N.N.N octet format). Four redaction methods are supported: masking (`[REDACTED]`), type-appropriate placeholders, cryptographic hashing, and field removal.

The Luhn checksum prevents false positive credit card detection: the digit string must satisfy $\sum_i d_i \equiv 0 \pmod{10}$ where alternating digits are doubled and reduced.

7 Discussion

AgenticData addresses the fragmentation problem by providing a single engine for format detection, schema inference, lineage tracking, quality monitoring, and security—capabilities that currently require assembling 5–10 separate tools. The MCP integration enables any AI agent to leverage these capabilities through a standard protocol.

Limitations. The current implementation uses in-memory storage; production deployments with datasets exceeding available RAM will require streaming ingestion. Binary format parsers (Excel, PDF, Word) require external libraries not yet integrated. PII detection uses pattern matching; context-dependent PII requires LLM-assisted

detection for full coverage.

Comparison with AgenticMemory. AgenticData and AgenticMemory [2] serve complementary roles. Memory stores the agent's cognitive state (beliefs, decisions, reasoning chains) as a navigable graph. Data comprehends external information (files, databases, APIs) with schema inference and quality assurance. The two systems share design principles—single-file binary format, Rust core, MCP interface, zero dependencies—but operate on fundamentally different domains.

Future work. Planned extensions include streaming ingestion for large datasets, binary format parsers (Parquet, Avro, Protocol Buffers), federated query execution across registered sources, and append-only storage with content-addressed blocks.

8 Conclusion

We have presented AgenticData, a universal data comprehension engine that unifies format detection, schema inference, lineage tracking, quality monitoring, and security in a single system. The implementation comprises 9,196 lines of Rust across 78 source files, 122 MCP tools organized in 24 capability groups, and 239 tests with zero failures. The `.adat` binary format provides portable, compressed, integrity-verified storage in a single file. By exposing data comprehension as MCP tools, AgenticData enables AI agents to understand, transform, and validate arbitrary data without custom integration—a capability that is fundamental to building agents that can operate reliably in data-rich environments.

References

[1] Ziawasch Abedjan, Xu Chu, Dong Deng, Raul Castro Fernandez, Ihab F Ilyas, Mourad Ouzzani, Paolo Papotti, Michael Stonebraker, and Nan Tang. Detecting data errors: Where are we and what needs to be done? In *Proceedings of the VLDB Endowment*, 2016.

[2] Anthropic. Model context protocol specification. 2024.

[3] Peter Buneman, Sanjeev Khanna, and Wang-Chiew Tan. Why and where: A characterization of data provenance. *International Conference on Database Theory*, 2001.

[4] Peter Christen. Data matching: Concepts and techniques for record linkage, entity resolution, and duplicate detection. *Springer*, 2012.

[5] Alon Halevy, Anand Rajaraman, and Joann Ordille. Data integration: The teenage years. *Proceedings of the VLDB Endowment*, 2006.

[6] Wes McKinney. Data structures for statistical computing in Python. *Proceedings of the 9th Python in Science Conference*, 2010.

[7] Erhard Rahm and Hong Hai Do. Data cleaning: Problems and current approaches. *IEEE Data Engineering Bulletin*, 23(4):3–13, 2000.