

Using the agents-repo CLI

`npx agents-repo` — install packages into your project

What it does

Official installer for the open registry.

It writes install-target files into **your** project (or global home with `-g`), plus `agents.json` and `agents-lock.json`.

It does **not** author registry packages (that is the registry deck).

Install targets

Marketing names (not IDs):

GitHub Copilot, Cursor, Claude Code, OpenAI Codex

Canonical IDs live in registry `specs/install-targets.md`. Use those IDs on `--targets`.

Quick start

```
npx agents-repo@latest --help  
npx agents-repo@latest init --targets cursor  
npx agents-repo@latest install
```

In a fresh project without install markers, pass `--targets` or `init` may exit `3`. `--target` remains an alias for `--targets`.

init

Creates or updates project config for one or more install targets.

```
npx agents-repo init --targets github-copilot claude-code openai-codex
```

See `docs/commands/init.md`.

install

Fetches catalog + version manifest, verifies SHA-256, extracts ZIPs into target paths.

After install, commit **agents-lock.json** (and **agents.json** when it changes).

See `docs/commands/install.md`.

`agents.json`

Project config: registry URL, selected packages, install targets.

Override the catalog with `AGENTS_REPO_REGISTRY_URL` or the URL in `agents.json`. Default org setups use **registry-proxy** with a `v2.x` ref.

agents-lock.json

Lockfile for reproducible installs (resolved versions and checksums).

Commit it. Repositories that commit a catalog (org hub **.github** and **registry** package authoring) run `agents:verify` in PR baseline when agent paths change. Run local `agents:ci` when you need full lock artifact verification.

Everyday commands

Command	Use
<code>add-target</code>	Add another install target
<code>update</code>	Refresh within lock/semver policy
<code>remove</code>	Uninstall a package
<code>search</code>	Find packages in the catalog
<code>list</code>	Show installed / configured packages

More commands

Command	Use
<code>suggest-agents</code>	Suggest packages for a prompt
<code>doctor</code>	Diagnose project/CLI problems
<code>ci</code>	Lockfile / extract drift check
<code>targets</code>	List install target ids

Docs: `docs/commands/<name>.md` .

Registry URL

Default production fetch goes through registry-proxy (cached, GET-only).

Point at GitHub or another base in development. See `org docs/ecosystem.md` and the proxy architecture deck for how fetches are cached.

Contributors

Changing CLI behavior: `docs/development.md` , `docs/ARCHITECTURE.md` ,
`.github/CONTRIBUTING.md` .

Validation typically: `env:check` , `lint:all` , `test` , `typecheck` ,
`check:secrets` .

This deck stays at **usage** level.

Not this deck

- Package authoring → registry slides
- Worker path mapping → registry-proxy slides

Links

- <https://agents-repo.org>
- Command docs under `docs/commands/`
- Org contributing workflow PDF in `.github`

Next

`npx agents-repo@latest init --targets <id>` then `install`.
Run `doctor` if something looks wrong.