

Webapp infrastructure

Browse, search, and download the registry

agents-repo.org

Purpose

Vite + React + TypeScript UI for the agents-repo catalog.

Users browse packages, read docs, and download artifacts. The site is **not** the registry source of truth — that is `agents-repo/registry`.

Stack (summary)

- React 19, Vite, TypeScript
- Bootstrap 5.3 + SCSS (`src/styles/bootstrap-theme.scss`)
- React Router, PWA (`vite-plugin-pwa`)
- Catalog cache: in-memory LRU + persistent browser storage

Details: `docs/styling-and-technology.md` .

Styling policy

- App styles in **SCSS only** (no new app `.css` files)
- Theme tokens in `bootstrap-theme.scss`
- Shell: `src/index.scss` , `src/App.scss`

Do not change the stack without updating the decision docs in the same PR.

Catalog fetch

Production default: **registry-proxy** (cached GitHub access).

Index: `packages/index.json`

Package pages: `packages/<namespace>/<id>/detail.json`

GitHub tree links may still point at the registry repo for browsing.

Env overrides

`VITE_*` settings select registry base URL, GitHub repo URL, and site origin.

Local and preview can point at GitHub or another base. Production uses the proxy `?ref=v2.x` line unless overridden.

See `docs/deployment.md` and README **Registry Source Configuration**.

build:pages

`npm run build:pages` produces the GitHub Pages `dist/` :

- SPA `404.html` copy of `index.html`
- `.nojekyll`

Then `test:crawl-files` checks sitemap/robots against the production origin.

Site vs Pages target

- **agents-repo.org** — custom domain users should use
- **agents-repo.github.io** — automated Pages deploy target, not a dev repo

Develop in **webapp**. Never treat `.github.io` as the source of changes.

Deploy vs release

- **Deploy Webapp:** path-filtered push to `main` → lint, test, `build:pages`, publish `dist/`
- **Release:** `semantic-release` tags; does **not** deploy Pages

Docs-only merges do not redeploy. Agents must not merge to `main`.

Cache and PWA (high level)

- Catalog index: 24h app TTL + conditional GET (ETag / Last-Modified)
- Service worker: HTML NetworkFirst (1-day offline); hashed assets precached
- HTTP Cache-Control : GitHub Pages defaults (typically max-age=600)
- Chat JSON/markdown: IndexedDB LRU (version-pinned URLs skip short TTL)

Privacy/SEO: docs/privacy.md , docs/seo.md . Not an a11y deep dive here.

Contributor validation

Typical PR baseline (see CONTRIBUTING):

- `env:check` , `lint:all` , `test` , `typecheck`
- `build:pages` , `test:crawl-files`
- UI/a11y: `test:a11y` (local; not always in PR CI)

Plus `slides:check` when you touch this deck.

Out of scope for this deck

- Click-through UI tour
- Accessibility deep dive (`docs/accessibility.md`)
- A presentations hub on agents-repo.org (future)

Links

- `docs/styling-and-technology.md`
- `docs/deployment.md`
- `docs/development.md`
- Org ecosystem PDF in `.github` `docs/slides/`

Next

Read `docs/deployment.md` , then `docs/development.md` for local setup.