

Tutorial 2: Analysis of Algorithm and Stack and Queue

- Q1** The function `subset()` below takes two linked lists of integers and determines whether the first is a subset of the second. Give the worst-case running time of `subset` as a function of the lengths of the two lists. When will this worst case happen?

```
1  typedef struct _listnode{
2      int item;
3      struct _listnode *next;
4  } ListNode;
5
6  //Check whether integer X is an element of linked list Q
7  int element (int X, ListNode* Q)
8  {
9      int found; //Flag whether X has been found
10     found = 0;
11     while ( Q != NULL && !found) {
12         found = Q->item == X;
13         Q = Q->next;
14     }
15     return found;
16 }
17
18 // Check whether L is a subset of M
19 int subset (ListNode* L, ListNode* M)
20 {
21     int success; // Flag whether L is a subset so far
22     success = 1;
23     while ( L != NULL && success) {
24         success = element(L->item, M);
25         L = L->next;
26     }
27     return success;
28 }
```

- Q2** Find the number of `printf` used in the following functions. Write down its time complexity in Θ notation in terms of N .

```
1  void Q2a (int N)
2  {
3      int j, k;
4      for (j=1; j<=N; j*=3)
5          for(k=1; k<=N; k*=2)
6              printf("SC1007\n");
7  }
```

```

1  void Q2b (int N)
2  {
3      int i;
4      if(N>0)
5      {
6          for(i=0;i<N;i++)
7              printf("SC1007\n");
8          Q2b(N-1);
9          Q2b(N-1);
10     }
11 }

```

Q3 Given the precedence of some operators,

Operators	Precedence
*, /, %	highest
+, -	
<<, >>	
&&	
=	lowest

- convert an infix expression, $x = a + b * c \% d >> e$, to a postfix expression
- convert a prefix expression, $= y \&\& << ab >> c + de$, to an infix expression
- convert a postfix expression, $abc * d \% + e >> =$, to a prefix expression