

# **CZ2007 Introduction to Database Systems (Week 4)**

## **Topic 4: Third Normal Form (1)**



---

## **Copyright Notice**

All course materials (including and not limited to lecture slides, handouts, recordings, assessments and assignments), are solely for your own educational purposes at NTU only. All course materials are protected by copyright, trademarks or other rights.

All rights, title and interest in the course materials are owned by, licensed to or controlled by the University, unless otherwise expressly stated. The course materials shall not be uploaded, reproduced, distributed, republished or transmitted in any form or by any means, in whole or in part, without written approval from the University.

You are also not allowed to take any photograph, video recording, audio recording or other means of capturing images and/or voice of any of the course materials (including and not limited to lectures, tutorials, seminars and workshops) and reproduce, distribute and/or transmit in any form or by any means, in whole or in part, without written permission from the University.

Appropriate action(s) will be taken against you (including and not limited to disciplinary proceedings and/or legal action) if you are found to have committed any of the above or infringed copyright.

# This Lecture

- 3NF 
- 3NF Decomposition

# Third Normal Form (3NF)

- A relaxation of BCNF that
  - Is less strict
  - Allows decompositions that **always** preserve functional dependencies

# 1NF, 2NF

- **Key-attribute**: An attribute in a multi-attribute key
- Key-attribute(s) = Partial key or part of a key
- 1NF: All attributes have atomic values
- 2NF: Every non-key attribute is dependent on the whole of **EVERY** candidate key
  - Even so, may still have additional dependencies, such as (non-key-attribute X)  $\rightarrow$  (non-key-attribute Y) in relation

# Third Normal Form (3NF)

- Definition: A table satisfies 3NF, if and only if for every non-trivial  $X \rightarrow Y$ 
  - Either X contains a key
  - Or each attribute in Y is contained in a key
- Example:
  - Given FDs:  $C \rightarrow B$ ,  $AB \rightarrow C$ ,  $BC \rightarrow C$
  - Keys: {AB}, {AC}
  - $AB \rightarrow C$  is OK, since **AB** is a key of R
  - $C \rightarrow B$  is OK, since **B** is in a key of R
  - $BC \rightarrow C$  is OK, since **C** is in AC and in BC (it is also trivial)
  - So R is in 3NF

R	A	B	C

# 3NF, BCNF

- 3NF: 2NF + all key-attributes determined **ONLY** by candidate keys (in whole or in part)
  - (non-key-attribute X)  $\rightarrow$  (non-key-attribute Y) cannot exist anymore, RHS must be key attribute in 3NF
  - But candidate keys may have **overlapping** attributes
  - May result in key-attribute(s) of one key depends on key-attribute(s) of another key (this dependency is eliminated in BCNF)
- BCNF: In all dependencies (FDs), LHS must contain key (cannot depend on partial key)

# Third Normal Form (3NF)

- Definition: A table satisfies 3NF, if and only if for every non-trivial  $X \rightarrow Y$ 
  - Either X contains a key
  - Or each attribute in Y is contained in a key
- Another Example:
  - Given FDs:  $A \rightarrow B$ ,  $B \rightarrow C$
  - Keys: {A}
  - $A \rightarrow B$  is OK, since **A** is a key of R
  - $B \rightarrow C$  is not OK, since **C** is NOT in a key of R, and it is NOT in the left hand side
  - So R is NOT in 3NF

R	A	B	C




# This Lecture

- 3NF
- 3NF Decomposition 


# 3NF Decomposition

- Given: A table NOT in 3NF
- Objective: Decompose it into smaller tables that are in 3NF
- Example
  - Given:  $R(A, B, C, D)$
  - FDs:  $AB \rightarrow C$ ,  $C \rightarrow B$ ,  $A \rightarrow D$
  - Keys:  $\{AB\}$ ,  $\{AC\}$
  - **R is not in 3NF, due to  $A \rightarrow D$**
  - 3NF decomposition of R:  
 $R_1(A, B, C)$ ,  $R_2(A, D)$



# 3NF Decomposition Algorithm

- Given: A table R, and a set S of FDs
  - e.g.,  $R(A, B, C, D)$   
 $S = \{A \rightarrow BD, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Step 1: Derive a **minimal basis** of S
  - e.g., a minimal basis of S is  $\{A \rightarrow B, A \rightarrow C, C \rightarrow D\}$
- Step 2: In the minimal basis, combine the FDs whose left hand sides are the same
  - e.g., after combining  $A \rightarrow B$  and  $A \rightarrow C$ , we have  $\{A \rightarrow BC, C \rightarrow D\}$
- Step 3: Create a table for each FD remained
  - $R_1(A, B, C), R_2(C, D)$
- Step 4: If none of the tables contain a key of the original table R, create a table that contains a key of R
- Step 5: Remove redundant tables (schema is a subset of another)



# Minimal Basis

- Given a set  $S$  of FDs, the **minimal basis** of  $S$  is a **simplified** version of  $S$
- Previous example:
  - $S = \{A \rightarrow BD, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
  - A minimal basis:  $\{A \rightarrow B, A \rightarrow C, C \rightarrow D\}$
- How simplified?
- Three conditions.
- **Condition 1: For any FD in the minimal basis, its right hand side has only one attribute.**
- Example in  $S$ :  $A \rightarrow BD$  does not satisfy this condition
- That is why  $A \rightarrow BD$  is not in the minimal basis

# Minimal Basis

- Previous example:
  - $S = \{A \rightarrow BD, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
  - A minimal basis:  $\{A \rightarrow B, A \rightarrow C, C \rightarrow D\}$
- Condition 2: No FD in the minimal basis is redundant.
- That is, no FD in the minimal basis can be derived from the other FDs.
- Example in S:  $BC \rightarrow D$  can be derived from  $C \rightarrow D$
- That is why  $BC \rightarrow D$  is not in the minimal basis

# Minimal Basis

- Previous example:
  - $S = \{A \rightarrow BD, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
  - A minimal basis:  $\{A \rightarrow B, A \rightarrow C, C \rightarrow D\}$
- Condition 3: For each FD in the minimal basis, none of the attributes on the left hand side is redundant
- That is, for any FD in the minimal basis, if we remove an attribute from the left hand side, then the resulting FD is a new FD that cannot be derived from the original set of FDs
- Example:
  - S contains  $AB \rightarrow C$
  - If we remove B from the left hand side, we have  $A \rightarrow C$
  - $A \rightarrow C$  can be derived from S, as  $\{A\}^+ = \{ABDC\}$
  - This indicates that  $A \rightarrow C$  is “hidden” in S
  - Hence, we can replace  $AB \rightarrow C$  with  $A \rightarrow C$ , as  $A \rightarrow C$  is “simpler”
  - This is why  $AB \rightarrow C$  is not in the minimal basis

# Algorithm for Minimal Basis

- Given: a set  $S$  of FDs
- Example:  $S = \{A \rightarrow BD, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Step 1: Transform the FDs, so that each right hand side contains only one attribute
- Result:  $S = \{A \rightarrow B, A \rightarrow D, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Reason:
  - Condition 1 for minimal basis:  
The right hand side of each FD contains only one attribute

# Algorithm for Minimal Basis

- Result of Step 1:
  - $S = \{A \rightarrow B, A \rightarrow D, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Step 2: Remove redundant FDs
- Is  $A \rightarrow B$  redundant?
- i.e., is  $A \rightarrow B$  implied by other FDs in  $S$ ?
- Let's check
- Without  $A \rightarrow B$ , we have  $\{A \rightarrow D, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Given those FDs, we have  $\{A\}^+ = \{AD\}$ , which does not contain  $B$
- Therefore,  $A \rightarrow B$  is not implied by the other FDs



# Algorithm for Minimal Basis

- Result of Step 1:
  - $S = \{A \rightarrow B, A \rightarrow D, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Continue Step 2: Remove redundant FDs
- Is  $A \rightarrow D$  redundant?
- i.e., is  $A \rightarrow D$  implied by other FDs in  $S$ ?
- Let's check
- Without  $A \rightarrow D$ , we have  $\{A \rightarrow B, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Given those FDs, we have  $\{A\}^+ = \{ABCD\}$ , which contains  $D$
- Therefore,  $A \rightarrow D$  is implied by the other FDs
- Hence,  $A \rightarrow D$  is redundant and should be removed
- Result:  $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$

# Algorithm for Minimal Basis

- Result of the last step:
  - $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Continue Step 2: Remove redundant FDs
- Is  $AB \rightarrow C$  redundant?
- i.e., is  $AB \rightarrow C$  implied by other FDs in  $S$ ?
- Let's check
- Without  $AB \rightarrow C$ , we have  $\{A \rightarrow B, C \rightarrow D, BC \rightarrow D\}$
- Given those FDs, we have  $\{AB\}^+ = \{AB\}$ , which does not contain  $C$
- Therefore,  $AB \rightarrow C$  is NOT implied by the other FDs
- Hence,  $AB \rightarrow C$  is not redundant and should not be removed

# Algorithm for Minimal Basis

- Result of the last step:
  - $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Continue Step 2: Remove redundant FDs
- Is  $C \rightarrow D$  redundant?
- i.e., is  $C \rightarrow D$  implied by other FDs in  $S$ ?
- Let's check
- Without  $C \rightarrow D$ , we have  $\{A \rightarrow B, AB \rightarrow C, BC \rightarrow D\}$
- Given those FDs, we have  $\{C\}^+ = \{C\}$ , which does not contain  $D$
- Therefore,  $C \rightarrow D$  is NOT implied by the other FDs and should not be removed

# Algorithm for Minimal Basis

- Result of the last step:
  - $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D, BC \rightarrow D\}$
- Continue Step 2: Remove redundant FDs
- Is  $BC \rightarrow D$  redundant?
- i.e., is  $BC \rightarrow D$  implied by other FDs in  $S$ ?
- Let's check
- Without  $BC \rightarrow D$ , we have  $\{A \rightarrow B, AB \rightarrow C, C \rightarrow D\}$
- Given those FDs, we have  $\{BC\}^+ = \{BCD\}$ , which contains  $D$
- Therefore,  $BC \rightarrow D$  is implied by the other FDs
- Hence,  $BC \rightarrow D$  is redundant and should be removed
- Result:  $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D\}$

# Algorithm for Minimal Basis

- Result of Step 2:
  - $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D\}$
- Step 3: Remove redundant attributes on the left hand side (lhs) of each FD
- Only  $AB \rightarrow C$  has more than one attribute on the lhs
- Let's check
- Is A redundant?
- If we remove A, then  $AB \rightarrow C$  becomes  $B \rightarrow C$
- Whether this removal is OK depends on whether  $B \rightarrow C$  is “hidden” in S already
- If  $B \rightarrow C$  is “hidden” in S, then the removal of A is OK, (since the removal does not add extraneous information into S)
- Is  $B \rightarrow C$  “hidden” in S?
- Check: Given S, we have  $\{B\}^+ = \{B\}$ , which does NOT contain C
- Therefore,  $B \rightarrow C$  is not “hidden” in S, and hence, A is NOT redundant

# Algorithm for Minimal Basis

- **Result** of Step 2:
  - $S = \{A \rightarrow B, AB \rightarrow C, C \rightarrow D\}$
- **Step 3: Remove redundant attributes on the left hand side (lhs) of each FD**
- Only  $AB \rightarrow C$  has more than one attribute on the lhs
- Let's check
- Is B redundant?
- If we remove B, then  $AB \rightarrow C$  becomes  $A \rightarrow C$
- Whether this is OK depends on whether  $A \rightarrow C$  is “hidden” in S
- Is  $A \rightarrow C$  “hidden” in S?
- Check: Given S, we have  $\{A\}^+ = \{ABCD\}$ , which contains C
- Therefore,  $A \rightarrow C$  is “hidden” in S
- Hence, we can simplify  $AB \rightarrow C$  to  $A \rightarrow C$
- Final minimal basis:  $S = \{A \rightarrow B, A \rightarrow C, C \rightarrow D\}$

---

To continue in

**Topic 4: Third Normal Form (2)**