

# SC2207/CZ2007 Introduction to Database Systems (Week 2)

## Topic 2: Functional Dependencies (1)



---

## **Copyright Notice**

All course materials (including and not limited to lecture slides, handouts, recordings, assessments and assignments), are solely for your own educational purposes at NTU only. All course materials are protected by copyright, trademarks or other rights.

All rights, title and interest in the course materials are owned by, licensed to or controlled by the University, unless otherwise expressly stated. The course materials shall not be uploaded, reproduced, distributed, republished or transmitted in any form or by any means, in whole or in part, without written approval from the University.

You are also not allowed to take any photograph, video recording, audio recording or other means of capturing images and/or voice of any of the course materials (including and not limited to lectures, tutorials, seminars and workshops) and reproduce, distribute and/or transmit in any form or by any means, in whole or in part, without written permission from the University.

Appropriate action(s) will be taken against you (including and not limited to disciplinary proceedings and/or legal action) if you are found to have committed any of the above or infringed copyright.

# This Lecture

- Data anomalies ←
- Functional dependencies
- Armstrong's axioms

# Database Design

- Applications → ER diagrams → tables
- It works in general, but sometimes things may go wrong:
  - ER diagrams may not be well designed
  - Not all requirements can be represented in ER diagram
  - Conversion from ER diagrams to tables may not be properly done
- As a result, resulting tables may have various problems

# Data Anomalies

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- Primary key of the table:  
(NRIC, PhoneNumber), one composite key
- There are several **anomalies** in the table
- First, redundancy:
  - Alice's address is duplicated, attribute values appear multiple times in different rows (columns) in table

# Data Anomalies

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- Primary key of the table:  
(NRIC, PhoneNumber), one composite key
- Second, update anomalies:
  - We may accidentally update one of Alice's addresses, leaving the other unchanged

# Data Anomalies

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- Primary key of the table:  
(NRIC, PhoneNumber), one composite key
- Third, deletion anomalies:
  - ❑ Bob no longer uses a phone
  - ❑ Can we remove Bob's phone number?
  - ❑ No. (Note: Primary key attributes cannot be NULL)

# Data Anomalies

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- Primary key of the table:  
(NRIC, PhoneNumber), one composite key
- Fourth, insertion anomalies:
  - Name = Cathy, NRIC = 9394, HomeAddress = YiShun
  - Can we insert this information into the table?
  - No. (Note: Primary key attributes cannot be NULL)



# Normalization

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- How do we get rid of those anomalies?
- **Normalize** the table (i.e., decompose it)

Name	<u>NRIC</u>	HomeAddress
Alice	1234	Jurong East
Bob	5678	Pasir Ris

<u>NRIC</u>	<u>PhoneNumber</u>
1234	67899876
1234	83848384
5678	98765432


# Effects of Normalization

Name	<u>NRIC</u>	HomeAddress
Alice	1234	Jurong East
Bob	5678	Pasir Ris

<u>NRIC</u>	<u>PhoneNumber</u>
1234	67899876
1234	83848384
5678	98765432

- Duplication?
  - No. (Alice's address is no longer duplicated.)
- Update anomalies?
  - No. (There is only one place where we can update the address of Alice)
- Deletion anomalies?
  - No. (We can freely delete Bob's phone number)
- Insertion anomalies?
  - No. (We can insert an individual without a phone)

# This Lecture

- Data anomalies
- Functional dependencies 
- Armstrong's axioms

# Road Map

- We will discuss
  - How to decide whether a table is good
  - If a table is not good, how to normalize it
- The plan
  - First, basic concepts (e.g., functional dependencies)
  - Second, reasoning with basic concepts
  - Finally, the real meat (e.g., normalization)

# Functional Dependencies: Intuition

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- Why was this table bad?
- It has a lot of anomalies
- Why does it have those anomalies?
- Intuitive answer: It contains a bad combination of attributes

# Functional Dependencies: Intuition

Name	<u>NRIC</u>	<u>PhoneNumber</u>	HomeAddress
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- In general, how do we know whether a combination of attributes is bad?
- We need to check the **correlations** among those attributes
- What kind of correlations?
- **Functional dependencies (FD)**

# Functional Dependencies (FD)

- Consider two attributes in practice: NRIC, Name
- Given an NRIC, can we always uniquely identify the name of the person?
- Theoretically yes -- We just need help from ICA
- Given a Name, can we always uniquely identify the NRIC of the person
- In general no -- Different people can have the same name
- Therefore
  - NRIC determines Name, but not vice versa
  - Functional dependencies:  
NRIC  $\rightarrow$  Name, but not Name  $\rightarrow$  NRIC

# Functional Dependencies (FD)

- Consider three attributes in practice:
  - StudentID, Name, Address, PostalCode
- Functional Dependencies:
  - $\text{StudentID} \rightarrow \text{Name, Address, PostalCode}$
  - $\text{Address} \rightarrow \text{PostalCode}$



# Formal Definition of FD

- Attributes  $A_1, A_2, \dots, A_m, B_1, B_2, \dots, B_n$
- $A_1 A_2 \dots A_m \rightarrow B_1 B_2 \dots B_n$
- Meaning: There do not exist two objects that
  - Have the same values on  $A_1, A_2, \dots, A_m$
  - but different values on  $B_1, B_2, \dots, B_n$
- Previous example: NRIC  $\rightarrow$  Name
- Meaning: There do not exist two persons that
  - have the same values on NRIC
  - but different values on Name

Name	Category	Color	Department	Price
Gizmo	Gadget	Green	Toys	49
Tweaker	Gadget	Black	Toys	99
Gizmo	Stationary	Green	Office Supplies	59

■ Functional dependencies that hold on the table:

- Category  $\rightarrow$  Department ✓
- Category, Color  $\rightarrow$  Price ✓
- Price  $\rightarrow$  Color ✓
- Name  $\rightarrow$  Color ✓
- Department, Category  $\rightarrow$  Name ✗
- Color, Department  $\rightarrow$  Name, Price, Category ✓

# Where Do FDs Come From?

- From common sense, knowledge in real world
- From application's requirements
- Example
  - Purchase( CustomerID, ProductID, ShopID, Price, Date )
  - Requirement: Each shop can sell at most one product
  - FD implied: **ShopID → ProductID**

# Where Do FDs Come From?

■ F	<b>ShopID</b>	<b>ProductID</b>	known	<b>ShopID</b>	<b>ProductID</b>
■ F	S1	P1		S1	P1
■ F	S1	P2	s re	S2	P1

## ■ Example

- Purchase( CustomerID, ProductID, ShopID, Price, Date )
- Requirement: Each shop can sell at most one product
- FD implied: **ShopID** → **ProductID**

# Where Do FDs Come From?


## ■ Example

- ❑ Purchase( CustomerID, ProductID, ShopID, Price, Date )
- ❑ Requirement: No two customers buy the same product
- ❑ FD implied: **ProductID → CustomerID**


# Where Do FDs Come From?

## ■ Example

- ❑ Purchase( CustomerID, ProductID, ShopID, Price, Date )
- ❑ Requirement: No two customers buy the same product
- ❑ FD implied: **ProductID** → **CustomerID**



CustomerID	ProductID
C1	P1
C2	P1




CustomerID	ProductID
C1	P1
C1	P2

# Where Do FDs Come From?

## ■ Example

- ❑ Purchase( CustomerID, ProductID, ShopID, Price, Date )
- ❑ Requirement: No shop will sell the same product to the same customer on the same date at two different prices
- ❑ FD implied:  
CustomerID, ProductID, ShopID, Date → Price


# Where Do FDs Come From?



CustomerID	ProductID	ShopID	Date	Price
C1	P1	S1	D1	99
C1	P1	S1	D1	33

■ E:

- Purchase( CustomerID, ProductID, ShopID, Price,



CustomerID	ProductID	ShopID	Date	Price
C1	P1	S1	D1	99
C2	P1	S1	D1	33

□

different prices

- FD implied:


CustomerID, ProductID, ShopID, Date → Price



# Roadmap

- To decide whether or not a table is good, we need to examine the relationships among attributes, i.e., the FDs
- Now we know what FDs are, and where they are from
- How do we use FDs to check whether a table is good?
- We need to learn how to **reason** with FDs

# This Lecture

- Data anomalies
- Functional dependencies
- Armstrong's axioms 

# Reasoning with FDs

- How to **reason** with FDs
- Example:
  - Given:  
NRIC  $\rightarrow$  Address,      Address  $\rightarrow$  PostalCode
  - We have: NRIC  $\rightarrow$  PostalCode
- In general
  - Given  $A \rightarrow B, B \rightarrow C$
  - We always have  $A \rightarrow C$
- We will discuss how we can do this kind of derivations

# Reasoning with FDs

- Why do we care about such derivations?
- Answer: it is needed in deciding whether a table is “bad” or not
- Intuitive explanation:
  - Suppose that  $A \rightarrow C$  is an FD that makes a table “bad”
  - But we are only given  $A \rightarrow B$  and  $B \rightarrow C$
  - If we do not know that  $A \rightarrow C$  is implied by  $A \rightarrow B$  and  $B \rightarrow C$ , then we may misjudge the table to be a “good” one

# Reasoning with FDs

- Armstrong's Axioms
  - Three axioms for FD reasoning
  - Easy to understand, but not easy to apply

# Armstrong's Axioms

- Axiom of Reflexivity

- A set of attributes  $\rightarrow$  A **subset** of the attributes

- Example

- **NRIC**, Name  $\rightarrow$  **NRIC**
  - StudentID, **Name**, **Age**  $\rightarrow$  **Name**, **Age**
  - **ABCD**  $\rightarrow$  **ABC**
  - **ABCD**  $\rightarrow$  **BCD**
  - **ABCD**  $\rightarrow$  **AD**

# Armstrong's Axioms

## ■ Axiom of Augmentation

- Given  $A \rightarrow B$
- We always have  $AC \rightarrow BC$ , for any  $C$

## ■ Example

- If  $NRIC \rightarrow Name$
- Then  $NRIC, Age \rightarrow Name, Age$
- and  $NRIC, Salary, Weight \rightarrow Name, Salary, Weight$
- and  $NRIC, Addr, Postal \rightarrow Name, Addr, Postal$

# Armstrong's Axioms

- Axiom of Transitivity

- Given  $A \rightarrow B$  and  $B \rightarrow C$
- We always have  $A \rightarrow C$

- Example

- If  $NRIC \rightarrow Addr$ , and  $Addr \rightarrow Postal$
- Then  $NRIC \rightarrow Postal$



# Reasoning with FDs

- Given  $A \rightarrow B$ ,  $BC \rightarrow D$
- Can you prove that  $AC \rightarrow D$ ?
- Proof
  - Given  $A \rightarrow B$ , we have  $AC \rightarrow BC$  (Augmentation)
  - Given  $AC \rightarrow BC$  and  $BC \rightarrow D$ , we have  $AC \rightarrow D$  (Transitivity)

# Reasoning with FDs

- Given  $A \rightarrow B, D \rightarrow C$
- Can you prove that  $AD \rightarrow BC$ ?
- Proof
  - Given  $A \rightarrow B$ , we have  $AD \rightarrow BD$  (Augmentation)
  - Given  $AD \rightarrow BD$ , we have  $AD \rightarrow B$  (Reflexivity)
  - Given  $D \rightarrow C$ , we have  $AD \rightarrow AC$  (Augmentation)
  - Given  $AD \rightarrow AC$ , we have  $AD \rightarrow C$  (Reflexivity)
  - In other words,  $AD$  decides  $B$  and  $C$
  - Therefore,  $AD \rightarrow BC$

# Reasoning with FDs


- Given  $A \rightarrow C$ ,  $AC \rightarrow D$ ,  $AD \rightarrow B$
- Can you prove that  $A \rightarrow B$ ?
- Proof
  - Given  $A \rightarrow C$ , we have  $A \rightarrow AC$  (Augmentation)
  - Given  $A \rightarrow AC$  and  $AC \rightarrow D$ , we have  $A \rightarrow D$  (Transitivity)
  - Given  $A \rightarrow D$ , we have  $A \rightarrow AD$  (Augmentation)
  - Given  $A \rightarrow AD$  and  $AD \rightarrow B$ , we have  $A \rightarrow B$  (Transitivity)

# Reasoning with FD

- Four attributes: A, B, C, D
- Given:  $B \rightarrow D$ ,  $DB \rightarrow A$ ,  $AD \rightarrow C$
- Can you prove  $B \rightarrow C$ ?
- Doable with Armstrong's axioms, but troublesome
- We will discuss a more convenient approach


# An Intuitive Solution

- Four attributes: A, B, C, D
  - Given:  $B \rightarrow D$ ,  $DB \rightarrow A$ ,  $AD \rightarrow C$
  - Can you prove  $B \rightarrow C$ ?
- 



# Steps of the Intuitive Solution

- Four attributes: A, B, C, D
- Given:  $B \rightarrow D$ ,  $DB \rightarrow A$ ,  $AD \rightarrow C$
- Can you prove  $B \rightarrow C$ ?



- 
- First, activate B
    - Activated set = { B }
  - Second, activate whatever B can activate
    - Activated set = { B, D }, since  $B \rightarrow D$
  - Third, use all activated elements to activate more
    - Activated set = { B, D, A }, since  $DB \rightarrow A$
  - Repeat the third step, until no more activation is possible
    - Activated set = { B, D, A, C }, since  $AD \rightarrow C$ ; done

# Exercise

- Given:  $A \rightarrow C$ ,  $C \rightarrow B$ ,  $B \rightarrow D$ ,  $D \rightarrow E$ ,  $E \rightarrow A$
- Can you prove  $C \rightarrow ABE$ ?
- We start with  $\{C\}$
- Since  $C \rightarrow B$ , we have  $\{C, B\}$
- Since  $B \rightarrow D$ , we have  $\{C, B, D\}$
- Since  $D \rightarrow E$ , we have  $\{C, B, D, E\}$
- Since  $E \rightarrow A$ , we have  $\{C, B, D, E, A\}$
- A, B, E are all in the set, so  $C \rightarrow ABE$  holds

# Exercise

- Given:  $C \rightarrow D$ ,  $AD \rightarrow E$ ,  $BC \rightarrow E$ ,  $E \rightarrow A$ ,  $D \rightarrow B$
- Can you prove  $C \rightarrow A$ ?
- We start with  $\{C\}$
- Since  $C \rightarrow D$ , we have  $\{C, D\}$
- Since  $D \rightarrow B$ , we have  $\{C, D, B\}$
- Since  $BC \rightarrow E$ , we have  $\{C, D, B, E\}$
- Since  $E \rightarrow A$ , we have  $\{C, D, B, E, A\}$
- A is in the set, so  $C \rightarrow A$  holds



# Exercise

- Given:  $C \rightarrow D$ ,  $AD \rightarrow E$ ,  $BC \rightarrow E$ ,  $E \rightarrow A$ ,  $D \rightarrow B$ ,  $B \rightarrow F$
- Can you prove  $D \rightarrow C$ ?
- We start with  $\{D\}$
- Since  $D \rightarrow B$ , we have  $\{D, B\}$
- Since  $B \rightarrow F$ , we have  $\{D, B, F\}$
- What else?
- No more.
- $\{D, B, F\}$  is all what can be decided by  $D$
- We refer to  $\{D, B, F\}$  as the **closure** of  $D$

---

To continue in

**Topic 2: Functional Dependencies (2)**