

CZ2007 Introduction to Database Systems (Week 4)

Topic 3: Boyce-Codd Normal Form (2)



Copyright Notice


All course materials (including and not limited to lecture slides, handouts, recordings, assessments and assignments), are solely for your own educational purposes at NTU only. All course materials are protected by copyright, trademarks or other rights.

All rights, title and interest in the course materials are owned by, licensed to or controlled by the University, unless otherwise expressly stated. The course materials shall not be uploaded, reproduced, distributed, republished or transmitted in any form or by any means, in whole or in part, without written approval from the University.

You are also not allowed to take any photograph, video recording, audio recording or other means of capturing images and/or voice of any of the course materials (including and not limited to lectures, tutorials, seminars and workshops) and reproduce, distribute and/or transmit in any form or by any means, in whole or in part, without written permission from the University.

Appropriate action(s) will be taken against you (including and not limited to disciplinary proceedings and/or legal action) if you are found to have committed any of the above or infringed copyright.

This Lecture

- Tricky case of BCNF 
- Properties of BCNF

Tricky Case of BCNF Decomposition

- $R(A, B, C, D, E)$
- $A \rightarrow B, BC \rightarrow D$
- Key of R: ACE (one single composite key)
- $A \rightarrow B$ is a violation.
- Decompose R
 - $\{A\}^+ = \{A, B\}$
 - $R_1(A, B), R_2(A, C, D, E)$
 - R_1 is in BCNF
 - How about R_2 ?
- Key of R_2 : ACE
- Violations any?
- A bit tricky ...

Tricky Case of BCNF Decomposition

- In general, we may have a tricky case in BCNF decomposition, if
 - We are checking whether a table T satisfies BCNF, and there is an FD $X \rightarrow Y$ such that
 - X contains some attribute in T , but
 - Y contains some attribute NOT in T
- Example in the previous slide:
 - We are checking $R_2(A, C, D, E)$
 - FDs: $A \rightarrow B$, $BC \rightarrow D$
 - A is in R_2 , but B is not
 - This leads to a tricky case
 - In this case, we have to use closures to check whether R_2 is in BCNF

Checking BCNF in a Tricky Case

- We are checking $R_2(A, C, D, E)$
- FDs that we have: $A \rightarrow B$, $BC \rightarrow D$
- Check the closures:
- $\{A\}^+ = \{A, B\}$
- B is not in $R_2(A, C, D, E)$, so the closure becomes
- $\{A\}^+ = \{A\}$
- Similarly, $\{C\}^+ = \{C\}$, $\{D\}^+ = \{D\}$, $\{E\}^+ = \{E\}$
- So far, none of these indicate a violation of BCNF (trivial FDs)
- We check further: $\{AC\}^+ = \{ACD\}$
- This indicates that $AC \rightarrow D$ and AC does not contain key ACE of R_2
- This means that R_2 is not in BCNF
- So we need to decompose it

Checking BCNF in a Tricky Case

- We are checking $R_2(A, C, D, E)$
- FDs that we have: $A \rightarrow B$, $BC \rightarrow D$
- We know that $AC \rightarrow D$ violates BCNF on R_2
- Decompose $R_2(A, C, D, E)$
 - $\{AC\}^+ = \{A, C, D\}$
 - $R_3(A, C, D)$, $R_4(A, C, E)$
- R_4 is in BCNF (ACE is key)
- What about R_3 ?
- Tricky case ($A \rightarrow B$); need to use closure again

Checking BCNF in a Tricky Case


- We are checking $R_3(A, C, D)$
- FDs that we have: $A \rightarrow B$, $BC \rightarrow D$
- $\{A\}^+ = \{A, B\} \rightarrow \{A\}^+ = \{A\}$ on R_3
- $\{C\}^+ = \{C\}$, $\{D\}^+ = \{D\}$
- $\{AC\}^+ = \{A, B, C, D\} \rightarrow \{AC\}^+ = \{A, C, D\}$ on R_3
- $\{AD\}^+ = \{A, B, D\} \rightarrow \{AD\}^+ = \{A, D\}$ on R_3
- $\{CD\}^+ = \{C, D\}$
- None of the closures indicate a violation of BCNF
- Therefore, R_3 is in BCNF
- Final decomposition: $R_1(A, B)$, $R_3(A, C, D)$, $R_4(A, C, E)$

Summary

- Whenever we have a tricky case in checking BCNF, we need to resort to closures
- How to use closures to check that a table T is NOT in BCNF:
 - If there is a closure $\{X\}^+ = \{Y\}$, such that
 - Y does not contain all attributes in T, and (not all)
 - Y contains more attributes than X (more but)
- Previous example:
 - $R_2(A, C, D, E)$, with $A \rightarrow B$, $BC \rightarrow D$
 - $\{AC\}^+ = \{A, C, D\}$
 - $\{A, C, D\}$ does not contain all attributes in R_2 , but
 - $\{A, C, D\}$ contains more attributes than $\{AC\}$


Exercise

- $R(A, B, C, D, E, F)$
- Given FDs: $B \rightarrow D$, $C \rightarrow E$, $DE \rightarrow A$
- Keys: BCF
- $B \rightarrow D$ violates BCNF
- Decompose R:
 - $R_1(B, D)$, $R_2(A, B, C, E, F)$
- R_1 is in BCNF
- What about R_2 ? Tricky case. We could address the tricky case, but ...
- we also notice $C \rightarrow E$ is violating. We can just decompose rightaway:
 - $R_3(C, E)$, $R_4(A, B, C, F)$




Exercise

- $R(A, B, C, D, E, F)$
- Given FDs: $B \rightarrow D$, $C \rightarrow E$, $DE \rightarrow A$
- $R_3(C, E)$ is in BCNF
- What about $R_4(A, B, C, F)$?
- Tricky case
- Check closures
 - $\{A\}^+ = \{A\}$, $\{B\}^+ = \{BD\}$, $\{C\}^+ = \{CE\}$, $\{F\}^+ = \{F\}$
 - $\{AB\}^+ = \{ABD\}$, $\{AC\}^+ = \{ACE\}$, $\{AF\}^+ = \{AF\}$, $\{BC\}^+ = \{BCDEA\}$
- So there is a non-trivial FD: $BC \rightarrow A$



Exercise

- $R(A, B, C, D, E, F)$
- Given FDs: $B \rightarrow D$, $C \rightarrow E$, $DE \rightarrow A$
- $R_3(C, E)$ is in BCNF
- What about $R_4(A, B, C, F)$?
- Keys of R_4 : BCF
- There is a non-trivial FD: $BC \rightarrow A$
- It violates BCNF
- Decompose R_4
 - $R_5(B, C, A)$, $R_6(B, C, F)$
- Final decomposition:
 - $R_1(B, D)$, $R_3(C, E)$, $R_5(B, C, A)$, $R_6(B, C, F)$



This Lecture

- Tricky case of BCNF
- Properties of BCNF ←

Properties of BCNF Decomposition

- Good properties
 - No update or deletion anomalies
 - Very small redundancy
 - The original table can always be reconstructed from the decomposed tables if functional dependencies are preserved (this is called the **lossless join** property)
 - Reconstruction is at the schema level only if some FDs not preserved

Lossless Join Property

Name	<u>NRIC</u>	<u>Phone</u>	Address
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- The table above can be perfectly reconstructed using the decomposed tables below as all FDs preserved:
- {NRIC, Phone} → Name, Address, NRIC → Name, Address

Name	<u>NRIC</u>	Address
Alice	1234	Jurong East
Bob	5678	Pasir Ris

<u>NRIC</u>	<u>Phone</u>
1234	67899876
1234	83848384
5678	98765432

Why BCNF guarantees lossless join?

- Say we decompose a table R into two tables R_1 and R_2
- The decomposition guarantees lossless join, whenever the common attributes in R_1 and R_2 constitute a **superkey** of R_1 or R_2
- Example
 - $R(A, B, C)$ decomposed into $R_1(A, B)$ and $R_2(B, C)$, with B being the key of R_2
 - $R(A, B, C, D)$ decomposed into $R_1(A, B, C)$ and $R_2(B, C, D)$, with BC being the key of R_1

Why BCNF guarantees lossless join?


- The decomposition of R guarantees lossless join, whenever the common attributes in R_1 and R_2 constitute a superkey of R_1 or R_2
- BCNF Decomposition of R
 - Find a BCNF violation $X \rightarrow Y$
 - Compute $\{X\}^+$
 - R_1 contains all attributes in $\{X\}^+$
 - R_2 contains X and all attributes NOT in $\{X\}^+$
 - X is both in R_1 and R_2
 - And X is a superkey of R_1
 - Therefore, R_1 and R_2 is a lossless decomposition of R

Properties of BCNF Decomposition

- Good properties
 - No update or deletion anomalies
 - Very small redundancy
 - The original table can always be reconstructed from the decomposed tables if functional dependencies are preserved (this is called the **lossless join** property)
- Bad property
 - It may not preserve all functional dependencies


Dependency Preservation

- Given: Table $R(A, B, C)$
 - with $AB \rightarrow C, C \rightarrow B$
- Keys: AB, AC
- BCNF Decomposition
 - $R_1(B, C)$
 - $R_2(A, C)$
- Non-trivial FDs on R_1 : $C \rightarrow B$
- Non-trivial FDs on R_2 : none
- The other FD, $AB \rightarrow C$, should hold on any individual table, but it is “lost”
- We say that a BCNF decomposition does not always **preserve** all FDs




Dependency Preservation

- Why do we want to preserve FDs?
- Because we want to make it easier to avoid “inappropriate” updates
- Previous example
 - We have two tables $R_1(B, C)$, $R_2(A, C)$
 - We have $C \rightarrow B$ and $AB \rightarrow C$
 - Due to $AB \rightarrow C$, we are not suppose to have two tuples $(a1, b1, c1)$ and $(a1, b1, c2)$
 -
 -
 -



Dependency Preservation

- Why do we want to preserve FDs?
- Because we want to make it easier to avoid “inappropriate” updates
- Previous example
 - We have two tables $R_1(B, C)$, $R_2(A, C)$
 - We have $C \rightarrow B$ and $AB \rightarrow C$
 - Due to $AB \rightarrow C$, we are not supposed to have two tuples $(a1, b1, c1)$ and $(a1, b1, c2)$
 - But as we store A and C separately in R_1 and R_2 , it is not easy to check whether such two tuples exist at the same time
 -
 -




Dependency Preservation

- Why do we want to preserve FDs?
- Because we want to make it easier to avoid “inappropriate” updates

- Previous example

- We have two tables $R_1(B, C)$, $R_2(A, C)$
- We have $C \rightarrow B$ and $AB \rightarrow C$
- Due to $AB \rightarrow C$, we are not supposed to have two tuples $(a1, b1, c1)$ and $(a1, b1, c2)$
- But as we store A and C separately in R_1 and R_2 , it is not easy to check whether such two tuples exist at the same time
- That is, if someone wants to insert $(a1, b1, c2)$, it is not easy for us to check whether $(a1, b1, c1)$ already exists
- This is less than ideal



Third Normal Form (3NF)

- A relaxation of BCNF that
 - Is less strict
 - Allows decompositions that **always** preserve functional dependencies
- Will be discussed in the next lecture



Next lecture:

Topic 4: Third Normal Form (1)