

# SC2207/CZ2007 Introduction to Database Systems (Week 3)

## Topic 2: Functional Dependencies (2)



---

## **Copyright Notice**


All course materials (including and not limited to lecture slides, handouts, recordings, assessments and assignments), are solely for your own educational purposes at NTU only. All course materials are protected by copyright, trademarks or other rights.

All rights, title and interest in the course materials are owned by, licensed to or controlled by the University, unless otherwise expressly stated. The course materials shall not be uploaded, reproduced, distributed, republished or transmitted in any form or by any means, in whole or in part, without written approval from the University.

You are also not allowed to take any photograph, video recording, audio recording or other means of capturing images and/or voice of any of the course materials (including and not limited to lectures, tutorials, seminars and workshops) and reproduce, distribute and/or transmit in any form or by any means, in whole or in part, without written permission from the University.

Appropriate action(s) will be taken against you (including and not limited to disciplinary proceedings and/or legal action) if you are found to have committed any of the above or infringed copyright.

# This Lecture

- Closure 
- Keys
- Finding keys
- Normal forms

# Closure

- Let  $S = \{A_1, A_2, \dots, A_n\}$  be a set  $S$  of  $n$  attributes
- Closure of  $S$  is the set of attributes that can be determined by  $A_1, A_2, \dots, A_n$
- Notation:  $\{A_1, A_2, \dots, A_n\}^+$
- Example
  - Given  $A \rightarrow B, B \rightarrow C, C \rightarrow D, D \rightarrow E$
  - $\{A\}^+ = \{A, B, C, D, E\}$
  - $\{B\}^+ = \{B, C, D, E\}$
  - $\{D\}^+ = \{D, E\}$
  - $\{E\}^+ = \{E\}$

# Exercise

- A table with six attributes A, B, C, D, E, F


- $AB \xrightarrow{\text{red}} C$ ,  $AD \xrightarrow{\text{blue}} E$ ,  $B \xrightarrow{\text{green}} D$ ,  $AF \xrightarrow{\text{purple}} B$

- Compute the following closures

- $\{B, C\}^+ =$


- $\{A, B\}^+ =$

- $\{A, F\}^+ =$



# Exercise

- A table with six attributes A, B, C, D, E, F
- $AB \rightarrow C$ ,  $AD \rightarrow E$ ,  $B \rightarrow D$ ,  $AF \rightarrow B$
- Compute the following closures
  - $\{B, C\}^+ = \{B, C, D\}$
  - $\{A, B\}^+ = \{A, B, C, D, E\}$
  - $\{A, F\}^+ = \{A, B, C, D, E, F\}$



# Closure & FD

- To prove that  $X \rightarrow Y$  holds, we only need to show that  $\{X\}^+$  contains  $Y$
- $AB \rightarrow C, AD \rightarrow E, B \rightarrow D, AF \rightarrow B$
- Prove that  $AF \rightarrow D$
- $\{AF\}^+ = \{AFBCDE\}$ , which contains  $D$
- Therefore,  $AF \rightarrow D$  holds

# Closure & FD

- To prove that  $X \rightarrow Y$  **does not** hold, we only need to show that  $\{X\}^+$  **does not** contain  $Y$
- $AB \rightarrow C, AD \rightarrow E, B \rightarrow D, AF \rightarrow B$
- Prove that  $AD \rightarrow F$  does not hold
- $\{AD\}^+ = \{ADE\}$ , which does not contain  $F$
- Therefore,  $AD \rightarrow F$  does not hold



# This Lecture

- Closure
- Keys ←
- Finding keys
- Normal forms

# Roadmap

- Now we know what a closure is
- We discuss the usage of closure for finding the **keys** in a table
  - This is a necessary step for checking whether a table is good or not
- Concepts
  - Superkeys
  - Keys
  - Candidate keys
  - Primary keys / Secondary keys

Notion of **keys** in a table



**keys** in a entity set

# Superkeys of a Table

Name	<u>NRIC</u>	Postal	Address
Alice	1234	939450	Jurong East
Bob	5678	234122	Pasir Ris
Cathy	3576	420923	Yishun

- Definition: A set of attributes in a table that determines all other attributes
- Example:
  - {NRIC} is a superkey (happens to be minimal)
  - Since  $\text{NRIC} \rightarrow \text{Name, Postal, Address}$
  - {NRIC, Name} is a superkey (not minimal)
  - Since  $\{\text{NRIC, Name}\} \rightarrow \text{Postal, Address}$

# Keys of a Table

Name	<u>NRIC</u>	Postal	Address
Alice	1234	939450	Jurong East
Bob	5678	234122	Pasir Ris
Cathy	3576	420923	Yishun

- Definition: A superkey that is minimal
- i.e., if we remove any attribute from the superkey, it will not be a superkey anymore
- Example:
  - {NRIC} is a superkey (happens to be minimal)
  - Since  $\text{NRIC} \rightarrow \text{Name, Postal, Address}$
  - {NRIC, Name} is a superkey
  - Since  $\{\text{NRIC, Name}\} \rightarrow \text{Postal, Address}$
  - NRIC is a key, but {NRIC, Name} is not a key, but a superkey

# Keys of a Table

Name	<u>NRIC</u>	Postal	Address
Alice	1234	939450	Jurong East
Bob	5678	234122	Pasir Ris
Cathy	3576	420923	Yishun

- Note: Not to be confused with the keys of entity sets because keys in entity sets need not be minimal.

# Candidate Keys

Name	NRIC	StudentID	Postal	Address
Alice	1234	1	939450	Jurong East
Bob	5678	2	234122	Pasir Ris
Cathy	3576	3	420923	Yishun

- A table may have multiple keys
- In that case, each key is referred to as a candidate key
- Example:
  - {NRIC} is a key
  - Since NRIC  $\rightarrow$  Name, StudentID, Postal, Address
  - {StudentID} is a key
  - Since StudentID  $\rightarrow$  Name, NRIC, Postal, Address
  - Both {NRIC} and {StudentID} are candidate keys

# Primary and Secondary Keys

Name	NRIC	StudentID	Postal	Address
Alice	1234	1	939450	Jurong East
Bob	5678	2	234122	Pasir Ris
Cathy	3576	3	420923	Yishun

- When a table have multiple keys ...
- We choose one of them as the primary key
- The others are referred to as secondary keys
- Example:
  - {NRIC} is a key
  - {StudentID} is a key
  - If we choose {NRIC} as the primary key
  - Then {StudentID} is the secondary key

# Summary

- Superkeys

- A set of attributes that determines all other attributes in a table

- Keys


- A minimal set of attributes that determines all other attributes in a table

- Example

- $R(A, B, C, D)$
- Given:  $A \rightarrow BCD$ ,  $BC \rightarrow A$
- A is a key and a superkey
- BC is also a key and a superkey
- AB is not a key; it is only a superkey



# This Lecture

- Closure
- Keys
- Finding keys 
- Normal forms

# Finding the Keys

- To check whether a table is “good”, we need to find the keys of the table
- How do we do that?
- Use functional dependencies (FDs) and closures

# Example

- Definition of a Key: A minimal set of attributes that determines all other attributes
- A table  $R(A, B, C)$
- FDs given:  $A \rightarrow B$ ,  $B \rightarrow C$
- Is A a key?
- $\{A\}^+ = \{\underline{ABC}\}$ , i.e.,  $A \rightarrow ABC$ . Yes.
- Is B a key?
- $\{B\}^+ = \{BC\}$ , i.e., B does not decide A. No.
- Is C a key?
- $\{C\}^+ = \{C\}$ . No.
- Is AB a key?
- No, since A is already a key.
- What about BC, AC, ABC?

# Example

- Definition of a Key: A minimal set of attributes that determines all other attributes
- A table  $R(A, B, C)$
- FDs given:  $A \rightarrow B$
- Is A a key?
- $\{A\}^+ = \{A, B\}$ . No.
- Is B or C a key?
- $\{B\}^+ = \{B\}$ .  $\{C\}^+ = \{C\}$ . No.
- Is AB or BC a key?
- $\{AB\}^+ = \{AB\}$ .  $\{BC\}^+ = \{BC\}$ . No.
- Is AC a key?
- $\{AC\}^+ = \{\underline{ABC}\}$ . Yes.
- Is ABC a key?

# Finding the Keys: Algorithm

- Check all possible combinations of attributes in the table
  - Example: A, B, C, AB, BC, AC, ABC
- For each combination, compute its closure
  - Example:  $\{A\}^+ = \dots$ ,  $\{B\}^+ = \dots$ ,  $\{C\}^+ = \dots$ , ...
- If a closure contains ALL attributes, then the combination might be a key (or superkey)
  - Example:  $\{A\}^+ = \{ABC\}$
- Make sure that you select only keys
  - Example:  $\{A\}^+ = \{ABC\}$ ,  $\{AB\}^+ = \{ABC\}$ , don't select AB

# Example

- A table  $R(A, B, C, D)$
- $AB \rightarrow C, AD \rightarrow B, B \rightarrow D$
- First, enumerate all attribute combinations:
  - $\{A\}, \{B\}, \{C\}, \{D\}$
  - $\{AB\}, \{AC\}, \{AD\}, \{BC\}, \{BD\}, \{CD\}$
  - $\{ABC\}, \{ABD\}, \{ACD\}, \{BCD\}$
  - $\{ABCD\}$

# Example

- A table  $R(A, B, C, D)$
- $AB \rightarrow C, AD \rightarrow B, B \rightarrow D$
- Second, compute the closures:
  - $\{A\}^+ = \{A\}, \{B\}^+ = \{BD\}, \{C\}^+ = \{C\}, \{D\}^+ = \{D\}$
  - $\{AB\}^+ = \{\underline{ABCD}\}, \{AC\}^+ = \{AC\}, \{AD\}^+ = \{\underline{ABCD}\}$
  - $\{BC\}^+ = \{BCD\}, \{BD\}^+ = \{BD\}, \{CD\}^+ = \{CD\}$
  - $\{ABC\}^+ = \{ABD\}^+ = \{ACD\}^+ = \{\underline{ABCD}\}$
  - $\{BCD\}^+ = \{BCD\}$
  - $\{ABCD\}^+ = \{\underline{ABCD}\}$
- Finally, output the keys

# A Small Trick

- Always check small combinations first
- A table  $R(A, B, C, D)$
- $A \rightarrow B, B \rightarrow C, C \rightarrow D, D \rightarrow A$
- Compute the closures:
  - $\{A\}^+ = \{\underline{ABCD}\}, \{B\}^+ = \{\underline{ABCD}\}, \{C\}^+ = \{\underline{ABCD}\}, \{D\}^+ = \{\underline{ABCD}\}$
  - No need to check others
  - The others are all superkeys but not keys
- Keys:  $\{A\}, \{B\}, \{C\}, \{D\}$



# Another Small Trick

- A table  $R(A, B, C, D)$
- $AB \rightarrow C, AD \rightarrow B, B \rightarrow D$
- Notice that A does not appear at the right hand side of any functional dependencies
- In that case, A must be in every key
- Keys of R: AB, AD (From the previous slide)
- In general, if an attribute that does not appear in the right hand side of any FD, then it must be in every key

# Exercise (Find the Keys)

- A table  $R(A, B, C, D)$
- $A \rightarrow B, A \rightarrow C, C \rightarrow D$
- A must be in every key
- Compute the closures:
  - $\{A\}^+ = \{\underline{ABCD}\}$
  - No need to check others
- Keys:  $\{A\}$


# Exercise (Find the Keys)

- A table  $R(A, B, C, D, E)$
- $AB \rightarrow C, C \rightarrow B, BC \rightarrow D, CD \rightarrow E$
- A must be in every key
- Compute the closures:
  - $\{A\}^+ = \{A\}$
  - $\{AB\}^+ = \underline{\{ABCDE\}}$
  - $\{AC\}^+ = \underline{\{ACBDE\}}$
  - $\{AD\}^+ = \{AD\}, \{AE\}^+ = \{AE\}$
  - $\{ADE\}^+ = \{ADE\}$

# Exercise (Find the Keys)

- A table  $R(A, B, C, D, E, F)$
- $AB \rightarrow C, C \rightarrow B, CBE \rightarrow D, D \rightarrow EF$
- A must be in every key
- Compute the closures:
  - $\{A\}^+ = \{A\}$
  - $\{AB\}^+ = \{ABC\}$
  - $\{AC\}^+ = \{ACB\}$
  - $\{AD\}^+ = \{ADEF\}$
  - $\{AE\}^+ = \{AE\}, \{AF\}^+ = \{AF\}$
  - $\{ABC\}^+ = \{ABC\}$
  - $\{ABD\}^+ = \{ABE\}^+ = \{ACD\}^+ = \{ACE\}^+ = \{\underline{ABCDEF}\}$
  - $\{ADE\}^+ = \{ADEF\}$

# This Lecture

- Closure
- Keys
- Finding keys
- Normal forms 

# Recap

- We have talked about a lot of abstract stuff
  - Functional Dependencies
  - Armstrong's Axioms
  - Closures
  - Keys
- Again, what are we doing here?
- The above stuff is needed for **normal forms** and **normalization**

# Recap

Name	<u>NRIC</u>	<u>Phone</u>	Address
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- The table has a number of anomalies
  - Redundancy, insertion anomalies, etc.
- We would like to get rid of tables like this
- For this purpose, we need
  - A method to **detect** “bad tables” like this
  - A method to **fix** “bad tables” like this

# Recap

Name	<u>NRIC</u>	<u>Phone</u>	Address
Alice	1234	67899876	Jurong East
Alice	1234	83848384	Jurong East
Bob	5678	98765432	Pasir Ris

- The table has a number of anomalies
  - Redundancy, insertion anomalies, etc.
- We would like to get rid of tables like this
- For this purpose, we need
  - A method to **detect** “bad tables” like this: **normal forms**
  - A method to **fix** “bad tables” like this: **normalization**



# Normal Forms

- Some conditions that a “good” table must satisfy
- Intuition
  - A student can get first-class honor, if her GPA is at least 4.0
  - “At least 4.0” is a condition that first-class-honor students must satisfy
  - Normal forms are conditions for “good” tables

# Normal Forms

- Various normal forms (in increasing order of strictness)
  - First normal form
  - Second normal form
  - Third normal form (3NF)
  - Boyce-Codd normal form (BCNF)
  - Fourth normal form
  - Fifth normal form
  - Sixth normal form
- 3NF and BCNF are most commonly used

# Normal Forms

- Various normal forms (in increasing order of strictness)
  - First normal form
  - Second normal form
  - Third normal form (3NF)
  - Boyce-Codd normal form (BCNF)
  - Fourth normal form
  - Fifth normal form
  - Sixth normal form
- 3NF and BCNF are most commonly used

---

Next lecture:

**Topic 3: Boyce-Codd Normal Form (1)**