```
Name
                  : simple.asm
 2
 3
     Build
                  : aclocal && autoconf && automake --add-missing --foreign
 4
                    mkdir build
 5
                    cd build
6
                    ../configure
7
                    make
8
9
     Description: a simple window with the basic functionalities and a title
10
11
   ; Source
                  : http://zetcode.com/qui/qtk2/firstprograms/
13 bits 64
15 [list -]
                   GTK WINDOW TOPLEVEL
16
       %define
17
       %define
                   GTK WIN POS CENTER
                                          1
18
       %define
                   FALSE
                                          0
19
       %define
                   TRUE
                                          1
                   gtk_init
20
       extern
21
       extern
                   gtk_main
22
       extern
                   gtk_main_quit
23
       extern
                   gtk_widget_show
24
       extern
                   gtk_window_new
25
       extern
                   gtk_window_set_title
26
       extern
                   g_signal_connect_data
27
       extern
                   exit
28 [list +]
29
30 section .data
31
       window:
                      dq
32
       title:
                      db
                            "simple",0
33
                      db
                            "destroy",0
       szDestroy:
34
35 section .text
36 global _start
37
38 _start:
39
       ;init qtk
40
       xor
               rdi, rdi
41
       xor
               rsi, rsi
42
       call
               gtk init
43
       ;if initialization doesn't succeed then the application
       ;terminates. If that is unwanted behaviour then we need
44
45
       ;to use gtk init check instead.
46
       ;https://developer.gnome.org/gtk2/stable/gtk2-General.html#gtk-init
47
       ;create a new window
48
       mov
                rdi,GTK WINDOW TOPLEVEL
49
       call
               gtk window new
50
       mov
               qword[window],rax
51
       ;set the title
52
                rdi,rax
       mov
53
       mov
                rsi,title
54
       call
               gtk_window_set_title
55
       ; connect the destroy signal to gtk main quit event handler
56
                                             ; combination of GConnectFlags
                r9d,r9d
       xor
57
                r8d, r8d
                                             ; a GClosureNotify for data
       xor
58
                rcx,rcx
                                             ; pointer to the data to pass
       xor
59
                                             ; pointer to the handler
       mov
                rdx,gtk_main_quit
60
                                             ; pointer to the signal
       mov
                rsi,szDestroy
                rdi,qword[window]
                                             ; pointer to the widget instance
61
       mov
62
       ;C programs uses g signal connect, this is not a library
63
       ; function.
64
       call
               g_signal_connect_data
65
       ;show the window
66
                rdi,qword[window]
       mov
67
       call
               gtk widget show
68
       ;go into applications main loop
69
       call
               gtk_main
70 .exit:
71
       ;exit program
72
               rdi,rdi
       xor
73
       call
               exit
```