

| Measurement Capacities | Minimum            | Maximum              |
|------------------------|--------------------|----------------------|
| Length                 | 0.5 in (1.0 cm)    | 36.00 in (90 cm)     |
| Width                  | 0.5 in (1.0 cm)    | 24.00 in (60 cm)     |
| Height                 | 0.5 in (1.0 cm)    | 30.00 in (75 cm)     |
| Weight                 | 0.05 lbs (0.02 kg) | 100.00 lbs (50.0 kg) |

**ENVIRONMENTAL**

Operating temperature: 14° to 104°F (-10° to 40°C)  
Humidity: 0% to 90% non-condensing

**DATA OUTPUT AND POWER REQUIREMENTS**

Power requirements: 100-240 VAC, 47-63 Hz, 0.15A  
Data outputs: Serial (1), Ethernet (1), USB (1)

**PHYSICAL SPECS**

Length: 44 in (112 cm)  
Width: 27 in (69 cm)  
Height: 38.5 in (98 cm)  
Weight: 70 lbs (34 kg)



**PERFORMANCE SPECS**

Operating speed: 1-2 seconds  
Dimensional increment: 0.1 in (0.2 cm)  
Weight increment: 0.05 lbs (0.02 kg)

**MEASUREMENT SENSOR**

Four load cells  
Ultrasonic