

Measurement Capacities	Minimum	Maximum
Length	3.0 in (8.0 cm)	48.00 in (120 cm)
Width	2.4 in (6.0 cm)	39.00 in (99 cm)
Height	2.4 in (6.0 cm)	40.00 in (101 cm)
Weight	0.05 lbs (0.02 kg)	150.00 lbs (70.0 kg)

ENVIRONMENTAL & TABLE HEIGHT RANGES

Operating temperature: 14° to 104°F (-10° to 40°C)
Humidity: 0% to 90% non-condensing
Table Height: Adjustable between 28-38 in (71-97 cm)

DATA OUTPUT AND POWER REQUIREMENTS

Power requirements: 100-240 VAC, 47-63 Hz, 0.15A
Data outputs: Ethernet (1), Serial (2), USB-A (1), USB-B (1)

PHYSICAL SPECS

Length: 65 in (165 cm)
Width: 52 in (132 cm)
Height: 87 in (221 cm)
Weight: 430 lbs (195 kg)



PERFORMANCE SPECS

Operating speed: 1-2 seconds
Dimensional increment: 0.1 in (0.2 cm)
Weight increment: 0.05 lbs (0.02 kg)

MEASUREMENT SENSOR

Four Load Cells
Ultrasonic