

MEASUREMENT CAPACITIES & ORIENTATIONS

Measurement Capacities	Minimum	Maximum
Length	6.0 in (15.0 cm)	60.00 in (153.0 cm)
Width (2' Belt)	4.0 in (10.0 cm)	23.00 in (58.0 cm)
Width (3' Belt)	4.0 in (10.0 cm)	35.00 in (89.0 cm)
Height (non-LFT)	0.2 in (0.5 cm)	36.00 in (91.0 cm)
Height (LFT)	1.9 in (3.0 cm)	36.00 in (91.0 cm)
Weight	0.55 lbs (0.25 kg)	132.27 lbs (60.0 kg)

ENVIRONMENTAL

Operating temperature: 14° to 104°F (-10° to 40°C)

Humidity: 15% to 85% non-condensing

DATA OUTPUT AND POWER REQUIREMENTS

Power requirements: 100-240 VAC, 47-63 Hz, 0.15A

Data Connections: RS232C/RS422/Ethernet/DIO/USB

PHYSICAL SPECS

Length: 68.3 in (173.0 cm)

Width: 53.1 in (135.0 cm)

Height: 61.4 in (156.0 cm)

Weight: 1014.1 lbs (460 kg)



BELT SPEEDS

Non-LFT: 100-400 ft (30-120 m) per minute

LFT: 100-328 ft (30-100 m) per minute

PERFORMANCE SPECS

Dimensional increment: 0.2 in (0.5 cm)

Weight increment: 0.11 lbs (0.05 kg)

Minimum interval between objects:
27.6 in (70.0 cm)

MEASUREMENT SENSOR

Infrared light beam