Artemis II Mission Architecture Rigorous Astrodynamics of the Crewed Lunar Flyby

Agha Tasheer Syedi[1]

cs.aghasyedi@gmail.com
[1]School of Quantum Technology, DIAT, Pune, India

April 3, 2026

Abstract

The Apollo-era paradigm of short-duration, expendable lunar excursions presents an immense energetic and logistical barrier, rendering a sustained, multi-planetary presence inaccessible via legacy architectures. This technical report explores the paradigm shift of the Artemis programme by rigorously detailing Artemis II: the inaugural crewed mission of the Orion Multi-Purpose Crew Vehicle (MPCV) and the critical validation of deep-space orbital mechanics.

Utilising the super-heavy-lift Space Launch System (SLS), we analyse the precise astrodynamics required to place the spacecraft—commanded by Reid Wiseman—into a highly elliptical Earth orbit, followed by a Translunar Injection (TLI). We provide a rigorous derivation of the hybrid free-return trajectory, distinguishing between patched-conic approximations and the precise multi-body kinematics that guarantee an Earth-return intercept via lunar gravitational slingshot without reliance on main engine propulsion.

Key engineering hurdles are addressed, including: (a) the cryogenic fluid thermodynamics of the upper stage to mitigate boil-off prior to the TLI burn; (b) the aerothermodynamic limits and phase-change physics of the Avcoat ablative heat shield during a targeted skip re-entry at roughly 11 km/s; (c) the survivability and closed-loop environmental control of the crew cabin amidst the ionising radiation flux beyond the Van Allen belts; and (d) the radiometric and optical communication architecture required to maintain high-fidelity telemetry via the Deep Space Network (DSN).

The report concludes that while the absence of a lunar lander necessitates a transient flyby, the Artemis II architecture represents the only rigorously tested, physically viable pathway for deploying the Lunar Gateway and establishing the foundation for crewed Martian transit.

Keywords: Artemis II, Astrodynamics, Free-Return Trajectory, Orion MPCV, Skip Re-entry, Space Launch System, Lunar Flyby.

ARTEMIS II: THE INTUITION & THE PROBLEM

1 THE SLING, THE STONE, AND THE BOOMERANG: THE FREE-RETURN TRAJECTORY

We begin with a classical thought experiment: imagine swinging a stone on a string, which serves as a macroscopic analogue for Earth's gravitational field. If you release the stone at precisely the right millisecond, it arcs perfectly around a smaller distant rock (representing the Moon) and returns directly to your hand without requiring any further tension or retrieval force. This intuitive mechanical conceptualisation forms the basis of the *free-return trajectory*, a critical safety mechanism in translunar navigation.

In orbital mechanics, this scenario cannot be fully described by simple two-body Keplerian motion. Instead, we must employ the Circular Restricted Three-Body Problem (CR3BP). We consider two massive primaries—the Earth ($M_\oplus$) and the Moon (M_L)—revolving in circular orbits about their common barycentre. The spacecraft is a massless third body whose motion is governed by the gravitational influence of both primaries.

In a rotating coordinate system frame with angular velocity ω, the equations of motion for the spacecraft admit a single integral of motion known as the Jacobi Constant, $\mathcal{J}$:

$$\mathcal{J} = n^2(x^2+y^2) + 2\left(\frac{\mu_1}{r_1} + \frac{\mu_2}{r_2}\right) - \dot{x}^2 - \dot{y}^2 - \dot{z}^2 \quad (1)$$

where n is the mean motion of the primaries, μ_1 and μ_2 are the standard gravitational parameters of the Earth and Moon, and r_1, r_2 are the distances from the spacecraft to the Earth and Moon, respectively.

The free-return trajectory is a highly specific solution within this framework. Following Translunar Injection (TLI), the spacecraft is placed on an unpowered path that intersects the Moon's sphere of influence. The lunar gravity acts as a gravitational slingshot, altering the spacecraft's velocity vector just enough to place it on a return trajectory that intersects the Earth's atmosphere at a precise, survivable reentry flight path angle (typically between $-5.5°$ and $-7.0°$).

2 THE GRAVITY WELL CONCEPT

To understand the energy requirements of deep space exploration, one must visualise Earth's gravitational pull as a steep, multi-dimensional funnel. The gravitational potential energy per unit mass at a distance r from the centre of the Earth is given by:

$$V(r) = -\frac{GM_\oplus}{r} = -\frac{\mu_\oplus}{r} \tag{2}$$

In Low Earth Orbit (LEO), the International Space Station (ISS) orbits at an altitude of approximately 400 km. The orbital velocity required to maintain this circular orbit is derived from the balance of centripetal and gravitational forces:

$$v_{\text{LEO}} = \sqrt{\frac{\mu_\oplus}{R_\oplus + h_{\text{LEO}}}} \approx 7.67 \text{ km/s} \tag{3}$$

To escape the "funnel" and reach the Moon, the Orion spacecraft must perform a Translunar Injection (TLI) manoeuvre. The energy required is exponentially higher than simply maintaining LEO. We use the *vis-viva* equation to determine the velocity at the perigee of the transfer orbit:

$$v_{\text{TLI}}^2 = \mu_\oplus \left(\frac{2}{r_{\text{perigee}}} - \frac{1}{a_{\text{transfer}}} \right) \tag{4}$$

Because the Moon is approximately $384,400$ km away, the semimajor axis a_{transfer} is massive, making v_{TLI} approach the Earth escape velocity ($v_{\text{esc}} \approx 11.2$ km/s). The required change in velocity (Δv) from LEO to TLI is roughly 3.1 km/s.

According to the Tsiolkovsky rocket equation, $\Delta v = I_{sp} g_0 \ln(m_0/m_f)$, achieving this additional 3.1 km/s requires a massive expenditure of propellant. This physical reality dictates the sheer size of the Space Launch System (SLS) required to push the Orion capsule out of Earth's gravity well, contrasting starkly with the relatively minor energy required to keep a station aloft in LEO.

3 THE APOLLO LEGACY VS. THE ARTEMIS IMPERATIVE

The Apollo programme was dictated by the geopolitics of the Cold War, resulting in a "flags and footprints" architecture. Apollo utilised the Lunar Orbit Rendezvous (LOR) profile, a mathematically efficient but short-term strategy. The physics of Apollo relied on equatorial, low lunar orbits (LLO), which are heavily perturbed by lunar *mascons* (mass concentrations), making them dynamically unstable for long-term habitation.

The Artemis imperative represents a paradigm shift from short-stay excursions to a sustainable, permanent deep-space architecture. Mathematically, this shifts the orbital target from LLO to a Near-Rectilinear Halo Orbit (NRHO).

An NRHO is a highly elliptical, three-dimensional orbit belonging to the L_1 or L_2 families of halo orbits in the Earth-Moon system. The Artemis programme primarily targets the Southern L_2 NRHO. The dynamics of NRHOs offer unique physical advantages:

1. **Stability:** Unlike LLO, an NRHO is nearly stable in the CR3BP, requiring minuscule station-keeping Δv (on the order of 10 m/s per year) to maintain.
2. **Continuous Communication:** The orbit's geometry ensures the spacecraft never passes behind the Moon relative to Earth, completely eliminating the communication blackouts experienced during Apollo.
3. **Thermal and Power Optimisation:** The orbit largely avoids lunar eclipses, providing continuous solar power.

This transition reflects a fundamental shift from optimising for a single, direct descent to optimising the boundary conditions for a long-term gateway to Mars.

4 THE CREWED FLYBY PROBLEM

Artemis II introduces a unique set of constraints. By placing Commander Reid Wiseman and his crew on a flight without a lunar lander acting as a life-support backup (as was heavily utilised during the Apollo 13 crisis), the trajectory mathematics must ensure absolute survivability purely through the Orion capsule's standalone systems.

The mission utilises a hybrid trajectory. It begins with a High Earth Orbit (HEO) phasing ellipse, allowing the crew to rigorously test the Environmental Control and Life Support Systems (ECLSS) and proximity operations while still close enough to Earth for an abort. Following a successful checkout, the TLI burn commits the spacecraft to a high-velocity lunar flyby.

The crux of the "Flyby Problem" is balancing the hyperbolic excess velocity (v_∞) at lunar encounter with the strict boundary condition of maximum mission duration ($T_{\max}$) dictated by Orion's consumables. The time of flight (T) for the entire free-return must strictly satisfy:

$$T_{\text{outbound}} + T_{\text{return}} \leq T_{\max} \tag{5}$$

During the flyby, the spacecraft's trajectory relative to the Moon is a hyperbola. The turning angle δ of the velocity vector is dictated by the perilune radius (r_p) and the hyperbolic excess velocity:

$$\sin\left(\frac{\delta}{2}\right) = \frac{1}{1 + \frac{r_p v_\infty^2}{\mu_L}} \tag{6}$$



Figure 1: Conceptual diagram of the Earth-Moon system illustrating a circumlunar free-return trajectory. The dashed lines indicate the spacecraft's unpowered path originating from Earth, swinging behind the Moon, and returning to the Earth's reentry corridor using purely gravitational influence.



Figure 2: Earth-Moon gravitational potential. L1 saddle requires $\Delta v \approx 11.2$ km/s escape.



Figure 3: Visualisation of the Near-Rectilinear Halo Orbit (NRHO) in the rotating Earth-Moon frame. The orbit is highly elliptical and eccentric over the lunar poles, providing a stable staging point with continuous line-of-sight to Earth for deep-space communications.

To execute an asymmetric free-return that safely brings the crew home in roughly 10 days, the perilune radius cannot be arbitrarily low. Artemis II targets a high-altitude flyby (approximately $7,400$ km above the lunar surface). This specific altitude provides the exact gravitational deflection δ required to morph the outbound trajectory into a safe Earth-return intercept, proving the capability of the navigation and life support systems in the harsh radiation environment of deep space, all while adhering to the uncompromising physics of the free-return safety net.

THE CONCEPTUAL BRIDGE

5 KEPLER'S LAWS AND CONIC SECTIONS

The foundational mechanics of spaceflight, preceding the complexities of multi-body dynamics, rely on the classical two-body problem. Johannes Kepler's empirical laws, later rigorously derived from Newton's laws of motion and universal gravitation, dictate that the unperturbed trajectory of a spacecraft around a primary body is a conic section.

For a spacecraft (mass m) orbiting Earth (mass $M_\oplus \gg m$), the governing equation of orbital motion in polar coordinates (r, θ) is defined by the polar equation of a conic:

$$r = \frac{p}{1 + e\cos\theta} \tag{7}$$

where $p = h^2/\mu_\oplus$ is the semi-latus rectum, h is the specific angular momentum, $\mu_\oplus = GM_\oplus$ is the standard gravitational parameter of Earth, e is the eccentricity, and θ is the true anomaly.

The physical pathway the Space Launch System (SLS) and the Orion spacecraft carve through space is fundamentally categorised by the specific orbital energy, ε:

$$\varepsilon = \frac{v^2}{2} - \frac{\mu_\oplus}{r} = -\frac{\mu_\oplus}{2a} \tag{8}$$

where v is the orbital velocity, r is the radial distance, and a is the semi-major axis.

- **LEO Parking Orbit ($0 \le e < 1, \varepsilon < 0$):** Following launch, Orion enters a nearly circular High Earth Orbit (HEO) phasing trajectory. This is a bound, elliptical state where the specific energy is negative.

- **Translunar Trajectory ($e \to 1, \varepsilon \to 0^-$):** The injection burn elongates the ellipse to a highly eccentric state. The apogee is raised to intersect the lunar orbit.

- **Lunar Flyby ($e > 1, \varepsilon > 0$):** Relative to the Moon, Orion's trajectory becomes a hyperbola. The spacecraft is not gravitationally bound to the Moon, possessing a positive specific energy relative to the lunar frame.

6 THE PATCHED CONIC APPROXIMATION

While the true trajectory of Artemis II is governed by the n-body problem (primarily the Earth, Moon, and Sun), analytical solutions do not exist for $n \ge 3$. To design missions and gain physical intuition, we employ the Patched Conic Approximation. This method elegantly bridges the gap between Earth's dominant gravity well and the Moon's local gravitational influence by breaking the continuous trajectory into a sequence of purely two-body Keplerian segments.

The mathematical boundary dictating where Orion "swaps" primary gravitational masters is defined by the Sphere of Influence (SOI), often formulated using Laplace's definition. The radius of the Moon's SOI, r_{SOI}, relative to Earth is:

$$r_{SOI} \approx D\left(\frac{M_L}{M_\oplus}\right)^{2/5} \tag{9}$$

where $D \approx 384,400$ km is the mean Earth-Moon distance, M_L is the mass of the Moon, and $M_\oplus$ is the mass of the Earth. Substituting the mass ratio ($M_L/M_\oplus \approx 1/81.3$), we find $r_{SOI} \approx 66,100$ km.

The operational procedure of the patched conic method is as follows:

1. **Geocentric Phase:** The spacecraft travels on an elliptical path with Earth as the primary focus. The Moon's gravity is treated as a negligible perturbation.

2. **Patch Point:** As Orion crosses the boundary $r = r_{SOI}$, a coordinate transformation occurs. We shift from a geocentric reference frame to a selenocentric (Moon-centric) frame. The spacecraft's state vectors (position $\boldsymbol{r}$ and velocity $\boldsymbol{v}$) are translated:

$$\boldsymbol{r}_{s/m} = \boldsymbol{r}_{s/\oplus} - \boldsymbol{r}_{m/\oplus} \tag{10}$$
$$\boldsymbol{v}_{s/m} = \boldsymbol{v}_{s/\oplus} - \boldsymbol{v}_{m/\oplus} \tag{11}$$

3. **Selenocentric Phase:** Inside the SOI, the trajectory is modelled as a hyperbola with the Moon at the focus. The velocity vector at the patch point becomes the hyperbolic excess velocity ($\boldsymbol{v}_\infty$) entering the lunar system.

This approximation, while requiring numerical integration for high-fidelity flight software, provides the fundamental framework for targeting the lunar flyby.

7 THE PHYSICS OF THE TRANSLUNAR INJECTION (TLI)

The Translunar Injection (TLI) is arguably the most critical propulsive manoeuvre of the Artemis II mission. It is the orbital mechanical process of elongating a relatively low, bound Earth orbit until its apogee intersects the path of the Moon.



Figure 4: Geometric representation of conic sections mapping to orbital trajectories. The diagram illustrates the transition from bound orbits (eccentricity $e < 1$) to escape trajectories ($e \geq 1$), where the central mass acts as one of the foci of the geometric curve.



Figure 5: The Patched Conic Approximation framework. The diagram details the geocentric elliptical transfer orbit intersecting the lunar Sphere of Influence (SOI), transitioning smoothly into a selenocentric hyperbolic flyby trajectory at the patch point boundary.

Unlike a simple Hohmann transfer, which aims to circularise at the target orbit, TLI is an intercept trajectory. The Interim Cryogenic Propulsion Stage (ICPS) executes a massive impulsive burn at the perigee of the parking orbit. Firing at perigee leverages the *Oberth effect*: a propulsive manoeuvre is vastly more efficient in terms of kinetic energy gain when executed at the highest possible velocity (deepest in the gravity well).

The required velocity at the conclusion of the TLI burn, v_{TLI}, is derived from the *vis-viva* equation, assuming the apogee (r_a) reaches the lunar orbit ($r_a \approx D$):

$$v_{TLI} = \sqrt{2\mu_{\oplus}\left(\frac{1}{r_p} - \frac{1}{r_p + D}\right)} \tag{12}$$

where r_p is the perigee radius of the parking orbit. The necessary change in velocity is simply $\Delta v_{TLI} = v_{TLI} - v_{LEO}$.

However, establishing the geometry is insufficient; timing is paramount. The Moon moves at roughly 1.02 km/s along its orbit. If Orion's Time of Flight (TOF) to apogee is typically $t_{TOF} \approx 3$ to 4 days, the Moon will travel a considerable angular distance during the transit. The TLI burn must be initiated at a specific *phase angle* such that the spacecraft and the Moon arrive at the rendezvous coordinates simultaneously. The required lead angle α_{lead} for the Moon is approximately:

$$\alpha_{lead} = \omega_L t_{TOF} \tag{13}$$

where ω_L is the mean angular velocity of the Moon. Artemis II must inject not just to lunar distance, but specifically target the leading edge of the Moon to execute the free-return slingshot described in Chapter 1.

8 DELTA-V (ΔV) BUDGETS AND THE ROCKET EQUATION

In the realm of orbital mechanics, distance is irrelevant; the absolute currency of spaceflight is Δv (change in velocity). Every manoeuvre, from orbital insertion to TLI to mid-course corrections, deducts from a strict finite budget.

The foundational mathematics governing this budget is the Tsiolkovsky rocket equation, derived from the conservation of momentum for a system with variable mass:

$$\Delta v = I_{sp} g_0 \ln\left(\frac{m_0}{m_f}\right) \tag{14}$$

where:

- I_{sp} is the specific impulse of the propulsion system (a measure of engine efficiency, in seconds).
- $g_0 \approx 9.80665$ m/s^2 is the standard gravitational acceleration (a conversion factor).
- m_0 is the initial total mass (including propellant).
- m_f is the final dry mass (after propellant expenditure).

Rearranging the equation to solve for the required mass fraction highlights the "tyranny of the rocket equation":

$$\frac{m_0}{m_f} = e^{\frac{\Delta v}{I_{sp} g_0}} \tag{15}$$

Because the mass ratio scales exponentially with the required Δv, deep-space manoeuvres impose severe mass penalties.

This exponential scaling dictates the architecture of the Artemis II mission. Over 9 km/s of Δv is required simply to reach orbit, necessitating the colossal solid rocket boosters and core stage of the SLS. The TLI burn demands an additional ~ 3.1 km/s. To spare the Orion capsule from carrying the immense propellant mass required for this burn, the ICPS acts as a dedicated stage strictly for this manoeuvre.

Once the ICPS is jettisoned, Orion is reliant on the European Service Module (ESM). Because Artemis II employs a free-return trajectory, the massive Δv penalty of a Lunar Orbit Insertion (LOI) and subsequent Trans-Earth Injection (TEI) is completely bypassed. The ESM's primary propulsion system is thus



Figure 6: Orbital mechanics of the Translunar Injection (TLI). The diagram shows the Orion spacecraft executing a prograde burn at perigee, utilising the Oberth effect to achieve maximum energy gain. The trajectory is calculated based on the phase angle of the Moon's future position to ensure a precise orbital rendezvous.

conserved solely for minor trajectory correction manoeuvres (TCMs), ensuring the Δv budget remains robust enough to handle contingency scenarios or emergency aborts far from home.

THE CORE PHYSICS & MATHEMATICS

9 THE CIRCULAR RESTRICTED THREE-BODY PROBLEM (CR3BP)

While the patched conic approximation provides foundational intuition, the rigorous trajectory design for the Artemis II mission demands a higher-fidelity model. The classical two-body problem yields elegant, analytical Keplerian solutions, but deep space navigation within the Earth-Moon system requires the integration of competing gravitational fields. This necessitates the introduction of the Circular Restricted Three-Body Problem (CR3BP).

The CR3BP is formulated under several simplifying, yet highly accurate, assumptions:

1. **Three Masses:** The system consists of two primary massive bodies, Earth (m_1) and the Moon (m_2), and a third body, the Orion spacecraft (m_3).
2. **Restricted Mass:** The mass of the spacecraft is infinitesimal compared to the primaries ($m_3 \ll m_2 \ll m_1$). Thus, m_3 is influenced by m_1 and m_2, but exerts no reciprocal gravitational perturbation on them.
3. **Circular Orbits:** The two primaries revolve around their common barycentre (centre of mass) in perfectly circular orbits at a constant angular velocity.

To render the equations of motion tractable, the system is non-dimensionalised. We define a mass parameter, $\mu = \frac{m_2}{m_1+m_2}$. Consequently, the normalised masses become $1-\mu$ (for Earth) and μ (for the Moon). Units of length are scaled such that the constant distance between the primaries is 1. Time is scaled such that the mean motion (and therefore the orbital period of the primaries) is 2π, setting the universal gravitational constant $G = 1$.

In this rotating, barycentric coordinate frame (x, y, z), Earth is located at $(-\mu, 0, 0)$ and the Moon is located at $(1-\mu, 0, 0)$. Because the CR3BP possesses no general analytical solution, determining the state vector of the Orion spacecraft at any future time t requires the numerical integration of its highly nonlinear equations of motion.

10 LAGRANGIAN DYNAMICS AND THE JACOBI CONSTANT

To derive the equations of motion for the spacecraft in the rotating frame, we construct the system's Lagrangian, $L = T - V$, where T is the kinetic energy and V is the potential energy. Due to the rotation of the reference frame at a constant angular velocity $\omega = 1$ about the z-axis, the kinetic energy must account for Coriolis and centrifugal accelerations.

The scalar distances from the spacecraft to Earth (r_1) and the Moon (r_2) are defined as:

$$r_1 = \sqrt{(x+\mu)^2 + y^2 + z^2} \tag{16}$$

$$r_2 = \sqrt{(x-(1-\mu))^2 + y^2 + z^2} \tag{17}$$

Defining a pseudo-potential function, often called the effective potential $\Omega(x, y, z)$, which absorbs the centrifugal potential:

$$\Omega(x, y, z) = \frac{1}{2}(x^2 + y^2) + \frac{1-\mu}{r_1} + \frac{\mu}{r_2} \tag{18}$$

Applying the Euler-Lagrange equations, we obtain the rigorous equations of motion for the Orion space-



Figure 7: Geometric representation of the Circular Restricted Three-Body Problem (CR3BP) in the rotating barycentric coordinate frame. The massive primaries m_1 and m_2 remain fixed on the x-axis, while the massless third body m_3 moves according to the combined gravitational and inertial (centrifugal/Coriolis) forces.

craft:

$$\ddot{x} - 2\dot{y} = \frac{\partial \Omega}{\partial x} \tag{19}$$

$$\ddot{y} + 2\dot{x} = \frac{\partial \Omega}{\partial y} \tag{20}$$

$$\ddot{z} = \frac{\partial \Omega}{\partial z} \tag{21}$$

Multiplying these equations by $\dot{x}, \dot{y}$, and $\dot{z}$ respectively, adding them together, and integrating with respect to time reveals the system's sole integral of motion—an energy-like conserved quantity known as the *Jacobi Constant*, C:

$$C = x^2 + y^2 + 2\left(\frac{1-\mu}{r_1} + \frac{\mu}{r_2}\right) - (\dot{x}^2 + \dot{y}^2 + \dot{z}^2) \tag{22}$$

Recognising that $v^2 = \dot{x}^2 + \dot{y}^2 + \dot{z}^2$ is the square of the spacecraft's velocity in the rotating frame, we can rewrite this elegantly as $C = 2\Omega(x, y, z) - v^2$.

10.1 Zero-Velocity Surfaces (ZVS)

Because velocity must be real, $v^2 \geq 0$, which mandates that $2\Omega(x, y, z) \geq C$. For a given energy state C dictated by the spacecraft's injection parameters, there are spatial regions where $2\Omega(x, y, z) < C$. These are mathematically forbidden zones. The boundary separating the accessible and forbidden regions is the Zero-Velocity Surface (ZVS), defined by $v = 0$.

By mapping the ZVS for various values of C, we visualise the exact mathematical boundaries restricting Orion's path. As the Jacobi constant decreases (representing an increase in orbital energy), "necks" or portals open at the collinear Lagrange points (L_1, L_2), allowing transit between the geocentric and selenocentric regions.

11 MANIFOLD THEORY IN ASTRODYNAMICS

Moving beyond the energetic boundaries dictated by the Jacobi constant, modern deep-space navigation leverages the phase space geometry of the CR3BP through dynamical systems theory. The five equilibrium solutions of the CR3BP are the Lagrange points (L_1 through L_5). By linearising the nonlinear equations of motion around the collinear points (L_1, L_2, L_3), we reveal the local phase space topology.

The characteristic equation for the linearised system about L_1 or L_2 yields eigenvalues of the form $\pm\lambda$ (real) and $\pm i\omega_1, \pm i\omega_2$ (imaginary). This specific saddle $\times$ centre $\times$ centre dynamical structure generates invariant manifolds.

An *invariant manifold* is a multi-dimensional surface embedded in the phase space such that if a state vector lies on the manifold, its forward and backward time evolution will eternally remain on that manifold.

- **Stable Manifold (W^s):** The set of all trajectories that asymptotically approach a periodic orbit (like a halo orbit) as $t \to +\infty$.
- **Unstable Manifold (W^u):** The set of all trajectories that asymptotically depart a periodic orbit as $t \to +\infty$ (or approach as $t \to -\infty$).

In mission design, these manifolds act as the unseen currents or "tubes" of gravity. Rather than fighting the gravitational field with brute-force Δv, a spacecraft can execute a minor propulsive manoeuvre to intersect a stable manifold. Once on the manifold, the natural chaotic flow of the Earth-Moon gravity field passively draws the spacecraft into the target orbit (e.g., a Near-Rectilinear Halo Orbit) with near-zero deterministic propellant expenditure. For a free-return trajectory, manifold intersections are meticulously calculated



Figure 8: Cross-sections of the Zero-Velocity Surfaces (ZVS) in the $x-y$ plane for decreasing values of the Jacobi constant C. The shaded areas represent energetically forbidden regions (Hill's regions), while the white spaces define the dynamically permissible spatial domain. As C decreases, the "throats" at the Lagrange points open, permitting transport between the Earth and the Moon.

to guarantee that the unstable manifold of the lunar flyby naturally overlaps with an Earth-return corridor.

12 AEROTHERMODYNAMICS OF HIGH-SPEED RE-ENTRY

The conclusion of the Artemis II mission subjects the Orion crew module to extreme physical environments. Returning from translunar space, the capsule encounters the Earth's upper atmosphere at velocities exceeding 11 km/s (Mach 32+). The primary physics objective is to dissipate the immense kinetic energy of the spacecraft via aerodynamic drag, converting it into heat, without incinerating the vehicle.

The fundamental behaviour of the hypersonic flow field surrounding the blunt body is governed by the compressible Navier-Stokes equations, encapsulating the conservation of mass, momentum, and energy. However, at these super-orbital velocities, the flow is non-ideal and chemically reacting.

A detached bow shock wave forms ahead of the vehicle. Across this shock, the fluid properties experience violent, discontinuous jumps described by the Rankine-Hugoniot relations. The kinetic energy of the freestream gas is violently converted into thermal energy, raising the post-shock gas temperature to over $10,000$ K.

The heat flux (q) experienced by Orion's ablative heat shield is comprised of two distinct regimes:

1. **Convective Heating (q_c):** Driven by the thermal gradient between the hot gas and the vehicle surface within the boundary layer. According to the classical Sutton-Graves approximation for the stagnation point:

$$q_c \propto \sqrt{\frac{\rho}{R_n}} v^3 \tag{23}$$

where ρ is the atmospheric density, v is the vehicle velocity, and R_n is the nose radius. The blunt-body design deliberately maximises R_n to reduce this convective flux.

2. **Radiative Heating (q_r):** At lunar return velocities, the shock layer temperature is so extreme that the atmospheric molecules (N_2, O_2) dissociate and ionise into a glowing plasma. This plasma emits thermal radiation directly into the heat shield. Radiative heating scales severely with velocity:

$$q_r \propto \rho^n v^m \quad (\text{where } m \approx 8 \text{ to } 10) \tag{24}$$

Because q_r scales approximately with v^8, even a marginal increase in re-entry velocity significantly amplifies the radiative heat load. This physics constraint strictly bounds the acceptable re-entry flight path angle. If the angle is too steep, the deceleration and radiative heat flux peak beyond the heat shield's material limits. If too shallow, the spacecraft fails to capture, skipping off the dense atmosphere back into a heliocentric orbit.

Furthermore, the dense plasma sheath engulfing the vehicle absorbs and reflects radio frequency signals, resulting in the characteristic communication blackout period, forcing the onboard autonomous guidance systems to operate independently during the most critical phase of the mission.



Figure 9: Visualisation of the invariant manifold "tubes" associated with an L_2 halo orbit in the Earth-Moon system. Navigators target the stable manifold (green) for ballistic or low-energy insertion into the orbit, while the unstable manifold (red) represents the natural flow of trajectories exiting the lunar vicinity toward deep space.



Figure 10: Aerothermodynamic flow field around a hypersonic blunt body. The diagram illustrates the detached bow shock, the superheated plasma sheath (shock layer) responsible for intense radiative heating, and the boundary layer where viscous effects drive convective heat transfer to the ablative heat shield.

THE HARDWARE & GENERATION

13 THE SPACE LAUNCH SYSTEM (SLS) CORE STAGE

The Space Launch System (SLS) represents a pinnacle of megastructure engineering, designed to impart the immense Δv required to propel the Orion spacecraft out of Earth's gravity well. The architecture relies on a parallel-staged configuration, combining the high specific impulse (I_{sp}) of cryogenic liquid engines with the overwhelming raw thrust of Solid Rocket Boosters (SRBs).

The core stage is powered by four RS-25 engines, operating on a staged combustion cycle using liquid hydrogen (LH_2) and liquid oxygen (LOX). The staged combustion cycle routes the entire propellant mass flow through preburners to drive the turbopumps before injecting the partially combusted, fuel-rich mixture into the main combustion chamber. This eliminates the thermodynamic losses associated with a gas-generator cycle.

The total thrust F generated by a single rocket engine is described by the thrust equation:

$$F = \dot{m}v_e + (p_e - p_a)A_e \tag{25}$$

where $\dot{m}$ is the propellant mass flow rate, v_e is the exhaust velocity relative to the nozzle, p_e is the exhaust pressure at the nozzle exit plane, p_a is the ambient atmospheric pressure, and A_e is the nozzle exit area. The RS-25 operates at extremely high chamber pressures (roughly 20.6 MPa), yielding an exhaust velocity that approaches the theoretical maximum for chemical propulsion ($I_{sp} \approx 452$ s in a vacuum).

However, the RS-25s alone cannot lift the fully fuelled SLS off the pad. The majority of the liftoff thrust (over 75%) is provided by two five-segment SRBs. Unlike liquid engines, which can be throttled dynamically via turbopump modulation, the thrust profile of an SRB is predetermined entirely by the solid propellant's internal geometry (the "grain").

The burn rate r_b (the linear regression rate of the propellant surface) is given by Saint-Robert's Law:

$$r_b = ap_c^n \tag{26}$$

where a is the temperature-dependent empirical constant, p_c is the chamber pressure, and n is the burn rate exponent. The mass flow rate of the solid motor is a strict function of the instantaneous burning surface area $A_b(t)$:

$$\dot{m}_{SRB} = \rho_p A_b(t) r_b \tag{27}$$

where ρ_p is the propellant density. To prevent the vehicle from experiencing catastrophic aerodynamic loads during ascent (max-q), the grain geometry is meticulously cast with a forward finocyl (star-like) shape that transitions to a cylinder. This topology ensures $A_b(t)$ naturally decreases as the vehicle approaches the denser lower atmosphere's sound barrier, throttling down the vehicle geometrically before increasing thrust again as the atmosphere thins.

14 ORION AND THE EUROPEAN SERVICE MODULE (ESM)

The Orion Multi-Purpose Crew Vehicle (MPCV) is heavily reliant on the European Service Module (ESM) to function as its primary power, propulsion, and life-support bus. Together, they form the anatomy of survival for the Artemis II crew in deep space.

14.1 Power Generation

Power is generated by the ESM's four solar array wings. The electrical power output P is dictated by the photovoltaic efficiency, the angle of incidence of solar radiation, and the solar flux:

$$P = \eta A I_s \cos(\theta) \tag{28}$$

where η is the inherent efficiency of the gallium arsenide (GaAs) solar cells, A is the total active area, I_s is the solar irradiance (1361 W/m^2 at 1 AU), and θ is the angle between the array normal vector and the Sun vector. The arrays are articulated along two axes to continuously minimise θ. To survive the structural loads of the Translunar Injection (TLI) burn and lunar flyby, the arrays are designed to sweep backwards, transferring the mechanical strain to the spacecraft's titanium chassis.

14.2 Environmental Control and Life Support System (ECLSS)

The ECLSS is governed by strict mass-balance and partial-pressure equations to maintain a breathable, non-toxic atmosphere. The metabolic consumption of oxygen (O_2) and production of carbon dioxide (CO_2) must be actively balanced. The partial pressure of carbon dioxide, p_{CO_2}, must be maintained well below 3 mmHg to prevent hypercapnia. The ESM manages this via swing-bed amine scrubbers, which physically adsorb CO_2 and water vapour, venting the CO_2 to the vacuum of space upon regular cycling, thus operating as an open-loop system.

14.3 Primary Propulsion

The ESM provides the orbital manoeuvring capability for Orion, utilising a repurposed Space Shuttle Orbital Maneuvering System (OMS) engine (the AJ10-190). Operating on hypergolic propellants (Monomethylhydrazine and Mixed Oxides of Nitrogen), it requires no ignition source—contact initiates spontaneous combustion. While its I_{sp} (~ 316 s) is significantly lower than cryogenic systems, hypergolics provide unparalleled reliability for critical deep-space burns, remaining liquid at ambient spacecraft temperatures and allowing for virtually unlimited restart capabilities.

15 CRYOGENIC FLUID MANAGEMENT

The storage of liquid hydrogen (LH_2) and liquid oxygen (LOX) in the vacuum of space presents a formidable



Figure 11: Cross-sectional diagram of the SRB propellant grain geometry alongside the corresponding time-dependent thrust profile. The star-shaped bore provides high initial surface area for liftoff, which naturally decreases (regressive burn) to create a thrust "bucket" during the maximum dynamic pressure (max-q) phase of the ascent.



Figure 12: Engineering schematic of the Orion European Service Module (ESM). The diagram details the integration of the Environmental Control and Life Support System (ECLSS) tanks, hypergolic propellant storage (MMH/MON-3), and the primary AJ10-190 engine used for translunar and orbit insertion manoeuvres.

thermodynamic challenge. The Interim Cryogenic Propulsion Stage (ICPS) must preserve these fluids over multi-day transits to execute the TLI.

LH_2 boils at $\sim$ 20 K, and LOX at $\sim$ 90 K. In the vacuum of space, convective heat transfer is entirely absent, making thermal radiation the dominant mode of heat ingress from the Sun, Earth, and Moon. The radiative heat flux q_{rad} incident on a spacecraft surface is governed by the Stefan-Boltzmann law:

$$q_{rad} = \epsilon_{eff}\sigma A(T_{env}^4 - T_{tank}^4) \tag{29}$$

where σ is the Stefan-Boltzmann constant, A is the surface area, T_{env} is the effective environmental temperature, and T_{tank} is the cryogenic fluid temperature.

To minimise ϵ_{eff}, the tanks are shielded with Multi-Layer Insulation (MLI), consisting of dozens of layers of highly reflective, metalised Mylar separated by low-conductivity netting. This forces the radiation to be successively emitted and absorbed, dropping the effective emissivity to $\epsilon_{eff} < 0.01$.

However, conductive heat paths (q_{cond}) inevitably exist through structural struts and propellant feedlines:

$$q_{cond} = -kA_c\frac{dT}{dx} \tag{30}$$

where k is the thermal conductivity of the material (typically titanium or composite for low k) and A_c is the cross-sectional area.

When heat inevitably leaks into the tank, sensible heating transitions to latent heating, leading to vaporisation. The boil-off mass flow rate $\dot{m}_{boil}$ is:

$$\dot{m}_{boil} = \frac{q_{total}}{h_{fg}} \tag{31}$$

where $q_{total} = q_{rad} + q_{cond}$ and h_{fg} is the latent heat of vaporisation of the fluid. Because h_{fg} for LH_2 is low, and its volumetric density is extremely small, hydrogen tanks require disproportionately thicker insulation to prevent catastrophic pressure buildup or loss of vital propellant mass before the TLI burn.

16 ADVANCED HEAT SHIELD MATERIALS

As discussed in Chapter 3, re-entry from a lunar trajectory generates severe convective and radiative heat fluxes. To protect the crew cabin, the Orion spacecraft employs an advanced ablative heat shield composed of Avcoat—an epoxy novolac resin reinforced with silica fibres, injected into a fibreglass honeycomb matrix.

The physics of ablation relies on a continuous phase change to dissipate thermal energy. Instead of attempting to conduct or radiate the heat away, the material intentionally undergoes pyrolysis and sublimation. The energy balance at the ablating surface is formulated as:

$$q_{conv} + q_{rad} = q_{cond} + q_{rerad} + \dot{m}_{ab}h_{ab} \tag{32}$$

where q_{conv} and q_{rad} are the incoming aerothermodynamic fluxes. The material reacts by conducting heat inwards (q_{cond}), re-radiating heat outward due to its own high surface temperature ($q_{rerad} = \epsilon\sigma T_{wall}^4$), and consuming energy via the mass ablation rate $\dot{m}_{ab}$ multiplied by the effective heat of ablation h_{ab} (the energy required to break the chemical bonds and vaporise the solid).

A crucial secondary physical mechanism occurs during this process: the *blowing effect*. As the Avcoat undergoes pyrolysis, it releases comparatively cool hydrocarbon gases. These gases are expelled outwards against the incoming hypersonic flow, actively thickening the boundary layer and forming a protective gaseous buffer that drastically reduces the incoming convective heat flux q_{conv}.

16.1 Structural Integrity vs. Aerodynamic Pressure

While the sublimation physics successfully regulates temperature, the capsule simultaneously experiences immense mechanical loads. The dynamic pressure q is defined as:

$$q = \frac{1}{2}\rho v^2 \tag{33}$$

where ρ is the atmospheric density and v is the velocity. Orion must endure dynamic pressures that can exceed traditional low-earth-orbit return profiles.

The heat shield is therefore not merely a thermal barrier; it is a load-bearing structure. The underlying titanium skeleton and carbon-composite carrier structure must maintain absolute rigidity. If the composite flexes under max-q, the brittle Avcoat resin could crack or spall. Spalling (the violent ejection of solid macroscopic chunks of heat shield rather than smooth gaseous vaporisation) rapidly alters the aerodynamic profile of the capsule and exposes the underlying structure to catastrophic blow-through. Thus, the thermal thickness of the heat shield is calculated to ensure the *internal* isotherm at the bondline between the Avcoat and the carrier structure remains strictly below $\sim$ 250°C throughout the entirety of the descent, ensuring the integrity of the pressure vessel securing the crew.

MEASUREMENT & DETECTION

17 THE DEEP SPACE NETWORK (DSN): PHASE-LOCKED LOOPS AND RADIOMETRIC TRACKING

The rigorous determination of the Orion spacecraft's state vector in deep space relies on the Deep Space Network (DSN), an international array of giant radio antennas. The primary observables derived from the RF link are *range* (distance) and *range-rate* (radial velocity). These measurements are not made by direct spatial observation, but rather by the highly precise extraction of phase and frequency shifts from the telemetry signal.

To pinpoint Orion's exact coordinates millions of kilometres away, the DSN employs continuous-wave ranging. A high-frequency uplink signal (typically in the



Figure 13: Thermodynamic diagram illustrating heat transfer mechanisms into a cryogenic propellant tank in space. The figure highlights the role of Multi-Layer Insulation (MLI) in mitigating incident solar radiation and the parasitic conduction through structural supports, which contribute to cryogenic boil-off gas (BOG) formation.



Figure 14: Detailed cross-section of the ablative physics occurring at the Avcoat surface during re-entry. The schematic depicts the internal pyrolysis zone where chemical decomposition occurs, the carbon-rich char layer that provides radiative cooling, and the ejection of pyrolysis gases (the blowing effect) that thickens the boundary layer and reduces convective heating.

X-band or Ka-band) is transmitted to the spacecraft, which phase-modulates a turnaround ranging code onto its downlink carrier and transmits it back.

The distance to the spacecraft, d, is calculated using the Round-Trip Light Time (RTLT), τ:

$$d = \frac{c\tau}{2} \tag{34}$$

where c is the speed of light in a vacuum.

The range-rate (velocity along the line of sight), v_r, is extracted via the Doppler effect. The received frequency f_r shifts relative to the transmitted frequency f_t due to the relative motion between the DSN station and Orion:

$$f_r = f_t\sqrt{\frac{1 - v_r/c}{1 + v_r/c}} \approx f_t\left(1 - \frac{2v_r}{c}\right) \tag{35}$$

To track these minute frequency shifts amidst deep-space background noise, the receiver architecture relies on a Phase-Locked Loop (PLL). A PLL is a nonlinear control system that generates an output signal whose phase is related to the phase of an input signal. The core governing equation in the time domain relates the rate of change of the phase error $\phi_e(t)$ to the input phase $\phi_{in}(t)$ and the Voltage Controlled Oscillator (VCO) output:

$$\frac{d\phi_e(t)}{dt} = \frac{d\phi_{in}(t)}{dt} - K_v K_d f(\phi_e(t)) * h(t) \tag{36}$$

where K_v is the VCO gain, K_d is the phase detector gain, $f(\cdot)$ represents the nonlinear phase detector characteristic, and $h(t)$ is the impulse response of the loop filter. By locking onto the carrier phase, the PLL effectively filters out broadband thermal noise, allowing the DSN to resolve line-of-sight velocities to within fractions of a millimetre per second.

18 OPTICAL COMMUNICATIONS (O2O): THE LASER LINK

Artemis II features the Optical to Orion (O2O) system, representing a paradigm shift from traditional Radio Frequency (RF) telemetry to laser-based data transfer. By operating in the near-infrared spectrum ($\lambda \approx 1550$ nm), optical communications offer significantly higher bandwidth, enabling the transmission of ultra-high-definition video and massive scientific datasets.

The physics of this advantage lies in the fundamental diffraction limit. The angular beam spread (divergence) θ of an electromagnetic wave emitted from an aperture of diameter D is approximated by the Rayleigh criterion:

$$\theta \approx 1.22\frac{\lambda}{D} \tag{37}$$

Because the optical wavelength is orders of magnitude smaller than RF, the laser beam experiences minimal geometric spreading. Consequently, a vast majority of the transmitted power is concentrated onto the receiving telescope.

However, this narrow beam introduces severe pointing, acquisition, and tracking (PAT) challenges. Pointing a tightly focused laser from the Moon back to an Earth-based receiver requires unprecedented angular precision. Furthermore, because light takes approximately 1.28 seconds to travel between the Earth and the Moon, the system must account for the *aberration of light*.

During the transit time of the photon, the target receiver on Earth has physically moved. Thus, the laser cannot simply be pointed at where the Earth station *is* when the signal is generated; it must be pointed to where the station *will be* upon photon arrival. This requires a point-ahead angle α, determined by the relative transverse velocity $v_\perp$ between the transmitter and receiver:

$$\alpha \approx \frac{2v_\perp}{c} \tag{38}$$

The O2O terminal utilises fine steering mirrors driven by high-bandwidth control algorithms to continuously calculate and adjust for this point-ahead angle, ensuring the infrared beam successfully links with the ground station.

19 SPACE RADIATION DOSIMETRY: MEASURING THE INVISIBLE THREAT

Beyond the protective envelope of Earth's magnetosphere, the Artemis crew is exposed to a harsh ionising radiation environment. The primary threats are Galactic Cosmic Rays (GCRs)—highly energetic, fully stripped atomic nuclei originating from outside the solar system—and Solar Particle Events (SPEs), which are intense bursts of protons accelerated by solar flares and coronal mass ejections.

To quantify the biological risk, physicists measure the Linear Energy Transfer (LET), defined as the amount of energy dE an ionising particle deposits per unit length dx as it traverses a material:

$$L = \frac{dE}{dx} \tag{39}$$

The absorbed dose D (measured in Grays, Gy, where 1 Gy = 1 J/kg) is not sufficient to evaluate human risk, because dense ionisation tracks (high-LET radiation like heavy GCR ions) cause more complex, irreparable DNA double-strand breaks than low-LET radiation (like X-rays or electrons). Therefore, dosimetrists calculate the *equivalent dose* H (measured in Sieverts, Sv), weighting the absorbed dose by a radiation weighting factor w_R:

$$H = \sum_R w_R D_R \tag{40}$$

Orion carries a suite of active and passive detectors to monitor this environment continuously. Active dosimetry utilises solid-state silicon detectors. When an ionising particle passes through the depletion region of a reversed-biased silicon p-n junction, it creates electron-



Figure 15: Clean block diagram illustrating the phase-locked loop (PLL) architecture utilised in DSN radiometric tracking. The loop function $H(s)$ is positioned lower in the feedback path to delineate the control topology, while the normalised 1 and phase-coherence star are placed higher for mathematical clarity.



Figure 16: Geometric representation of the optical communication link between the Orion spacecraft and Earth. The diagram highlights the narrow diffraction-limited beam divergence and the requisite point-ahead angle α, which compensates for the transverse relative velocity and the finite speed of light during the ≈ 1.3-second transit time.

hole pairs. The number of pairs N is directly proportional to the deposited energy E_{dep}:

$$N = \frac{E_{dep}}{W_{eh}} \tag{41}$$

where $W_{eh} \approx 3.6$ eV is the average energy required to create one electron-hole pair in silicon. By measuring the resultant charge pulse via a charge-sensitive preamplifier, the onboard computers can generate real-time spectral histograms of the radiation environment, alerting the crew to seek shelter during a sudden SPE.

20 INERTIAL MEASUREMENT UNITS (IMUS) AND STAR TRACKERS

If communications with the DSN are lost, Orion must possess the capability for autonomous attitude determination—understanding its exact 3D orientation in space relative to an inertial reference frame without Earth's assistance. This is achieved through the fusion of data from Inertial Measurement Units (IMUs) and optical Star Trackers.

The IMUs measure angular velocity and specific force. Modern spacecraft employ Ring Laser Gyroscopes (RLGs). An RLG operates on the Sagnac effect: two counter-propagating laser beams travel around a closed optical cavity. If the spacecraft rotates with an angular velocity Ω perpendicular to the plane of the cavity, the beam travelling in the direction of rotation takes slightly longer to complete the circuit than the beam travelling against it.

This path length difference induces a phase shift $\Delta\phi$, which translates into a measurable beat frequency Δf when the two beams are recombined:

$$\Delta f = \frac{4A}{\lambda P}\Omega \tag{42}$$

where A is the enclosed area of the ring, P is the perimeter, and λ is the laser wavelength. By integrating this angular rate, the flight computer continuously propagates the spacecraft's attitude.

However, IMUs suffer from inherent physical constraints: their measurements drift over time due to sensor bias and random walk noise. To eliminate this drift, the spacecraft utilises Star Trackers. A Star Tracker takes high-resolution optical images of the star field and compares the observed geometric patterns against an onboard digital catalogue of known star positions.

The fundamental mathematics of this attitude estimation involves solving Wahba's Problem: finding the orthogonal transformation matrix $\mathbf{A}$ (with $\det(\mathbf{A}) = +1$) that optimally maps a set of known reference unit vectors $\mathbf{v}_i$ (from the star catalogue) to the corresponding measured observation unit vectors $\mathbf{w}_i$ (from the camera). The problem seeks to minimise the cost function $J(\mathbf{A})$:

$$J(\mathbf{A}) = \frac{1}{2}\sum_{i=1}^{n} a_i \|\mathbf{w}_i - \mathbf{A}\mathbf{v}_i\|^2 \tag{43}$$

where a_i are non-negative weights representing the confidence in each measurement. The solution, frequently parameterised using quaternions to avoid gimbal lock, provides an absolute, drift-free inertial attitude fix. The flight computer processes this via an Extended Kalman Filter (EKF), rigorously fusing the high-frequency stability of the RLG with the low-frequency absolute accuracy of the Star Tracker.

THE ENGINEERING NIGHTMARES

21 NAVIGATING THE VAN ALLEN BELTS: MAGNETIC TOPOLOGY AND PARTICLE TRAPPING

Before Orion can reach the relative quiescence of deep space, it must traverse the Van Allen radiation belts—two toroidal regions of high-energy ionising particles entrapped by Earth's magnetosphere. The inner belt (extending from roughly $1,000$ to $12,000$ km in altitude) is predominantly populated by highly energetic protons (up to hundreds of MeV), whilst the outer belt (extending from roughly $13,000$ to $60,000$ km) primarily contains high-energy electrons.

The physical entrapment of these particles is governed by the Lorentz force law. A charged particle moving with velocity $\mathbf{v}$ in a magnetic field $\mathbf{B}$ experiences a force:

$$\mathbf{F} = q(\mathbf{E} + \mathbf{v} \times \mathbf{B}) \tag{44}$$

Assuming the macroscopic electric field $\mathbf{E}$ is negligible, the particle undergoes a helical spiralling motion along the magnetic field lines. As the particle approaches the Earth's magnetic poles, the converging field lines increase the magnetic flux density B. Due to the conservation of the first adiabatic invariant—the magnetic moment μ—given by:

$$\mu = \frac{mv_\perp^2}{2B} = \text{constant} \tag{45}$$

the perpendicular velocity $v_\perp$ must increase. Because the total kinetic energy must remain constant in a purely magnetic field, the parallel velocity $v_\parallel$ decreases until it reaches zero at the "mirror point". The particle is then reflected back towards the opposite hemisphere, bouncing between the poles and forming the continuous threat of the radiation belts.

For the Artemis II spacecraft, the high-energy protons of the inner belt represent a severe risk of Single Event Effects (SEEs) in avionics. When a high-energy proton penetrates a CMOS (Complementary Metal-Oxide-Semiconductor) transistor, it generates an ionisation track. This can induce a "Single Event Latch-up" (SEL), creating an unintended low-impedance path that can permanently short-circuit and destroy the microchip.

Whilst increasing the thickness of the aluminium pressure vessel shields against lower-energy protons, there is a strict mass limit. Furthermore, for the outer belt electrons, excessive shielding ironically becomes a hazard: incident electrons rapidly decelerating in dense metal produce secondary X-rays via



Figure 17: Visualisation of the deep-space radiation environment impacting the Orion capsule. The diagram distinguishes between the isotropic, high-energy background flux of Galactic Cosmic Rays (GCRs) and the directional, proton-dominated Solar Particle Events (SPEs). The interaction with the spacecraft hull depicts the production of secondary spallation particles.



Figure 18: Schematic of a Ring Laser Gyroscope (RLG). The diagram illustrates the counter-propagating light beams within the triangular optical cavity and the resulting beat frequency generated by the Sagnac effect during rotation. The photodetector measures the interference pattern to determine the angular rate Ω.



Figure 19: Conceptual diagram of Star Tracker attitude determination. The instrument performs optical recognition of stellar constellations within its field of view to determine the coordinate transformation (typically expressed as a quaternion or Direction Cosine Matrix) required to align the spacecraft body frame with the J2000 inertial celestial reference frame.

Bremsstrahlung (braking radiation), necessitating layered, low-Z (atomic number) shielding materials like polyethylene to mitigate both the primary particles and the secondary cascade.

22 THERMAL EXTREMES AND GRADIENT STRESS

In the vacuum of space, convective heat transfer is impossible. The thermal environment is dictated entirely by radiative exchange. The sun-facing side of the Orion spacecraft is subjected to the unattenuated solar constant, $G_s \approx 1361$ W/m^2, while the side facing deep space radiates heat away into an environmental sink of approximately 3 K.

The equilibrium temperature T_{eq} of an exposed surface patch is governed by the balance of absorbed solar radiation and emitted thermal radiation (Stefan-Boltzmann Law):

$$\alpha_s G_s \cos(\theta) = \epsilon \sigma T_{eq}^4 \tag{46}$$

where α_s is the solar absorptivity of the surface, θ is the angle of incidence, ϵ is the infrared emissivity, and σ is the Stefan-Boltzmann constant. Without intervention, this leads to an extreme temperature delta (ΔT) across the spacecraft hull, with the sunlit side exceeding $+150°$C and the shadowed side plunging below $-150°$C.

This thermal gradient induces severe mechanical stress across the spacecraft's titanium and composite structures. The thermal strain ε_{th} is given by:

$$\varepsilon_{th} = \alpha_L \Delta T \tag{47}$$

where α_L is the coefficient of linear thermal expansion. A high ΔT causes the sun-facing hull to expand while the shadowed hull contracts, resulting in thermal warping. Over a multi-day transit, this asymmetric stress could compromise pressure seals, warp the service module umbilical connections, or misalign the highly calibrated optical star trackers.

To mitigate this, navigators employ Passive Thermal Control (PTC)—colloquially known as the "barbecue roll". The spacecraft is commanded to rotate slowly (typically one revolution every 60 to 90 minutes) along its longitudinal axis. This transforms the static $\cos(\theta)$ term into a time-dependent function, effectively averaging the solar irradiance over the spacecraft's cylindrical surface and preventing the steady-state ΔT from reaching structurally dangerous thresholds.

23 CLOSED-LOOP ECOLOGY FAILURES

The Orion Environmental Control and Life Support System (ECLSS) manages a delicate, life-or-death chemical balance. The primary atmospheric constraints are maintaining the oxygen partial pressure (p_{O_2}) and scrubbing toxic metabolic byproducts, specifically carbon dioxide (CO_2).

While Apollo famously relied on consumable Lithium Hydroxide (LiOH) canisters—where the exothermic chemical reaction $2\text{LiOH} + \text{CO}_2 \rightarrow \text{Li}_2\text{CO}_3 + \text{H}_2\text{O}$ permanently bound the carbon—Artemis relies on regenerable amine swing-beds to save mass on extended missions. However, the failure modes remain analogous. If the amine beds fail to vent to the vacuum properly, or if mechanical fans fail to circulate the air, local pockets of high p_{CO_2} will form around the astronauts' faces, leading to rapid respiratory acidosis, hypercapnia, and ultimately, lethal narcosis.

A more immediate catastrophic failure is rapid depressurisation caused by a Micrometeoroid and Orbital Debris (MMOD) strike. If the pressure vessel is breached, the air exhausts into space. The mass flow rate $\dot{m}$ of the escaping gas is governed by the choked flow equation for a compressible fluid escaping into a vacuum:

$$\dot{m} = C_d A P_0 \sqrt{\frac{\gamma M}{R T_0} \left(\frac{2}{\gamma + 1}\right)^{\frac{\gamma+1}{\gamma-1}}} \tag{48}$$

where C_d is the discharge coefficient, A is the area of the hull breach, P_0 and T_0 are the cabin pressure and temperature, γ is the heat capacity ratio of the air (≈ 1.4), M is the molar mass, and R is the universal gas constant.

Because the flow is choked (escaping at Mach 1 relative to the hole), the depressurisation rate is strictly proportional to the area A of the breach. The time available for the crew to don pressure suits—known as the Time of Useful Consciousness (TUC)—drops exponentially as cabin pressure falls below the Armstrong Limit (6.3 kPa), where bodily fluids begin to boil at human body temperature.

24 THE SKIP RE-ENTRY TARGETING CONSTRAINTS

Unlike the Apollo direct-entry profile, Artemis implements a "skip re-entry" manoeuvre to bleed off the ~ 11 km/s lunar return velocity. This involves dipping into the upper atmosphere, using aerodynamic lift to skip back out into space (cooling the heat shield), and then re-entering for the final descent.

The dynamics of atmospheric flight are governed by the lift (L) and drag (D) forces:

$$L = \frac{1}{2}\rho v^2 S C_L \tag{49}$$

$$D = \frac{1}{2}\rho v^2 S C_D \tag{50}$$

where ρ is the atmospheric density (which varies exponentially with altitude), v is the velocity, S is the aerodynamic reference area, and C_L, C_D are the lift and drag coefficients. By offsetting its centre of mass, the Orion capsule generates a lift vector. The flight computer modulates the trajectory not by changing the magnitude of the lift, but by changing its direction via the bank angle σ.

The skip re-entry requires threading a microscopic targeting needle, known as the *aerodynamic corridor*:



Figure 20: The magnetic topology of the Van Allen Belts. The diagram illustrates the helical trajectories of trapped charged particles following Earth's dipole field lines and the magnetic mirror effect. This effect occurs as field lines converge near the poles, causing the particles to reflect back toward the equator.



Figure 21: Conceptual diagram of the Passive Thermal Control (PTC) roll. The diagram demonstrates how the slow longitudinal rotation of the Orion spacecraft evenly distributes the incident solar flux G_s over the hull's surface area. This rotation is crucial to mitigate severe thermal gradients that could otherwise lead to structural stress or exceed the design limits of internal subsystems.

1. **The Undershoot Boundary (Too Steep):** If the Flight Path Angle (γ) at atmospheric interface is too steep, the exponential increase in atmospheric density ρ results in a catastrophic spike in drag D. The deceleration force rapidly exceeds human physiological limits (crushing the crew with $> 10g$ loads) and pushes the convective and radiative heat fluxes beyond the ablation limits of the Avcoat shield, resulting in structural disintegration.

2. **The Overshoot Boundary (Too Shallow):** If the angle γ is too shallow, the spacecraft does not encounter sufficient atmospheric density to slow down. Even with the lift vector pointed firmly towards Earth (bank angle $\sigma = 180°$), the centrifugal force mv^2/r overpowers gravity and aerodynamic control, causing the capsule to skip entirely out of the atmosphere, placing it into a highly eccentric, potentially unrecoverable heliocentric orbit with exhausted life support.

The governing equation for the flight path angle rate of change $\dot{\gamma}$ highlights this precarious balance:

$$mv\dot{\gamma} = L\cos\sigma - mg\cos\gamma + m\frac{v^2}{r}\cos\gamma \tag{51}$$

The guidance algorithms must continuously calculate and command the bank angle σ to ensure the sum of these forces perfectly navigates the narrow corridor between incineration and eternal exile.

THE SUPERKNOWLEDGE & ENDGAME APPLICATION

25 THE LUNAR GATEWAY INTEGRATION: ESTABLISHING A PERMANENT STAGING POST

The Artemis II mission is not a solitary objective but a precursor to the Lunar Gateway, a permanent deep-space station. Operating the Gateway requires scaling the orbital mechanics proven by Artemis to maintain a long-duration presence in a highly specific trajectory: the Near Rectilinear Halo Orbit (NRHO).

As introduced in previous chapters, the NRHO is a three-dimensional, highly elliptical orbit belonging to the L_1 or L_2 families in the Circular Restricted Three-Body Problem (CR3BP). The stability of a periodic orbit in the CR3BP is determined by analysing the linearised dynamics over one complete orbital period, T. The evolution of a small perturbation $\delta\mathbf{x}(t)$ is governed by the state transition matrix $\Phi(t, t_0)$:

$$\delta\mathbf{x}(T) = \Phi(T, 0)\delta\mathbf{x}(0) \tag{52}$$

where $\Phi(T, 0)$ is the *monodromy matrix*. According to Floquet theory, the eigenvalues λ_i of the monodromy matrix dictate the local stability of the orbit. Because the CR3BP is a Hamiltonian system, the six eigenvalues occur in reciprocal pairs: $(1, 1, \lambda_1, 1/\lambda_1, \lambda_2, 1/\lambda_2)$.

An orbit is strictly stable if all eigenvalues lie on the unit circle in the complex plane ($|\lambda_i| = 1$). The Gateway targets a specific Southern L_2 NRHO that is *marginally stable*. We define a stability index ν:

$$\nu = \frac{1}{2}\left(|\lambda_{max}| + \frac{1}{|\lambda_{max}|}\right) \tag{53}$$

For the chosen NRHO, ν is very close to 1. This delicate mathematical balance means the exponential divergence of the unstable manifold is extremely slow. Consequently, the Δv budget required for orbital station-keeping is exceptionally low—typically less than 10 m/s per year. Artemis II serves as the definitive empirical test of navigating these invariant manifolds, proving the astrodynamic viability of staging multi-planetary missions from an energy-efficient cis-lunar node.

26 SUSTAINED MARS ARCHITECTURE: THE DIRECT TRANSLATION OF TECHNOLOGY

The leap from the Earth-Moon system to a heliocentric Martian transit requires the direct translation of the technologies validated during Artemis II. The energy requirement for an Earth-to-Mars transit is defined by the specific energy of the hyperbolic escape trajectory, denoted as C_3 (the characteristic energy):

$$C_3 = v_\infty^2 = v_{inj}^2 - \frac{2\mu_\oplus}{r_{inj}} \tag{54}$$

where v_{inj} and r_{inj} are the velocity and radius at the engine cutoff, respectively. A typical Hohmann-style transfer to Mars requires a $C_3 \approx 10$ to 15 km^2/s^2. The deep-space propulsion and avionics architecture of Orion is specifically designed to endure these high-energy transfers.

However, the primary engineering translation lies in the Environmental Control and Life Support System (ECLSS). A Martian transit requires approximately 9 months outbound. The open-loop or partially closed-loop systems sufficient for a 10-day lunar flyby will catastrophically deplete their consumables on a Mars trajectory.

To achieve closure in the oxygen and carbon cycles, the physics of the spacecraft atmosphere must transition to fully regenerative chemical engineering. The core of this is the *Sabatier reaction*, an exothermic methanation process where the carbon dioxide scrubbed from the crew's breath is reacted with hydrogen gas over a nickel or ruthenium catalyst at elevated temperatures ($\sim 300°$C to $400°$C):

$$\mathrm{CO_2} + 4\mathrm{H_2} \rightleftharpoons \mathrm{CH_4} + 2\mathrm{H_2O} \quad (\Delta H \approx -165 \text{ kJ/mol}) \tag{55}$$

The produced methane (CH_4) can be vented or used as propellant, whilst the water (H_2O) is captured, purified, and then electrolysed back into breathable O_2 and metabolic H_2 for the Sabatier reactor. Artemis II's ECLSS acts as the rigorous zero-gravity testbed for the partial-pressure monitoring and fluid dynamics necessary to scale up to this closed-loop chemical equilibrium.



Figure 22: The flight mechanics of the skip re-entry corridor. The diagram highlights the razor-thin margin between the steep undershoot boundary, characterised by excessive g-loads and heat flux, and the shallow overshoot boundary, which results in a failure to capture within the atmosphere. The nominal skip trajectory enables targeted landing and thermal management for lunar return velocities (≈ 11 km/s).



Figure 23: Clean block diagram illustrating the Near-Rectilinear Halo Orbit (NRHO) in the Earth-Moon rotating frame. The stable ($\mathbf{v}_s$) and unstable ($\mathbf{v}_u$) eigenvalue vectors are highlighted at apoapsis, showing the local dynamical flow that necessitates minor, periodic station-keeping manoeuvres to maintain the Gateway's position.



Figure 24: Clean block diagram mapping the closed-loop ECLSS architecture. The schematic illustrates the Sabatier reactor as the primary loop function, translating carbon dioxide and hydrogen into water for crew consumption and methane as a byproduct, establishing the baseline for Martian transit survivability.

27 IN-SITU RESOURCE UTILISATION (ISRU): SCALING UP TO LUNAR ICE HARVESTING

The absolute limits of the Tsiolkovsky rocket equation dictate that carrying all the propellant required for deep-space exploration from the surface of the Earth is economically and physically unfeasible. The endgame application of the Artemis programme is In-Situ Resource Utilisation (ISRU)—specifically, harvesting lunar water ice from permanently shadowed craters at the lunar south pole.

The chemical engineering endgame involves using high-efficiency solar arrays to electrolyse lunar H_2O into cryogenic liquid hydrogen (LH_2) and liquid oxygen (LOX) to refuel spacecraft at the Lunar Gateway. The thermodynamics of water electrolysis are governed by the change in Gibbs free energy (ΔG):

$$\Delta G(T, P) = \Delta H - T\Delta S \tag{56}$$

At standard conditions (298 K, 1 atm), the splitting of liquid water requires an enthalpy input of $\Delta H^\circ = 285.8$ kJ/mol. The minimum electrical work required is defined by the reversible cell potential E°_{rev}:

$$E^\circ_{rev} = \frac{\Delta G^\circ}{zF} \approx 1.23 \text{ V} \tag{57}$$

where $z = 2$ is the number of electrons transferred per mole of water, and $F \approx 96485$ C/mol is Faraday's constant. Due to activation overpotentials and ohmic resistances at the electrodes, the actual operating voltage V_{op} is greater than E°_{rev}. The total electrical power P required to produce a mass flow rate $\dot{m}_{H_2O}$ of propellant is:

$$P = V_{op} \cdot I = V_{op}\left(\frac{\dot{m}_{H_2O}}{M_{H_2O}} zF\right)\frac{1}{\eta_F} \tag{58}$$

where η_F is the Faraday efficiency. This rigorous power requirement dictates the macroscopic solar array infrastructure required on the lunar surface. Artemis II's successful execution proves the viability of placing and supplying the robotic infrastructure needed to initiate this chemical propellant factory, effectively severing humanity's absolute dependence on Earth's gravity well.

28 THE INTERSTELLAR HORIZON

While Artemis II firmly targets the Moon, the infrastructure it validates points directly towards the interstellar horizon. The Optical to Orion (O2O) system, which replaces traditional RF telemetry with high-bandwidth infrared laser links, is the embryonic precursor to macroscopic projects like Breakthrough Starshot.

If we can accurately point and track a laser link across cis-lunar space, we can scale this technology to project immense power over astronomical distances. Breakthrough Starshot proposes using a massive Earth- or Moon-based laser array to accelerate a gram-scale nanocraft equipped with a highly reflective lightsail to relativistic speeds ($\sim 0.2c$) towards Alpha Centauri.

The physical propulsion mechanism relies purely on radiation pressure. For a laser beam of power P reflecting perfectly (reflectivity $R \approx 1$) off a lightsail of area A, the force exerted is:

$$F_{rad} = \frac{2P}{c} \tag{59}$$

To achieve meaningful interstellar transit times, the acceleration must be extreme. The relativistic equation of motion for the sail (rest mass m_0) is:

$$F_{rad} = \frac{dp}{dt} = \frac{d}{dt}(\gamma m_0 v) \tag{60}$$

where $\gamma = (1 - v^2/c^2)^{-1/2}$ is the Lorentz factor. Achieving $v = 0.2c$ requires an array power P on the order of 100 Gigawatts continuously illuminating the sail for several minutes.

Building a 100 GW laser array on Earth is severely hampered by atmospheric distortion and immense gravity. Building it on the Moon, operating in a hard vacuum with deep-space clarity, becomes feasible only if the ISRU capabilities and Gateway infrastructure piloted by the Artemis programme are fully realised. Thus, the physics and telemetry proven on Commander Wiseman's flyby represent the indispensable first steps of humanity's expansion beyond the solar system.



Figure 25: A clean and simple schematic of Lunar ISRU. The diagram illustrates the extraction of water ice from permanently shadowed craters, the thermodynamic electrolysis process separating it into hydrogen and oxygen, and the subsequent liquefaction into cryogenic LH_2 and LOX propellant for deep-space transport.



Figure 26: Conceptual diagram of relativistic lightsail propulsion. The diagram illustrates how a ground-based phased laser array provides continuous radiation pressure to a nanocraft. This demonstrates the scaling of laser pointing technologies from the Artemis O2O system to meet the requirements of interstellar precursor missions.

29 REFERENCES

Astrodynamics and Artemis Mission Architecture

References

[1] Vallado, D. A. (2013). *Fundamentals of Astrodynamics and Applications* (4th ed.). Microcosm Press. (The definitive modern text on orbital mechanics, patched conics, and reference frames).

[2] Szebehely, V. (1967). *Theory of Orbits: The Restricted Problem of Three Bodies*. Academic Press. (Foundational mathematics for the CR3BP and the Jacobi constant derivation in Chapter 3).

[3] Schwaninger, A. J. (1963). Trajectories in the Earth-Moon Space with Symmetrical Free Return Properties. *NASA Technical Note*, D-1833. (The mathematical baseline and historical context for circumlunar navigation).

[4] Creech, S., & Askins, B. (2022). Space Launch System: The Foundation for Artemis. *IEEE Aerospace Conference*. (Detailed engineering specifications of the SLS core stage, thrust-curve profiling, and RS-25 combustion cycles).

[5] Venkatapathy, E., et al. (2014). Orion Heat Shield Development and Advanced Ablators. *NASA Technical Reports Server*. (Phase-change physics and Avcoat ablative shielding performance under extreme 11 km/s shockwave limits).

[6] Mrozinski, R. B., et al. (2019). Orion Skip Entry Trajectory Design. *AIAA Scitech 2019 Forum*. doi:10.2514/6.2019-0931. (Aerothermodynamic targeting constraints and microscopic margins of error for atmospheric re-entry).

[7] Hurlbert, K. M., et al. (2020). Orion Environmental Control and Life Support System (ECLSS) Overview. *International Conference on Environmental Systems*. (Crucial parameters for Chapter 6's closed-loop ecology and carbon dioxide scrubbing limits).

[8] Zeitlin, C., et al. (2019). Radiation Environments and Shielding for Deep Space Missions. *Space Weather*, **17**(1), 108–115. (Solid-state dosimetry and shielding constraints against Galactic Cosmic Rays beyond the Van Allen belts).

[9] Israel, A., et al. (2023). Orion Optical Communications (O2O) System Architecture. *Free-Space Laser Communications XXXV*. (The transition from DSN radiometric phase-locked loops to high-bandwidth infrared laser data transfer).

[10] Williams, J., et al. (2025). Trajectory Optimisation for the Artemis II Crewed Lunar Flyby. *Journal of Spacecraft and Rockets*, **62**(3), 415–430. (The latest orbital mechanics formulations governing the specific multi-body parameters of the Artemis II flight path).