

By: Brennen Bearnes



Subscribe



# How To Install Linux, Apache, MySQL, PHP (LAMP) stack on Ubuntu 16.04

179

Posted April 21, 2016 2.2m LAMP STACK PHP MYSQL APACHE UBUNTU 16.04

Not using Ubuntu 16.04? Choose a different version: ▾

# Introduction

A "LAMP" stack is a group of open source software that is typically installed together to enable a server to host dynamic websites and web apps. This term is actually an acronym which represents the **L**inux operating system, with the **A**pache web server. The site data is stored in a **M**ySQL database, and dynamic content is processed by **P**HP.

In this guide, we'll get a LAMP stack installed on an Ubuntu 16.04 Droplet. Ubuntu will fulfill our first requirement: a Linux operating system.

## Prerequisites

Before you begin with this guide, you should have a separate, non-root user account with `sudo` privileges set up on your server. You can learn how to do this by completing steps 1-4 in the [initial server setup for Ubuntu 16.04](#).

## Step 1: Install Apache and Allow in Firewall

The Apache web server is among the most popular web servers in the world. It's well-documented, and has been in wide use for much of the history of the web, which makes it a great default choice for hosting a website.

We can install Apache easily using Ubuntu's package manager, `apt`. A package manager allows us to install most software pain-free from a repository maintained by Ubuntu. You can learn more about [how to use apt](#) here.

For our purposes, we can get started by typing these commands:

```
$ sudo apt-get update
$ sudo apt-get install apache2
```

Since we are using a `sudo` command, these operations get executed with root privileges. It will ask you for your regular user's password to verify your intentions.

Once you've entered your password, `apt` will tell you which packages it plans to install and how much extra disk space they'll take up. Press **Y** and hit **Enter** to continue, and the installation will proceed.

# Set Global ServerName to Suppress Syntax Warnings

Next, we will add a single line to the `/etc/apache2/apache2.conf` file to suppress a warning message. While harmless, if you do not set `ServerName` globally, you will receive the following warning when checking your Apache configuration for syntax errors:

```
$ sudo apache2ctl configtest
```

Output

```
AH00558: apache2: Could not reliably determine the server's fully qualified
domain name, using 127.0.1.1. Set the 'ServerName' directive globally to
suppress this message
Syntax OK
```

Open up the main configuration file with your text edit:

```
$ sudo nano /etc/apache2/apache2.conf
```

Inside, at the bottom of the file, add a `ServerName` directive, pointing to your primary domain name. If you do not have a domain name associated with your server, you can use your server's public IP address:

## Note

If you don't know your server's IP address, skip down to the section on [how to find your server's public IP address](#) to find it.

```
/etc/apache2/apache2.conf
```

```
...
ServerName server_domain_or_IP
```

Save and close the file when you are finished.

Next, check for syntax errors by typing:

```
$ sudo apache2ctl configtest
```

Since we added the global `ServerName` directive, all you should see is:

Output

```
Syntax OK
```

Restart Apache to implement your changes:

```
$ sudo systemctl restart apache2
```

You can now begin adjusting the firewall.

## Adjust the Firewall to Allow Web Traffic

Next, assuming that you have followed the initial server setup instructions to enable the UFW firewall, make sure that your firewall allows HTTP and HTTPS traffic. You can make sure that UFW has an application profile for Apache like so:

```
$ sudo ufw app list
```

Output

```
Available applications:
```

```
  Apache
```

```
  Apache Full
```

```
  Apache Secure
```

```
OpenSSH
```

If you look at the `Apache Full` profile, it should show that it enables traffic to ports 80 and 443:

```
$ sudo ufw app info "Apache Full"
```

Output

Profile: Apache Full

Title: Web Server (HTTP,HTTPS)

Description: Apache v2 is the next generation of the omnipresent Apache web server.

Ports:

80,443/tcp


Allow incoming traffic for this profile:

```
$ sudo ufw allow in "Apache Full"
```

You can do a spot check right away to verify that everything went as planned by visiting your server's public IP address in your web browser (see the note under the next heading to find out what your public IP address is if you do not have this information already):

[http://your\\_server\\_IP\\_address](http://your_server_IP_address)

You will see the default Ubuntu 16.04 Apache web page, which is there for informational and testing purposes. It should look something like this:



## Apache2 Ubuntu Default Page

ubuntu

It works!

This is the default welcome page used to test the correct operation of the Apache2 server after installation on Ubuntu systems. It is based on the equivalent page on Debian, from which the Ubuntu Apache packaging is derived. If you can read this page, it means that the Apache HTTP server installed at this site is working properly. You should **replace this file** (located at `/var/www/html/index.html`) before continuing to operate your HTTP server.

If you are a normal user of this web site and don't know what this page is about, this probably means that the site is currently unavailable due to maintenance. If the problem persists, please contact the site's administrator.

Configuration Overview

Ubuntu's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Ubuntu tools. The configuration system is **fully documented in** [`/usr/share/doc/apache2/README.Debian.gz`](#). Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the [`manual`](#) if the `apache2-doc` package was installed on this server.

The configuration layout for an Apache2 web server installation on Ubuntu systems is as follows:

```
/etc/apache2/  
|-- apache2.conf  
|   |-- ports.conf  
|-- mods-enabled
```



- `apache2.conf` is the main configuration file. It puts the pieces together by including all remaining configuration files when starting up the web server.
- `ports.conf` is always included from the main configuration file. It is used to determine the listening ports for incoming connections, and this file can be customized anytime.
- Configuration files in the `mods-enabled/`, `conf-enabled/` and `sites-enabled/` directories contain particular configuration snippets which manage modules, global configuration fragments, or virtual host configurations, respectively.
- They are activated by symlinking available configuration files from their respective `*-available/` counterparts. These should be managed by using our helpers `a2enmod`, `a2dismod`, `a2ensite`, `a2dissite`, and `a2enconf`, `a2disconf`. See their respective man pages for detailed information.
- The binary is called `apache2`. Due to the use of environment variables, in the default configuration, `apache2` needs to be started/stopped with `/etc/init.d/apache2` or `apache2ctl`. **Calling `/usr/bin/apache2` directly will not work** with the default configuration.

By default, Ubuntu does not allow access through the web browser to *any* file apart of those located in `/var/www`, **public\_html** directories (when enabled) and `/usr/share` (for web applications). If your site is using a web document root located elsewhere (such as in `/srv`) you may need to whitelist your document root directory in `/etc/apache2/apache2.conf`.

## Reporting Problems

Please report bugs specific to modules (such as PHP and others) to respective packages, not to the web server itself.

## How To Find your Server's Public IP Address

From the command line, you can find this a few ways. First, you can use the `iproute2` tools to get your address by typing this:

```
$ ip addr show eth0 | grep inet | awk '{ print $2; }' | sed 's/\//.*/'
```

This will give you two or three lines back. They are all correct addresses, but your computer may only be able to use one of them, so feel free to try each one.

An alternative method is to use the `curl` utility to contact an outside party to tell you how *it* sees your server. You can do this by asking a specific server what your IP address is:

```
$ sudo apt-get install curl
$ curl http://icanhazip.com
```

Regardless of the method you use to get your IP address, you can type it into your web browser's address bar to get to your server.

## Step 2: Install MySQL

Now that we have our web server up and running, it is time to install MySQL. MySQL is a database management system. Basically, it will organize and provide access to databases where our site can store information.

Again, we can use `apt` to acquire and install our software. This time, we'll also install some other "helper" packages that will assist us in getting our components to communicate with each other:

```
$ sudo apt-get install mysql-server
```

**Note:** In this case, you do not have to run `sudo apt-get update` prior to the command. This is because we recently ran it in the commands above to install Apache. The package index on our computer should already be up-to-date.

Again, you will be shown a list of the packages that will be installed, along with the amount of disk space they'll take up. Enter **Y** to continue.

During the installation, your server will ask you to select and confirm a password for the MySQL "root" user. This is an administrative account in MySQL that has increased privileges. Think of it as being similar to the root account for the server itself (the one you are configuring now is a MySQL-specific account, however). Make sure this is a strong, unique password, and do not leave it blank.

When the installation is complete, we want to run a simple security script that will remove some dangerous defaults and lock down access to our database system a little bit. Start the interactive script by running:

```
$ mysql_secure_installation
```

You will be asked to enter the password you set for the MySQL root account. Next, you will be asked if you want to configure the `VALIDATE PASSWORD PLUGIN`.

**Warning:** Enabling this feature is something of a judgment call. If enabled, passwords which don't match the specified criteria will be rejected by MySQL with an error. This will cause issues if you use a weak password in conjunction with software which automatically configures MySQL user credentials, such as the Ubuntu packages for phpMyAdmin. It is safe to leave validation disabled, but you should always use strong, unique passwords for database credentials.

Answer **y** for yes, or anything else to continue without enabling.

```
VALIDATE PASSWORD PLUGIN can be used to test passwords
and improve security. It checks the strength of password
and allows the users to set only those passwords which are
secure enough. Would you like to setup VALIDATE PASSWORD plugin?
```

```
Press y|Y for Yes, any other key for No:
```

You'll be asked to select a level of password validation. Keep in mind that if you enter **2**, for the strongest level, you will receive errors when attempting to set any password which does not contain numbers, upper and lowercase letters, and special characters, or which is based on common dictionary words.

```
There are three levels of password validation policy:
```

```
LOW      Length >= 8
```

```
MEDIUM Length >= 8, numeric, mixed case, and special characters
```

```
STRONG Length >= 8, numeric, mixed case, special characters and dictionary
file
```



```
Please enter 0 = LOW, 1 = MEDIUM and 2 = STRONG: 1
```

If you enabled password validation, you'll be shown a password strength for the existing root password, and asked you if you want to change that password. If you are happy with your current password, enter **n** for "no" at the prompt:

```
Using existing password for root.
```

```
Estimated strength of the password: 100
```

```
Change the password for root ? ((Press y|Y for Yes, any other key for No) : n
```

For the rest of the questions, you should press **Y** and hit the **Enter** key at each prompt. This will remove some anonymous users and the test database, disable remote root logins, and load these new rules so that MySQL immediately respects the changes we have made.

At this point, your database system is now set up and we can move on.

## Step 3: Install PHP

PHP is the component of our setup that will process code to display dynamic content. It can run scripts, connect to our MySQL databases to get information, and hand the processed content over to our web server to display.

We can once again leverage the `apt` system to install our components. We're going to include some helper packages as well, so that PHP code can run under the Apache server and talk to our MySQL database:

```
$ sudo apt-get install php libapache2-mod-php php-mcrypt php-mysql
```

This should install PHP without any problems. We'll test this in a moment.

In most cases, we'll want to modify the way that Apache serves files when a directory is requested. Currently, if a user requests a directory from the server, Apache will first look for a file called `index.html`. We want to tell our web server to prefer PHP files, so we'll make Apache look for an `index.php` file first.

To do this, type this command to open the `dir.conf` file in a text editor with root privileges:

```
$ sudo nano /etc/apache2/mods-enabled/dir.conf
```

It will look like this:

```
/etc/apache2/mods-enabled/dir.conf
```

```
<IfModule mod_dir.c>
    DirectoryIndex index.html index.cgi index.pl index.php index.xhtml index.htm
</IfModule>
```

We want to move the PHP index file highlighted above to the first position after the `DirectoryIndex` specification, like this:

```
/etc/apache2/mods-enabled/dir.conf
```

```
<IfModule mod_dir.c>
    DirectoryIndex index.php index.html index.cgi index.pl index.xhtml index.htm
</IfModule>
```

When you are finished, save and close the file by pressing **Ctrl-X**. You'll have to confirm the save by typing **Y** and then hit **Enter** to confirm the file save location.

After this, we need to restart the Apache web server in order for our changes to be recognized. You can do this by typing this:

```
$ sudo systemctl restart apache2
```

We can also check on the status of the `apache2` service using `systemctl`:

```
$ sudo systemctl status apache2
```

#### Sample Output

- `apache2.service` – LSB: Apache2 web server  
Loaded: loaded (/etc/init.d/apache2; bad; vendor preset: enabled)

```
Drop-In: /lib/systemd/system/apache2.service.d
└─apache2-systemd.conf
Active: active (running) since Wed 2016-04-13 14:28:43 EDT; 45s ago
Docs: man:systemd-sysv-generator(8)
Process: 13581 ExecStop=/etc/init.d/apache2 stop (code=exited,
status=0/SUCCESS)
Process: 13605 ExecStart=/etc/init.d/apache2 start (code=exited,
status=0/SUCCESS)
Tasks: 6 (limit: 512)
CGroup: /system.slice/apache2.service
├─13623 /usr/sbin/apache2 -k start
├─13626 /usr/sbin/apache2 -k start
├─13627 /usr/sbin/apache2 -k start
├─13628 /usr/sbin/apache2 -k start
├─13629 /usr/sbin/apache2 -k start
└─13630 /usr/sbin/apache2 -k start

Apr 13 14:28:42 ubuntu-16-lamp systemd[1]: Stopped LSB: Apache2 web server.
Apr 13 14:28:42 ubuntu-16-lamp systemd[1]: Starting LSB: Apache2 web server...
Apr 13 14:28:42 ubuntu-16-lamp apache2[13605]: * Starting Apache httpd web
server apache2
Apr 13 14:28:42 ubuntu-16-lamp apache2[13605]: AH00558: apache2: Could not
reliably determine the server's fully qualified domain name, using 127.0.1.1.
Set the 'ServerNam
Apr 13 14:28:43 ubuntu-16-lamp apache2[13605]: *
Apr 13 14:28:43 ubuntu-16-lamp systemd[1]: Started LSB: Apache2 web server.
```

## Install PHP Modules

To enhance the functionality of PHP, we can optionally install some additional modules.

To see the available options for PHP modules and libraries, you can pipe the results of `apt-cache search` into `less`, a pager which lets you scroll through the output of other commands:

```
$ apt-cache search php- | less
```

Use the arrow keys to scroll up and down, and **q** to quit.

The results are all optional components that you can install. It will give you a short description for

each:

```
libnet-libidn-perl - Perl bindings for GNU Libidn
php-all-dev - package depending on all supported PHP development packages
php-cgi - server-side, HTML-embedded scripting language (CGI binary) (default)
php-cli - command-line interpreter for the PHP scripting language (default)
php-common - Common files for PHP packages
php-curl - CURL module for PHP [default]
php-dev - Files for PHP module development (default)
php-gd - GD module for PHP [default]
php-gmp - GMP module for PHP [default]
...
:
```

To get more information about what each module does, you can either search the internet, or you can look at the long description of the package by typing:

```
$ apt-cache show package_name
```

There will be a lot of output, with one field called `Description-en` which will have a longer explanation of the functionality that the module provides.

For example, to find out what the `php-cli` module does, we could type this:

```
$ apt-cache show php-cli
```

Along with a large amount of other information, you'll find something that looks like this:

```
Output
...
Description-en: command-line interpreter for the PHP scripting language
(default)
This package provides the /usr/bin/php command interpreter, useful for
testing PHP scripts from a shell or performing general shell scripting tasks.
.
PHP (recursive acronym for PHP: Hypertext Preprocessor) is a widely-used
```



open source general-purpose scripting language that is especially suited for web development and can be embedded into HTML.

•

This package is a dependency package, which depends on Debian's default PHP version (currently 7.0).

...

If, after researching, you decide you would like to install a package, you can do so by using the `apt-get install` command like we have been doing for our other software.

If we decided that `php-cli` is something that we need, we could type:

```
$ sudo apt-get install php-cli
```

If you want to install more than one module, you can do that by listing each one, separated by a space, following the `apt-get install` command, like this:

```
$ sudo apt-get install package1 package2 ...
```

At this point, your LAMP stack is installed and configured. We should still test out our PHP though.

## Step 4: Test PHP Processing on your Web Server

In order to test that our system is configured properly for PHP, we can create a very basic PHP script.

We will call this script `info.php`. In order for Apache to find the file and serve it correctly, it must be saved to a very specific directory, which is called the "web root".

In Ubuntu 16.04, this directory is located at `/var/www/html/`. We can create the file at that location by typing:

```
$ sudo nano /var/www/html/info.php
```

This will open a blank file. We want to put the following text, which is valid PHP code, inside the

file:

info.php

```
<?php  
phpinfo();  
?>
```

When you are finished, save and close the file.

Now we can test whether our web server can correctly display content generated by a PHP script. To try this out, we just have to visit this page in our web browser. You'll need your server's public IP address again.

The address you want to visit will be:

```
http://your_server_IP_address/info.php
```

The page that you come to should look something like this:

System	Linux ubuntu-16-lamp 4.4.0-12-generic #28-Ubuntu SMP Wed Mar 9 00:33:55 UTC 2016 x86_64
Server API	Apache 2.0 Handler
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/etc/php/7.0/apache2
Loaded Configuration File	/etc/php/7.0/apache2/php.ini
Scan this dir for additional .ini files	/etc/php/7.0/apache2/conf.d
Additional .ini files parsed	/etc/php/7.0/apache2/conf.d/10-mysqld.ini, /etc/php/7.0/apache2/conf.d/10-opcache.ini, /etc/php/7.0/apache2/conf.d/10-pdo.ini, /etc/php/7.0/apache2/conf.d/20-calendar.ini, /etc/php/7.0/apache2/conf.d/20-ctype.ini, /etc/php/7.0/apache2/conf.d/20-exif.ini, /etc/php/7.0/apache2/conf.d/20-fileinfo.ini, /etc/php/7.0/apache2/conf.d/20-ftp.ini, /etc/php/7.0/apache2/conf.d/20-gettext.ini, /etc/php/7.0/apache2/conf.d/20-iconv.ini, /etc/php/7.0/apache2/conf.d/20-json.ini, /etc/php/7.0/apache2/conf.d/20-mcrypt.ini, /etc/php/7.0/apache2/conf.d/20-mysqli.ini, /etc/php/7.0/apache2/conf.d/20-pdo_mysql.ini, /etc/php/7.0/apache2/conf.d/20-phar.ini, /etc/php/7.0/apache2/conf.d/20-posix.ini, /etc/php/7.0/apache2/conf.d/20-readline.ini, /etc/php/7.0/apache2/conf.d/20-shmop.ini, /etc/php/7.0/apache2/conf.d/20-sockets.ini, /etc/php/7.0/apache2/conf.d/20-sysvmsg.ini, /etc/php/7.0/apache2/conf.d/20-sysvsem.ini, /etc/php/7.0/apache2/conf.d/20-sysvshm.ini, /etc/php/7.0/apache2/conf.d/20-tokenizer.ini
PHP API	20151012
PHP Extension	20151012
Zend Extension	320151012
Zend Extension Build	API320151012,NTS
PHP Extension Build	API20151012,NTS
Debug Build	no
Thread Safety	disabled
Zend Signal Handling	disabled
Zend Memory Manager	enabled
Zend Multibyte Support	disabled
IPv6 Support	enabled
DTrace Support	enabled
Registered PHP Streams	https, ftps, compress.zlib, php, file, glob, data, http, ftp, phar
Registered Stream Socket Transports	tcp, udp, unix, udg, ssl, tls, tlsv1.0, tlsv1.1, tlsv1.2
Registered Stream Filters	zlib.*, string.rot13, string.toupper, string.tolower, string.strip_tags, convert.*, consumed, dechunk, convert.iconv.*, mcrypt.*, mdecrypt.*

This program makes use of the Zend Scripting Language Engine:  
 Zend Engine v3.0.0, Copyright (c) 1998-2016 Zend Technologies  
 with Zend OPcache v7.0.6-dev, Copyright (c) 1999-2016, by Zend Technologies



This page basically gives you information about your server from the perspective of PHP. It is useful for debugging and to ensure that your settings are being applied correctly.

If this was successful, then your PHP is working as expected.

You probably want to remove this file after this test because it could actually give information about your server to unauthorized users. To do this, you can type this:

```
$ sudo rm /var/www/html/info.php
```

You can always recreate this page if you need to access the information again later.

# Conclusion

Now that you have a LAMP stack installed, you have many choices for what to do next. Basically, you've installed a platform that will allow you to install most kinds of websites and web software on your server.

As an immediate next step, you should ensure that connections to your web server are secured, by serving them via HTTPS. The easiest option here is to [use Let's Encrypt](#) to secure your site with a free TLS/SSL certificate.

Some other popular options are:

- [Install Wordpress](#) the most popular content management system on the internet.
- [Set Up PHPMyAdmin](#) to help manage your MySQL databases from web browser.
- [Learn more about MySQL](#) to manage your databases.
- [Learn how to use SFTP](#) to transfer files to and from your server.

**Note:** We will be updating the links above to our 16.04 documentation as it is written.

By: Brennen Bearnes

♡ Upvote (179)

✚ Subscribe



# Spin up an SSD cloud server in under a minute.

Simple setup. Full root access.  
Straightforward pricing.

DEPLOY SERVER



## Related Tutorials

[How To Secure Roundcube on Ubuntu 16.04](#)

[How To Secure Web Server Infrastructure With DigitalOcean Cloud Firewalls Using Doctl](#)

[How To Install Your Own Webmail Client with Roundcube on Ubuntu 16.04](#)

[How to Install and Configure SimpleSAMLphp for SAML Authentication on Ubuntu 16.04](#)

[How to Install Virtualmin with Webmin, LAMP, BIND, and PostFix on Ubuntu 16.04](#)

## 117 Comments

**B** *I*      



**B** *I*      



Leave a comment...

Logged in as:  
agiansante00



Notify me of replies  
to my comment

Comment

^ [laurimaa](#) April 22, 2016



- How to find your droplets IP:  
type 'ifconfig' and it should be the top device/interface. inet addr: YOUR\_IP

[Reply](#) · [Report](#)

^ [Ablon](#) April 22, 2016



- Nice!

How can I restore a Full Backup done with Cpanel, in my new VPS after install wordpress?

[Reply](#) · [Report](#)

^ [jschwenn](#) **MOD** April 22, 2016



- Hi,

The cPanel full backup is a compressed file that normally is named like **backup-[date]\_[time]\_[cPanel user name].tar.gz**. This file can be be uncompressed on a Mac by double clicking on it. For Windows, most unzip utilities should also be able to uncompress the file.

After uncompressing the file you'll have a folder with many other folders and files in it. All of

your website files should be in `homedir/public_html` and you'll see the database backups under the `mysql` folder. Those two items will make up your WordPress site.

You can then follow a process very similar to the outlined here to migrate the WordPress site to your new server.



## How To Migrate WordPress from Shared Hosting to a Cloud Server with Zero Downti...

by Ramesh Jha

If you read through this article you'll have the knowledge to migrate your WordPress site from Shared Hosting to a Cloud Server with zero downtime.

[Reply](#) · [Report](#)

^ [Ablon](#) April 22, 2016



o Thank you!

I can do this procedure in a Ubuntu 1 click to wordpress?

[Reply](#) · [Report](#)

^ [jschwenn](#) **MOD** April 23, 2016



1 In theory yes, but you may be better off using the **phpMyAdmin** one-click. you can upload all the files in the `homedir/public_html` folder of the backup to `/var/www/html/` of the One-click based Droplet. Then you would create the database in phpMyAdmin and import your database backup also through the phpMyAdmin panel. You would need to update the database connection details in the

/var/www/html/wp-config.php file, but after that the WordPress site should load.

[Reply](#) · [Report](#)

---

^ [Ablon](#) April 23, 2016

- I receive this error, after put my pass of userdb:  
`mysql -h localhost -u (i change here) -p (and here for mu db name) < (and put correct file here)backupdb.sql.gz`

Enter password:

ERROR at line 1: Unknown command '\  
'

What you think? It's better start configuration a Ubuntu 16.04 manually?

[Report](#)

---

^ [Ablon](#) April 23, 2016

- Yo!  
It's ok now. Backup restored and imported db... how I can configure my domain from bluehost here on my VPS? The Domain will still there.

[Report](#)

---

^ [jschwenn](#) MOD April 24, 2016

- [@Ablon](#) - Here is a great tutorial on how to setup a Domain using our DNS feature.

[Report](#)

---

^ [Hmza](#) April 25, 2016

- Awesome tutorial!

PHP doesn't seem to work with Apache though.

```
sudo a2enconf php7.0.conf returns ERROR: Conf php7.0 does not exist!.  
ls -la | grep php returns:
```

```
-rw-r--r-- 1 root root 867 Apr 14 13:13 php7.0.conf  
-rw-r--r-- 1 root root 79 Apr 14 13:13 php7.0.load
```

I also ran `sudo a2enmod php7.0`, which returned:

```
Considering conflict php5 for php7.0:
```



Enabling module php7.0.

To activate the new configuration, you need to run:

```
service apache2 restart
```

However, `php5` is not installed. `sudo a2dismod php5` returns another error saying it doesn't exist.

[Reply](#) · [Report](#)

---

^ [g1646002](#) *June 22, 2017*

- I had the same problem, apache2 wasn't restarting after enabling php7.0 and when I ran `sudo apache2ctl configtest` gave the error: `/usr/lib/apache2/modules/libphp7.0.so: cannot open shared object file: No such file or directory` then, I installed it with `sudo apt-get install libapache2-mod-php7.0` and the restart the apache with `sudo systemctl restart apache2` and after that, I am able to see `phpinfo()`.

[Reply](#) · [Report](#)

---

^ [akligom](#) *April 27, 2016*

- I successfully installed apache2 but there is not in ufw list. Why and how can I configured it?

[Reply](#) · [Report](#)

---

^ [jacobsandeep](#) *April 30, 2016*

- Thank you, thank you, thank you! i cannot thank you enough. i could fall at your feet and kiss them. this tut saved my life!

[Reply](#) · [Report](#)

---

^ [SergeOvD](#) *May 1, 2016*

- Thx for helpful guide.

[Reply](#) · [Report](#)

---

^ [shankhadev123](#) *May 2, 2016*

- Unable to render php code after upgrading the ubuntu 16.04. By following to install the php with above process.

[Reply](#) · [Report](#)

---

^ [RobertLangore](#) *May 25, 2016*

- Hi,

I had the same issue. I followed the install guide above, but installed php5.6 instead of php7

(which comes with ubuntu 16.04).

output of: `apachectl configtest`

"Apache is running a threaded MPM, but your PHP Module is not compiled to be threadsafe.  
You need to recompile PHP"

I solved in this way (for apache to render php code):

`a2dismod mpmevent`

`a2enmod mpmprefork`

check again with: `apachectl configtest`

restart apache: `service apache2 restart`

Hope it works for you, too.

[Reply](#) · [Report](#)

---

^ [edwerf](#) *May 6, 2016*

- Should this work on 32 bit computers as well? Or do you need php7 in combination with 64 bit computer?

I try to install lamp on ubuntu 16.04 for 2 weeks already and guess that 32 bit will be the reason of my failures?

[Reply](#) · [Report](#)

---

^ [Jasonrawlings](#) *June 8, 2016*

- Step 3: Install PHP  
\$ `sudo apt-get install php libapache2-mod-php php-mcrypt php-mysql`  
Reading package lists... Done  
Building dependency tree  
Reading state information... Done  
E: Unable to locate package php  
E: Unable to locate package libapache2-mod-php  
E: Unable to locate package php-mcrypt  
E: Unable to locate package php-mysql

Yeah, this works. Not.

[Reply](#) · [Report](#)

---

^ [Luraguse](#) *June 25, 2016*

- Had the same problem, for future references if someone else gets that error, I only had to add a 5 (the current version of php) after php to make it work:

sudo apt-get install php5 libapache2-mod-php5 php5-mcrypt php5-mysql

[Reply](#) · [Report](#)

---

^ [packetsniffer](#) *August 20, 2016*  
♡

- thank you very much for this. I had the same problem as JasonRawlings above. Your trick worked.

[Reply](#) · [Report](#)

---

^ [todderh](#) *September 25, 2017*  
♡

- Thumbs up for this ^^

[Reply](#) · [Report](#)

---

^ [rboc12](#) *June 9, 2016*  
♡

- Nice Tutorial... Question though, I was able to install apache2, php, mysql but Web browser is displaying PHP codes instead of executing it.. My guess is apache issue? any input? Thanks

[Reply](#) · [Report](#)

---

^ [wwwhq199](#) *June 18, 2016*  
♡

◦

Would you like send some information to my mailbox (www.hq199@hotmail.com) about the Ubuntu 16 LTS system ?

Think very much.

[Reply](#) · [Report](#)

---

^ [maunghuu](#) *July 12, 2016*  
♡

- Please Update Tutorial  
I can't install php with your command on 16.04  
" sudo apt-get install php libapache2-mod-php php-mcrypt php-mysql "

It's not working

[Reply](#) · [Report](#)

---

^ [treehousetim](#) *July 14, 2016*  
♡

- For those who struggle with seeing the code in the browser instead of the phpinfo() page...

```
<? phpinfo();
```

PHP is installed by default with short tags off. Either change your code or change php.ini. This sed command will do the trick if you opt to turn short tags on.

```
sed -i "s/short_open_tag = .*/short_open_tag = On/"  
/etc/php/7.0/apache2/php.ini
```

[Reply](#) · [Report](#)

---

^ [mrdrew](#) *September 26, 2016*

- Looks like the default is ON.  
; shortopentag  
; Default Value: On  
; Development Value: Off  
; Production Value: Off

[Reply](#) · [Report](#)

---

^ [oargus](#) *July 18, 2016*

- Hello everyone :D

I have a problem.

I can access the application, phpmyadmin, etc. But only inside the server.

What I need to do, for external access. Like a computer in my network?

[Reply](#) · [Report](#)

---

^ [viniciusdepaula](#) *July 24, 2016*

- Thanks very nice tutorial!!!

[Reply](#) · [Report](#)

---

^ [macinfosoft](#) *July 28, 2016*

- Awesome! you made my day!!

[Reply](#) · [Report](#)

---

^ [macinfosoft](#) *July 28, 2016*

- Awesome! I Installed it in 10 minutes. Wow!! All thanks to your tutorial!!

[Reply](#) · [Report](#)

---



^ [omissoni](#) *August 3, 2016*



1 For very lazy sysadmins like me:

sudo tasksel

then choose LAMP-Server.

Drink a coffee and enjoy

[Reply](#) · [Report](#)

---

^ [slowdive](#) *December 7, 2016*



- this is great, this should be indicated at the very beginning of this tutorial as an alternative option!

[Reply](#) · [Report](#)

---

^ [advaitju](#) *June 28, 2017*



- For goodness sake doesn't matter how lazy you are **DON'T USE TASKSEL!** tasksel is practically a blackbox. When you want to uninstall something tasksel has installed it'll remove half of your system, because it **overzealously removes any and all dependencies**. Google: tasksel uninstall issues

You don't know how it set things up, so modifying stuff it installed is guesswork.

[Reply](#) · [Report](#)

---

^ [kainoack](#) *August 11, 2016*



- One of the best tutorials I have ever seen regarding servers. ALL steps worked (!) without any issue. This is highly professional. Well done.

[Reply](#) · [Report](#)


Load More Comments



This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License.



Copyright © 2018 DigitalOcean™ Inc.

[Community](#) [Tutorials](#) [Questions](#) [Projects](#) [Tags](#) [Newsletter](#) [RSS](#) 

[Distros & One-Click Apps](#) [Terms, Privacy, & Copyright](#) [Security](#) [Report a Bug](#) [Write for DOnations](#) [Shop](#)

SCROLL TO TOP