Pacifique Agizo- Lab 18 Social Engineering Attacks with Social Engineering Toolkit

The lab session demonstrated Social Engineering Toolkit functionality while showing how attackers use it for user credential extraction to demonstrate attack mechanisms through simulated attacks in a protected environment.

You would use this topic in real environments to evaluate how users respond to phishing attempts. You test authentication workflows and identify weak points in your security controls. You also measure how often users enter credentials into spoofed login pages so you can improve training.

The lab process ran without issues. The menus in SET responded as expected, and the fake Google page loaded after a short delay. The credential capture displayed correctly in the terminal once the victim system submitted the information.

The laboratory session demonstrated how attackers track user input submissions. The lab demonstrated the location of SET reports and provided instructions for validating obtained data.



SPC St. Petersburg College

Home Reservation pagizo1-1@live.spcollege.edu

MyNETLAB > NDG Ethical Hacking v2 Host 6 Pod 1 > Reservation 106473 > Lab 18: Social Engineering Attacks with SET

Time Remaining 0 hrs. 23 min.

Topology Content Status OpenSUSE pfSense Kali

[root@kali: ~] root@kali: ~ 11:26 PM

root@kali: ~

File Actions Edit View Help

root@kali: ~

```
GNU nano 4.5                    /etc/setoolkit/set.config
#
### This will configure whether or not to use "EnableStageEncoding" within Metasploit payloads.
STAGE_ENCODING=OFF
#
### This feature will determine whether or not automatic redirection is used. By default, for example, in multi-attack,
### the site will redirect once one successful attack is used. Some people may want to use Java applet
### and credential harvester, for example.
AUTO_REDIRECT=ON
#
### This will redirect the harvester victim to this website once executed, rather than the original website.
### For example, if you clone "abcompany.com" and below it says "blahblahcompany.com," it will redirect there instead.
### This is useful if you want to redirect the victim to an additional site after harvester has taken the credentials.
### Simply enable harvester redirect, and then enter "http://websiteofyourchoosing.com" in the "HARVESTER_URL" below
### to change.
HARVESTER_REDIRECT=ON
HARVESTER_URL=http://192.168.9.2
#
### This will allow you to specify where the harvester log file goes when you use Apache.
### By default, this will be in the "/var/www" directory.
HARVESTER_LOG=/var/www
#
### This will turn off the ability to log passwords in the credential harvester. Note that this isn't always
### reliable. It will only not present content that is password oriented. Otherwise, it will still
### show the content.
HARVESTER_LOG_PASSWORDS=ON
#
### This feature will auto embed an "img src" tag to a UNC path of your attack machine.
### This is useful if you want to intercept the half LM keys with rainbow tables. What will happen
### is as soon as the victim clicks the webpage link, a UNC path will be initiated,
### and the Metasploit "auxiliary/server/capture/smb" will intercept the hash values.
UNC_EMBED=OFF
#
### This feature will attempt to create a rogue access point and redirect victims back to the
### SET web server when associated.
ACCESS_POINT_SSID=linksys

^G Get Help   ^O Write Out   ^W Where Is   ^K Cut Text   ^J Justify   ^C Cur Pos   M-U Undo   M-A Mark Text
^X Exit       ^R Read File   ^\ Replace    ^U Paste Text ^T To Spell   ^_ Go To Line M-E Redo   M-6 Copy Text
```

SPC St. Petersburg College

Home Reservation pagizo1-1@live.spcollege.edu

MyNETLAB > NDG Ethical Hacking v2 Host 6 Pod 1 > Reservation 106473 > Lab 18: Social Engineering Attacks with SET

Time Remaining 0 hrs. 44 min.

Topology Content Status OpenSUSE pfSense Kali

root@kali: ~ root@kali: ~ 12:05 AM

root@kali: ~

File Actions Edit View Help

root@kali: ~

```
set:webattack> Select a template:2

[*] Cloning the website: http://www.google.com
[*] This could take a little bit ...

The best way to use this attack is if username and password form
fields are available. Regardless, this captures all POSTs on a website.
[*] You may need to copy /var/www/* into /var/www/html depending on where your directory structure is.
Press {return} if you understand what we're saying here.
[*] The Social-Engineer Toolkit Credential Harvester Attack
[*] Credential Harvester is running on port 80
[*] Information will be displayed to you as it arrives below:
192.168.9.1 - - [21/Nov/2025 00:04:07] "GET / HTTP/1.1" 200 -
192.168.9.1 - - [21/Nov/2025 00:04:07] "GET / HTTP/1.1" 200 -
directory traversal attempt detected from: 192.168.9.1
192.168.9.1 - - [21/Nov/2025 00:04:07] "GET /favicon.ico HTTP/1.1" 404 -
[*] WE GOT A HIT! Printing the output:
PARAM: GALX=SJLCkfgaqoM
PARAM: continue=https://accounts.google.com/o/oauth2/auth?zt=ChRsWFBwd2JmV1hIcDhtUFdldzBENhIfVWsxSTdNLW9MdThibW1TMFQzVUZFc1
BGaURvWmlRSQEZ6BSK99APsBz4gAAAAUy4_qD7Hbfz38wBkxnaNouLcRiD3YTjX
PARAM: service=lso
PARAM: dsh=-7381887106725792428
PARAM: _utf8=☃
PARAM: bgresponse=js_disabled
PARAM: pstMsg=1
PARAM: dnConn=
PARAM: checkConnection=
PARAM: checkedDomains=youtube
POSSIBLE USERNAME FIELD FOUND: Email=John+Smith
POSSIBLE PASSWORD FIELD FOUND: Passwd=Letmein
PARAM: signIn=Sign+in
PARAM: PersistentCookie=yes
[*] WHEN YOU'RE FINISHED, HIT CONTROL-C TO GENERATE A REPORT.


192.168.9.1 - - [21/Nov/2025 00:04:47] "GET / HTTP/1.1" 200 -
192.168.9.1 - - [21/Nov/2025 00:04:47] "GET / HTTP/1.1" 200 -
```