

Package ‘SSRTcalc’

April 3, 2021

Type Package
Title Easy SSRT Calculation in R
Version 0.2.1
Author Anton Leontyev
Maintainer Anton Leontyev <a.g.leontiev@tamu.edu>
Description This is a collection of functions to calculate stop-signal reaction time (SSRT) in R. This package includes functions for both integration and mean methods; both fixed and adaptive stop-signal delays are supported (see appropriate functions).
License GPL-3
Encoding UTF-8
LazyData true
RoxygenNote 7.1.1

R topics documented:

integration_adaptiveSSD	1
integration_fixedSSD	2
mean_adaptiveSSD	3
mean_fixedSSD	3
plotInhFunc	4
Index	6

integration_adaptiveSSD	
	<i>SSRT using integration method for studies with "adaptive" method of setting SSD</i>

Description

Estimating SSRT using integration method for studies that use adaptive (increasing/decreasing by a given increment) stop-signal delays.

Usage

```
integration_adaptiveSSD(df, stop_col, rt_col, acc_col, ssd_col)
```

Arguments

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial (0 = go, 1 = stop)
rt_col	Name of the column in the dataframe df that contains response time in seconds
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition (0 = incorrect, 1 = correct)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays

Value

SSRT corresponding to the nth rt -ssd; $n = p(\text{respond}|\text{signal}) \times \text{number of goRTs}$

Examples

```
## Not run: integration_adaptiveSSD(df = results_df, stop_col = 'stopgo',
ssd_col = 'soa', rt_col = 'RT', acc_col = 'acc')
## End(Not run)
```

integration_fixedSSD	<i>SSRT using integration method for studies with "fixed" method of setting SSD</i>
----------------------	---

Description

Estimating SSRT using integration method for studies that use fixed (randomly chosen on each trial from a pre-determined set) stop-signal delays.

Usage

```
integration_fixedSSD(df, stop_col, rt_col, acc_col, ssd_col, ssd_list)
```

Arguments

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial (0 = go, 1 = stop)
rt_col	Name of the column in the dataframe df that contains response time in seconds
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition (0 = incorrect, 1 = correct)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
ssd_list	List of stop-signal delays used in the experiment

Value

SSRT corresponding to the nth rt -ssd; $n = p(\text{respond}|\text{signal}) \times \text{number of goRTs}$

Examples

```
## Not run: integration_fixedSSD(df = results_df, stop_col = 'stopgo',  ssd_col = 'soa',
rt_col = 'RT', acc_col = 'acc', ssd_list = c(0.4, 0.6, 0.8, 0.9, 1.0))
## End(Not run)
```

mean_adaptiveSSD	<i>SSRT using mean method for studies with "adaptive" method of setting SSD</i>
------------------	---

Description

Estimating SSRT using mean method for studies that use adaptive (increasing/decreasing by a given increment) stop-signal delays

Usage

```
mean_adaptiveSSD(df, rt_col, ssd_col, stop_col)
```

Arguments

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
rt_col	Name of the column in the dataframe df that contains response time in seconds
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial (0 = go, 1 = stop)

Value

Spline-interpolated stop-signal reaction time corresponding roughly to 50

Examples

```
## Not run: mean_adaptiveSSD(df = results_df, stop_col = 'stopgo',  ssd_col = 'soa', rt_col = 'RT')
```

mean_fixedSSD	<i>SSRT using mean method for studies with "fixed" method of setting SSD</i>
---------------	--

Description

Estimating SSRT using mean method for studies that use fixed (randomly chosen on each trial from a pre-determined set) stop-signal delays

Usage

```
mean_fixedSSD(df, stop_col, rt_col, acc_col, ssd_col, ssd_list)
```

Arguments

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial (0 = go, 1 = stop)
rt_col	Name of the column in the dataframe df that contains response time in seconds
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition (0 = incorrect, 1 = correct)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
ssd_list	List of stop-signal delays used in the experiment

Value

Stop-signal reaction time corresponding roughly to 50 percent inhibition accuracy.

Examples

```
## Not run: mean_fixedSSD(df = results_df, rt_col = 'RT', stop_col = 'stopgo', acc_col = 'sst_acc',
ssd_col = 'soa', ssd_list = c(0.1, 0.2, 0.3, 0.5, 0.6))
## End(Not run)
```

plotInhFunc

Plots and prints stop-signal delays and accuracies

Description

Plots and prints stop-signal delays and corresponding accuracies. For studies that use fixed (randomly chosen on each trial from a pre-determined set) stop-signal delays.

Usage

```
plotInhFunc(df, stop_col, ssd_col, acc_col)
```

Arguments

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial (0 = go, 1 = stop)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition (0 = incorrect, 1 = correct)

Value

Line plot of the inhibition function.

Examples

```
## Not run: plotInhFunc(df = df, stop_col='vol', ssd_col='soa', acc_col='agn_acc')
```

Index

integration_adaptiveSSD, [1](#)
integration_fixedSSD, [2](#)

mean_adaptiveSSD, [3](#)
mean_fixedSSD, [3](#)

plotInhFunc, [4](#)