

# Package ‘SSRTcalc’

April 2, 2021

**Type** Package  
**Title** Easy SSRT Calculation in R  
**Version** 0.1.4  
**Author** Anton Leontyev  
**Maintainer** Anton Leontyev <a.g.leontiev@tamu.edu>  
**Description** This is a collection of functions to calculate stop-signal reaction time (SSRT) in R. This package includes functions for both integration and mean methods; both fixed and adaptive stop-signal delays are supported (see appropriate functions)  
**License** GPL-3  
**Encoding** UTF-8  
**LazyData** true  
**RoxygenNote** 7.1.1

## R topics documented:

integration_adaptiveSSD . . . . .	1
integration_fixedSSD . . . . .	2
mean_adaptiveSSD . . . . .	3
mean_fixedSSD . . . . .	3
<b>Index</b>	<b>5</b>

---

integration_adaptiveSSD	<i>SSRT using integration method for studies with "adaptive" method of setting SSD</i>
-------------------------	--

---

**Description**

Estimating SSRT using integration method for studies that use adaptive (increasing/decreasing by a given increment) stop-signal delays

**Usage**

```
integration_adaptiveSSD(df, stop_col, rt_col, acc_col, ssd_col)
```

**Arguments**

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial ( 0 = go, 1 = stop)
rt_col	Name of the column in the dataframe df that contains response time in seconds
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition ( 0 = incorrect, 1 = correct)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays

**Value**

SSRT corresponding to the nth rt -ssd;  $n = p(\text{respond}|\text{signal}) \times \text{number of goRTs}$

**Examples**

```
## Not run: integration_adaptiveSSD(df = results_df, stop_col = 'stopgo',
ssd_col = 'soa', rt_col = 'RT', acc_col = 'acc')
## End(Not run)
```

---

integration_fixedSSD	<i>SSRT using integration method for studies with "fixed" method of setting SSD</i>
----------------------	---

---

**Description**

Estimating SSRT using integration method for studies that use fixed (randomly chosen on each trial from a pre-determined set) stop-signal delays

**Usage**

```
integration_fixedSSD(df, stop_col, rt_col, acc_col, ssd_col, ssd_list)
```

**Arguments**

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial ( 0 = go, 1 = stop)
rt_col	Name of the column in the dataframe df that contains response time in seconds
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition ( 0 = incorrect, 1 = correct)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
ssd_list	List of stop-signal delays used in the experiment

**Value**

SSRT corresponding to the nth rt -ssd;  $n = p(\text{respond}|\text{signal}) \times \text{number of goRTs}$

**Examples**

```
## Not run: integration_fixedSSD(df = results_df, stop_col = 'stopgo',  ssd_col = 'soa',
rt_col = 'RT', acc_col = 'acc', ssd_list = c(0.4, 0.6, 0.8, 0.9, 1.0))
## End(Not run)
```

---

mean_adaptiveSSD	<i>SSRT using mean method for studies with "adaptive" method of setting SSD</i>
------------------	---

---

**Description**

Estimating SSRT using mean method for studies that use adaptive (increasing/decreasing by a given increment) stop-signal delays

**Usage**

```
mean_adaptiveSSD(df, rt_col, ssd_col, stop_col)
```

**Arguments**

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
rt_col	Name of the column in the dataframe df that contains response time in seconds
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial ( 0 = go, 1 = stop)

**Value**

Spline-interpolated stop-signal reaction time corresponding roughly to 50

**Examples**

```
## Not run: mean_adaptiveSSD(df = results_df, stop_col = 'stopgo',  ssd_col = 'soa', rt_col = 'RT')
```

---

mean_fixedSSD	<i>SSRT using mean method for studies with "fixed" method of setting SSD</i>
---------------	--

---

**Description**

Estimating SSRT using mean method for studies that use fixed (randomly chosen on each trial from a pre-determined set) stop-signal delays

**Usage**

```
mean_fixedSSD(df, stop_col, rt_col, acc_col, ssd_col, ssd_list)
```

**Arguments**

df	Dataframe with response time, accuracy, indication whether trial is stop or go, and delays for a given trial.
stop_col	Name of the column in the dataframe df that indicates whether a given trial is a "stop" or a "go" trial ( 0 = go, 1 = stop)
rt_col	Name of the column in the dataframe df that contains response time in seconds
acc_col	Name of the column in the dataframe df that contains accuracy of inhibition ( 0 = incorrect, 1 = correct)
ssd_col	Name of the column in the dataframe df that contains stop-signal delays
ssd_list	List of stop-signal delays used in the experiment

**Value**

Stop-signal reaction time corresponding roughly to 50

**Examples**

```
## Not run: mean_fixedSSD(df = results_df, rt_col = 'RT', stop_col = 'stopgo', acc_col = 'sst_acc',  
ssd_col = 'soa', ssd_list = c(0.1, 0.2, 0.3, 0.5, 0.6))  
## End(Not run)
```

# Index

integration\_adaptiveSSD, [1](#)

integration\_fixedSSD, [2](#)

mean\_adaptiveSSD, [3](#)

mean\_fixedSSD, [3](#)