



<a href="#">Home</a>	<a href="#">Q&amp;A</a>	<a href="#">Interview Corner</a>	<a href="#">Ask a question</a>	<a href="#">Contribute</a>	<a href="#">GATE</a>	<a href="#">Algorithms</a>	<a href="#">C</a>	<a href="#">C++</a>	<a href="#">Books</a>	<a href="#">About us</a>
<a href="#">Arrays</a>	<a href="#">Bit Magic</a>	<a href="#">C/C++ Puzzles</a>	<a href="#">Articles</a>	<a href="#">GFactS</a>	<a href="#">Linked Lists</a>	<a href="#">MCQ</a>	<a href="#">Misc</a>	<a href="#">Output</a>	<a href="#">Strings</a>	<a href="#">Trees</a>

Hus

August 14, 2012



What will be the size of following structure?

```
struct employee
{
    int    emp_id;
    int    name_len;
    char   name[0];
};
```

4 + 4 + 0 = 8 bytes.

And what about size of "name[0]". In gcc, when we create an array of zero length, it is considered as array of incomplete type that's why gcc reports its size as "0" bytes. This technique is known as "Struct Hack". When we create array of zero length inside structure, it must be (and only) last member of structure. Shortly we will see how to use it.

"Struct Hack" technique is used to create variable length member in a structure. In the above structure, string length of "name" is not fixed, so we can use "name" as variable length array.

Let us see below memory allocation.

```
struct employee *e = malloc(sizeof(*e) + sizeof(char) * 128);
```

is equivalent to

```
struct employee
{
    int    emp_id;
    int    name_len;
    char   name[128]; /* character array of size 128 */
};
```

And below memory allocation

```
struct employee *e = malloc(sizeof(*e) + sizeof(char) * 1024);
```

is equivalent to

```
struct employee
{
    int    emp_id;
    int    name_len;
    char   name[1024]; /* character array of size 1024 */
};
```

Note: since name is character array, in malloc instead of "sizeof(char) \* 128", we can use "128" directly. sizeof is used to avoid confusion.

Now we can use "name" same as pointer. e.g.

```
e->emp_id = 100;
e->name_len = strlen("Geeks For Geeks");
strcpy(e->name, "Geeks For Geeks", e->name_len);
```

When we allocate memory as given above, compiler will allocate memory to store "emp\_id" and "name\_len" plus contiguous memory to store "name". When we use this technique, gcc guarantees that, "name" will get contiguous memory.

Obviously there are other ways to solve problem, one is we can use character pointer. But there is no guarantee that character pointer will get contiguous memory, and we can take advantage of this contiguous memory. For example, by using this technique, we can allocate and deallocate memory by using single malloc and free call (because memory is contiguous). Other advantage of this is, suppose if we want to write data, we can write whole data by using single "write()" call. e.g.

```
write(fd, e, sizeof(*e) + name_len); /* write emp_id + name_len + name */
```

If we use character pointer, then we need 2 write calls to write data. e.g.

```
write(fd, e, sizeof(*e)); /* write emp_id + name_len */
write(fd, e->name, e->name_len); /* write name */
```

Note: In C99, there is feature called "flexible array members", which works same as "Struct Hack"

This article is compiled by **Narendra Kangraikar**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



3



0



0

## Download COBOL Editor

[www.scitools.com](http://www.scitools.com)

Code comprehension, maintenance  
Metrics, graphs and documentation

<a href="#">Interview Experiences</a>
<a href="#">Advanced Data Structures</a>
<a href="#">Dynamic Programming</a>
<a href="#">Greedy Algorithms</a>
<a href="#">Backtracking</a>
<a href="#">Pattern Searching</a>
<a href="#">Divide &amp; Conquer</a>
<a href="#">Graph</a>
<a href="#">Mathematical Algorithms</a>
<a href="#">Recursion</a>
<a href="#">Java</a>

[Like](#)

32,227 people like GeeksforGeeks.

Facebook social plugin

lenovo FOR THOSE WHO DO.

YOGA

Ultrabook™. Inspired by Intel. Powered by 3rd Gen Intel® Core™ i7 Processor.

LEARN MORE

sdp

<a href="#">All permutations of a given string</a>
<a href="#">Memory Layout of C Programs</a>
<a href="#">Understanding "extern" keyword in C</a>
<a href="#">Median of two sorted arrays</a>
<a href="#">Tree traversal without recursion and without stack!</a>
<a href="#">Structure Member Alignment, Padding and Data Packing</a>
<a href="#">Intersection point of two Linked Lists</a>
<a href="#">Lowest Common Ancestor in a BST.</a>
<a href="#">Check if a binary tree is BST or not</a>
<a href="#">Sorted Linked List to Balanced BST</a>

HP ENVY 15z A8-5550M;  
750GB Hybrid HD; 12GB  
Memory; Windows 8 64  
HPDirect



Find Great Deals at HP®  
Official Store!

\$659.99



Writing code in comment? Please refer [here](#) for guidelines.



[Learn Xcode and iOS](#)

[Mobile Apps Development](#)

[Kata 7.9" Quadcore tablet](#)

[Enterprise Web Hardware](#)

[Follow](#) 1,670 followers

[+1](#) 648



Subscribe



**Sanjay Agarwal**

```
#include<stdio.h> #include<conio.h>...</conio.h></stdio.h>
```

Detect Cycle in a Graph · 29 minutes ago

**Samish Chandra Kollii** think we may to  
add a check for detecting...

Find the first circular tour that visits all petrol  
pumps · 53 minutes ago

**Samish Chandra Kollii** think we may to  
add a check for detect the...

Find the first circular tour that visits all petrol  
pumps · 53 minutes ago

**Thien Nguyen**Small improve : change  
k to k - node->data when...

Remove all nodes which don't lie in any path  
with sum>= k · 57 minutes ago

**thiennguyen**Small improve : change  
k to k - node->data when...

Remove all nodes which don't lie in any path  
with sum>= k · 1 hour ago

**Krishna Prasad**For step 2: what if i  
use.... int flag=1;...

Dynamic Programming | Set 23 (Bellman  
-Ford Algorithm) · 2 hours ago

AdChoices [D](#)

[Data Structure](#)

[Code C++](#)

[C C++ Java](#)

AdChoices [D](#)

[Function](#)

[Char](#)

[C++ Programming](#)

AdChoices [D](#)

[Hack](#)

[C++ Compiler](#)

[GCC](#)