

Longest common substring (DP)

```
# Time c. O(nm), space c. O(nm)
def longest_common_substring(s1, s2):
    m = [[0] * (1+len(s2)) for i in \
          range(1+len(s1))]
    max_len, end_idx = 0, 0
    for i in range(1, 1 + len(s1)):
        for j in range(1, 1 + len(s2)):
            if s1[i - 1] == s2[j - 1]:
                m[i][j] = m[i-1][j-1] + 1
                if m[i][j] > max_len:
                    max_len = m[i][j]
                    end_idx = i
            else:
                m[i][j] = 0
    return s1[end_idx-max_len : end_idx]
```

Longest common subsequence (DP)

```
# time c. O(nm), space c.
def lcs(s1, s2):
    matrix = [ [ '' for x in range(len(s2))]\
               for y in range(len(s1)) ]
    for i in range(len(s1)):
        for j in range(len(s2)):
            if s1[i] == s2[j]:
                if i == 0 or j == 0:
                    matrix[i][j] = s1[i]
                else:
                    matrix[i][j] = matrix[i-1][j-1] +\
                                   s1[i]
            else:
                matrix[i][j] = max( matrix[i-1][j],
                                    matrix[i][j-1],
                                    key=len)
    return matrix[-1][-1]
```

Make sentences with dictionary

```
def make_sent(string, dictionaries):
    global count
    if len(string) == 0:
        return True
    for i in range(0, len(string) + 1):
        prefix,suffix=string[:i],string[i:]
        if prefix in dictionaries:
            if suffix in dictionaries or\
               make_sent(suffix, dictionaries):
                count += 1
    return True

count = 0
string1 = "applet"
dictionary1 = {'app', 'let', 'apple', 't', 'applet'}
print( make_sent(string1, dictionary1) )
print( count )
```

True

3

Longest common substring in array

```
# time c. O(n*n*(n + n-1 + n-2 ... etc.)?
def longest_substr(arr):

    if len(arr) <= 1:
        return ''
    res      = ''
    reference = arr[0]
    for i in range(len(reference)):
        for j in range(len(reference)-i+1):
            candidate = reference[i:i+j]
            if j > len(res) and\
               all(candidate in x for x in arr):
                res = candidate
    return res
```

```
def max_subarray_sum(arr):
    if len(arr)==0: return 0
    max_sum = curr_sum = arr[0] # if neg
    start, tstart, end = 0, 0, 0
    for i in range(1, len(arr)):
        if arr[i] > curr_sum + arr[i]:
            curr_sum = arr[i]
            tstart = i
        else:
            curr_sum += arr[i]
        if curr_sum > max_sum:
            max_sum = curr_sum
            start = tstart
            end = i
    return max_sum, arr[ start:end+1 ]
```

```
# Time c. O(n), space c. O(n)
from collections import defaultdict
def findSubarraysWithSumK(arr, k):
    hash_map = defaultdict(list) # key=sum, value=end indices
    res = [] # subarrays
    curr_sum = 0
    for i in range( len(arr) ):
        curr_sum += arr[i]
        if curr_sum == k:
            res.append(arr[:i+1]) # or res.append((0, i+1))
        if curr_sum-k in hash_map:
            for value in hash_map[ curr_sum-k ]:
                res.append( arr[ value+1:i+1 ] )
                # or res.append((value+1, i+1))
        hash_map[ curr_sum ].append(i)
    return res
```

All non-contig. pairs sum up to k (unsorted)

```
def pair_sum(arr, k):
    if len(arr) < 2: return
    seen, output = set(), set()
    for num in arr:
        if k-num not in seen:
            seen.add(num)
        else:
            output.add( (min(num,k-num), max(num,k-num)) )
    return '\n'.join(map(str,list(output)))
```

Non-contig pair, sum closest to k (sorted)

```
# time c. O(n)
MAX_VAL = 1000000000
def closest_sum(arr, n, k):
    res = 0, 0
    l, r, diff = 0, n-1, MAX_VAL
    while l < r:
        if abs(arr[l] + arr[r] - k) < diff:
            res = l, r
            diff = abs(arr[l] + arr[r] - k)
        if arr[l] + arr[r] > k:
            r -= 1
        else:
            l += 1
    return arr[res[0]], arr[res[1]]
```

Partition - two subarrays equal sum

Optional

```
# Recursive, t. complexity = 2**n
def isSubsetSum(arr, n, sum_):
    if sum_ == 0:
        return True
    if n == 0 and sum_ != 0:
        return False
    if arr[n-1] > sum_:
        return isSubsetSum(arr, n-1, sum_)
    return isSubsetSum(arr, n-1, sum_) or\
           isSubsetSum(arr, n-1, sum_-arr[n-1])

# t.c.= O(n*sum)
def isSubsetSum_dp(arr, n):
    sum_ = 0
    for i in range(n): sum_ += arr[i]
    if sum_ % 2 != 0: return 0
    part = [0] * ((sum_ // 2) + 1) # 0 (False)
    # part[j]=true if exists subset w/sum=j
    for i in range(n):
        for j in range(sum_ // 2, arr[i]-1, -1):
            if (part[j - arr[i]] == 1 or j == arr[i]):
                part[j] = 1
    return part[sum_ // 2]
```

Smallest +int != sum of subarray

- If $\text{arr}[i] > \text{res} \Rightarrow$ found a gap $[1, 2, 5] \Rightarrow 4$
- Elems after $\text{arr}[i] > \text{res}$
- res = solution

```
# time c. O(n) - sorted array
def findSmallest(arr, n):
    res = 1
    for i in range(n):
        if arr[i] <= res:
            res = res + arr[i]
        else:
            break
    return res
```

Partition - two subarrayys w/min diff. sums

Finds arrays w/min. possible difference

```
# t.c.= O(2**n)
def findMinRec(arr, i, sumCalculated, sumTotal):
    # If last elem, sum of one subset = sumCalculated,
    # sum of other subset = (sumTotal-sumCalculated). Return abs diff
    if i == 0:
        return abs( (sumTotal-sumCalculated) - sumCalculated )
    # For each arr[i], (1) we can exclude it from first set,
    # (2) we can include it. return min of two choices
    return min( findMinRec( arr,
                           i-1,
                           sumCalculated + arr[i-1],
                           sumTotal),
                findMinRec( arr,
                           i-1,
                           sumCalculated,
                           sumTotal ) )

def findmin_recursive(arr, n):
    # total sum of arr
    sumTotal = 0
    for i in range(n):
        sumTotal += arr[i]
    return findMinRec(arr, n, 0, sumTotal)
```

Balanced parenthesis check

```
def balance_check(s):
    if len(s)%2 != 0: return False
    opening = set('([{')
    # matching pairs
    matches = set([ ('(', ')'),
                   ('[', ']'),
                   ('{', '}'), ]))
    stack = []
    for paren in s:
        if paren in opening:
            stack.append(paren)
        else:
            if len(stack) == 0:
                return False
            last_open = stack.pop()
            if (last_open,paren) not in matches:
                return False
    return len(stack) == 0
```

All non-contig. triplets w/ sum < k

```
# Time c. O(n^2); sort() + smart iteration
def count_triplets(arr, k):
    arr.sort()
    n = len(arr)
    count = 0
    for i in range(n-2):
        start = i + 1
        end = n - 1
        while start < end:
            if (arr[i] + arr[start] + arr[end]) >= k:
                end -= 1
            else:
                count += (end-start) # array sorted
                start += 1
    return count
```

Count paths

```
# Time c. = O(c**n) exponential
def count_paths_rec(m, n):
    if m == 1 or n == 1: return 1
    return count_paths_rec(m-1, n) + count_paths_rec(m, n-1)
```

```
# Time & space = O(mn)
def count_paths(m, n):
    if m < 1 or n < 1: return -1
    count = [[None for j in range(n)] for i in range(m)]
    for i in range(n): count[0][i] = 1
    for j in range(m): count[j][0] = 1
    for i in range(1, m):
        for j in range(1, n):
            count[i][j] = count[i - 1][j] + count[i][j - 1]
    return count[m - 1][n - 1]
```

```
# Time O(mn), space O(n)
def count_paths_dp(m, n):
    dp = [1 for i in range(n)]
    for i in range(1, m):
        for j in range(1, n):
            dp[j] = dp[j] + dp[j - 1]
    return dp[n - 1]
```

All non-contig. triplets w/sum=0

```
# Time c. O(n^2), space c. O(1)
def findTriplets(arr):
    arr.sort()
    n = len(arr)
    count = 0
    for i in range(n-2):
        start = i + 1
        end = n - 1
        while start < end:
            if arr[i] + arr[start] + arr[end] == 0:
                count += 1
                start += 1
            end -= 1
            elif (arr[i] + arr[start] + arr[end] < 0):
                start += 1
            else:
                end -= 1
    return count
```

Get all permutations of string

```
def permute(s):
    out = []
    if len(s) == 1:
        out = [s]
    else:
        for i, char in enumerate(s):
            for perm in permute(s[:i] + s[i+1:]):
                out += [char + perm]
    return out
```

```
permute('abc')
```

```
['abc', 'acb', 'bac', 'bca', 'cab', 'cba']
```

Merge Sort (mid)

Usage: sorting **linked lists**, inversion count in nearly sorted arr ($i < j$, but $A[i] > A[j]$), external sort (data too big for memory)

```
# time c. O(nLogn), space c. O(n)
def merge_sort(arr):
    # arr of length 1 - returned as is
    if len(arr) > 1:
        mid = len(arr) // 2
        left = merge_sort(arr[ :mid])
        right = merge_sort(arr[mid: ])
        i, j, k = 0, 0, 0
        while i < len(left) and j < len(right):
            if left[i] < right[j]:
                arr[k] = left[i]
                i += 1
            else:
                arr[k] = right[j]
                j += 1
            k += 1
        while i < len(left):
            arr[k] = left[i]
            i += 1
            k += 1
        while j < len(right):
            arr[k] = right[j]
            j += 1
            k += 1
    return arr
```

Quick Sort (pivot)

Pick **pivot** element (*first, last, random, median*), and **partition** array: all smaller elems before pivot, greater elements after pivot
Usage: sorting arrays

```
# O(nLogn), worst case O(n^2)
# time c. O(logn), qualifies as in-place
def quick_sort(arr, low, high):
    if low < high:
        pi = partition(arr, low, high)
        quick_sort(arr, low, pi-1)
        quick_sort(arr, pi+1, high)

def partition(arr, low, high):
    pivot = arr[high]
    i = low - 1
    for j in range(low, high):
        if arr[j] < pivot:
            i += 1
            arr[i], arr[j] = arr[j], arr[i]
    # place pivot in the middle
    arr[i+1], arr[high] = arr[high], arr[i+1]
    return i+1
```

Edit Levenshtein Distance

```
def levenshtein(s1, s2):
    if len(s1) > len(s2):
        s1, s2 = s2, s1
    distances = range(len(s1) + 1)
    for idx2, char2 in enumerate(s2):
        distances_ = [idx2+1]
        for idx1, char1 in enumerate(s1):
            if char1 == char2:
                distances_.append(distances[idx1])
            else:
                distances_.append(1 + min((distances[idx1],
                                           distances[idx1+1], distances_-[-1])))
        distances = distances_
    return distances[-1]
```

Heap Sort

Usage: sort nearly sorted array, k largest (smallest) elems

Complete binary tree = every level filled, except possibly last, and nodes are in far left

Binary Heap = cbt where parent $>(<)$ children

Procedure: build max heap; replace max w/ last elem; reduce heap by 1; heapify root; repeat Array repr: root = arr[0];

for any i-th node arr[i]:

- a) arr[i-1]/2 = parent node
- b) arr[(2*i)+1] = left child
- c) arr[(2*i)+2] = right child

time O(nLogn), space in-place

```
def heap_sort(arr):
    n = len(arr)
    for i in range(n, -1, -1):
        heapify(arr, n, i)
    for i in range(n-1, 0, -1):
        arr[i], arr[0] = arr[0], arr[i]
        heapify(arr, i, 0)
```

def heapify(arr, n, i):

```
largest = i
l = 2 * i + 1
r = 2 * i + 2
if (l < n and arr[i] < arr[l]):
    largest = l
if (r < n and arr[largest] < arr[r]):
    largest = r
if (largest != i):
    arr[i], arr[largest] = arr[largest], arr[i]
    heapify(arr, n, largest)
```

Binary Search

```
# time O(Logn), space (O1)
def binary_search(arr, value):
    if len(arr) == 0: return None
    min_idx, max_idx = 0, len(arr)
    while min_idx < max_idx:
        mid = (min_idx + max_idx) // 2
        if arr[mid] == value:
            return mid
        elif arr[mid] < value:
            min_idx = mid + 1
        else: max_idx = mid
    return None
```

Graphs

- vertices / nodes w/names (keys) and payloads (additional info);
- unordered = **undirected graph** vs **directed graph** (digraph);
- weight on edge - cost from 1 vertex to the other (distance betw. cities)
- Path - # vertices connected by edges.
- Path length - # edges in unweighted g. ($n-1$) OR sum of weights in weighted g.
- Cycle in directed g. - path starts / ends at same vertex.
- If no cycles - **acyclic graph**; if also directed - directed acyclic graph (**DAG**)

Adjacency matrix = $\begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 0 \end{bmatrix}$

- time c. $O(1)$ see if edge present, add / remove edge;
- $O(n)$ get vertex's adj. list, $O(V^2)$ _add vertex
- memory hog: space c. $O(n^2) \Rightarrow$ good for **dense graphs**:
- better for **weighted graphs**;
- good for matrix operations (**insights**);
- Undirected graphs - adj. matrix **symmetric**

Adjacency list r.: edge_list = $\begin{bmatrix} [0,1], [0,2] \end{bmatrix}$ or dict[[list]] (node: verts) or dict[dicts] (if weigh

- time c. $O(1)$ get vertex's adj. list (array indexing)
- $O(E) (E=\# v-s)$ if edge (i,j) exists
- Efficient storage (space c. = $O(2E)$)

Objects/pointer r.

- time c. $O(n)$ access a node;
- space c. $O(n)$ if nodes only, $O(n^2)$ w/pointers;
- better for **directed graphs** (pointers);
- high search time c.

Incidence matrix

rows = vertices, columns = edges, entries = is vertex incident to edge (bool)

BFS2

```
def bfs2(graph, start):
    visited, queue = {start}, [start]
    while queue:
        vertex = queue.pop(0)
        print(str(vertex) + " ", end="")
        for neighbor in graph[vertex]:
            if neighbor not in visited:
                visited.add(neighbor)
                queue.append(neighbor)

graph = {0: [1, 2], 1: [2], 2: [3], 3: [1, 2]}
bfs2(graph, 0)
```

DFS

queue.pop(0) for BFS

```
# time c. O(V+E), space c. O(V)
def dfs(graph, start):
    visited, stack = set(), [start]
    while stack:
        vertex = stack.pop()
        if vertex not in visited:
            print(vertex, end=' ')
            visited.add(vertex)
            stack.extend(graph[vertex] - visited)
    return visited
```

```
graph = { 0: set([1, 2]), 1: set([2]),
          2: set([3]), 3: set([1, 2]) }
dfs(graph, 0)
```

0 2 3 1

Shortest path

Always returned first by BFS

```
def shortest_path(graph, start, goal):
    try:
        return next(bfs_paths(graph, start, goal))
    except StopIteration:
        return None
```

```
graph = {'A': set(['B', 'C']),
         'B': set(['A', 'D', 'E']),
         'C': set(['A', 'F']),
         'D': set(['B']),
         'E': set(['B', 'F']),
         'F': set(['C', 'E'])}

shortest_path(graph, 'A', 'F')
['A', 'C', 'F']
```

```
def kahn_toposort( graph ):
    topo = []
    in_degree = { k: 0 for k in graph }
    for k in graph:
        for v in graph[ k ]:
            in_degree[v] += 1
    q = [k for k,v in in_degree.items() if v==0]
    while q:
        k = q.pop()
        topo.append( k )
        for v in graph[ k ]:
            in_degree[ v ] -= 1
            if in_degree[ v ] == 0:
                q.append( v )
    return topo if len(topo)==len(graph) else []
```

Articulation point

(vertex) or

bridge (edge) –

disconnects graph when removed.

Connectedness verified by DFS

All Paths from Vertex A to Vertex B

```
def bfs_paths(graph, start, goal):
    queue = [(start, [start])]
    while queue:
        (vertex, path) = queue.pop(0)
        for nxt in graph[vertex] - set(path):
            if nxt == goal:
                yield path + [nxt]
            else:
                queue.append((nxt, path + [nxt]))
```

2a. Depth First Traversals (Binary Tree) BFS (iterative)

```
# time O(n), space O(h), h=height
class Node:
    def __init__(self, val):
        self.val = val
        self.left = None
        self.right = None

# Root Left Right
def Preorder(root):
    if root:
        print(root.val, end=' ')
        Preorder(root.left)
        Preorder(root.right)

# Left Right Root
def Postorder(root):
    if root:
        Postorder(root.left)
        Postorder(root.right)
        print(root.val, end=' '),

# Left Root Right
def Inorder(root):
    if root:
        Inorder(root.left)
        print(root.val, end=' ')
        Inorder(root.right)
```

```
root          = Node(1)
root.left     = Node(2)
root.right    = Node(3)
root.left.left = Node(4)
root.left.right = Node(5)
print("Preorder traversal:")
Preorder(root)
```

```
# time O(n), space O(n)
class Node:
    # create a new node
    def __init__(self, key):
        self.val = key
        self.left = None
        self.right = None

# print height
def LevelOrder(root):
    # base case
    if root is None:
        return
    queue = []
    queue.append(root)
    while(len(queue) > 0):
        node = queue.pop(0)
        print(node.val, end=' ')
        if node.left is not None:
            queue.append(node.left)
        if node.right is not None:
            queue.append(node.right)
```

Array representation of bin. tree:

node i
parent: $(i-1)/2$
left child: $2*i + 1$
right child: $2*i + 2$

TYPES OF TREES:

- **m-ary tree** - rooted tree, each node has no more than m children
- **Binary tree (BT)** - each node has *at most two children*
- **Complete BT** = bin tree, **every level is full**, except possibly last (far left).
- **BST** - parent's value greater than values in left subtree & less values in right subtree
- **Binary Heap** (max / min) = cbt, parent $>(<)$ children
- **Full (proper or plane) BT** - every node has **0 or 2 children**
- **Perfect BT** - all interior nodes have two children and all leaves have same depth
- **Infinite complete BT** - every node has two children (infinite levels)
- **Balanced BT** - L and R subtrees of each node differ in height by no more than 1
- **Degenerate (pathological) tree** - each parent has only one child = **linked list**
- **Representation:** list, dict, object

BFS (recursive) incl. height

```
# Recursive - time O(n^2), space O(n)
def LevelOrder_rec(root):
    h = height(root)
    for i in range(1, h+1):
        printGivenLevel(root, i)

# print nodes at a given level
def printGivenLevel(root, level):
    if root is None:
        return
    if level == 1:
        print(root.val, end=" ")
    elif level > 1:
        printGivenLevel(root.left, level-1)
        printGivenLevel(root.right, level-1)

# compute height - number of nodes from root :
def height(node):
    if node is None:
        return 0
    else:
        # Compute the height of each subtree
        lheight = height(node.left)
        rheight = height(node.right)

        #Use the larger one
        if lheight > rheight:
            return lheight+1
        else:
            return rheight+1
```

```
root = Node(1)
root.left = Node(2)
root.right = Node(3)
root.left.left = Node(4)
root.left.right = Node(5)
LevelOrder_rec(root)
```

Check if BT is balanced

```
# time O(n)
def is_balanced(root):
    return -1 != get_depth(root)
# return 0 if unbalance. else depth+1
def get_depth(root):
    if not root:
        return 0
    left = get_depth(root.left)
    right = get_depth(root.right)
    if abs(left-right) > 1 or \
        left == -1 or right == -1:
        return -1
    return 1 + max(left, right)
```

Lowest common ancestor (any BT)

```
def lca(root, p, q):
    if not root or root is p or root is q:
        return root
    left = lca(root.left, p, q)
    right = lca(root.right, p, q)
    if left and right:
        return root
    return left if left else right
```

Check if tree is BST

```
# If BST=>inorder traversal = sorted list
def inorder( root ):
    if tree != None:
        inorder(root.left)
        tree_vals.append(root.val)
        inorder(root.right)

def sort_check( tree_vals ):
    return tree_vals == sorted(tree_vals)

tree_vals = []
inorder(tree)
sort_check(tree_vals)
```

Invert a binary tree

```
def reverse(root):
    if not root: return
    root.left,root.right=root.right,root.left
    if root.left:
        reverse(root.left)
    if root.right:
        reverse(root.right)
```

Check if 2 BTs equal

```
# time O(min(N,M)), N,M=# nodes
# space O(min(h1, h2))
def is_same_tree(p, q):
    if not p and not q:
        return True
    if p and q and p.val == q.val:
        return is_same_tree(p.left, q.left) and\
               is_same_tree(p.right, q.right)
    return False
```

Min / Max height

```
def max_height(root):
    if not root: return 0
    return max(max_height(root.left),\n              max_height(root.right)) + 1

def min_height(root):
    if not root: return 0
    if not root.left or not root.right:
        return max(min_height(root.left),\n                  min_height(root.right))+1
    return min(min_height(root.left),\n              min_height(root.right)) + 1
```

Trim BST

```
def trimBST(tree, minVal, maxVal):
    if not tree: return
    tree.left=trimBST(tree.left, minVal, maxVal)
    tree.right=trimBST(tree.right, minVal, maxVal)
    if minVal<=tree.val<=maxVal:
        return tree
    if tree.val < minVal:
        return tree.right
    if tree.val > maxVal:
        return tree.left
```

BST node w/value closest to k

```
def closest_value(root, k):
    a = root.val
    child = root.left if k < a else root.right
    if not child:
        return a
    b = closest_value(child, k)
    return min(k-a, k-b)|
```

Rotate matrix clockwise, in place

```
# time O(2M) -> O(M), space O(1)
class Solution(object):
    def rotate(self, matrix):
        self.transpose(matrix)
        self.reflect(matrix)

    def transpose(self, matrix):
        n = len(matrix)
        for i in range(n):
            for j in range(i+1, n):
                matrix[i][j], matrix[j][i] =\
                    matrix[j][i], matrix[i][j]

    def reflect(self, matrix):
        n = len(matrix)
        for i in range(n):
            for j in range(n//2):
                matrix[i][j], matrix[i][-j-1] =\
                    matrix[i][-j-1], matrix[i][j]
```

Maximum path sum

```
def max_path_sum(root):
    maximum = float("-inf")
    maximum = helper_max(root, maximum)
    return maximum

def helper_max(root, maximum):
    if not root: return 0
    left = helper_max(root.left, maximum)
    right = helper_max(root.right, maximum)
    maximum = max(maximum, left+right+root.val)
    return root.val + maximum

max_path_sum(tree)
```

BST nodes in given range

```
#Time O(h + k), k=num nodes
def getCount(root, low, high):
    if root == None: return 0
    if root.data==high and root.data==low:
        return 1
    if root.data <= high and root.data >= low:
        return (1 + getCount(root.left, low, high) +\
                getCount(root.right, low, high))
    elif root.data < low:
        return getCount(root.right, low, high)
    else:
        return getCount(root.left, low, high)
```

Queue with two stacks

```
class Queue2Stacks(object):
    def __init__(self):
        self.instack = []
        self.outstack = []

    def enqueue(self, element):
        self.instack.append(element)

    def dequeue(self):
        if not self.outstack:
            while self.instack:
                self.outstack.append(
                    self.instack.pop())
        return self.outstack.pop()
```

Queue - FIFO, stack - LIFO

Dequeue – double-ended queue

Compare 2 strings as linked lists

```
# 0=same, 1=1st str lexicographically >,
# -1 - 2nd
class Node:
    def __init__(self, key):
        self.c = key
        self.next = None

def compare(list1, list2):
    while (list1 and list2 and
           list1.c == list2.c):
        list1 = list1.next
        list2 = list2.next
    if (list1 and list2):
        return 1 if list1.c > list2.c else -1
    if (list1 and not list2):
        return 1
    if (list2 and not list1):
        return -1
    return 0

list1 = Node('g')
list1.next = Node('o')
...
print(compare(list1, list2))
```

Reverse SLL

```
# time O(n), space O(1)
def reverse_sll(head):
    current = head
    previous = None
    next_node = None
    while current:
        next_node = current.next
        current.next = previous
        previous = current
        current = next_node
    return previous
```

Stack using two queues

```
from queue import Queue
class Stack:
    def __init__(self):
        self.q1 = []
        self.q2 = []
        self.curr_size = 0

    def push(self, x):
        self.curr_size += 1
        self.q2.append(x)
        while self.q1:
            self.q2.append(self.q1.pop(0))
        self.q1 = self.q2
        self.q2 = self.q1

    def pop(self):
        if not self.q1:
            return
        self.curr_size -= 1
        return self.q1.pop(0)

    def peek(self):
        if not self.q1:
            return -1
        return self.q1[0]

    def size(self):
        return self.curr_size
```

(SLL) nth to the last element

```
def nth_to_last_node(head, n):
    left_pointer = head
    right_pointer = head
    for i in range(n-1):
        if not right_pointer.next:
            print('n > length list')
            return
        right_pointer = right_pointer.next
    while right_pointer.next:
        left_pointer = left_pointer.next
        right_pointer = right_pointer.next
    return left_pointer.value
```

Break cycle (SLL)

```
def removeLoop(head, loop_node):
    pointer1 = head
    while(1):
        pointer2 = loop_node
        while (pointer2.next != loop_node and
               pointer2.next != pointer1):
            pointer2 = pointer2.next
        if pointer2.next == pointer1:
            break
        pointer1 = pointer1.next
        pointer2.next = None
```

Next greater elem w/stack

[11, 14, 21] => 11:14, 14:21, 21:-1

```
# time O(n)
def printNGE(arr):
    stack = []
    stack.append(arr[0])
    for i in range(1, len(arr)):
        next_ = arr[i]
        if stack:
            elem = stack.pop()
            while elem < next_:
                print(str(elem) + " : " + str(next_))
                if not stack:
                    break
                elem = stack.pop()
            if elem > next_:
                stack.append(elem)
        stack.append(next_)
    while stack:
        elem = stack.pop()
        next_ = -1
        print(str(elem) + " : " + str(next_))

arr = [11, 14, 21, 3]
printNGE(arr)
```

Singly Linked List (SLL)

```
class Node:
    def __init__(self, value):
        self.value = value
        self.next = None
```

Doubly Linked List (DLL)

```
class DLL_Node(object):
    def __init__(self, value):
        self.value = value
        self.next = None
        self.prev = None
```

9

Check if cycle (SLL)

```
def cycle_check(node):
    marker1 = node
    marker2 = node
    while marker2 and marker2.next:
        marker1 = marker1.next
        marker2 = marker2.next.next
        if marker2 == marker1:
            return True
    return False
```

Length of linked list (SLL)

```
def length_LL(LL, head):
    if (not head):
        return 0
    else:
        return 1 + \
length_LL(LL, head.next)
```

Knapsack DP

```
# max sum of values for subset of weights <= W
# O(N*W) time and space
def knapSack(W, weights, values, n):
    DP = [[0 for x in range(W + 1)] for x in range(n + 1)]
    for i in range(n + 1):
        for w in range(W + 1):
            if i == 0 or w == 0:
                DP[i][w] = 0
            elif weights[i-1] <= w:
                DP[i][w] = max(values[i-1] + DP[i-1]\[w - weights[i-1]], DP[i-1][w])
            else:
                DP[i][w] = DP[i-1][w]
    return DP[n][W]

values = [60, 100, 120]
weights = [10, 20, 30]
W = 50
print(knapSack(W, weights, values, len(values)))
```

Num ways to cover distance

All ways to cover distance it w/1, 2, 3 steps

```
# time O(n), space O(n)
def count_dp(dist):
    count = [0] * (dist + 1)
    count[0] = 1
    count[1] = 1
    count[2] = 2
    for i in range(3, dist + 1):
        count[i] = (count[i-1] +\ 
                    count[i-2] +\ 
                    count[i-3])
    return count[dist];

dist = 20
print(count_dp(dist))
```

121415

Memoization

```
def factorial(n):
    if n < 2:
        return 1
    if not n in memo:
        memo[n] = n * factorial(n-1)
    return memo[n]

memo = {}
factorial(1)
```

Recursion

```
def fact(n):
    if n < 2:
        return 1
    else:
        return n * fact(n-1)

fact(5)
```

Coin change (knapsack variant)

```
# recursion + memoization
# arr coins + target amnt => fewest coins as change
def coins_dp(target, coins, known_results):
    min_coins = target
    if target in coins:
        known_results[target] = 1
        return 1
    elif known_results[target] > 0:
        return known_results[target]
    else:
        for i in [c for c in coins if c <= target]:
            num_coins = 1 + coins_dp(target-i,
                                      coins,
                                      known_results, )
            if num_coins < min_coins:
                min_coins = num_coins
                known_results[target] = min_coins
    return min_coins
```

Fibonnaci dynamic

```
target = 74
coins = [1, 5, 10, 25]
known_results = [0] * (target+1)
coins_dp(target, coins, known_results)
8
```

Fibonnaci recursive

```
# time O(2^n)
def fib_rec(n):
    if n == 0 or n == 1:
        return n
    else:
        return fib_rec(n-1) + fib_rec(n-2)

# print 1st 20 Fib. nums
for i in range(20):
    print(fib_rec(i), end=', ')
```

```
# memoization (dynamic)
# time O(n) - counting sequentially
def fib_dyn(n):
    if n == 0 or n == 1:
        return n
    if not n in memo:
        memo[n] = fib_dyn(n-1) +\ 
                  fib_dyn(n-2)
    return memo[n]

for n in range(20):
    memo = [None] * (n + 1)
    print(fib_dyn(n), end=', ')
```

Fibonnaci iterative

```
# iterative - tuple unpacking
# time O(n) - counting sequentially
def fib_iter(n):
    a = 0
    b = 1
    for i in range(n):
        a, b = b, a + b
    return a

for i in range(20):
    print(fib_iter(i), end=', ')
```

Longest Substr. w/K Chars

```
# Time c. O(n), space c. O(1)
# At most k distinct characters
def LongestSubstring(s, k):
    n = len(s)
    if n*k==0:
        return 0
    l, r = 0, 0
    mapp = dict()
    max_len = 2
    for c in s:
        mapp[ s[r] ] = r
        r += 1
        if len(mapp) == k+1:
            del_idx = min(mapp.values())
            del mapp[ s[del_idx] ]
            l = del_idx + 1
            max_len = max(max_len, r - 1)
    return max_len
```

Longest Substr. w/Unique Ch

```
def lengthOfLongestSubstring2(s):
    mapp = {c:0 for c in s}
    left = 0
    max_len = 0
    for right, c in enumerate(s):
        mapp[c] += 1
        while mapp[c] > 1:
            mapp[ s[left] ] -= 1
            left += 1
        max_len = max(max_len,
                      right-left+1)
    return max_len
```

Minimum Window Substring

11

```
# time/space c. O(n+m)
# min. contig. substr. of s w/all chars from t
from collections import Counter
def minWindow(s, t):
    if not t or not s:
        return ''
    # unique chars in t and curr window
    dict_t = Counter(t)
    curr = {}
    len_t = len(dict_t)
    len_curr = 0
    l,r = 0,0
    # length, l, r
    res = float('inf'), None, None
    while r < len(s):
        char = s[r]
        curr[ char ] = curr.get(char, 0) + 1
        if char in dict_t and\
           curr[char] == dict_t[char]:
            len_curr += 1
        while l <= r and len_curr == len_t:
            char = s[l]
            if r - l + 1 < res[0]:
                res = (r - l + 1, l, r)
            curr[ char ] -= 1
            if char in dict_t and\
               curr[char] < dict_t[char]:
                len_curr -= 1
            l += 1
        r += 1
    return '' if res[0]==float('inf') else\
              s[res[1]:res[2]+1]
```

Median of Two Sorted Arrays

```
# time O(log(min(N,M)), space O(1). BIN SEARCH
def median(nums1, nums2):
    # capture edge cases
    if len(nums2) < len(nums1):
        nums1, nums2 = nums2, nums1
    total = len(nums1) + len(nums2)
    half = total // 2
    l, r = 0, len(nums1)-1
    # median is guaranteed
    while True:
        i = (l + r) // 2      # for nums1
        # subtr. 2 - j starts at 0, i starts at 0
        j = half - i - 2     # for nums2
        # overflow of indices
        nums1_left = nums1[i] if i >= 0 else float("-inf")
        nums1_right = nums1[i+1] if (i+1) < len(nums1) else float("inf")
        nums2_left = nums2[j] if j >= 0 else float("-inf")
        nums2_right = nums2[j+1] if (j+1) < len(nums2) else float("inf")
        # if correct partition is found
        if nums1_left <= nums2_right and nums2_left <= nums1_right:
            if total % 2:
                return min(nums1_right, nums2_right)
            else:
                return ( max(nums1_left, nums2_left) + \
                         min(nums1_right, nums2_right) ) / 2
        # if no correct partition - arrays are in ascending order
        elif nums1_left > nums2_right:
            r = i - 1
        else:
            l = i + 1
```

Multiply strings

```
# GET NUMBER FROM CHAR: ord(char) - ord('0')
def multiply_strings(num1, num2):
    res = 0
    for i, c1 in enumerate(num1[::-1]):
        for j, c2 in enumerate(num2[::-1]):
            res += (ord(c1)-ord('0')) * \
                   (ord(c2)-ord('0')) * \
                   (10**((i+j)))
    return str(res)
num1, num2 = '123', '456'
multiply_strings(num1, num2)      # '56088'
```

Merge k Sorted Linked Lists

```
# time c. O(Nlogk), k = # lists. Space c. O(1)
def mergeKLists(lists):
    n = len(lists)
    interval = 1
    while interval < n:
        for i in range(0, n-interval, interval*2):
            lists[i] = merge2Lists( lists[i], lists[i+interval] )
        interval *= 2
    return lists[0] if n > 0 else None

def merge2Lists(l1, l2):
    head = point = Node(0)
    while l1 and l2:
        if l1.val <= l2.val:
            point.next = l1
            l1 = l1.next
        else:
            point.next = l2
            l2 = l1
            l1 = point.next.next
        point = point.next
    if not l1: point.next=l2
    else: point.next=l1
    return head.next
```

Merge k Sorted Arrays

```
# time c. O(kN*Logk) since
# using heap (N*Logk) k times;
# space c. O(N) - output array
from heapq import merge
def mergeK(arr, k):
    l = arr[0]
    for i in range(k-1):
        l = list(merge(l, arr[i + 1]))
    return l
```

Kth Largest Element in Array

```

# time = O(n), space = O(1)
def findKthLargest(nums, k):
    def partition(left, right, pivot_idx):
        pivot = nums[pivot_idx]
        # 1. move pivot to end
        nums[pivot_idx], nums[right] = nums[right], nums[pivot_idx]
        # 2. move all smaller elements to the left
        store_idx = left
        for i in range(left, right):
            if nums[i] < pivot:
                nums[store_idx], nums[i] = nums[i], nums[store_idx]
                store_idx += 1
        # 3. move pivot to its final place
        nums[right], nums[store_idx] = nums[store_idx], nums[right]
        return store_idx

    def select_rec(left, right, k_smallest):
        if left == right:      # base case - 1 elem
            return nums[left]
        pivot_idx = random.randint(left, right)
        # find pivot pos in sorted list
        pivot_idx = partition(left, right, pivot_idx)
        # if pivot in final sorted position
        if k_smallest == pivot_idx:
            return nums[k_smallest]
        elif k_smallest < pivot_idx:    # go left
            return select_rec(left, pivot_idx-1, k_smallest)
        else:                      # go right
            return select_rec(pivot_idx+1, right, k_smallest)
    # kth largest = (n - k)th smallest
    return select_rec(0, len(nums)-1, len(nums)-k)

```

Dijkstra's Algorithm

Shortest path from one vertex to all others

```
# time c. O(V + E*logE), iterative, BFS
import heapq    # min heap of (distance, vertex) pairs
# control iteration order - to pick vertex w/smallest dist
def calculate_distances(graph, start):
    # cost from start to each destination
    distances = {vertex: float('infinity') for vertex in graph}
    distances[start] = 0
    pq = [(0, start)]           # min heap or priority queue
    while len(pq) > 0:
        # pop smallest, maintain heap
        current_distance, current_vertex = heapq.heappop(pq)
        # nodes can be added to pq multiple times; process node
        # first time it's removed from pq
        if current_distance > distances[current_vertex]:
            continue
        for neighbor, weight in graph[current_vertex].items():
            distance = current_distance + weight
            # only if new path is better
            if distance < distances[neighbor]:
                distances[neighbor] = distance
                # push onto heap, maintain heap
                heapq.heappush(pq, (distance, neighbor))
    return distances
```

Min. spanning tree - Prim's algo

15

S.t. for a graph $G = (V, E)$ is acyclic subset of E connecting all vertices in V (sum of edge weights minimized)

Most efficient info flow. There may be several spanning trees - we need to find the minimum one.

Using priority queue to select next vertex for growing graph

```
from collections import defaultdict
import heapq
def min_spanning_tree(graph, start):
    ''' Outputs mst - min. spanning tree '''
    mst = defaultdict(set)
    visited = set([start])
    edges = [ (cost, start, to)
              for to, cost in graph[start].items() ]
    heapq.heapify(edges)
    while edges:
        cost, frm, to = heapq.heappop(edges)
        if to not in visited:
            visited.add(to)
            mst[frm].add(to)
            for to_next, cost in graph[to].items():
                if to_next not in visited:
                    heapq.heappush(edges, (cost, to, to_next))
    return mst
```

Floyd Warshall Algorithm

Shortest path between all pairs of nodes

```
# time c. O(V^3)
def floyd_marshall(graph):
    dist = list(map(lambda i : list(map(lambda j : j , i)) , graph))
    for k in range(V):
        for i in range(V):          # all vertices as source
            for j in range(V):      # all vertices as destination
                # update dist[i][j] if vertex k on shortest path from i to j
                dist[i][j] = min(dist[i][j], dist[i][k] + dist[k][j])
    return dist
```

Traveling Salesman Problem (TSP)

NP hard problem. There is no known polynomial time solution

```
# Naive approach. Time c. n!
from sys import maxsize
V = 4
def travellingSalesmanProblem(graph, s):
    vertices = [] # all verteces, but source vtx
    for i in range(V):
        if i != s:
            vertices.append(i)
    min_pathweight = maxsize # min weight Hamiltonian Cycle
    while True:
        current_pathweight = 0 # current Path weight(cost)
        k = s # compute current path weight
        for i in range(len(vertices)):
            current_pathweight += graph[k][vertices[i]]
            k = vertices[i]
        current_pathweight += graph[k][s]
        min_pathweight = min(min_pathweight,
                             current_pathweight) #update min
        if not next_permutation(vertices):
            break
    return min_pathweight
```

```
def next_permutation(L):
    n = len(L)
    i = n - 2
    while i >= 0 and L[i] >= L[i + 1]:
        i -= 1
    if i == -1:
        return False
    j = i + 1
    while j < n and L[j] > L[i]:
        j += 1
    j -= 1
    L[i], L[j] = L[j], L[i]
    left = i + 1
    right = n - 1
    while left < right:
        L[left], L[right] = L[right], L[left]
        left += 1
        right -= 1
    return True

# matrix representation of graph
graph = [[0, 10, 15, 20], [10, 0, 35, 25],
          [15, 35, 0, 30], [20, 25, 30, 0]]
start = 0
print(travellingSalesmanProblem(graph, s))
```

Build Bin Tree from Array

Use level-order traversal to convert back to array

```
# time = space = O(n)
class Node:
    def __init__(self, val):
        self.val = val
        self.left = self.right = None

def insertLevelOrder(arr, i, n):
    root = None
    if i < n:                      # base case
        root = Node(arr[i])
        root.left = insertLevelOrder(arr, 2*i+1, n)
        root.right = insertLevelOrder(arr, 2*i+2, n)
    return root

arr = [1,2,3,4,5,6,None,None,None,7,8]
n = len(arr)
root = insertLevelOrder(arr, 0, n)
```

Delete Nodes, Return Forest

```
def delNodes( root: Node,
              to_delete: List[int],
            ) -> List[Node]:
    res, to_delete = [], set(to_delete)
    def helper(root):
        if root:
            # next line exec. after recursion on way up
            root.left, root.right = (helper(root.left),
                                      helper(root.right))

            if root.val not in to_delete:
                return root
            res.append(root.left) # if root is deleted
            res.append(root.right) # if root is deleted
    res.append(helper(root))
    return([ i for i in res if i ])
```

Nodes in Compl. Bin. Tree < O(n) 18

```
# time=O(d^2)=O((logN)^2), d=depth, space = O(1)
def countNodes(root: TreeNode) -> int:
    if not root: return 0
    d = compute_depth(root)
    if d == 0: return 1
    # Last level nodes - 0 to 2**d-1 (left->right)
    # Bin search to check how many nodes exist
    left, right = 1, 2**d - 1
    while left <= right:
        pivot = left + (right - left) // 2
        if exists(pivot, d, root):
            left = pivot + 1
        else:
            right = pivot - 1
    # there are only left nodes on last level
    return (2**d - 1) + left

def compute_depth(node: Node) -> int:
    d = 0
    while node.left:
        node = node.left
        d += 1
    return d

def exists(idx: int, d: int, node: Node) -> bool:
    '''Return True if last level node idx exists'''
    left, right = 0, 2**d - 1
    for _ in range(d):
        pivot = left + (right - left) // 2
        if idx <= pivot:
            node = node.left
            right = pivot
        else:
            node = node.right
            left = pivot + 1
    return node is not None
```

```
# time = O(N * (4^N)), N = len(digits), space = O(n)
def letterCombinations(digits: str) -> List[str]:
    if len(digits) == 0: return []
    letters = {"2": "abc", "3": "def", "4": "ghi",
               "5": "jkl", "6": "mno", "7": "pqrs",
               "8": "tuv", "9": "wxyz"}
    def backtrack(index, path):
        if len(path) == len(digits): # base case
            combinations.append("".join(path))
            return
        # letters mapped to current digit
        possible_letters = letters[digits[index]]
        for letter in possible_letters:
            path.append(letter)
            backtrack(index + 1, path)
            path.pop() # remove before moving on
    combinations = []
    backtrack(0, [])
    return combinations
```

Longest Increasing Path in Matrix

```
# time and space = O(mn)
def longestIncreasingPath(matrix):
    def dfs(i, j):
        if not dp[i][j]:
            val = matrix[i][j]
            dp[i][j] = 1 + max(
                dfs(i - 1, j) if i and val > matrix[i - 1][j] else 0,
                dfs(i + 1, j) if i < M - 1 and val > matrix[i + 1][j] else 0,
                dfs(i, j - 1) if j and val > matrix[i][j - 1] else 0,
                dfs(i, j + 1) if j < N - 1 and val > matrix[i][j + 1] else 0)
        return dp[i][j]
    if not matrix or not matrix[0]: return 0
    M, N = len(matrix), len(matrix[0])
    dp = [[0] * N for i in range(M)]
    return max(dfs(x, y) for x in range(M) for y in range(N))
```

Reorder List (3 challenges in one)

$L_0 \rightarrow L_n \rightarrow L_1 \rightarrow L_{n-1} \rightarrow L_2 \rightarrow L_{n-2} \rightarrow \dots$

```
# in-place, time O(n), space O(1)
def reorderList(head: Node) -> None:
    if not head: return
    # FIND MIDDLE
    slow = fast = head
    while fast and fast.next:
        slow = slow.next
        fast = fast.next.next
    # REVERSE SECOND LIST IN-PLACE
    prev, curr = None, slow
    while curr:
        curr.next, prev, curr = prev, curr, curr.next
    # MERGE 1->6->2->5->3->4
    first, second = head, prev
    while second.next:
        first.next, first = second, first.next
        second.next, second = first, second.next
```

```
tips.assign(tip_rate = tips["tip"] / tips["total_bill"])
tips.loc[tips["tip"] < 2, "tip"] *= 2
```

GROUP BY

```
tips.groupby("sex").size()      # female = 87, male = 90
tips.groupby("day").agg({"tip": "mean", "day": "size"})
```

| | tip | day | # agg() on one column in each df from grouped |
|-----|----------|-----|---|
| day | | | df.groupby('Team')['Points'].agg(np.mean) |
| Fri | 2.586842 | 19 | Team |
| Sat | 2.986897 | 87 | Angels 768.000000 Kings 761.666667 |

```
tips.groupby(["smoker", "day"]).agg({"tip": ["size", "mean"]})
```

| | | tip | df.groupby('Team').agg(np.size) | | | | |
|--------|-----|------|---------------------------------|--------|------|--------|------|
| smoker | day | size | mean | Rank | Year | Points | Team |
| | | | | | | | |
| | Fri | 4 | 2.562500 | | | | |
| No | Sat | 45 | 3.052889 | Angels | 2 | 2 | 2 |
| | | | | Kings | 3 | 3 | 3 |

MULTIPLE AGGREGATION FUNCTIONS ON ONE COL

```
df.groupby('Team')['Points'].agg([np.sum, np.mean, np.std])
```

| Team | sum | mean | std |
|--------|------|------------|------------|
| Angels | 1536 | 768.000000 | 134.350288 |
| Kings | 2285 | 761.666667 | 24.006943 |

Remove missing data

```
# Remove rows with ANY missing values
df_dropped_rows = df.dropna()
# Remove columns with ANY missing values
df_dropped_columns = df.dropna(axis=1)
# Remove rows with missing values in specific columns
df_dropped_specific1 = df.dropna(subset=['A'])
# Remove columns with missing values in specific rows
df_dropped_specific2 = df.dropna(subset=[1], axis=1)
```

Transformation: df.groupby().transform()

Applied to **group** or **column**, returns an obj w/same index size

```
score = lambda x: (x - x.mean()) / x.std()*10
df.groupby('Team').transform(score)
```

| Rank | Year | Points |
|------|------|--------|
|------|------|--------|

| | | | |
|---|------------|------------|-----------|
| 0 | -15.000000 | -11.618950 | 12.843272 |
|---|------------|------------|-----------|

| | | | |
|---|----------|-----------|----------|
| 1 | 5.000000 | -3.872983 | 3.020286 |
|---|----------|-----------|----------|

Filtration: df.groupby().filter()

Returns subset of df, filtering data on a criteria

```
df.groupby('Team').filter(lambda x: len(x) >= 3)
```

| Team | Rank | Year | Points |
|------|------|------|--------|
|------|------|------|--------|

| | | | | |
|---|--------|---|------|-----|
| 0 | Riders | 1 | 2014 | 876 |
|---|--------|---|------|-----|

| | | | | |
|---|--------|---|------|-----|
| 1 | Riders | 2 | 2015 | 789 |
|---|--------|---|------|-----|

MULTIPLE AGGREGATION FUNCTIONS ON MANY COLS

```
df.groupby('Team')[['Points', 'Rank']].agg([np.sum, np.mean, np.std])
```

| Team | Points | | | Rank | | |
|--------|--------|------------|------------|------|----------|----------|
| | sum | mean | std | sum | mean | std |
| Angels | 1536 | 768.000000 | 134.350288 | 5 | 2.500000 | 0.707107 |
| Kings | 2285 | 761.666667 | 24.006943 | 5 | 1.666667 | 1.154701 |

JOIN

```
DataFrame.merge( right_df,
                  how='inner', # {'left', 'right', 'outer', 'inner', 'cross'}
                  on=None,          # join key(s) - column
                  left_on=None,    # if join key(s) w/different names (but same)
                  right_on=None,
                  left_index=False, # use index as join key(s)
                  right_index=False,
                  sort=False,       # Sort join keys lexicographically
                  suffixes=('_x', '_y'),
                  copy=True,
                  indicator=False, # col _merge saying source of each row
                  validate=None,   # check merge keys if "1:1", "1:m", etc.
```

)

Fill missing data

```
DataFrame.fillna(
    value=None, # number/dict/Series/df
    method=None, # 'bfill', 'ffill', None
    limit=None, # # of fffills/bfills
    axis=None,
    inplace=False,)

# Fill with a constant value
df_filled_constant = df.fillna(250)
# propagate next valid observation forward
df_filled_ffill = df.fillna(method='ffill')
# propagating next valid observation backward
df_filled_bfill = df.fillna(method='bfill')
# Fill all NaNs in cols w/values
values = {"A": 100, "B": 200, "C": 300,}
print(df.fillna(value=values))
# Fill w/df - replacement at same cols & idx
print(df.fillna(df2))
# Fill w/mean of col
df_filled_mean = df.fillna(df.mean())
# Fill w/median of cols
df_filled_median = df.fillna(df.median())
# Fill with mode of cols (mode() returns df)
df_filled_mode = df.fillna(df.mode().iloc[0])
# Interpolation (default: linear)
# method: 'index','pad','nearest','zero', etc.
df_interpolated = df.interpolate() |
print(df_interpolated)
```

Handling outliers

```
# REMOVE
df_no_outliers = df[(df['A'] >= lower_bound) & (df['A'] <= upper_bound)]
# CAP
df['A'] = np.where(df['A'] > upper_bound, upper_bound, df['A'])
df['A'] = np.where(df['A'] < lower_bound, lower_bound, df['A'])
# IMPUTE
median = df['A'].median()
df['A'] = np.where(df['A'] > upper_bound, median, df['A'])
df['A'] = np.where(df['A'] < lower_bound, median, df['A'])
# SCALE - RobustScaler if robust to outliers
from sklearn.preprocessing import RobustScaler
scaler = RobustScaler()
df['A'] = scaler.fit_transform(df[['A']])
```

Transforming Data

Z-Score: # standard deviations a data point is from the mean.

$z\text{-score} = (\text{value} - \text{mean}) / \text{std_dev}$ => StandardScaler()

```
from scipy.stats import zscore
df['A_log'] = np.log(df['A'])
df['A_zscore'] = zscore(df['A'])
print(df)

      A   A_capped     A_log   A_zscore
0    10      10.000  2.302585 -0.425312
1   -50     -20.625      NaN -2.115292
```

Identifying outliers using the IQR (Interquartile Range)

```
# Calculate Q1 (25th perc.) & Q3 (75th perc.)
Q1 = df['A'].quantile(0.25)
Q3 = df['A'].quantile(0.75)
IQR = Q3 - Q1
# Define outlier boundaries
lower_bound = Q1 - 1.5 * IQR
upper_bound = Q3 + 1.5 * IQR
# Identify outliers
outliers = df[(df['A'] < lower_bound) | \
               (df['A'] > upper_bound)]
```

Isolation Forest - ML to identify and handle outliers

```
from sklearn.ensemble import IsolationForest
iso = IsolationForest(contamination=0.1)
df['outliers'] = iso.fit_predict(df[['A']])
outliers = df[df['outliers'] == -1]
```

| | A | A_capped | A_log | A_zscore | A_median | A_scaled | outliers |
|---|-----|----------|----------|-----------|----------|-----------|----------|
| 0 | 10 | 10.000 | 2.302585 | -0.425312 | 10.0 | -0.473118 | 1 |
| 1 | -50 | -20.625 | NaN | -2.115292 | 21.0 | -3.053763 | -1 |

Read CSV files

```
pandas.read_csv()
```

- **filepath, sep=',' / regex, header='infer' / None / row number (numbers for multi-index),**
- **names=col names.** If they already exist in file, pass header=0 to rename,
- **index_col=col(s) for row labels (None), usecols=subset of cols to use (None)**
- **dtype=dtypes for cols (None), skiprows=line numbers to skip (0-indexed) or # lines to skip (int)**
- **skipfooter=# lines at bottom of file to skip (0), nrows=# rows to read (None),**
- **na_values=additional strings to recognize as NaN, (also true_values and false_values),**
- **skip_blank_lines=True, parse_dates=None, infer_datetime_format=_NoDefault.no_default,**
- **keep_date_col= keep original date col, date_format=None,**
- **thousands=None, decimal='.', quotechar='', quoting=0 (csv.QUOTE_MINIMAL, etc.),**
- **escapechar=None, encoding=None,**
- **encoding_errors='strict' / 'ignore' / 'replace', on_bad_lines='error' / 'warn' / 'skip',**
- **delim_whitespace=whether or not whitespace will be used as the sep (equ. to sep='\s+')**

```
df.to_json(file_name)
df = pd.read_json(file_name)
```

Rank

Rank col values in descend or ascen order

Method - How rank group of records that have the same value (ties):

- average: average rank of group
- min: lowest rank in group
- max: highest rank in group
- first: in order ranks appear
- dense: = 'min', but rank increases by 1

Axending=False => max value has rank 1

```
df['rank'] = df['num_legs_1178'].rank(
    method='first',
    ascending=False).astype("int")
df[['num_legs_1178', 'rank']]
```

| | num_legs_1178 | rank |
|--------|---------------|------|
| falcon | 2 | 3 |
| dog | 4 | 2 |
| spider | 8 | 1 |
| fish | 0 | 4 |

Set value for a cell

```
df.at['C', 'a'] = 10 # BY VALUE
df.iat[5,10] = 2 # BY INDEX
```

Select columns

```
df.dtypes.value_counts()
# col by type
df.select_dtypes(include=['int'])
# col by name - has "num" in name
df.filter(like='num')
# has digit(s) in col name
df.filter(regex='\d')
```

num_legs_1178

falcon 2

Select w/"get_loc" and "index"

```
start = df.columns.get_loc('num_legs_1178')
end = df.columns.get_loc('num_specimen')
df.iloc[:4, start:end+1]
```

```
start = df.index.get_loc('dog')
end = df.index.get_loc('fish')
df.iloc[start:end+1, 2:5]
```

same things

```
df[df['num_legs_1178'] > 2]
df.query('num_legs_1178 > 2')
```

Melt - unpivot df from wide to long format

| >>> df | | | >>> pd.melt(df, id_vars=['A'], value_vars=['B', 'C']) | | |
|--------|---|---|---|----------|-------|
| | A | B | A | variable | value |
| 0 | a | 1 | 0 | a | B |
| 1 | b | 3 | 1 | b | B |
| 2 | c | 5 | 2 | c | B |
| | | | 3 | a | C |
| | | | 4 | b | C |
| | | | 5 | c | C |

1a. Aggregations on entire dataframe

WINDOW FUNCTIONS - find trends in data graphically by smoothing the curve

- **df.rolling()** - rolling window calculations; **window=window size, min_periods=min num observations in window required to have a value.**
- **df.expanding()** - same as rolling, but uses all the data up to that point in time. Equivalent statements: [df.rolling(window=len(df), min_periods=1).mean()] = [df.expanding(min_periods=1).mean()]
- **df.ewm()** - exponentially weighted window similar to expanding window, but each prior point is exponentially weighted down relative to the current point

```
df['column'].rolling(2).sum()
df['column'].rolling(2, min_periods=1).sum()
df['column'].rolling(2).mean()
```

Other

```
# cross-tabulation of 2+ factors
pd.crosstab(
    df["genus_overall"],
    df["rating_overall"],
    margins=True,
    normalize=0,)
```

```
# SQLite
import sqlite3
query = 'SELECT * FROM dune_table'
conn = sqlite3.connect('dune.db')
dune_df = pd.read_sql(query, conn)
dune_df.to_sql('dune_table', conn,
               index=False)
```

```
# reshape w/new cols & values + aggr.
pivot_df = pd.pivot_table(
    df, index='Name',
    columns=['Pets', 'Stores'],
    values='Weight' # col for values
    aggfunc='mean')
```

| rating_overall | 1.2 | 3.4 | 5.2 | 7.8 |
|----------------|------|------|------|------|
| avian | 1.00 | 0.00 | 0.00 | 0.00 |
| canine | 0.00 | 1.00 | 0.00 | 0.00 |

