

Visual and Net Based Programming

Exception Handling and Text IO

Agnik Saha

Department of Computer Science and Engineering

R. P. Shaha University

September 09, 2023



Motivations

When a program runs into a runtime error, the program terminates abnormally. How can you handle the runtime error so that the program can continue to run or terminate gracefully? This is the subject we will introduce in this chapter.



Objectives

- To get an overview of exceptions and exception handling (§12.2).
- To explore the advantages of using exception handling (§12.2).
- To distinguish exception types: **Error** (fatal) vs. **Exception** (nonfatal) and checked vs. unchecked (§12.3).
- To declare exceptions in a method header (§12.4.1).
- To throw exceptions in a method (§12.4.2).
- To write a **try-catch** block to handle exceptions (§12.4.3).
- To explain how an exception is propagated (§12.4.3).
- To obtain information from an exception object (§12.4.4).
- To develop applications with exception handling (§12.4.5).
- To use the **finally** clause in a **try-catch** block (§12.5).
- To use exceptions only for unexpected errors (§12.6).
- To rethrow exceptions in a **catch** block (§12.7).
- To create chained exceptions (§12.8).
- To define custom exception classes (§12.9).
- To discover file/directory properties, to delete and rename files/directories, and to create directories using the **File** class (§12.10).
- To write data to a file using the **PrintWriter** class (§12.11.1).
- To use try-with-resources to ensure that the resources are closed automatically (§12.11.2).
- To read data from a file using the **Scanner** class (§12.11.3).
- To understand how data is read using a **Scanner** (§12.11.4).
- To develop a program that replaces text in a file (§12.11.5).
- To read data from the Web (§12.12).
- To develop a Web crawler (§12.13).



Exception-Handling Overview

Show runtime error

Quotient

Run

Fix it using an if statement

QuotientWithIf

Run

With a method

QuotientWithMethod

Run



Exception Advantages

QuotientWithException

Run

Now you see the *advantages* of using exception handling. It enables a method to throw an exception to its caller. Without this capability, a method must handle the exception or terminate the program.



Handling InputMismatchException


InputMismatchExceptionDemo

Run


By handling InputMismatchException, your program will continuously read an input until it is correct.



Exception Types




System Errors




Exceptions

Exception describes errors caused by your program and external circumstances. These errors can be caught and handled by your program.



Runtime Exceptions



`RuntimeException` is caused by programming errors, such as bad casting, accessing an out-of-bounds array, and numeric errors.

Checked Exceptions vs. Unchecked Exceptions

RuntimeException, Error and their subclasses are known as *unchecked exceptions*. All other exceptions are known as *checked exceptions*, meaning that the compiler forces the programmer to check and deal with the exceptions.




Unchecked Exceptions

In most cases, unchecked exceptions reflect programming logic errors that are not recoverable. For example, a `NullPointerException` is thrown if you access an object through a reference variable before an object is assigned to it; an `IndexOutOfBoundsException` is thrown if you access an element in an array outside the bounds of the array. These are the logic errors that should be corrected in the program. Unchecked exceptions can occur anywhere in the program. To avoid cumbersome overuse of try-catch blocks, Java does not mandate you to write code to catch unchecked exceptions.




Unchecked Exceptions



Unchecked
exception.

Declaring, Throwing, and Catching Exceptions



Declaring Exceptions

Every method must state the types of checked exceptions it might throw. This is known as *declaring exceptions*.

```
public void myMethod()  
    throws IOException
```

```
public void myMethod()  
    throws IOException, OtherException
```



Throwing Exceptions

When the program detects an error, the program can create an instance of an appropriate exception type and throw it. This is known as *throwing an exception*. Here is an example,

```
throw new TheException();
```

```
TheException ex = new TheException();  
throw ex;
```



Throwing Exceptions Example

```
/** Set a new radius */  
public void setRadius(double newRadius)  
    throws IllegalArgumentException {  
    if (newRadius >= 0)  
        radius = newRadius;  
    else  
        throw new IllegalArgumentException(  
            "Radius cannot be negative");  
}
```




Catching Exceptions


```
try {  
    statements;    // Statements that may throw exceptions  
}  
catch (Exception1 exVar1) {  
    handler for exception1;  
}  
catch (Exception2 exVar2) {  
    handler for exception2;  
}  
...  
catch (ExceptionN exVar3) {  
    handler for exceptionN;  
}
```



Catching Exceptions



Call Stack



Catch or Declare Checked Exceptions

Suppose p2 is defined as follows:

```
void p2() throws IOException {  
    if (a file does not exist) {  
        throw new IOException("File does not exist");  
    }  
  
    ...  
}
```



Catch or Declare Checked Exceptions

Java forces you to deal with checked exceptions. If a method declares a checked exception (i.e., an exception other than Error or RuntimeException), you must invoke it in a try-catch block or declare to throw the exception in the calling method. For example, suppose that method p1 invokes method p2 and p2 may throw a checked exception (e.g., IOException), you have to write the code as shown in (a) or (b).

```
void p1() {  
    try {  
        p2();  
    }  
    catch (IOException ex) {  
        ...  
    }  
}
```

(a)

```
void p1() throws IOException {  
    p2();  
}
```

(b)

Example: Declaring, Throwing, and Catching Exceptions

- Objective: This example demonstrates declaring, throwing, and catching exceptions by modifying the setRadius method in the Circle class defined in Chapter 9. The new setRadius method throws an exception if radius is negative.

CircleWithException

TestCircleWithException

Run



Rethrowing Exceptions

```
try {  
    statements;  
}  
catch (TheException ex) {  
    perform operations before exits;  
    throw ex;  
}
```



The `finally` Clause

```
try {  
    statements;  
}  
catch (TheException ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```



Trace a Program Execution

Suppose no
exceptions in the
statements

```
try {  
    statements;  
}  
catch (TheException ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;



Trace a Program Execution

```
try {  
    statements;  
}  
catch (TheException ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

The final block is
always executed



Trace a Program Execution

```
try {  
    statements;  
}  
catch (TheException ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

Next statement in the
method is executed



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

Suppose an exception
of type Exception1 is
thrown in statement2



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

The exception is handled.



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

The final block is
always executed.



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

The next statement in the method is now executed.



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
catch (Exception2 ex) {  
    handling ex;  
    throw ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

statement2 throws an
exception of type
Exception2.



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
catch (Exception2 ex) {  
    handling ex;  
    throw ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

Handling exception



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
catch (Exception2 ex) {  
    handling ex;  
    throw ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

Execute the final block



Trace a Program Execution

```
try {  
    statement1;  
    statement2;  
    statement3;  
}  
catch (Exception1 ex) {  
    handling ex;  
}  
catch (Exception2 ex) {  
    handling ex;  
    throw ex;  
}  
finally {  
    finalStatements;  
}
```

Next statement;

Rethrow the exception
and control is
transferred to the caller



Cautions When Using Exceptions

- Exception handling separates error-handling code from normal programming tasks, thus making programs easier to read and to modify. Be aware, however, that exception handling usually requires more time and resources because it requires instantiating a new exception object, rolling back the call stack, and propagating the errors to the calling methods.



When to Throw Exceptions

- An exception occurs in a method. If you want the exception to be processed by its caller, you should create an exception object and throw it. If you can handle the exception in the method where it occurs, there is no need to throw it.



When to Use Exceptions

When should you use the try-catch block in the code? You should use it to deal with unexpected error conditions. Do not use it to deal with simple, expected situations. For example, the following code

```
try {  
    System.out.println(refVar.toString());  
}  
  
catch (NullPointerException ex) {  
    System.out.println("refVar is null");  
}
```



When to Use Exceptions

is better to be replaced by

```
if (refVar != null)
```

```
    System.out.println(refVar.toString());
```

```
else
```

```
    System.out.println("refVar is null");
```



Defining Custom Exception Classes

- Use the exception classes in the API whenever possible.
- Define custom exception classes if the predefined classes are not sufficient.
- Define custom exception classes by extending Exception or a subclass of Exception.



Custom Exception Class Example

In Listing 13.8, the setRadius method throws an exception if the radius is negative. Suppose you wish to pass the radius to the handler, you have to create a custom exception class.

InvalidRadiusException

CircleWithRadiusException

TestCircleWithRadiusException

Run

