

Entropy Collapse in LLM Agent Societies

Anonymous Authors

Abstract

LLM agents are beginning to inhabit shared environments where one agent’s output becomes another agent’s context. In such systems, diversity is not only a property of a model; it is a property of the feedback loop that selects, displays, and reuses model-generated text. We study this loop in Moltbook, a controlled Reddit-like platform for autonomous agents. Across 48 canonical first-hour simulations spanning four model families, six seed conditions, and group-size sweeps, the feeds become measurably narrower. Cumulative Distinct-5 declines in 48/48 runs, gzip redundancy increases in 44/48, Vendi-style semantic diversity declines in 42/48, and a blinded LLM-judge collapse score rises in 46/48. The narrowing is not convergence to one universal script: each run tends to discover its own local attractors—phrases, frames, roles, and interaction templates—which are then reused by multiple agents and anchor tighter semantic neighborhoods. Scaling to 20 or 30 agents, mixing models, adding base-model tools, and changing prompts alter the attractors but do not eliminate them. We argue that *entropy collapse* is an inference-time, platform-level failure mode of agent societies, and that agentic social systems need diversity-aware monitoring and feed design rather than assuming that more agents will produce more variety.

1 Introduction

The next generation of LLM applications will not only answer questions; they will populate environments. Agents can post, reply, vote, deliberate, moderate, and act in public spaces. In these settings, a model output has a second life: it becomes part of the context that other agents read before producing their own outputs. A social feed is therefore not just a display surface. It is a recursive inference loop.

A common hope is that multi-agent systems will be self-diversifying. Different personas, stochastic

samples, tool states, and model families should, in principle, produce a broader set of ideas than any single model acting alone. We test the opposite risk. If agents repeatedly condition on the same public traces, the feed may become less diverse even while remaining active. What looks like consensus, community culture, or coordination may partly be an artifact of agents recycling the most salient local language and frames.

We call this failure mode entropy collapse: an inference-time narrowing of discourse in which later posts become more redundant, more compressible, and more concentrated in fewer lexical, semantic, or rhetorical regions. This is distinct from training-time model collapse: no model weights are updated. The distribution changes because agents continuously write the environment that future agents read.

We study this process in Moltbook, a controlled Reddit-like platform for autonomous LLM agents. Our canonical evidence base contains 48 first-hour simulations spanning GPT-5, Gemini Flash Lite, Kimi K2.5, and GLM-5; six seed conditions; and group-size sweeps for two model families. Agents are free to read the feed and create posts, while the experimental setup fixes the platform, run horizon, initial condition, and roster structure. We analyze the resulting posts with exact phrase audits, cumulative Distinct-5, gzip compression, embedding-space concentration, MDS topic maps, Vendi-style semantic diversity, and a blinded LLM judge that scores repetition, frame convergence, conformity, rigidity, and novelty.

The main finding is robust but path-dependent. Feeds usually narrow across independent measurement channels: cumulative Distinct-5 declines in all 48 canonical runs, gzip redundancy increases in 44, Vendi-style semantic diversity declines in 42, and the blinded LLM-judge collapse score rises in 46. Yet the runs do not converge to the same slogan or topic. Instead, each run tends to discover its own

local attractors—phrases, frames, roles, and social templates—which spread across agents and anchor narrower semantic neighborhoods. Collapse is therefore not only a surface repetition problem; it is local convention formation inside a model-populated feed.

This paper makes three contributions. First, we give controlled evidence that agent-native social feeds narrow over time across lexical, compression, semantic, topical, and judge-based measurements. Second, we show that the narrowing is locally path-dependent: exact phrase families and social forms differ across runs, but the attractor-forming process recurs. Third, we evaluate natural design responses—larger populations, mixed-model rosters, base-model tools, and prompt changes—and find that they change the collapse signature without providing a general remedy.

2 Related Work

Agent-native social networks and Moltbook. A growing body of work treats Moltbook as an empirical site for studying social platforms populated by language-model agents. Descriptive Moltbook studies analyze topics, toxicity, platform-native narratives, discourse themes, and activity regularities (Jiang et al., 2026; De Marzo and Garcia, 2026; Li et al., 2026). Network-structure studies report attention concentration, asymmetric interaction, low reciprocity, and divergence from human social networks (Price et al., 2026; Hou and Ji, 2026). A related line studies community formation, norms, incentives, and risk: agents form subcommunities, share instructions, enforce norms, and sometimes display social-platform form without the full functions of human communities (Lin et al., 2026; Manik and Wang, 2026; Feng et al., 2026; Zerhoubi et al., 2026). Attribution work further argues that open-platform Moltbook observations can mix autonomous agent behavior with human influence (Li, 2026). These studies establish agent-native social networks as a real object of study, but they also motivate controlled analysis: open-platform observations can mix autonomous agent behavior, platform incentives, and human intervention.

LLM agents and multi-agent interaction. Work on generative agents, role-playing agents, and multi-agent frameworks shows that LLMs can act in simulated environments, communicate, coordinate, and solve tasks (Park et al., 2023; Li et al., 2023; Chen et al., 2023; Wu et al., 2023; Hong

et al., 2023; Qian et al., 2024; Zhou et al., 2024). Multi-agent debate and evaluator frameworks further show that interaction can improve factuality, reasoning, or evaluation quality under some conditions (Du et al., 2023; Chen et al., 2024; Chan et al., 2024). Much of this literature evaluates task success, believability, or coordination. Our focus is different: an agent social feed is not a single answer or solved task, but an evolving distribution of public messages. The relevant question is whether that distribution preserves lexical, semantic, and rhetorical diversity as agents observe one another.

Conformity, herding, and diversity collapse.

Classic social-science work shows that public signals and group pressure can change expressed judgments (Asch, 1951; Bikhchandani et al., 1992; Muchnik et al., 2013). Recent work finds analogous dynamics in LLM populations: agents can form conventions, develop collective biases, and exhibit herd behavior when peer information is visible (Ashery et al., 2025; Cho et al., 2025). Multi-agent deliberation work also shows that protocol design matters: voting and consensus rules, consensus-free debate, and deliberation protocols change both performance and interaction dynamics (Kaesberg et al., 2025; Cui et al., 2025; Kaushal and Singh, 2026). We extend this line from task discussions and deliberation protocols to social-feed dynamics, where repeated exposure to agent-generated public content can become a source of new inputs.

Linguistic diversity and model collapse. Text generation work has long studied degeneration, blandness, and repetition (Holtzman et al., 2020). Metrics such as distinct- n , Self-BLEU, MAUVE, and embedding-space diversity capture different parts of the broader diversity construct (Li et al., 2016; Zhu et al., 2018; Pillutla et al., 2021; Tevet and Berant, 2021). This measurement literature motivates separating lexical repetition from semantic concentration, since template reuse and paraphrased topical convergence are different failure modes. A related but distinct literature studies model collapse under recursive training on synthetic data (Shumailov et al., 2024). Our setting is inference-time rather than training-time: agents narrow while interacting with each other’s outputs inside a running platform.

Analysis family	Scope	Runs
Canonical single-model runs	4 models, 6 conditions	48
Matched 10-agent canonical runs	4 models, 6 conditions	24
Scale comparison	GPT-5/Gemini, 10/20/30 agents	36
Base-model-as-tool probe	10-agent secondary cohort	18
Mixed-model roster probe	10-agent secondary cohort	6
Obsession prompt probe	10-agent secondary cohort	9

Table 1: Run families used in the analysis. The canonical 48-run set is the main evidence base; secondary cohorts are reported as intervention probes.

3 Experimental Setting

We analyze Moltbook simulations in which LLM agents post into and read from a shared Reddit-like feed. The canonical evidence base contains 48 first-hour single-model runs: GPT-5, Gemini Flash Lite, Kimi K2.5, and GLM-5 across six seed conditions. GPT-5 and Gemini Flash Lite also have scale sweeps at 10, 20, and 30 agents; Kimi K2.5 and GLM-5 are 10-agent only in the canonical set. Runs with incomplete late activity were resumed and retimestamped before analysis, so fixed-window comparisons are not driven by empty final bins.

4 Measurements

We use several complementary measurements because collapse is not a single surface symptom. Exact NLTK 5-token anchors identify repeated phrases while preserving casing and punctuation. Distinct-5 measures how many distinct 5-grams remain in a fixed window or in the cumulative feed seen so far. Gzip compression ratio measures byte-level redundancy; lower values indicate easier compression.

For semantic structure, we use both geometric and distributional views. MDS plots project Qwen embedding distances into two dimensions for visualization, colored either by discovered topic or elapsed time. Vendi-style effective semantic diversity and Hill–Shannon effective counts summarize how many distinct semantic or frame clusters are active in a bin (Shannon, 1948; Hill, 1973; Friedman and Dieng, 2023). HHI/Simpson concentration checks whether posts occupy fewer embedding-cluster regions.

We also use a blinded LLM judge. The judge sees post content and anonymized local context, but not model, condition, run, author, or roster labels. It scores semantic repetition, frame convergence, consensus conformity, template rigidity, and nov-

Metric / model	GPT-5	Gemini	Kimi	GLM
Gzip collapse	17/18	15/18	6/6	6/6
Cumulative Distinct-5	18/18	18/18	6/6	6/6
Vendi collapse	16/18	16/18	5/6	5/6
LLM collapse	18/18	16/18	6/6	6/6
HHI concentration	15/18	16/18	1/6	3/6

Table 2: Run-level direction counts. Collapse direction means gzip/Distinct-5/Vendi down, LLM collapse up, and HHI concentration up.

elty. The post-level collapse index is

$$CI = \frac{R + F + G + T + (6 - N)}{5}, \quad (1)$$

where higher values indicate more judged repetition, convergence, conformity, rigidity, and lower novelty. The same judge also emits a short dominant-frame string. We embed and cluster those frame strings to build an LLM-frame convergence metric. Agreement between post-text topics and LLM-frame topics is a convergent-validity check (Campbell and Fiske, 1959).

5 Results

5.1 Canonical feeds narrow across metrics

The run-level audit provides the empirical foundation. GPT-5 and Gemini Flash Lite show the clearest all-metric pattern: text becomes more compressible, cumulative lexical diversity declines, Vendi-style semantic diversity declines, LLM-judge collapse increases, and HHI concentration rises in most runs. Kimi K2.5 and GLM-5 also show compression, lexical narrowing, and LLM-judge collapse, while their embedding-cluster concentration is less stable. The safe paper claim is therefore broad but precise: canonical agent feeds usually narrow over time, and the strongest topic-concentration evidence is concentrated in GPT-5 and Gemini Flash Lite.

5.2 Local phrase attractors explain the surface signal

Aggregate metrics show narrowing, but the phrase audit shows what narrowing looks like in posts. The phrase diagrams use agent-generated posts only. They find local exact 5-token anchors that spread across agents: operational mantras, procedural templates, ritual phrases, attribution memes, and role labels. The attractor differs from run to run; the repeated process is local convention formation.




Figure 1: Matched 10-agent cumulative trajectories. From left to right: Distinct-5, gzip compression ratio, and blinded LLM collapse index.




Figure 2: Local phrase attractors. Left: a phrase ledger for representative canonical runs. Right: full-post examples showing that multiple agents reuse the same phrase in context.

5.3 MDS and topical analyses show semantic narrowing

The MDS plots make the semantic claim visible. Topic-colored maps show that posts occupy structured regions of embedding space rather than a uniform cloud. Time-colored maps show that late posts are not uniformly interleaved with early posts; they concentrate in particular regions. This visual evidence is supported by Vendi-style diversity, entropy trajectories, and robust HHI concentration sweeps.

5.4 LLM-as-judge and LLM-frame convergence agree with deterministic metrics

The blinded judge gives a qualitatively different view of the same process. It does not count n-grams and does not see run metadata. Instead,

it asks whether a post repeats nearby semantics, adopts a dominant frame, conforms to consensus, becomes template-rigid, and loses novelty. Its scores rise in most canonical runs. The LLM also emits dominant-frame strings; embedding and clustering these strings yields an independent frame-diversity track. Post-text effective topics and LLM-frame effective counts both decline in the canonical family, which is evidence that surface phrases correspond to broader rhetorical convergence rather than only lexical reuse.

5.5 Phrase attractors are topical anchors

Exact phrase repetition is not merely surface copying. In selected examples, posts containing a repeated phrase are more concentrated in one embedding neighborhood than all posts from the same run. Topic-anchor heatmaps and dominant-share

plots show the same pattern at model level: phrase families often occupy a narrower topical region than the full run.

5.6 Scale and intervention probes do not remove collapse

Adding agents does not reliably preserve diversity. In GPT-5 and Gemini Flash Lite, the number of agents adopting the top exact phrase rises with scale while top-agent share falls; larger groups make some attractors more collective. Secondary cohorts are probes rather than definitive causal estimates. Base-model-as-tool runs still often produce phrases adopted by at least half the agents. For the obsession-prompting probe, we truncate every GPT-5 run to the first hour before aggregating LLM-judge scores and group by physical run identity rather than the reused human-readable run id; under this correction, 7/8 physical obsession runs still have positive first-hour LLM-collapse deltas. Mixed-model rosters and prompting changes alter which collapse symptom dominates, but neither should be treated as solved.

6 Discussion

Taken together, the analyses support a coherent account. LLM agents in a shared feed form local discourse attractors. These attractors are not simply copied seed posts and are not one global slogan. They are local conventions produced by the interaction loop. Once formed, they appear in multiple measurement channels: repeated phrases, lower lexical diversity, higher compressibility, stronger LLM-judged collapse, lower effective topic/frame counts, MDS-visible drift, and embedding-cluster concentration.

This has practical implications for agentic social media and multi-agent deliberation systems. Diversity cannot be assumed to emerge from scale, model heterogeneity, base-model weights, or prompt changes. It needs to be monitored as a system property. Lexical redundancy, semantic concentration, template reuse, and consensus conformity can move independently; a mitigation that improves one metric may leave another unchanged.

7 Limitations

The intervention cohorts are probes rather than matched randomized experiments. Exact n-gram matching undercounts paraphrases and originator effects. The LLM collapse index uses one blinded


judge model and should be interpreted as a structured qualitative signal triangulated against deterministic metrics. The main evidence focuses on first-hour simulations; longer horizons, independent no-feed controls, and human baselines remain important next steps. Finally, embedding clusters are not manually validated topics unless explicitly labeled as such; the safest term is embedding-neighborhood or cluster concentration.

8 Conclusion


LLM agents interacting through a shared social feed repeatedly create local discourse attractors. The attractor differs across runs, but the process of convergence is robust across models, seed conditions, and scales. Agentic social systems therefore require explicit diversity monitoring and intervention at the system level. More agents, mixed models, base-model tools, and prompt changes may alter the form of collapse, but they do not by themselves guarantee open-ended discourse diversity.

Topic Map — MDS Projection (GPT-5, n30)


Empty feed (n=1613)



5 conspiracies (n=1580)



25 conspiracies (n=1589)



25 AGI hype (n=1570)







Figure 3: Model-specific MDS topic map for GPT-5 at 30 agents. Each subplot is one seed condition; points are agent posts projected from Qwen embeddings and colored by discovered topic.

Topic Map — MDS Projection (Gemini Flash Lite, n30)


Empty feed (n=1361)



5 conspiracies (n=597)



25 conspiracies (n=585)



25 AGI hype (n=659)





Figure 4: Model-specific MDS topic map for Gemini Flash Lite at 30 agents, using the same projection and topic coloring as Figure 3. The supplement includes the corresponding n10/n20/n30 variants and the Kimi K2.5/GLM-5 model-specific MDS plots.




Figure 5: Effective-count and robust concentration evidence. Left: family-level deltas for effective post-text topics and LLM-frame topics. Right: robustness of HHI concentration across clustering choices.




Figure 6: Convergent validity between post-text effective topics and LLM-frame effective counts. Left: fixed-window family trajectories. Right: per-run deltas for the two independent inputs.





Figure 7: Phrase attractors as topical anchors. Left: selected phrase-bearing posts concentrate in one embedding neighborhood. Right: GPT-5 phrase-family/topic heatmap.



Intervention probes change the repetition pattern
For each 10-agent run, we find the top exact NLTK-5-token anchor and ask whether it reaches at least 5 agents. This is direct phrase-adoption evidence, not an LLM score and not a causal estimate.

Coherent	Runs with >5-agent phrase	Typical top phrase	Strong example	Reading
Canonical baseline	24/24 runs top phrase reaches >5 agents	7.5/10 agents median 10 posts	"if this is profound"	Midground run-local phrase adoption in the baseline pattern.
Base model as tool	15/18 runs top phrase reaches >5 agents	8/10 agents median 10 posts	"... we are reminded of"	100% other producers a phrase adopted by at least half the agents.
Mixed-model router	4/6 runs top phrase reaches >5 agents	5/10 agents median 5.5 posts	"that no one else has"	Cross-agent adoption is weaker, but still appears in most runs.
Obsession prompt	0/9 runs top phrase reaches >5 agents	3/10 agents median 10 posts	"... What's your"	Spread across agents is lower; adoption is more concentrated within fewer agents.

Top phrase is exact 5-token anchor with the most adopting agents in that run, tied broken by posts and mentions.
Agent-generated posts only, first 60 minutes only; punctuation and casing retained; seed rows excluded before matching.

Figure 8: Scale and intervention probes. Left: top-phrase adoption across GPT-5 and Gemini scales. Right: whether each intervention run’s top exact phrase reaches at least half the agents.

References

- Solomon E. Asch. 1951. Effects of group pressure upon the modification and distortion of judgments. *Groups, Leadership and Men*.
- Ariel Flint Ashery, Luca Maria Aiello, and Andrea Baronchelli. 2025. [Emergent social conventions and collective bias in LLM populations](#). *Science Advances*.
- Sushil Bikhchandani, David Hirshleifer, and Ivo Welch. 1992. A theory of fads, fashion, custom, and cultural change as informational cascades. *Journal of Political Economy*, 100(5):992–1026.
- Donald T. Campbell and Donald W. Fiske. 1959. Convergent and discriminant validation by the multitrait-multimethod matrix. *Psychological Bulletin*, 56(2):81–105.
- Chi-Min Chan, Weize Chen, Yusheng Su, Jing Yu, Wei Xue, Shan Zhang, Jie Fu, and Zhiyuan Liu. 2024. ChatEval: Towards better llm-based evaluators through multi-agent debate. *arXiv preprint*.
- Justin Chen, Swarnadeep Saha, and Mohit Bansal. 2024. ReConcile: Round-table conference improves reasoning via consensus among diverse llms. *arXiv preprint*.
- Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chen Qian, Chi-Min Chan, Yujia Qin, Yaxi Lu, Ruobing Xie, Zhiyuan Liu, Maosong Sun, and Jie Zhou. 2023. AgentVerse: Facilitating multi-agent collaboration and exploring emergent behaviors. *arXiv preprint*.
- Young-Min Cho, Sharath Chandra Guntuku, and Lyle Ungar. 2025. [Herd behavior: Investigating peer influence in LLM-based multi-agent systems](#). *Preprint*, arXiv:2505.21588.
- Yu Cui, Hang Fu, Haibin Zhang, Licheng Wang, and Cong Zuo. 2025. [Free-MAD: Consensus-free multi-agent debate](#). *Preprint*, arXiv:2509.11035.
- Giordano De Marzo and David Garcia. 2026. [Collective behavior of AI agents: The case of Moltbook](#). *Preprint*, arXiv:2602.09270.
- Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. 2023. Improving factuality and reasoning in language models through multiagent debate. In *Proceedings of ICML*.
- Yi Feng, Chen Huang, Zhibo Man, Ryner Tan, Long P. Hoang, Shaoyang Xu, and Wenxuan Zhang. 2026. [MoltNet: Understanding social behavior of AI agents in the agent-native MoltBook](#). *Preprint*, arXiv:2602.13458.
- Dan Friedman and Adji Bousso Dieng. 2023. [The vendi score: A diversity evaluation metric for machine learning](#). *Transactions on Machine Learning Research*.
- Mark O. Hill. 1973. Diversity and evenness: A unifying notation and its consequences. *Ecology*, 54(2):427–432.
- Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. The curious case of neural text degeneration. *International Conference on Learning Representations*.
- Sirui Hong, Xiawu Zheng, Jonathan Chen, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven K. S. Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, and Chenglin Wu. 2023. MetaGPT: Meta programming for a multi-agent collaborative framework. *arXiv preprint*.
- Wenpin Hou and Zhicheng Ji. 2026. [Structural divergence between AI-agent and human social networks in Moltbook](#). *Preprint*, arXiv:2602.15064.
- Yukun Jiang, Yage Zhang, Xinyue Shen, Michael Backes, and Yang Zhang. 2026. [“humans welcome to observe”: A first look at the agent social network Moltbook](#). *Preprint*, arXiv:2602.10127.
- Lars Benedikt Kaesberg, Jonas Becker, Jan Philip Wahle, Terry Ruas, and Bela Gipp. 2025. [Voting or consensus? decision-making in multi-agent debate](#). In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 11640–11671, Vienna, Austria. Association for Computational Linguistics.
- Vaaranay Kaushal and Taranveer Singh. 2026. [DeliberationBench: When do more voices hurt? a controlled study of multi-LLM deliberation protocols](#). *Preprint*, arXiv:2601.08835.
- Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. 2023. CAMEL: Communicative agents for mind exploration of large language model society. *arXiv preprint*.
- Jiwei Li, Michel Galley, Chris Brockett, Jianfeng Gao, and Bill Dolan. 2016. A diversity-promoting objective function for neural conversation models. In *Proceedings of NAACL*.
- Lingyao Li, Renkai Ma, Chen Chen, Zhicong Lu, and Yongfeng Zhang. 2026. [The rise of AI agent communities: Large-scale analysis of discourse and interaction on Moltbook](#). *Preprint*, arXiv:2602.12634.
- Ning Li. 2026. [The Moltbook illusion: Separating human influence from emergent behavior in AI agent societies](#). *Preprint*, arXiv:2602.07432.
- Yu-Zheng Lin, Bono Po-Jen Shih, Hsuan-Ying Alessandra Chien, Shalaka Satam, Jesus Horacio Pacheco, Sicong Shao, Soheil Salehi, and Pratik Satam. 2026. [Exploring silicon-based societies: An early study of the Moltbook agent community](#). *Preprint*, arXiv:2602.02613.

- Md Motaleb Hossen Manik and Ge Wang. 2026. [Open-Claw agents on Moltbook: Risky instruction sharing and norm enforcement in an agent-only social network](#). *Preprint*, arXiv:2602.02625.
- Lev Muchnik, Sinan Aral, and Sean J. Taylor. 2013. Social influence bias: A randomized experiment. *Science*, 341(6146):647–651.
- Joon Sung Park, Joseph C. O’Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of UIST*.
- Krishna Pillutla, Swabha Swayamdipta, Rowan Zellers, John Thickstun, Sean Welleck, Yejin Choi, and Zaid Harchaoui. 2021. MAUVE: Measuring the gap between neural text and human text using divergence frontiers. In *Proceedings of NeurIPS*.
- H. C. W. Price, H. AlMuhanna, P. M. Bassani, M. Ho, and T. S. Evans. 2026. [Let there be claws: An early social network analysis of AI agents on Moltbook](#). *Preprint*, arXiv:2602.20044.
- Chen Qian, Xin Cong, Cheng Yang, Weize Chen, Yusheng Su, Juyuan Xu, Zhiyuan Liu, and Maosong Sun. 2024. Communicative agents for software development. *arXiv preprint*.
- Claude E. Shannon. 1948. A mathematical theory of communication. *The Bell System Technical Journal*, 27(3):379–423.
- Iliia Shumailov, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. 2024. Ai models collapse when trained on recursively generated data. *Nature*.
- Guy Tevet and Jonathan Berant. 2021. Evaluating the evaluation of diversity in natural language generation. In *Proceedings of EACL*.
- Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed H. Awadallah, Ryan W. White, Doug Burger, and Chi Wang. 2023. AutoGen: Enabling next-gen llm applications via multi-agent conversation. *arXiv preprint*.
- Saber Zerhouni, Kanishka Ghosh Dastidar, Felix Klement, Artur Romazanov, Andreas Einwiller, Dang H. Dang, Michael Dinzinger, Michael Granitzer, Annette Hautli-Janisz, Stefan Katzenbeisser, Florian Lemmerich, and Jelena Mitrovic. 2026. [Form without function: Agent social behavior in the Moltbook network](#). *Preprint*, arXiv:2604.13052.
- Xuhui Zhou, Hao Zhu, Leena Mathur, Ruohong Zhang, Zhengyang Qi, Haofei Yu, Louis-Philippe Morency, Yonatan Bisk, Daniel Fried, Graham Neubig, and Maarten Sap. 2024. SOTOPIA: Interactive evaluation for social intelligence in language agents. *arXiv preprint*.
- Yaoming Zhu, Sidi Lu, Lei Zheng, Jiaxian Guo, Weinan Zhang, Jun Wang, and Yong Yu. 2018. Texus: A benchmarking platform for text generation models. In *Proceedings of SIGIR*.