

# Introducing stringr

STRING MANIPULATION WITH STRINGR IN R



**Charlotte Wickham**

Assistant Professor at Oregon State  
University

# stringr

- Powerful but easy to learn
- Built on stringi
- Concise and consistent
- All functions start with str\_
- All functions take a vector of strings as the first argument

# str\_c()

```
my_toppings
```

```
"green peppers" "olives" "onions"
```

```
paste(c("", "", "and "), my_toppings, sep = "")
```

```
"green peppers" "olives" "and onions"
```

```
library(stringr)  
str_c(c("", "", "and "), my_toppings)
```

```
"green peppers" "olives" "and onions"
```

- `str_length()` , `str_sub()`

# Babynames

- USA from 1880 to 2014
- You'll use 2014 only

```
library(babynames)  
head(babynames)
```

```
  year sex   name    n      prop  
1 1880  F   Mary  7065 0.07238359  
2 1880  F   Anna  2604 0.02667896  
3 1880  F   Emma  2003 0.02052149  
4 1880  F Elizabeth 1939 0.01986579  
5 1880  F   Minnie 1746 0.01788843  
6 1880  F Margaret 1578 0.01616720
```

# Let's practice!

STRING MANIPULATION WITH STRINGR IN R

# Hunting for matches

STRING MANIPULATION WITH STRINGR IN R



**Charlotte Wickham**

Assistant Professor at Oregon State  
University

# stringr functions that look for matches

- All take a pattern argument
  - `str_detect()`
  - `str_subset()`
  - `str_count()`

# Finding matches

```
pizzas <- c("cheese", "pepperoni", "sausage and green peppers")  
str_detect(string = pizzas, pattern = "pepper")
```

```
FALSE TRUE TRUE
```

```
str_detect(string = pizzas, pattern = fixed("pepper"))
```

```
FALSE TRUE TRUE
```



# Finding matches

```
str_subset(string = pizzas, pattern = fixed("pepper"))
```

```
"pepperoni" "sausage and green peppers"
```

```
str_count(string = pizzas, pattern = fixed("pepper"))
```

```
0 1 1
```

# Let's practice!

STRING MANIPULATION WITH STRINGR IN R

# Splitting strings

STRING MANIPULATION WITH STRINGR IN R



**Charlotte Wickham**

Assistant Professor at Oregon State  
University

# str\_split()

"Tom & Jerry"

# str\_split()

"Tom & Jerry"

```
str_split(string = "Tom & Jerry", pattern = " & ")
```

```
[[1]]  
"Tom"  "Jerry"
```

```
str_split("Alvin & Simon & Theodore", pattern = " & ")
```

```
[[1]]  
"Alvin"  "Simon"  "Theodore"
```

```
str_split("Alvin & Simon & Theodore", pattern = " & ", n = 2)
```

```
[[1]]  
"Alvin"      "Simon & Theodore"
```

# str\_split() returns a list

```
chars <- c("Tom & Jerry",  
           "Alvin & Simon & Theodore")  
  
str_split(chars, pattern = " & ")
```

```
[[1]]  
"Tom" "Jerry"  
[[2]]  
"Alvin" "Simon" "Theodore"
```

# str\_split() can return a matrix

```
chars <- c("Tom & Jerry",  
           "Alvin & Simon & Theodore")  
  
str_split(chars, pattern = " & ", simplify = TRUE)
```

```
      [,1] [,2] [,3]  
[1,] "Tom" "Jerry" ""  
[2,] "Alvin" "Simon" "Theodore"
```

# Combining with lapply()

```
chars <- c("Tom & Jerry",  
          "Alvin & Simon & Theodore")  
split_chars <- str_split(chars, pattern = " & ")  
split_chars
```

```
[[1]]  
"Tom"  "Jerry"  
[[2]]  
"Alvin" "Simon" "Theodore"
```

```
lapply(split_chars, length)
```

```
[[1]]  
2  
[[2]]  
3
```



# Let's practice!

STRING MANIPULATION WITH STRINGR IN R

# Replacing matches in strings

STRING MANIPULATION WITH STRINGR IN R



**Charlotte Wickham**

Assistant Professor at Oregon State University

# str\_replace()

```
str_replace("Tom & Jerry",  
            pattern = "&",  
            replacement = "and")
```

```
"Tom and Jerry"
```

```
str_replace("Alvin & Simon & Theodore",  
            pattern = "&",  
            replacement = "and")
```

```
"Alvin and Simon & Theodore"
```

```
str_replace_all("Alvin & Simon & Theodore",  
                pattern = "&",  
                replacement = "and")
```

```
"Alvin and Simon and Theodore"
```

# str\_replace() with vectors

```
chars <- c("Tom & Jerry",  
           "Alvin & Simon & Theodore")  
  
str_replace_all(chars,  
                pattern = "&",  
                replacement = "and")
```

```
"Tom and Jerry" "Alvin and Simon and Theodore"
```

# Let's practice!

STRING MANIPULATION WITH STRINGR IN R