



What is Quarkus?

Quarkus is a Kubernetes Native Java stack tailored for GraalVM & OpenJDK HotSpot, crafted from the best of breed Java libraries and standards. Also focused on developer experience, making things just work with little to no configuration and allowing to do live coding.

Cheat-sheet tested with **Quarkus 0.16.0**.

Getting Started

Quarkus comes with a Maven archetype to scaffold a very simple starting project.

```
mvn io.quarkus:quarkus-maven-plugin:0.16.0:create \
  -DprojectId=org.acme \
  -DprojectArtifactId=getting-started \
  -DclassName="org.acme.quickstart.GreetingResource" \
  -Dpath="/hello"
```

This creates a simple JAX-RS resource called `GreetingResource`.

```
@Path("/hello")
public class GreetingResource {

    @GET
    @Produces(MediaType.TEXT_PLAIN)
    public String hello() {
        return "hello";
    }
}
```

Extensions

Quarkus comes with extensions to integrate with some libraries such as JSON-B, Camel or MicroProfile spec. To list all available extensions just run:

```
./mvnw quarkus:list-extensions
```

Tip You can use `-DsearchPattern=panache` to filter out all extensions except the ones matching the expression.

And to register the extensions into build tool:

```
./mvnw quarkus:add-extension -Dextensions=""
```

Tip `extensions` property supports CSV format to register more than one extension at once.

Application Lifecycle

You can be notified when the application starts/stops by observing `StartupEvent` and `ShutdownEvent` events.

```
@ApplicationScoped
public class ApplicationLifecycle {
    void onStart(@Observes StartupEvent event) {}
    void onStop(@Observes ShutdownEvent event) {}
}
```

Adding Configuration Parameters

To add configuration to your application, Quarkus relies on `MicroProfile Config` spec (<https://github.com/eclipse/microprofile-config>).

```
@ConfigProperty(name = "greetings.message")
String message;

@ConfigProperty(name = "greetings.message",
    defaultValue = "Hello")
String messageWithDefault;

@ConfigProperty(name = "greetings.message")
Optional<String> optionalMessage;
```

Properties can be set as:

- Environment variables.
- System properties.
- Resources
`src/main/resources/application.properties`.
- External config directory under the current working directory:
`config/application.properties`.

```
greetings.message = Hello World
```

Tip `Array`, `List` and `Set` are supported. The delimiter is comma (,) char and `\` is the escape char.

Configuration Profiles

Quarkus allow you to have multiple configuration in the same file (`application.properties`).

The syntax for this is `%{profile}.config.key=value`.

```
quarkus.http.port=9090
%dev.quarkus.http.port=8181
```

HTTP port will be 9090, unless the 'dev' profile is active.

Default profiles are:

- `dev`: Activated when in development mode (`quarkus:dev`).
- `test`: Activated when running tests.
- `prod`: The default profile when not running in development or test mode

You can create custom profile names by enabling the profile either setting `quarkus-profile` system property or `QUARKUS_PROFILE` environment variable.

```
quarkus.http.port=9090
%staging.quarkus.http.port=9999
```

And enable it `quarkus-profile=staging`.

Custom Loader

You can implement your own `ConfigSource` to load configuration from different places than the default ones provided by Quarkus. For example, database, custom XML, REST Endpoints, ...

You need to create a new class and implement `ConfigSource` interface:

```
package com.acme.config;

public class InMemoryConfig implements ConfigSource {

    private Map<String, String> prop = new HashMap<>();

    public InMemoryConfig() {
        // Init properties
    }

    @Override
    public int getOrdinal() {
        // The highest ordinal takes precedence
        return 900;
    }

    @Override
    public Map<String, String> getProperties() {
        return prop;
    }

    @Override
    public String getValue(String propertyName) {
        return prop.get(propertyName);
    }

    @Override
    public String getName() {
        return "MemoryConfigSource";
    }
}
```

Then you need to register the ConfigSource as Java service. Create a file /META-INF/services/org.eclipse.microprofile.config.spi.ConfigSource with next content:

```
com.acme.config.InMemoryConfig
```

Custom Converters

You can implement your own conversion types from String. Implement org.eclipse.microprofile.config.spi.Converter interface:

```
@Priority(DEFAULT_QUARKUS_CONVERTER_PRIORITY + 100)
public class CustomInstantConverter
    implements Converter<Instant> {

    @Override
    public Instant convert(String value) {
        if ("now".equals(value.trim())) {
            return Instant.now();
        }
        return Instant.parse(value);
    }
}
```

@Priority annotation is used to override the default InstantConverter.

Then you need to register the Converter as Java service. Create a file /META-INF/services/org.eclipse.microprofile.config.spi.Converter with next content:

```
com.acme.config.CustomInstantConverter
```

Injection

Quarkus is based on CDI 2.0 to implement injection of code. It is not fully supported and only a subset of the specification is implemented.

```
@ApplicationScoped
public class GreetingService {

    public String message(String message) {
        return message.toUpperCase();
    }
}
```

Scope annotation is mandatory to make the bean discoverable.

```
@Inject
GreetingService greetingService;
```

Quarkus is designed with Substrate VM in mind. For **Important** this reason, we encourage you to use *package-private* scope instead of *private*.

JSON Marshalling/Unmarshalling

To work with JSON-B you need to add a dependency:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-resteasy-jsonb"
```

Any POJO is marshaled/unmarshalled automatically.

```
public class Sauce {
    private String name;
    private long scovilleHeatUnits;

    // getter/setters
}
```

JSON equivalent:

```
{
    "name": "Blair's Ultra Death",
    "scovilleHeatUnits": 1100000
}
```

In a POST endpoint example:

```
@POST
@Consumes(MediaType.APPLICATION_JSON)
public Response create(Sauce sauce) {
    // Create Sauce
    return Response.created(URI.create(sauce.getId()))
        .build();
}
```

Validator

Quarkus uses Hibernate Validator to validate input/output of REST services and business services using Bean validation spec.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-hibernate-validator"
```

Annotate POJO objects with validator annotations such as: @NotNull, @Digits, @NotBlank, @Min, @Max, ...

```
public class Sauce {

    @NotBlank(message = "Name may not be blank")
    private String name;
    @Min(0)
    private long scovilleHeatUnits;

    // getter/setters
}
```

To validate that an object is valid you need to annotate where is used with @Valid annotation:

```
public Response create(@Valid Sauce sauce) {}
```

If a validation error is triggered, a violation report is generated and serialized as JSON. **Tip** If you want to manipulate the output, you need to catch in the code the ConstraintViolationException exception.

Create Your Custom Constraints

First you need to create the custom annotation:

```
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR,
          PARAMETER, TYPE_USE })
@Retention(RUNTIME)
@Documented
@Constraint(validatedBy = { NotExpiredValidator.class})
public @interface NotExpired {

    String message() default "Sauce must not be expired";
    Class<?>[] groups() default { };
    Class<? extends Payload>[] payload() default { };

}
```

You need to implement the validator logic in a class that implements `ConstraintValidator`.

```
public class NotExpiredValidator
    implements ConstraintValidator<NotExpired, LocalDate>
{

    @Override
    public boolean isValid(LocalDate value,
                          ConstraintValidatorContext ctx) {
        if ( value == null ) return true;
        LocalDate today = LocalDate.now();
        return ChronoUnit.YEARS.between(today, value) > 0;
    }
}
```

And use it normally:

```
@NotExpired
@JsonbDateFormat(value = "yyyy-MM-dd")
private LocalDate expired;
```

Manual Validation

You can call the validation process manually instead of relaying to `@Valid` by injecting `Validator` class.

```
@Inject
Validator validator;
```

And use it:

```
Set<ConstraintViolation<Sauce>> violations =
    validator.validate(sauce);
```

Logging

You can configure how Quarkus logs:

```
quarkus.log.console.enable=true
quarkus.log.console.level=DEBUG
quarkus.log.console.color=false
quarkus.log.category."com.lordofthejars".level=DEBUG
```

Prefix is `quarkus.log`.

Property	Default	Description
console.enable	true	Console enabled.
console.format	%d{yyyy-MM-dd HH:mm:ss,SSS} %-5p [%c{3.}] (%t) %s%e%n	Format pattern to use for logging.
console.level	INFO	Minimum log level.
console.color	INFO	Allow color rendering.
file.enable	false	File logging enabled.
file.format	%d{yyyy-MM-dd HH:mm:ss,SSS} %h %N[%i] %-5p [%c{3.}] (%t) %s%e%n	Format pattern to use for logging.
file.level	ALL	Minimum log level.
file.path	quarkus.log	The path to log file.
category."<category-name>".level	INFO	Minimum category. level
level	INFO	Default level. minimum

Rest Client

Quarkus implements `MicroProfile Rest Client` spec:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-rest-client"
```

To get content from <http://worldclockapi.com/api/json/cet/now> you need to create a service interface:

```
@Path("/api")
@RegisterRestClient
public interface WorldClockService {

    @GET @Path("/json/cet/now")
    @Produces(MediaType.APPLICATION_JSON)
    WorldClock getNow();

    @GET
    @Path("/json/{where}/now")
    @Produces(MediaType.APPLICATION_JSON)
    WorldClock getSauce(@BeanParam
                        WorldClockOptions worldClockOptions);

}
```

```
public class WorldClockOptions {
    @HeaderParam("Authorization")
    String auth;

    @PathParam("where")
    String where;
}
```

And configure the hostname at `application.properties`:

```
org.acme.quickstart.WorldClockService/mp-rest/url=
    http://worldclockapi.com
```

Injecting the client:

```
@Inject
@RestClient
WorldClockService worldClockService;
```

If invocation happens within JAX-RS, you can propagate headers from incoming to outgoing by using `next` property.

```
org.eclipse.microprofile.rest.client.propagateHeaders=
    Authorization,MyCustomHeader
```

Tip You can still use the JAX-RS client without any problem

```
ClientBuilder.newClient().target(...)
```

Adding headers

You can customize the headers passed by implementing `MicroProfile ClientHeadersFactory` annotation:

```
@RegisterForReflection
public class BaggageHeadersFactory
    implements ClientHeadersFactory {

    @Override
    public MultivaluedMap<String, String> update(
        MultivaluedMap<String, String> incomingHeaders,
        MultivaluedMap<String, String> outgoingHeaders) {}

}
```

And registering it in the client using `RegisterClientHeaders` annotation.

```
@RegisterClientHeaders(BaggageHeadersFactory.class)
@RegisterRestClient
public interface WorldClockService {}
```

Or statically set:

```
@GET
@ClientHeaderParam(name="X-Log-Level", value="ERROR")
Response getNow();
```

Asynchronous

A method on client interface can return a `CompletionStage` class to be executed asynchronously.

```
@GET @Path("/json/cet/now")
@Produces(MediaType.APPLICATION_JSON)
CompletionStage<WorldClock> getNow();
```

Testing

Quarkus archetype adds test dependencies with JUnit 5 and Rest-Assured library to test REST endpoints.

To package and run the application for testing:

```
@QuarkusTest
public class GreetingResourceTest {

    @Test
    public void testHelloEndpoint() {
        given()
            .when().get("/hello")
            .then()
                .statusCode(200)
                .body(is("hello"));
    }

}
```

Test port can be modified by using `quarkus.http.test-port` configuration property.

You can also inject the URL where Quarkus is started:

```
@TestHTTPResource("index.html")
URL url;
```

If you need to provide an alternative implementation of a service (for testing purposes) you can do it by using CDI `@Alternative` annotation using it in the test service placed at `src/test/java`:

```
@Alternative
@Priority(1)
@ApplicationScoped
public class MockExternalService extends ExternalService {}
```

Important This does not work when using native image testing.

To test native executables you can annotate the test with `@SubstrateTest`.

Persistence

Quarkus works with JPA(Hibernate) as persistence solution. But also provides an Active Record pattern implementation under Panache project.

To use database access you need to add Quarkus JDBC drivers instead of the original ones. At this time H2, MariaDB, MSSQL and PostgreSQL drivers are supported.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-hibernate-orm-panache,
            io.quarkus:quarkus-jdbc-mariadb"
```

```
@Entity
public class Developer extends PanacheEntity {

    // id field is implicit

    public String name;

}
```

And configuration in `src/main/resources/application.properties`:

```
quarkus.datasource.url=jdbc:mariadb://localhost:3306/mydb
quarkus.datasource.driver=org.mariadb.jdbc.Driver
quarkus.datasource.username=developer
quarkus.datasource.password=developer
quarkus.hibernate-orm.database.generation=update
```

Database operations:

```
// Insert
Developer developer = new Developer();
developer.name = "Alex";
developer.persist();

// Find All
Developer.findAll().list();

// Find By Query
Developer.find("name", "Alex").firstResult();

// Delete
Developer developer = new Developer();
developer.id = 1;
developer.delete();

// Delete By Query
long numberOfDeleted = Developer.delete("name", "Alex");
```


Remember to annotate methods with `@Transactional` annotation to make changes persisted in the database.

If queries start with the keyword `from` then they are treated as *HQL* query, if not then next short form is supported:

- `order by` which expands to `from EntityName order by ...`
- `<columnName>` which expands to `from EntityName where <columnName>=?`
- `<query>` which is expanded to `from EntityName where <query>`

Static Methods

Field	Parameters	Return
findById	Object	Returns object or null if not found.
find	String, [Object..., Map<String, Object>, Parameters]	Lists of entities meeting given query with parameters set.
find	String, Sort, [Object..., Map<String, Object>, Parameters]	Lists of entities meeting given query with parameters set sorted by Sort attribute/s.
findAll		Finds all entities.
findAll	Sort	Finds all entities sorted by Sort attribute/s.
stream	String, [Object..., Map<String, Object>, Parameters]	<code>java.util.stream.Stream</code> of entities meeting given query with parameters set.
stream	String, Sort, [Object..., Map<String, Object>, Parameters]	<code>java.util.stream.Stream</code> of entities meeting given query with parameters set sorted by Sort attribute/s.
streamAll		<code>java.util.stream.Stream</code> of all entities.

Field	Parameters	Return
streamAll	Sort	<code>java.util.stream.Stream</code> of all entities sorted by Sort attribute/s.
count		`Number of entities.
count	String, [Object..., Map<String, Object>, Parameters]	Number of entities meeting given query with parameters set.
deleteAll		Number of deleted entities.
delete	String, [Object..., Map<String, Object>, Parameters]	Number of deleted entities meeting given query with parameters set.
persist	[Iterable, Steram, Object...]	

If entities are defined in external JAR, you need to enable in these projects the Jandex plugin in project.

```
<plugin>
  <groupId>org.jboss.jandex</groupId>
  <artifactId>jandex-maven-plugin</artifactId>
  <version>1.0.3</version>
  <executions>
    <execution>
      <id>make-index</id>
      <goals>
        <goal>jandex</goal>
      </goals>
    </execution>
  </executions>
  <dependencies>
    <dependency>
      <groupId>org.jboss</groupId>
      <artifactId>jandex</artifactId>
      <version>2.1.1.Final</version>
    </dependency>
  </dependencies>
</plugin>
```

DAO pattern

Panache also supports *DAO* pattern by providing `PanacheRepository<TYPE>` interface.

```
@ApplicationScoped
public class DeveloperRepository
    implements PanacheRepository<Person> {
    public Person findByName(String name){
        return find("name", name).firstResult();
    }
}
```

Flyway

Quarkus integrates with Flyway to help you on database schema migrations.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-flyway"
```

Then place migration files to the migrations folder (`classpath:db/migration`).

You can inject `org.flywaydb.core.Flyway` to programmatically execute the migration.

```
@Inject
Flyway flyway;

flyway.migrate();
```

Or can be automatically executed by setting `migrate-at-start` property to `true`.

```
quarkus.flyway.migrate-at-start=true
```

List of Flyway parameters.

`quarkus.` as prefix is skipped in the next table.

Parameter	Default	Description
flyway.migrate-at-start	false	Flyway migration automatically.
flyway.locations	classpath:db/migration	CSV locations to scan recursively for migrations. Supported prefixes <code>classpath</code> and <code>filesystem</code>

Parameter	Default	Description
flyway.connect-retries	0	The maximum number of retries when attempting to connect.
flyway.schemas	none	CSV case-sensitive list of schemas managed.
flyway.table	flyway_schema_history	The name of Flyway's schema history table.
flyway.sql-migration-prefix	V	Prefix for versioned SQL migrations.
flyway.repeatable-sql-migration-prefix	R	Prefix for repeatable SQL migrations.

Hibernate Search

Quarkus integrates with Elasticsearch to provide a full-featured full-text search using Hibernate Search API.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-hibernate-search-elasticsearch"
```

You need to annotate your model with Hibernate Search API to index it:

```
@Entity
@Indexed
public class Author extends PanacheEntity {

    @FullTextField(analyzer = "english")
    public String bio;

    @FullTextField(analyzer = "name")
    @KeywordField(name = "firstName_sort",
        sortable = Sortable.YES,
        normalizer = "sort")
    public String firstName;

    @OneToMany
    @IndexedEmbedded
    public List<Book> books;

}
```

Important It is not mandatory to use Panache.

You need to define the analyzers and normalizers defined in annotations. You only need to implement ElasticsearchAnalysisConfigurer interface and configure it.

```
public class MyQuarkusAnalysisConfigurer
    implements ElasticsearchAnalysisConfigurer {

    @Override
    public void configure(
        ElasticsearchAnalysisDefinitionContainerContext ctx)
    {

        ctx.analyzer("english").custom()
            .withTokenizer("standard")
            .withTokenFilters("asciifolding",
                "lowercase", "porter_stem");

        ctx.normalizer("sort").custom()
            .withTokenFilters("asciifolding", "lowercase");

    }

}
```

Use Hibernate Search in REST service:

```
public class LibraryResource {

    @Inject
    EntityManager em;

    @Transactional
    public List<Author> searchAuthors(
        @QueryParam("pattern") String pattern) {
        return Search.getSearchSession(em)
            .search(Author.class)
            .predicate(f ->
                pattern == null || pattern.isEmpty() ?
                    f.matchAll() :
                    f.simpleQueryString()
                        .onFields("firstName",
                            "lastName", "books.title")
                        .matching(pattern)

                )
            .sort(f -> f.byField("lastName_sort")
                .then().byField("firstName_sort"))
            .fetchHits();

    }

}
```

IMPORTANT If you are importing data without using Hibernate ORM, you need to index data by using Search.getSearchSession(em).createIndexer().startAndWait() at startup time.

You need to configure the extension in application.properties:

```
quarkus.hibernate-search.elasticsearch.version=7
quarkus.hibernate-search.elasticsearch.
    analysis-configurer=MyQuarkusAnalysisConfigurer
quarkus.hibernate-search.elasticsearch.
    automatic-indexing.synchronization-strategy=searchable
quarkus.hibernate-search.elasticsearch.
    index-defaults.lifecycle.strategy=drop-and-create
quarkus.hibernate-search.elasticsearch.
    index-defaults.lifecycle.required-status=yellow
```

List of Hibernate-Elasticsearch properties prefixed with quarkus.hibernate-search.elasticsearch:

Parameter	Description
backends	Map of configuration of additional backends.
version	Version of Elasticsearch
analysis-configurer	Class or name of the neab used to configure.
hosts	List of Elasticsearch servers hosts.

Parameter	Description
username	Username for auth.
password	Password for auth.
connection-timeout	Duration of connection timeout.
max-connections	Max number of connections to servers.
max-connections-per-route	Max number of connections to server.
indexes	Per-index specific configuration.
discovery.enabled	Enables automatic discovery.
discovery.refresh-interval	Refresh interval of node list.
discovery.default-scheme	Scheme to be used for the new nodes.
automatic-indexing.synchronization-strategy	Status for which you wait before considering the operation completed (queued,committed or searchable).
automatic-indexing.enable-dirty-check	When enabled, re-indexing of is skipped if the changes are on properties that are not used when indexing.
index-defaults.lifecycle.strategy	Index lifecycle (none, validate, update, create, drop-and-create, drop-abd-create-drop)
index-defaults.lifecycle.required-status	Minimal cluster status (green, yellow, red)

Parameter	Description
index-defaults.lifecycle.required-status-wait-timeout	Waiting time before failing the bootstrap.
index-defaults.refresh-after-write	Set if index should be refreshed after writes.
Possible annotations:	
Parameter	Description
@Indexed	Register entity as full text index
@FullTextField	Full text search. Need to set an analyzer to split tokens.
@KeywordField	The string is kept as one single token but can be normalized.
IndexedEmbedded	Include the Book fields into the Author index.
@ContainerExtraction	Sets how to extract a value from container, e.g from a Map.
@DocumentId	Map an unusual entity identifier to a document identifier.
@GenericField	Full text index for any supported type.
@IdentifierBridgeRef	Reference to the identifier bridge to use for a @DocumentId.
@IndexingDependency	How a dependency of the indexing process to a property should affect automatic reindexing.
@ObjectPath	
@ScaledNumberField	For java.math.BigDecimal or java.math.BigInteger that you need higher precision.

Reactive Programming

Quarkus implements MicroProfile Reactive spec and uses RXJava2 to provide reactive programming model.

```
./mvnw quarkus:add-extension
-Dextensions="
    io.quarkus:quarkus-smallrye-reactive-streams-operators"
```

Asynchronous HTTP endpoint is implemented by returning Java CompletionStage. You can create this class either manually or using MicroProfile Reactive Streams spec:

```
@GET
@Path("/reactive")
@Produces(MediaType.TEXT_PLAIN)
public CompletionStage<String> getHello() {
    return ReactiveStreams.of("h", "e", "l", "l", "o")
        .map(String::toUpperCase)
        .toList()
        .run()
        .thenApply(list -> list.toString());
}
```

Creating streams is also easy, you just need to return Publisher object.

```
@GET
@Path("/stream")
@Produces(MediaType.SERVER_SENT_EVENTS)
public Publisher<String> publishers() {
    return Flowable
        .interval(500, TimeUnit.MILLISECONDS)
        .map(s -> atomicInteger.getAndIncrement())
        .map(i -> Integer.toString(i));
}
```

Reactive Messaging

Quarkus relies on MicroProfile Reactive Messaging spec (<https://github.com/eclipse/microprofile-reactive-messaging>) to implement reactive messaging streams.

```
mvn quarkus:add-extension
-Dextensions="
    io.quarkus:quarkus-smallrye-reactive-messaging"
```

You can just start using in-memory streams by using @Incoming to produce data and @Outgoing to consume data.

Produce every 5 seconds one piece of data.

```
@ApplicationScoped
public class ProducerData {

    @Outgoing("my-in-memory")
    public Flowable<Integer> generate() {
        return Flowable.interval(5, TimeUnit.SECONDS)
            .map(tick -> random.nextInt(100));
    }
}
```

Consumes generated data from my-in-memory stream.

```
@ApplicationScoped
public class ConsumerData {
    @Incoming("my-in-memory")
    public void randomNumber(int randomNumber) {
        System.out.println("Received " + randomNumber);
    }
}
```

You can also inject an stream as a field:

```
@Inject
@Stream("my-in-memory") Publisher<Integer> randomNumbers;
```

Possible return types:

Kafka

To integrate with Kafka you need to add next extensions:

```
mvn quarkus:add-extension
-Dextensions="
io.quarkus:quarkus-smallrye-reactive-messaging-kafka,
io.quarkus:quarkus-vertx"
```

Then @Outgoing, @Incoming or @Stream can be used.

Kafka configuration schema: smallrye.messaging.[sink|source].{stream-name}.<property>=<value>

```
smallrye.messaging.source.prices.type=
io.smallrye.reactive.messaging.kafka.Kafka
smallrye.messaging.source.prices.topic=
prices
smallrye.messaging.source.prices.bootstrap.servers=
localhost:9092
smallrye.messaging.source.prices.key.deserializer=
org.apache.kafka.common.serialization.StringDeserializer
smallrye.messaging.source.prices.value.deserializer=
org.apache.kafka.common.serialization.IntegerDeserializer
smallrye.messaging.source.prices.group.id=
my-group-id
```

A complete list of supported properties are in Kafka site. For producer and for consumer

Important If the stream is not configured then it is assumed to be an in-memory stream.

Reactive PostgreSQL Client

You can use Reactive PostgreSQL to execute queries to PostgreSQL database in a reactive way, instead of using JDBC way.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-health"
```

Database configuration is the same as shown in Persistence section, but URL is different as it is not a *jdbc*.

```
quarkus.datasource.url=
vertx-reactive:postgresql://host:5431/db
```

Then you can inject io.reactiveverse.axle.pgclient.PgPool class.

```
@Inject
PgPool client;

CompletionStage<JsonArray> =
    client.query("SELECT * FROM table")
    .thenApply(pgRowSet -> {
        JsonArray jsonArray = new JsonArray();
        PgIterator iterator = pgRowSet.iterator();
        return jsonArray;
    })
```

JWT

Quarkus implements MicroProfile JWT RBAC spec.

```
mvn quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-jwt"
```

Minimum JWT required claims: typ, alg, kid, iss, sub, exp, iat, jti, upn, groups.

You can inject token by using JsonWebToken or a claim individually by using @Claim.

```
@Inject
JsonWebToken jwt;

@Inject
@Claim(standard = Claims.preferred_username)
String name;

@Inject
@Claim("groups")
Set<String> groups;
```

Set of supported types: String, Set<String>, Long, Boolean, `javax.json.JsonValue`, Optional, org.eclipse.microprofile.jwt.ClaimValue.

And configuration in src/main/resources/application.properties:

```
mp.jwt.verify.publickey.location=
META-INF/resources/publicKey.pem
mp.jwt.verify.issuer=
https://quarkus.io/using-jwt-rbac
```

Configuration options:

Parameter	Default	Description
quarkus.smallrye-jwt.enabled	true	Determine if the jwt extension is enabled.
quarkus.smallrye-jwt.realm-name	Quarkus-JWT	Name to use for security realm.
quarkus.smallrye-jwt.auth-mechanism	MP-JWT	Authentication mechanism.

Parameter	Default	Description
<code>mp.jwt.verify.publickey</code>	none	Public Key text itself to be supplied as a string.
<code>mp.jwt.verify.publickey.location</code>	none	Relative path or URL of a public key.
<code>mp.jwt.verify.issuer</code>	none	iss accepted as valid.

Supported public key formats:

- PKCS#8 PEM
- JWK
- JWKS
- JWK Base64 URL
- JWKS Base64 URL

To send a token to server-side you should use Authorization header: `curl -H "Authorization: Bearer eyJraWQiOi...`

To inject claim values, the bean must be `@RequestScoped` CDI scoped. If you need to inject claim values in scope with a lifetime greater than `@RequestScoped` then you need to use `javax.enterprise.inject.Instance` interface.

```
@Inject
@Claim(standard = Claims.iat)
private Instance<Long> providerIAT;
```

RBAC

JWT groups claim is directly mapped to roles to be used in security annotations.

```
@RolesAllowed("Subscriber")
```

Keycloak

Quarkus can use Keycloak to protect resources using bearer token issued by Keycloak server.

```
mvn quarkus:add-extension
-Dextensions="io.quarkus:quarkus-keycloak"
```

You can get token information by injecting `KeycloakSecurityContext` object.

```
@Inject
KeycloakSecurityContext keycloakSecurityContext;
```

You can also protect resources with security annotations.

```
@GET
@RolesAllowed("admin")
```

Configure application to Keycloak service in `application.properties` file.

```
quarkus.keycloak.realm=quarkus
quarkus.keycloak.auth-server-url=http://localhost:8180/auth
quarkus.keycloak.resource=backend-service
quarkus.keycloak.bearer-only=true
quarkus.keycloak.credentials.secret=secret
quarkus.keycloak.policy-enforcer.enable=true
quarkus.keycloak.policy-enforcer.enforcement-mode=PERMISSIVE
```

You can see all possible Configuration parameters here.

Tip you can also use `src/main/resources/keycloak.json` standard Keycloak configuration file.

CORS Filter

Quarkus comes with a CORS filter that can be enabled via configuration:

```
quarkus.http.cors=true
```

Prefix is `quarkus.http`.

Property	Default	Description
<code>cors</code>	false	Enable CORS.
<code>origins</code>	Any request valid.	CSV of origins allowed.
<code>methods</code>	Any method valid.	CSV of methods valid.
<code>headers</code>	Any requested header valid.	CSV of valid allowed headers.
<code>exposed-headers</code>		CSV of valid exposed headers.

Fault Tolerance

Quarkus uses <https://github.com/eclipse/microprofile-fault-tolerance>[MicroProfile Fault Tolerance spec:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-fault-tolerance"
```

MicroProfile Fault Tolerance spec uses CDI interceptor and it can be used in several elements such as CDI bean, JAX-RS resource or MicroProfile Rest Client.

To do automatic **retries** on a method:

```
@Path("/api")
@RegisterRestClient
public interface WorldClockService {
    @GET @Path("/json/cet/now")
    @Produces(MediaType.APPLICATION_JSON)
    @Retry(maxRetries = 2)
    WorldClock getNow();
}
```

You can set fallback code in case of an error by using `@Fallback` annotation:

```
@Retry(maxRetries = 1)
@Fallback(fallbackMethod = "fallbackMethod")
WorldClock getNow(){}

public String fallbackMethod() {
    return "It could beworse";
}
```

fallbackMethod must have the same parameters and return type as the annotated method.

You can also set logic into a class that implements FallbackHandler interface:

```
public class RecoverFallback
    implements FallbackHandler<String> {
    @Override
    public String handle(ExecutionContext context) {
        return "It could be worse";
    }
}
```

And set it in the annotation as value @Fallback(RecoverFallback.class).

In case you want to use **circuit breaker** pattern:

```
@CircuitBreaker(requestVolumeThreshold = 4,
                failureRatio=0.75,
                delay = 1000)
WorldClock getNow(){}


```

If 3 (4 x 0.75) failures occur among the rolling window of 4 consecutive invocations then the circuit is opened for 1000 ms and then be back to half open. If the invocation succeeds then the circuit is back to closed again.

You can use **bulkahead** pattern to limit the number of concurrent access to the same resource. If the operation is synchronous it uses a semaphore approach, if it is asynchronous a thread-pool one. When a request cannot be processed BulkheadException is thrown. It can be used together with any other fault tolerance annotation.

```
@Bulkhead(5)
@Retry(maxRetries = 4,
        delay = 1000,
        retryOn = BulkheadException.class)
WorldClock getNow(){}


```

Fault tolerance annotations:

Annotation	Properties
@Timeout	unit

Annotation	Properties
@Retry	maxRetries, delay, delayUnit, maxDuration, durationUnit, jitter, jitterDelayUnit, retryOn, abortOn
@Fallback	fallbackMethod
@Bulkhead	waitingTaskQueue (only valid in asynchronous)
@CircuitBreaker	failOn, delay, delayUnit, requestVolumeThreshold, failureRatio, successThreshold
@Asynchronous	

You can override annotation parameters via configuration file using property [classname/methodname/]annotation/parameter:

```
org.acme.quickstart.WorldClock/getNow/Retry/maxDuration=30
# Class scope
org.acme.quickstart.WorldClock/Retry/maxDuration=3000
# Global
Retry/maxDuration=3000


```

You can also enable/disable policies using special parameter enabled.

```
org.acme.quickstart.WorldClock/getNow/Retry/enabled=false
# Disable everything except fallback
MP_Fault_Tolerance_NonFallback_Enabled=false


```

MicroProfile Fault Tolerance integrats with MicroProfile Tip Metrics spec. You can disable it by setting MP_Fault_Tolerance_Metrics_Enabled to false.

Observability

Health Checks

Quarkus relies on MicroProfile Health spec to provide health checks.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-health"


```

By just adding this extension, an endpoint is registered to /health providing a default health check.

```
{
  "outcome": "UP",
  "checks": [
  ]
}
```

To create a custom health check you need to implement the HealthCheck interface and annotate it with @Health annotation.

```
@Health
public class DatabaseHealthCheck implements HealthCheck {
    @Override
    public HealthCheckResponse call() {
        HealthCheckResponseBuilder responseBuilder =
            HealthCheckResponse.named("Database conn");

        try {
            checkDatabaseConnection();
            responseBuilder.withData("connection", true);
            responseBuilder.up();
        } catch (IOException e) {
            // cannot access the database
            responseBuilder.down()
                .withData("error", e.getMessage());
        }
        return responseBuilder.build();
    }
}
```

Builds the next output:

```
{
  "outcome": "UP",
  "checks": [
    {
      "name": "Database connection",
      "state": "UP",
      "data": {
        "connection": true
      }
    }
  ]
}
```

Metrics

Quarkus can utilize the MicroProfile Metrics spec to provide metrics support.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-metrics"


```

The metrics can be read with JSON or the OpenMetrics format. An endpoint is registered automatically at `/metrics` providing default metrics.

MicroProfile Metrics annotations:

Annotation	Description
<code>@Timed</code>	Method, constructor, or class as timed.
<code>@Metered</code>	Method, constructor, or class as metered.
<code>@Counted</code>	Method, constructor, or class as counted.
<code>@Gauge</code>	Method or field as a gauge.
<code>@Metric</code>	Requesting that a metric be injected or registered.

```
@GET
//...
@Timed(name = "checksTimer",
description = "A measure of how long it takes
                to perform a hello.",
unit = MetricUnits.MILLISECONDS)
public String hello() {}
```

`@Gauge` annotation returning a measure as a gauge.

```
@Gauge(name = "hottestSauce", unit = MetricUnits.NONE,
description = "Hottest Sauce so far.")
public Long hottestSauce() {}
```

Injecting a histogram using `@Metric`.

```
@Inject
@Metric(name = "histogram")
Histogram historgram;
```

Tracing

Quarkus can utilize the MicroProfile OpenTracing spec.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-opentracing"
```

Requests sent to any endpoint are traced automatically.

Jaeger tracer configuration:

```
quarkus.jaeger.service-name=myservice
quarkus.jaeger.sampler-type=const
quarkus.jaeger.sampler-param=1
quarkus.jaeger.endpoint=http://localhost:14268/api/traces
```

`@Traced` annotation can be set to disable tracing at class or method level.

Tracer class can be injected into the class.

```
@Inject
Tracer tracer;

tracer.activeSpan().setBaggageItem("key", "value");
```

Cloud

Native

You can build a native image by using GraalVM. The common use case is creating a Docker image so you can execute the next commands:

```
./mvnw package -Pnative -Dnative-image.docker-build=true

docker build -f src/main/docker/Dockerfile.native
                -t quarkus/getting-started .
docker run -i --rm -p 8080:8080 quarkus/getting-started
```

To configure native application, you can create a config directory at the same place as the native file and place an `application.properties` file inside. `config/application.properties`.

Kubernetes

Quarks can use `ap4k` to generate Kubernetes resources.

```
./mvnw quarkus:add-extensions
-Dextensions="io.quarkus:quarkus-kubernetes"
```

Running `./mvnw package` the Kubernetes resources are created at `target/wiring-classes/META-INF/kubernetes/` directory.

Property	Default	Description
<code>quarkus.kubernetes.group</code>	Current username	Set Docker Username.
<code>quarkus.application.name</code>	Current project name	Project name

Amazon Lambda

Quarkus integrates with Amazon Lambda.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-amazon-lambda"
```

And `com.amazonaws.services.lambda.runtime.RequestHandler` then implement `interface`.

```
public class TestLambda
    implements RequestHandler<MyInput, MyOutput> {
    @Override
    public MyInput handleRequest(MyOutput input,
                                Context context) {

        // ...
    }
}
```

Test

You can write tests for Amazon lambdas:

```
<dependency>
  <groupId>io.quarkus</groupId>
  <artifactId>quarkus-test-amazon-lambda</artifactId>
  <scope>test</scope>
</dependency>
```

```
@Test
public void testLambda() {
    MyInput in = new MyInput();
    in.setGreeting("Hello");
    in.setName("Stu");
    MyOutput out = LambdaClient.invoke(MyOutput.class, in);
}
```

Apache Camel

Quarkus integrates wih Apache Camel.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-camel-core"
```

You can inject CamelRuntime and CamelContext instances:

```
@Inject
CamelRuntime runtime;

@Inject
CamelContext context;
```

And also observing Camel events InitializingEvent, InitializedEvent, StartingEvent, StartedEvent. StoppingEvent, StoppedEvent.

```
public void init(@Observes InitializingEvent event) {
    runtime.getContext()
        .setUuidGenerator(new DefaultUuidGenerator());
}
```

You can create RouteBuilder for routing rules:

```
public class CamelRoute extends RouteBuilder {

    @Override
    public void configure() {
        from("timer:keep-alive?" +
            "period={{camel.timer-route.period}}")
            .id("timer-route")
            .setBody(constant(""))
            .to("log:keep-alive");
    }
}
```

Custom properties are set in application.properties.

```
camel.timer-route.period=1s
```

List of Camel parameters.

quarkus. as a prefix is skipped in the next table.

Parameter	Default	Description
camel.routesUri		Uri to an XML with camel routes.

Parameter	Default	Description
camel.deferInitPhase	false	Defer context initialization phase until runtime.
camel.disableJaxb	false	Disable support for JAXB at runtime. Useful when routes loaded at build time.
camel.disableXml	false	Disable XML support in various parts of Camel.
camel.dumpRoutes	false	Dump loaded routes .

Quarkus also comes with support for Camel in form of next extensions: camel-aws-s3, camel-aws-sqs, camel-infinispan, camel-netty4-http, camel-salesforce.

WebSockets

Quarkus can be used to handling web sockets.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-undertow-websockets"
```

And web sockets classes can be used:

```
@ServerEndpoint("/chat/{username}")
@ApplicationScoped
public class ChatSocket {

    @OnOpen
    public void onOpen(Session session,
        @PathParam("username") String username) {}

    @OnClose
    public void onClose(..) {}

    @OnError
    public void onError(..., Throwable throwable) {}

    @OnMessage
    public void onMessage(...) {}

}
```


OpenAPI

Quarkus can expose its API description as OpenAPI spec and test it using Swagger UI.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-openapi"
```

Then you only need to access to /openapi to get OpenAPI v3 spec of services.

Also, in case of starting Quarkus application in dev or test mode, Swagger UI is accessible at /swagger-ui. If you want to use it in production mode you need to set quarkus.swagger-ui.always-include property to true.

You can update the Swagger UI path by setting quarkus.swagger-ui.path property.

```
quarkus.swagger-ui.path=/my-custom-path
```

Mail Sender

You can send emails by using Quarkus Mailer extension:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-mailer"
```

You can inject two possible classes io.quarkus.mailer.Mailer for synchronous API or io.quarkus.mailer.ReactiveMailer for asynchronous API.

```
@Inject
Mailer mailer;

@Inject
ReactiveMailer reactiveMailer;
```

And then you can use them to send an email:

```
mailer.send(
    Mail.withText("to@acme.org", "Subject", "Body")
);

CompletionStage<Void> stage =
    reactiveMailer.send(
        Mail.withText("to@acme.org", "Subject", "Body")
    );
```

Mail class contains methods to add cc, bcc, headers, bounce address, reply to, attachments, inline attachments and html body.

```
mailer.send(Mail.withHtml("to@acme.org", "Subject", body)
    .addInlineAttachment("quarkus.png",
        new File("quarkus.png"),
        "image/png", "<my-image@quarkus.io>"));
```

Tip If you need deep control you can inject Vert.x mail client @Inject MailClient client;

You need to configure SMTP properties to be able to send an email:

```
quarkus.mailer.from=test@quarkus.io
quarkus.mailer.host=smtp.sendgrid.net
quarkus.mailer.port=465
quarkus.mailer.ssl=true
quarkus.mailer.username=...
quarkus.mailer.password=...
```

List of Mailer parameters. quarkus. as a prefix is skipped in the next table.


Parameter	Default	Description
mailer.from		Default address.
mailer.mock	false	Emails not sent, just printed.
mailer.bounce-address		Default address.
mailer.host	mandatory	SMTP host.
mailer.port	25	SMTP port.
mailer.username		The username.
mailer.password		The password.
mailer.ssl	false	Enables SSL.
mailer.trust-all	false	Trust all certificates.

Parameter	Default	Description
mailer.max-pool-size	10	Maximum number of open connections .
mailer.own-host-name		Hostname for HELO/EHLO and Message-ID
mailer.keep-alive	true	Connection pool enabled.
mailer.disable-esmtp	false	Disable ESMTP.
mailer.start-tls	OPTIONAL	TLS security mode. NONE, OPTIONAL, REQUIRED.
mailer.login	NONE	Login mode. NONE, OPTIONAL, REQUIRED.
mailer.auth-methods	All methods.	Space-separated list.
mailer.key-store		Path of the key store.
mailer.key-store-password		Key store password.

Resources

- https://quarkus.io/guides/
- https://www.youtube.com/user/lordofthejars

Authors :



@alexsotob
Java Champion and SW Engineer at Red Hat

0.16.0

