

Package ‘biblionetwork’

February 4, 2021

Title A Package For Creating Different Types of Bibliometric Networks

Version 0.0.0.9000

Author François Claveau, Aurélien Goutsmedt and Alexandre Truc.

Maintainer Aurélien Goutsmedt <agoutsmedt@hotmail.fr>

Description This package brings different functions to create bibliometric networks like bibliographic coupling network, co-citation network and co-authorship network. The weights of network edges can be calculated according to different methods, depending on the type of networks, the type of nodes, and what you want to analyse. These functions are optimized to be used on very large dataset.

URL <https://github.com/agoutsmedt/biblionetwork>

BugReports <https://github.com/agoutsmedt/biblionetwork/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Imports data.table,
Rdpack (>= 0.7)

Depends R (>= 2.10)

RdMacros Rdpack

R topics documented:

Authors_stagflation	2
biblio_cocitation	2
biblio_coupling	3
coauth_network	5
coupling_entity	7
coupling_similarity	8
coupling_strength	9
Nodes_stagflation	10
Ref_stagflation	11
Index	12

Authors_stagflation	<i>List Of Authors Of The Articles and Books Explaining the 1970s US Stagflation.</i>
---------------------	---

Description

A dataset associating the books and academic articles endeavouring to explain the US stagflation and their authors (Nodes_stagflation just takes the first author; here is the complete list of authors per document).

Usage

Authors_stagflation

Format

A data frame with 558 rows and 7 variables:

ItemID_Ref Identifier of the document published by the author

Author Author of the document

Order Use this as a label for nodes

Source

Goutsmedt A. (2020) “From Stagflation to the Great Inflation: Explaining the 1970s US Economic Situation”. Revue d’Economie Politique, Forthcoming 2021.

biblio_cocitation	<i>Calculating The Coupling Angle Measure For Edges In A Co-citation Network</i>
-------------------	--

Description

This function has basically the same as the `biblio_coupling()` function but it is explicitly framed for bibliographic co-citation network (and not for bibliographic coupling networks). It takes a data frame with direct citations, and calculates the number of times two references are citing together, and calculate a measure similar to the coupling angle value (Sen and Gan 1983): it divides the number of times two references are cited together by the rootsquare of the product of the total number of citations (in the whole corpus) of each reference. The more two references are cited, the more they have to be cited together for their link to be important.

Usage

```
biblio_cocitation(
  dt,
  source,
  ref,
  normalized_weight_only = TRUE,
  weight_threshold = 1,
  output_in_character = TRUE
)
```

Arguments

<code>dt</code>	The dataframe with citing and cited documents. It could also be used
<code>source</code>	the column name of the source identifiers, that is the documents that are citing.
<code>ref</code>	the column name of the cited references identifiers. In co-citation network, these references are the nodes of the network.
<code>normalized_weight_only</code>	if set to FALSE, the function returns the weights normalized by the cosine measure, but also simply the number of times two references are cited together.
<code>weight_threshold</code>	Correspond to the value of the non-normalized weights of edges. The function just keeps the edges that have a non-normalized weight superior to the <code>weight_threshold</code> . In a large bibliographic co-citation network, you can consider for instance that being cited only once together is not sufficient/significant for two references to be linked together. This parameter could also be modified to avoid creating untractable networks with too many edges.
<code>output_in_character</code>	If TRUE, the function ends by transforming the <code>from</code> and <code>to</code> columns in character, to make the creation of a tidygraph graph easier.

Details

This function uses `data.table` package and is thus very fast. It allows the user to compute the coupling angle on a very large dataframe very quickly.

Value

A `data.table` with the articles (or authors) identifier in `from` and `to` columns, with one or two additional columns (the coupling angle measure and the number of shared references). It also keeps a copy of `from` and `to` in the `Source` and `Target` columns. This is useful if you are using the `tidygraph` package then, where `from` and `to` values are modified when creating a graph.

References

Sen SK, Gan SK (1983). "A Mathematical Extension of the Idea of Bibliographic Coupling and Its Applications." *Annals of library science and documentation*, **30**(2). [http://nopr.niscair.res.in/bitstream/123456789/28008/1/ALIS%2030\(2\)%2078-82.pdf](http://nopr.niscair.res.in/bitstream/123456789/28008/1/ALIS%2030(2)%2078-82.pdf).

biblio_coupling

Calculating The Coupling Angle Measure For Edges

Description

This function calculates the number of references that different articles share together, as well as the coupling angle value of edges in a bibliographic coupling network (Sen and Gan 1983), from a direct citation data frame. This is a standard way to build bibliographic coupling network using Salton's cosine measure: it divides the number of references that two articles share by the rootsquare of the product of both articles bibliography lengths. It avoids giving too much importance to articles with a large bibliography.

Usage

```
biblio_coupling(
  dt,
  source,
  ref,
  normalized_weight_only = TRUE,
  weight_threshold = 1,
  output_in_character = TRUE
)
```

Arguments

dt	For bibliographic coupling (or co-citation), the dataframe with citing and cited documents. It could also be used <ol style="list-style-type: none"> 1. for title co-occurrence network, with source being the articles, and ref being the list of words in articles titles; 2. for co-authorship network, with source being the authors, and ref the list of articles.
source	the column name of the source identifiers, that is the documents that are citing. In coupling network, these documents are the nodes of the network.
ref	the column name of the cited references identifiers.
normalized_weight_only	if set to FALSE, the function returns the weights normalized by the cosine measure, but also simply the number of shared references.
weight_threshold	Correspond to the value of the non-normalized weights of edges. The function just keeps the edges that have a non-normalized weight superior to the weight_threshold. In a large bibliographic coupling network, you can consider for instance that sharing only one reference is not sufficient/significant for two articles to be linked together. This parameter could also be modified to avoid creating untractable networks with too many edges.
output_in_character	If TRUE, the function ends by transforming the from and to columns in character, to make the creation of a tidygraph graph easier.

Details

This function uses data.table package and is thus very fast. It allows the user to compute the coupling angle on a very large dataframe very quickly.

This function is a relatively general function that can also be used

1. for co-citation networks (just by inversing the source and ref columns). If you want to avoid confusion, rather use the biblio_cocit function.
2. for title co-occurrence networks (taking care of the lenght of the title thanks to the coupling angle measure);
3. for co-authorship networks (taking care of the number of co-authors an author has collaborated with on a period). For co-authorship, rather use the coauth_network function.

Value

A data.table with the articles (or authors) identifier in from and to columns, with one or two additional columns (the coupling angle measure and the number of shared references). It also keeps a copy of from and to in the Source and Target columns. This is useful if you are using the tidygraph package then, where from and to values are modified when creating a graph.

References

Sen SK, Gan SK (1983). "A Mathematical Extension of the Idea of Bibliographic Coupling and Its Applications." *Annals of library science and documentation*, **30**(2). [http://nopr.niscair.res.in/bitstream/123456789/28008/1/ALIS%2030\(2\)%2078-82.pdf](http://nopr.niscair.res.in/bitstream/123456789/28008/1/ALIS%2030(2)%2078-82.pdf).

coauth_network	<i>Creating Co-Authorship Network With Different Measures For Weights</i>
----------------	---

Description

This function creates a edges data table from a data frame with a list of authors and their publications. The weight of edges can be calculated following different methods. The nodes of the network could be indifferently authors, institutions or countries.

Usage

```
coauth_network(
  dt,
  authors,
  articles,
  method = c("full_counting", "fractional_counting", "fractional_counting_refined"),
  cosine_normalized = FALSE
)
```

Arguments

dt	The dataframe with authors (or institutions or countries) and the list of documents they have published.
authors	The column name of the source identifiers, that is the authors (or institutions or countries).
articles	The column name of the documents identifiers.
method	Method for calculating the edges weights, to be chosen among "full_counting", "fractional_counting" or "fractional_counting_refined".
cosine_normalized	Possibility to take into account the total number of articles written by two linked authors and to normalize the weight of their link.

Details

Weights can be calculated with:

1. the `full_counting` method: the links between authors correspond to their absolute number of collaborations
2. the `fractional_counting` method which takes into account the number of authors in each article, following (Perianes-Rodriguez et al. 2016) equation:

$$\sum_{k=1}^M \frac{a_{ik} \cdot a_{jk}}{n_k - 1}$$

with M the total number of articles,

$$a_{ik} \cdot a_{jk}$$

which takes 1 if author i and j have co-written the article k, and

$$n_k$$

the number of authors for article k.

3. the `fractional_counting_refined` method, inspired by (Leydesdorff and Park 2017) which is similar to `fractional_counting` but which is formalised in a way that allows the sum of weights to equal the number of articles in the corpus:

$$\sum_{k=1}^M \frac{a_{ik} \cdot a_{jk} \cdot 2}{n_k \cdot (n_k - 1)}$$

In addition, it is possible to take into account the total number of collaborations of two linked authors. If `cosine_normalized` is set to `True`, the weight calculated with one of the three methods above is divided by

$$\sqrt{C_i \cdot C_j}$$

, with

$$C_i$$

being the number of articles co-written by author i.

Value

A data.table with the authors (or institutions or countries) identifier in `from` and `to` columns, with a weight column whose values depend on the method chosen. It also keeps a copy of `from` and `to` in the `Source` and `Target` columns. This is useful if you are using the `tidygraph` package then, where `from` and `to` values are modified when creating a graph.

References

Leydesdorff L, Park HW (2017). “Full and Fractional Counting in Bibliometric Networks.” *Journal of Informetrics*, **11**(1), 117–120. ISSN 17511577, <https://linkinghub.elsevier.com/retrieve/pii/S1751157716303133>.

Perianes-Rodriguez A, Waltman L, Van Eck NJ (2016). “Constructing Bibliometric Networks: A Comparison between Full and Fractional Counting.” *Journal of Informetrics*, **10**(4), 1178–1195. https://www.sciencedirect.com/science/article/pii/S1751157716302036?casa_token=AtzjmZ-1QmYAAAAA:2m1BPZsjGULeYi9mnybHODFw2RmMh3GHvRAuMYXygRm63cQOv07M4ixbAmJXuGq71tx2ug29b

coupling_entity *function for edges of bibliographic coupling*

Description

This function creates the edges of a network of entities from a direct citations data frame (i.e. documents citing references). Entities could be authors, affiliations, journals, etc. Consequently, Coupling links are calculated using the coupling angle measure or the coupling strength measure. Coupling links are calculated depending of the number references two authors share, taking into account the minimum number of times two authors are citing each references. For instance, if two entities share a reference in common, the first one citing it twice (in other words, citing it in two different articles), the second one three times, the function takes two as the minimum value. In addition to the features of the coupling strength measure (see [coupling_strength\(\)](#)) or the coupling angle measure (see [biblio_coupling\(\)](#)), it means that, if two entities share two reference in common, the fact that the first reference is cited at least four times by the two entities, whereas the second reference is cited at least only once, the first reference contributes more to the edge weight than the second reference. This use of minimum shared reference for entities coupling comes from Zhao and Strotmann (2008).

Usage

```
coupling_entity(
  dt,
  source,
  ref,
  entity,
  weight_threshold = 1,
  output_in_character = FALSE,
  method = c("coupling_strength", "coupling_angle")
)
```

Arguments

dt	The table with citing and cited documents.
source	the column name of the source identifiers, that is the documents that are citing.
ref	the column name of the cited references identifiers.
entity	the column name of the entity (authors, journals, institutions) that are citing.
weight_threshold	Correspond to the value of the non-normalized weights of edges. The function just keeps the edges that have a non-normalized weight superior to the weight_threshold. In a large bibliographic coupling network, you can consider for instance that sharing only one reference is not sufficient/significant for two articles (above all for two entities like authors or journals) to be linked together. This parameter could also be modified to avoid creating untractable networks with too many edges.
output_in_character	If TRUE, the function ends by transforming the from and to columns in character, to make the creation of a tidygraph graph easier.
method	Choose the method you want to use for calculating the edges weights: either "coupling_strength" like in the coupling_strength() function, or "coupling_angle" like in the biblio_coupling() function.

Value

A data.table with the entity identifiers in from and to columns, with the coupling strength or coupling angle measures in another column, as well as the method used. It also keeps a copy of from and to in the Source and Target columns. This is useful if you are using the tidygraph package then, where from and to values are modified when creating a graph.

References

Zhao D, Strotmann A (2008). “Author Bibliographic Coupling: Another Approach to Citation-Based Author Knowledge Network Analysis.” *Proceedings of the American Society for Information Science and Technology*, **45**(1), 1–10. <https://asistdl.onlinelibrary.wiley.com/doi/full/10.1002/meet.2008.1450450292>.

coupling_similarity *Calculating The Coupling Strength Measure For Edges*

Description

This function calculates a refined similarity measure of coupling links, from a direct citation data frame. It is inspired by (Shen et al. 2019). To a certain extent, it mixes the `coupling_strength()` function with the cosine measure of the `biblio_coupling()` function.

Usage

```
coupling_similarity(
  dt,
  source,
  ref,
  weight_threshold = 1,
  output_in_character = FALSE
)
```

Arguments

dt	The table with citing and cited documents.
source	The column name of the source identifiers, that is the documents that are citing. In bibliographic coupling, these documents are the nodes of the network.
ref	The column name of the references that are cited.
weight_threshold	Correspond to the value of the non-normalized weights of edges. The function just keeps the edges that have a non-normalized weight superior to the weight_threshold. In a large bibliographic coupling network, you can consider for instance that sharing only one reference is not sufficient/significant for two articles to be linked together. This parameter could also be modified to avoid creating untractable networks with too many edges.
output_in_character	If TRUE, the function ends by transforming the from and to columns in character, to make the creation of a tidygraph graph easier.

Details

The function use the following formalisation:

$$\frac{R_S(A) \bullet R_S(B)}{\sqrt{R_S(A) \cdot R_S(B)}}$$

1. with

$$R_S(A) \bullet R_S(B) = \sum_j \sqrt{\log\left(\frac{N}{\text{freq}(R_j)}\right)}$$

that is a measure similar to the coupling strength measure;

2. and

$$R_S(A) \cdot R_S(B) = \sum_j \sqrt{\log\left(\frac{N}{\text{freq}(R_j(A))}\right)} \cdot \sum_j \sqrt{\log\left(\frac{N}{\text{freq}(R_j(B))}\right)}$$

which is the separated sum for each article of the normalized value of a citation.

Value

A data.table with the articles identifiers in from and to columns, with the similarity measure in another column. It also keeps a copy of from and to in the Source and Target columns. This is useful if you are using the tidygraph package then, where from and to values are modified when creating a graph.

References

Shen S, Zhu D, Rousseau R, Su X, Wang D (2019). “A Refined Method for Computing Bibliographic Coupling Strengths.” *Journal of Informetrics*, **13**(2), 605–615. <https://linkinghub.elsevier.com/retrieve/pii/S1751157716300244>.

coupling_strength

Calculating The Coupling Strength Measure For Edges

Description

This function calculates the coupling strength measure (following Vladutz and Cook 1984 and Shen et al. 2019) from a direct citation data frame. It is a refinement of `biblio_coupling()`: it takes into account the frequency with which a reference shared by two articles has been cited in the whole corpus. In other words, the most cited references are less important in the links between two articles, than references that have been rarely cited. To a certain extent, it is similar to the TF-IDF measure.

Usage

```
coupling_strength(
  dt,
  source,
  ref,
  weight_threshold = 1,
  output_in_character = FALSE
)
```

Arguments

dt	The table with citing and cited documents.
source	the column name of the source identifiers, that is the documents that are citing.
ref	the column name of the references that are cited.
weight_threshold	Correspond to the value of the non-normalized weights of edges. The function just keeps the edges that have a non-normalized weight superior to the weight_threshold. In a large bibliographic coupling network, you can consider for instance that sharing only one reference is not sufficient/significant for two articles to be linked together. This parameter could also be modified to avoid creating untractable networks with too many edges.
output_in_character	If TRUE, the function ends by transforming the from and to columns in character, to make the creation of a tidygraph graph easier.

Value

A data.table with the articles identifiers in from and to columns, with the coupling strength measure in another column. It also keeps a copy of from and to in the Source and Target columns. This is useful if you are using the tidygraph package then, where from and to values are modified when creating a graph.

References

Shen S, Zhu D, Rousseau R, Su X, Wang D (2019). “A Refined Method for Computing Bibliographic Coupling Strengths.” *Journal of Informetrics*, **13**(2), 605–615. <https://linkinghub.elsevier.com/retrieve/pii/S1751157716300244>.

Vladutz G, Cook J (1984). “Bibliographic Coupling and Subject Relatedness.” *Proceedings of the American Society for Information Science*, **21**, 204–207.

Nodes_stagflation	<i>Articles and Books Explaining the 1970s US Stagflation.</i>
-------------------	--

Description

A dataset containing the books and academic articles endeavouring to explain what happened in the US economy in the 1970s, as well as all the articles and books cited at least twice by the first set of articles and books (on the stagflation).

Usage

```
Nodes_stagflation
```

Format

A data frame with 558 rows and 7 variables:

ItemID_Ref Identifier of the document

Author Author of the document

Author_date Use this as a label for nodes

Year Year of publication of the document

Title Title of the document

Journal Journal of publication of the document (if an article)

Type If "Stagflation", the document is listed as an explanation of the US stagflation. If "Non-Stagflation", the document is cited by a document explaining the stagflation

Source

Goutsmedt A. (2020) "From Stagflation to the Great Inflation: Explaining the 1970s US Economic Situation". Revue d'Economie Politique, Forthcoming 2021.

Ref_stagflation	<i>Articles and Books Explaining the 1970s US Stagflation.</i>
-----------------	--

Description

A dataset containing all the articles and books cited by the books and academic articles endeavouring to explain what happened in the US economy in the 1970s.

Usage

Ref_stagflation

Format

A data frame with 4416 rows and 6 variables:

Citing_ItemID_Ref Identifier of the citing document

ItemID_Ref Identifier of the cited document

Author Author of the cited document

Year Year of publication of the cited document

Title Title of the cited document

Journal Journal of publication of the cited document (if an article)

Source

Goutsmedt A. (2020) "From Stagflation to the Great Inflation: Explaining the 1970s US Economic Situation". Revue d'Economie Politique, Forthcoming 2021.

Index

* datasets

Authors_stagflation, [2](#)

Nodes_stagflation, [10](#)

Ref_stagflation, [11](#)

Authors_stagflation, [2](#)

biblio_cocitation, [2](#)

biblio_coupling, [3](#)

biblio_coupling(), [2](#), [7–9](#)

coauth_network, [5](#)

coupling_entity, [7](#)

coupling_similarity, [8](#)

coupling_strength, [9](#)

coupling_strength(), [7](#), [8](#)

Nodes_stagflation, [10](#)

Ref_stagflation, [11](#)