

S01-Text to Audio

GenAI-June-HomeAssignment > S01-Text to Audio

POST

https://api.groq.com/openai/v1/audio/speech

Send

DocsParamsAuthorizationHeaders 12BodyScriptsSettings

noneform-datax-www-form-urlencodedrawbinaryGraphQLJSON

SchemaBeautify

```
1 {
2   "model": "canopylabs/orpheus-v1-english",
3   "input": "[Polite] Hi, Thanks for your payment of rupees 10000. You will receive a receipt over email shortly",
4   "voice": "diana",
5   "response_format": "wav"
6 }
```

BodyCookies 1Headers 21Test Results

200 OK • 1.23 s • 342.05 KB

Save Response

HexPreviewVisualize

0:07 / 0:07

Request

```
{
  "model": "canopylabs/orpheus-v1-english",
  "input": "[Polite] Hi, Thanks for your payment of rupees 10000. You will receive a receipt over email shortly",
  "voice": "diana",
  "response_format": "wav"
}
```

S02- MultiLingual

[illegible]

Request

```
{
  "model": "llama-3.3-70b-versatile",
  "max_completion_tokens": 500,
  "messages": [
    {
      "role": "system",
      "content": "You are an Kiosk system. Always respond in the same language as the user."
    },
    {
      "role": "user",
      "content": "மிகவும் நன்றி! வேறு வங்கியில் கணக்கு வைத்திருக்கும் நண்பருக்கு பணம் எப்படி மாற்றுவது?"
    }
  ]
}
```

Response

```
{
  "id": "chatcmpl-f9e84bdf-ed2b-479d-8722-42edd3f010e8",
  "object": "chat.completion",
  "created": 1781431878,
  "model": "llama-3.3-70b-versatile",
  "choices": [
    {
      "index": 0,
      "message": {
        "role": "assistant",
        "content": "வங்கிக் கணக்குகளுக்கு இடையே பணம் மாற்றுவதற்கு பல வழிகள் உள்ளன. இதில் சில பொதுவான வழிகள்:\n\n1. **வங்கி பரிவர்த்தனை**: ஒரு வங்கியிலிருந்து மற்றொரு வங்கிக்கு பணம் மாற்ற வங்கி பரிவர்த்தனை வசதியைப் பயன்படுத்தலாம். இதற்கு அனுப்புநர் மற்றும் பெறுநரின் வங்கி விவரங்கள் தேவை.\n\n2. **நேரடி பரிவர்த்தனை**: இந்தியாவில், நேரடி பரிவர்த்தனை மூலம் பணம் மாற்ற முடியும். இதற்கு, அனுப்புநர் தனது வங்கிக் கணக்கில்"
      },
      "logprobs": null,
      "finish_reason": "length"
    }
  ],
}
```

```

"usage": {
  "queue_time": 0.046344035,
  "prompt_tokens": 161,
  "prompt_time": 0.009426113,
  "completion_tokens": 500,
  "completion_time": 2.098727775,
  "total_tokens": 661,
  "total_time": 2.108153888
},
"usage_breakdown": null,
"system_fingerprint": "fp_dae98b5ecb",
"x_groq": {
  "id": "req_01kv2stedreha8vwyqc2bh3y2g",
  "seed": 769550781
},
"service_tier": "on_demand"
}

```

S03-GenerateAPITestcasesFromSwaggerCode

The screenshot displays the Groq IDE interface. On the left, a sidebar lists collections of prompts, including 'GenAI Training' and 'GenAI-June'. The main workspace shows a REST client request to `https://api.groq.com/openai/v1/chat/completions` with a POST method. The request body is in raw JSON format, containing a system message and a user message. The system message instructs the model to generate REST Assured Java code for flight API services. The user message provides a specific instruction to generate code for flight API services, including mandatory rules and a request body.

The response is a 200 OK status, returned in 2.34 seconds with a 2.6 KB body. The response is in JSON format and contains a message object with a role of 'assistant' and a content field that contains the generated REST Assured Java code. The code includes imports for REST Assured, TestNG, and Hamcrest, and defines a test class `FlightBookingApiTest` with methods for testing flight availability, booking, and cancellation.

Request

```
{
```

```

"model": "openai/gpt-oss-120b",

"temperature": 0.5,

"messages": [

{

  "role": "system",

  "content": "You are a Senior API Test Automation Architect with strong expertise in Rest Assured,
TestNG, Maven, and API schema-driven test generation."

},

{

  "role": "user",

  "content": "I — INSTRUCTION\nGenerate Rest Assured Java code for flight API
services.\n\nMANDATORY RULES:\n1) Generate ONLY Java Rest Assured code.\n2) Do NOT include
explanations, markdown, or extra text.\n3) Use TestNG as the test runner.\n4) Use meaningful class,
method, and variable names.\n5) Include imports required for Rest Assured, TestNG, and
assertions.\n6) Use reusable base URI setup.\n8) Add assertions for status code and important
response fields.\n9) Keep the code clean, executable, and production-style.\n10) Do NOT use
placeholder comments.\n\nC — CONTEXT\nThe code will be used by QA engineers for API
automation practice using Swagger flight Booking.\n\nP — PERSONA\nYou are a Senior API Test
Automation Architect creating enterprise-style reusable Rest Assured automation code.\n\nO —
OUTPUT\nReturn ONLY executable Java code with:\n- One test class\n- @BeforeClass setup\n- Test
methods for getflightavailability, book flight, cancel flight\n- Request body creation\n- Response
validation\n\nRules:\n- No markdown fences\n- No explanation text\n- No assumptions outside
Swagger Flight Bkking API\n- Use business-readable method names\n\nTARGET API:\nFlight
Booking\nResource: Flight Booking\nOperations required:\n- Check for flight availability\n- Book
flight by id\n- cancel a booking"

}

]

}

```

Response

```

{
  "id": "chatcmpl-73676ac7-184a-4c92-99e1-d7fe9c84836a",
  "object": "chat.completion",
  "created": 1781431851,
  "model": "openai/gpt-oss-120b",
  "choices": [
    {
      "index": 0,
      "message": {
        "role": "assistant",
        "content": "import io.restassured.RestAssured;\nimport
io.restassured.http.ContentType;\nimport io.restassured.response.Response;\nimport

```

```

org.testng.annotations.BeforeClass;\nimport org.testng.annotations.Test;\nimport static
org.hamcrest.Matchers.*;\nimport static org.testng.Assert.*;\n\npublic class FlightBookingApiTest
{\n\n    private static final String BASE_URI = \"https://api.flightbooking.com\";\n    private static final
String AVAILABILITY_ENDPOINT = \"/flights/availability\";\n    private static final String
BOOKING_ENDPOINT = \"/flights/book\";\n    private static final String CANCELLATION_ENDPOINT =
\"/flights/cancel\";\n\n    private String bookingId;\n\n    @BeforeClass\n    public void setUp() {\n
RestAssured.baseURI = BASE_URI;\n    }\n\n    @Test(priority = 1)\n    public void
testCheckFlightAvailability() {\n        Response response = RestAssured\n            .given()\n
.contentType(ContentType.JSON)\n            .queryParams(\"origin\", \"JFK\")\n
.queryParam(\"destination\", \"LAX\")\n            .queryParams(\"date\", \"2023-12-15\")\n
.when()\n            .get(AVAILABILITY_ENDPOINT)\n            .then()\n            .assertThat()\n
.statusCode(200)\n            .body(\"available\", equalTo(true))\n            .body(\"flights\",
not(empty()))\n            .extract()\n            .response();\n\n        assertTrue(response.jsonPath().getList(\"flights\").size() > 0, \"Flight list should not be empty\");\n    }\n\n    @Test(priority = 2, dependsOnMethods = \"testCheckFlightAvailability\")\n    public void
testBookFlight() {\n        String requestBody = \"{\\n            \\\"flightId\\\":\n
\\\"FL1234\\\",\\n            \\\"passenger\\\": {\\n                \\\"firstName\\\": \\\"John\\\",\\n
\\\"lastName\\\": \\\"Doe\\\",\\n                \\\"email\\\": \\\"john.doe@example.com\\\",\\n            },\\n
\\\"payment\\\": {\\n                \\\"cardNumber\\\": \\\"4111111111111111\\\",\\n
\\\"expiryMonth\\\": \\\"12\\\",\\n                \\\"expiryYear\\\": \\\"2025\\\",\\n                \\\"cvv\\\": \\\"123\\\"\\n
            }\\n        }\\\";\n\n        Response response = RestAssured\n            .given()\n
.contentType(ContentType.JSON)\n            .body(requestBody)\n            .when()\n
.post(BOOKING_ENDPOINT)\n            .then()\n            .assertThat()\n            .statusCode(201)\n
.body(\"bookingId\", notNullValue())\n            .body(\"status\", equalTo(\"CONFIRMED\"))\n
.extract()\n            .response();\n\n        bookingId = response.jsonPath().getString(\"bookingId\");\n        assertNotNull(bookingId, \"Booking ID should be returned\");\n    }\n\n    @Test(priority = 3,
dependsOnMethods = \"testBookFlight\")\n    public void testCancelFlight() {\n        String
requestBody = String.format(\"{\\\"\\\"\\\"bookingId\\\"\\\":\\\"%s\\\"}\", bookingId);\n\n        RestAssured\n
.given()\n            .contentType(ContentType.JSON)\n            .body(requestBody)\n
.when()\n            .post(CANCELLATION_ENDPOINT)\n            .then()\n            .assertThat()\n
.statusCode(200)\n            .body(\"bookingId\", equalTo(bookingId))\n            .body(\"status\",
equalTo(\"CANCELED\"));\n    }\n}

```

"reasoning": "We need to output Java code only, no markdown fences. Include imports, class, @BeforeClass, test methods for get flight availability, book flight, cancel flight. Use Rest Assured, TestNG. Use reusable base URI. Include request body creation. Assertions for status code and important response fields.\n\nWe need to assume endpoint paths. Since not given, we can infer typical: /flights/availability, /flights/book, /flights/cancel or similar. Use path parameters maybe flightId. Provide request bodies as JSON strings or using Map.\n\nWe'll create a BaseTest class with static baseURI. Or within same class.\n\nWe'll include import static io.restassured.RestAssured.*; import static org.hamcrest.Matchers.*;\n\nWe'll use Response response = given()....when().get(...).then().assertThat().statusCode(200).body(...).extract().response();\n\nWe'll need to store bookingId for cancel test, maybe use a class variable.\n\nImplement three test methods: testCheckFlightAvailability, testBookFlight, testCancelFlight.\n\nUse @Test(priority=1) etc.\n\nWill need to set baseURI in @BeforeClass: RestAssured.baseURI = \"https://api.example.com\"; (maybe placeholder but not placeholder comment). Use actual string maybe \"https://api.flightbooking.com\". That's fine.\n\nAdd content-type header for JSON.\n\nImplement request body for book flight: flightId, passenger details.\n\nCancel flight: send bookingId.\n\nAdd assertions: status code 200, response fields like \"available\": true, \"bookingId\" not null, \"status\": \"canceled\".\n\nOk produce code."

```

},
"logprobs": null,

```

```
    "finish_reason": "stop"
  },
  "usage": {
    "queue_time": 0.159219019,
    "prompt_tokens": 376,
    "prompt_time": 0.016522894,
    "completion_tokens": 1020,
    "completion_time": 2.126983487,
    "total_tokens": 1396,
    "total_time": 2.143506381,
    "completion_tokens_details": {
      "reasoning_tokens": 329
    }
  },
  "usage_breakdown": null,
  "system_fingerprint": "fp_4727af4560",
  "x_groq": {
    "id": "req_01kv2sskskeetsgvgk03rfkdxt",
    "seed": 1232234677
  },
  "service_tier": "on_demand"
}
```