Covenant Planner - Railway deploy walkthrough

Printable checklist for deploying the sync API on Railway (managed Postgres + HTTPS). You paste secrets in Railway / Google / SMTP dashboards - agents cannot log in for you. Full detail: docs/DEPLOY_WALKTHROUGH.md

Do Step 1 right now: create the Railway project.

0. Prerequisites

- Railway account (GitHub login recommended)
- Google Cloud OAuth Web client (for Continue with Google)
- SMTP: Resend, SendGrid, Mailgun, or Gmail App Password
- Optional later: Cloudflare R2 or AWS S3 for photos

```
cd C:\Users\arian\the-covenant-wedding-planner
git checkout cursor/offline-cloud-sync-017e
git pull origin cursor/offline-cloud-sync-017e
```

1. Create Railway project (do this now)

- railway.app -> New Project -> Deploy from GitHub
- Repo: agray1088/the-covenant-wedding-planner
- Branch: cursor/offline-cloud-sync-017e (or master after merge)
- Settings -> Build: Builder = Dockerfile
- Dockerfile path = Dockerfile | Root Directory = / (empty)
- Click Deploy on pending-changes banner if shown
- If Railpack 'No start command': set Builder/path above FIRST, then pull + redeploy

2. Add Postgres

- Add PostgreSQL service; link it so DATABASE_URL is injected

```
DATABASE_SSL=1
```

3. Session secret

```
openssl rand -hex 32
```

4. Core Variables (paste in Railway)

```
NODE_ENV=production
PORT=8787
HOST=0.0.0.0
TRUST_PROXY=1
DATABASE_SSL=1
SESSION_SECRET=<openssl output>
SESSION_DAYS=30
SERVE_STATIC=0
BOOTSTRAP_EMAIL=
```

```
BOOTSTRAP_PASSWORD=
```

Omit FEATURE_*=0 from the example (or set to 1) so RSVP/portal features stay on.

5. PUBLIC_URL + CORS (after Railway gives HTTPS)

```
PUBLIC_URL=https://covenant-api-production.up.railway.app
CORS_ORIGIN=http://localhost:8000
CLIENT_APP_URL=http://localhost:8000
```

No trailing slash on PUBLIC_URL. Add hosted UI origins to CORS later if needed.

6. Post-deploy checks

```
curl -s https://YOUR-PUBLIC-URL-HOST/health
curl -s https://YOUR-PUBLIC-URL-HOST/setup/status
```

Expect /health ok + db up. /setup/status shows booleans only (never secrets).

7. Google OAuth redirect URI

```
${PUBLIC_URL}/auth/google/callback
```

Example: https://covenant-api-production.up.railway.app/auth/google/callback

```
GOOGLE_CLIENT_ID=<from Google>
GOOGLE_CLIENT_SECRET=<from Google>
GOOGLE_REDIRECT_URI=
```

Leave GOOGLE_REDIRECT_URI empty to use the default above.

8. SMTP examples

Resend:

```
SMTP_HOST=smtp.resend.com
SMTP_PORT=587
SMTP_USER=resend
SMTP_PASS=<API key>
SMTP_FROM=noreply@your-verified-domain.com
SMTP_SECURE=0
```

Gmail App Password:

```
SMTP_HOST=smtp.gmail.com
SMTP_PORT=587
SMTP_USER=you@gmail.com
SMTP_PASS=<app password>
SMTP_FROM=you@gmail.com
SMTP_SECURE=0
```

9. Point planner at HTTPS API

Settings -> Cloud sync (beta) -> paste PUBLIC_URL -> Save & enable. Or console:

```
localStorage.setItem('covenant_cloud_api', 'https://YOUR-PUBLIC-URL-HOST');
localStorage.setItem('covenant_cloud_enabled', '1');
```

```
location.reload();
```

10. Optional R2 photos

```
PHOTO_STORAGE=r2
R2_BUCKET=covenant-photos
R2_ACCESS_KEY_ID=<key>
R2_SECRET_ACCESS_KEY=<secret>
R2_ENDPOINT=https://<accountid>.r2.cloudflarestorage.com
R2_PUBLIC_BASE_URL=https://photos.example.com
```

Troubleshooting (short)

- Railpack 'No start command': Builder=Dockerfile, path=Dockerfile, Deploy banner
- Healthcheck fail: link Postgres, DATABASE_SSL=1, wait for DATABASE_URL
- CORS errors: exact planner origin in CORS_ORIGIN
- redirect_uri_mismatch: Console URI = PUBLIC_URL + /auth/google/callback
- 503 smtp_not_configured: paste SMTP_* and redeploy
- Client mismatch: covenant_cloud_api must equal PUBLIC_URL

Local demo (unchanged)

```
demo@covenant.local
covenant-demo
http://localhost:18787
```

Do not point production secrets at local Docker. See RECONNECT_AFTER_RESTART.md.

Keep this PDF with your deploy notes. Full walkthrough: docs/DEPLOY_WALKTHROUGH.md