RMarkdown YAML Test

Andy Grogan-Kaylor

2021-02-12

Contents

0.1 Background

You will need to install some of these packages from CRAN

```
# install.packages(c("bookdown", "distill", "revealjs", "tint", "tufte"))
```

You will need to install pagedown from GitHub

```
# remotes::install_github('rstudio/pagedown')
```

0.2 R Markdown

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see http://rmarkdown.rstudio.com.

> This is an example of a blockquote.

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:

```
summary(cars)
```

```
##     speed           dist
##  Min.   : 4.0   Min.   :  2.00
##  1st Qu.:12.0   1st Qu.: 26.00
##  Median :15.0   Median : 36.00
##  Mean   :15.4   Mean   : 42.98
##  3rd Qu.:19.0   3rd Qu.: 56.00
##  Max.   :25.0   Max.   :120.00
```

0.3 Including Plots

You can also embed plots, for example:

Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.