

Data Visualization With Stata

Andy Grogan-Kaylor

10 May 2024 14:12:51

Introduction

- Stata is a powerful and intuitive data analysis program.
- Learning how to graph in Stata is an important part of learning how to use Stata.
- Yet, the default graphs in Stata can sometimes be less than optimal.
- This document is an introduction to (a) basic graphing ideas in Stata; and (b) some simple ways to make your Stata graphs look more professional.

What are Variables?

- By variables, I simply mean the columns of data that you have.
- For our purposes, you may think of variables as synonymous with questionnaire items, or columns of data.

Variable Types

- *categorical variables* represent unordered categories like *neighborhood*, or *religious affiliation*, or *place of residence*.
- *continuous variables* represent a continuous scale like a *mental health scale*, or a *measure of life expectancy*.

A Data Visualization Strategy

Once we have discerned the type of variable that have, there are two followup questions we may ask before deciding upon a chart strategy:

- Is our graph about **one thing at a time**?
 - How much of x is there?
 - What is the distribution of x ?
- Is our graph about **two things at a time**?
 - What is the relationship of x and y ?
 - How are x and y associated?

Data

We are going to use the famous “iris” data collected by Edgar Anderson in the early 20th Century.

```
. use "iris.dta", clear
.
. summarize
  Variable |      Obs      Mean   Std. dev.      Min      Max
```

Sepal_Length	150	5.843333	.8280661	4.3	7.9
Sepal_Width	150	3.057333	.4358663	2	4.4
Petal_Length	150	3.758	1.765298	1	6.9
Petal_Width	150	1.199333	.7622377	.1	2.5
Species	150	2	.8192319	1	3

The iris data set has 5 variables.

Species of Iris

Iris species images courtesy Wikipedia.



Figure 1: Iris Species

Petals and Sepals

Basic Graphs

Continuous Variable histogram

```
. histogram Petal_Length
(bin=12, start=1, width=.49166667)
```

Categorical Variable graph bar

```
. graph bar, over(Species)
```

Continuous by Continuous twoway

```
. twoway scatter Petal_Length Petal_Width
```



Figure 2: Petals and Sepals




Figure 3: Histogram of Petal Width




Figure 4: Bar Graph of Species




Figure 5: Scatterplot

Categorical by Categorical graph bar

```
. recode Petal_Length ///  
> (min/3.758 = 0 "below mean") ///  
> (3.758/max = 1 "above mean"), ///  
> generate(Petal_Group) // dichotomize Petal_Length  
(150 differences between Petal_Length and Petal_Group)  
.  
. graph bar, over(Species) over(Petal_Group)
```




Figure 6: Bar Graph of Species by Category of Petal Length

Continuous by Categorical graph bar

```
. graph bar Petal_Length, over(Species)
```




Figure 7: Bar Graph of Petal Length by Species

Titles and Labels , title(...) xtitle(...) ytitle(...)

```
. twoway scatter Petal_Length Petal_Width, scheme(s1rcolor) ///  
> title("Petal Length by Petal Width") ///  
> xtitle("Petal Width") ytitle("Petal Width") ///  
> caption("Iris Data")
```




Figure 8: Graph With Titles and Labels

Better Graphing With Schemes ,scheme(...)

The easiest method to make better Stata graphs is through the use of predefined Stata graphing schemes.

Pre-Defined Schemes

Some schemes, e.g. `economist`, `sj`, `s1color`, and `s1rcolor` are pre-installed with Stata.

Economist Scheme

```
. twoway scatter Petal_Length Petal_Width, scheme(economist)
```

Stata Journal Scheme

```
. twoway scatter Petal_Length Petal_Width, scheme(sj)
```

s1color Scheme

```
. twoway scatter Petal_Length Petal_Width, scheme(s1color)
```




Figure 9: Scatterplot with Economist Scheme




Figure 10: Scatterplot with *Stata Journal* Scheme




Figure 11: Scatterplot with `s1color` Scheme

s1rcolor Scheme

```
. twoway scatter Petal_Length Petal_Width, scheme(s1rcolor)
```




Figure 12: Scatterplot with `s1rcolor` Scheme

User Written Schemes

Two of the best user written schemes are `plottig` and `lean2`.

Use the `findit` command e.g. `findit lean2` to find these schemes.

lean2 Scheme

```
. twoway scatter Petal_Length Petal_Width, scheme(lean2)
```

Michigan graph scheme

I have written a `michigan` graph scheme described here.

```
. twoway (scatter Petal_Length Petal_Width) ///  
> (lfit Petal_Length Petal_Width), scheme(michigan)
```

Schemes as a Base for Further Tweaking

Schemes can be used as a base that can then be further modified.

```
. twoway (scatter Petal_Length Petal_Width, msymbol(0) mcolor(red)) ///  
> (lfit Petal_Length Petal_Width), ///  
> scheme(lean2)  
(note: named style 0 not found in class symbol, default attributes used)
```




Figure 13: Scatterplot with lean2 Scheme




Figure 14: Scatterplot with michigan Scheme




Figure 15: Modified Scatterplot with `lean2` Scheme as a Base

Even More Tweaks

Based upon an example at <https://blog.stata.com/2018/10/02/scheming-your-way-to-your-favorite-graph-style/>

```
. twoway scatter Sepal_Length Sepal_Width Petal_Width Petal_Length, ///
> color(%50 %50 %50) /// transparency
> title("Multiple Iris Characteristics") /// title
> scheme(s1rcolor) // scheme
```

More Information

See also [Two Page Stata](#)

Created by agrogan@umich.edu




Figure 16: Modified Scatterplot with `s1rcolor` Scheme as a Base