

Two Page Stata

An Introduction to Stata In 2 Pages

Andy Grogan-Kaylor

2026-08-11

1 Introduction

An introduction to Stata in 2 pages.¹ Commands that you actually type into Stata are represented in `monospace font`. `x` and `y` refer to variables in your data. The treatment here is intended to be extremely brief, in order to create a kind of “cheat sheet” that can be presented in 2 pages. More documentation on any command is available in the printed or PDF Stata manuals, or by typing `help` command.

So many projects have the same, or similar, workflow.



Figure 1: A common data workflow

💡 Key Idea

A little bit of Stata can go a long way.

The general idea of most Stata commands is `command variable(s), options`. Often it is not necessary to use any options since the authors of Stata have done such a good job of thinking about the defaults.

The Stata interface makes it extremely easy to do rapid interactive data analysis. Hit **PAGE-UP** to recall the most recent command, which you can then quickly edit and resubmit.

Use the **DO FILE EDITOR** to save Stata commands that you want to use again in a `.do` file, and to create an *audit trail* of your work so that your workflow is *documented* and *replicable*.

¹Comments, questions and corrections most welcome and may be sent to: Andrew Grogan-Kaylor @ agrogan@umich.edu. This document available on the web @ <https://agrogan1.github.io/Stata/>

2 Get (And Get Acquainted With) Data

Once you are in the right directory, use `"mydata.dta"` will open your data. `save "mydata.dta", replace` will save your data.

It is good practice to start by *looking at* your data. `browse x y z` will open a data window with variables `x`, `y` and `z`.

`codebook x y` will produce a nicely formatted codebook of selected variables, which is especially useful if you have added variable labels and value labels. `codebook` is especially useful for seeing how numerical values are associated with value labels. `codebook` by itself will list every variable in your data and generate a lot of [probably too much] output.

`lookfor` allows you to find variables that contain a specified keyword. This is especially useful in large data sets with many variables. Often abbreviated keywords are the most helpful. e.g. to find a poverty variable, type `lookfor pov`.

With very large data sets, it may be helpful to use `keep x y z` to only keep the variables with which you are working.

`describe` tells you about the contents of a specific variable. E.g. `describe x y`. `describe, short` will tell you very basic things about your data, including the number of observations in the data set, and the size of your data file.

3 Process And Clean Data

Data with missing values, often represented as negative numbers (e.g. `-99`, `-9`, `-8`) need to be recoded so that the missing values are represented as a missing value character (`.`) that Stata knows to exclude from calculations.

²While generating a new variable is optional, it is almost always a good idea.

`recode x (oldvalue = newvalue), generate(xR)`² will recode a variable into a *new* variable. `recode x (-99/-1 = .), generate(xR)` will recode negative numbers from -99 to -1 to missing for x. `recode x (7/9 = .), generate(xR)` changes 7 through 9 to be missing for x. Indeed, `recode` will change specific values in your data to anything you want, not just missing values. Reverse coding often looks something like `recode x (1=3) (2=2) (3=1), generate(xR)`.

Like many other statistical programs, Stata makes a large distinction between variables that are coded as *numeric*, and variables that are coded as *strings*. `describe x` will help you to ascertain the variable type. `encode x, generate(x_NUMERIC)` is often useful to create a *numeric* version of *string* variables. In the special case where the values of your variables are actually *numbers* but stored as *strings*, `destring x, generate(x_NUMERIC)` may be the more helpful and appropriate command. The differences between the two commands are subtle, so consult Stata help on each command.

It is often convenient to `rename` your variables so that the variables have more intuitively understandable names e.g. `rename x depression`.

You can create new variables (e.g. scales) out of old variables using `generate newvar = expression` e.g. `generate newvar = (oldvar1 + oldvar2 + oldvar3) / 3` will create a scale out of these three variables.³

It is sometimes useful to `sort` your data. `sort x` will sort your data by the values of x.

4 Analyze Data

4.1 Descriptive Statistics

`summarize` gives you basic descriptive statistics for a variable, such as the mean (average), especially useful for continuous variables. E.g. `summarize x y` or `summarize x y, detail`. `tabulate` gives you a frequency distribution for your variable, especially useful for categorical variables. e.g. `tabulate x`.

4.2 Bivariate Statistics

Tabulating two categorical variables together gives you a cross-tabulation of those variables, e.g. `tabulate x y, row col chi2 pwcorr x y, sig` gives you the pairwise correlation of two continuous variables. `oneway x z, tabulate`

gives you a oneway ANOVA of continuous variable x over categorical variable z.

4.3 Multivariate Statistics

`regress y x` regresses y on x.⁴ `regress y x z` regresses y on x and z.⁵ `regress y x i.z` regresses y on x and z, treating x as continuous and z as a set of categorical indicator variables.⁶ `regress y c.x##i.z` regresses y on continuous x and categorical z, providing both main effects for x and z and the interaction of x and z.

5 Visualize Data⁷⁸

`histogram x` will give you a nice display of one variable.⁹

`twoway scatter y x` gives you a scatterplot of your data. `twoway lfit y x` will give you a linear fit graph. The two syntaxes may be combined e.g. `twoway (scatter y x) (lfit y x)`.

`graph bar, over(x)` is useful for creating a bar graph of the counts of a categorical variable x. `graph bar y, over(x)` will create a bar graph of the means of y over categories of x.

⁴After running a multivariate model `estat summarize` will give you simple descriptive statistics for the specific sample used in that particular analysis.

⁵Other regression commands follow a very similar format: `command y x z` but are beyond the purview of this 2 page guide.

⁶`i.x` is Stata's notation for treating independent variables as *categorical* or *indicator* variables.

⁷For all graphs, options after a ";" will be helpful in titling your graph e.g. `twoway lfit y x, title("...") xtitle("...") ytitle("...")`

⁸Graph schemes can change the overall look of a graph. `, scheme(slc)` is often a good choice. In newer versions of Stata, `scheme(stcolor)` works well.

⁹`histogram x, percent` will scale the y-axis more intuitively in terms of percentages. `histogram x, discrete` gives a nicer display for categorical variables. The `percent` and `discrete` options can be combined.

³`alpha oldvar1 oldvar2 oldvar3` will calculate Cronbach's alpha from this scale.