Bar Charts to Pie Charts: Another Look

Andy Grogan-Kaylor 2020-02-18

Contents

```
Background
1
2
     Get Data
                  1
3
     Call ggplot
                      2
     One Dimension of Data (program)
4
                                            2
         Bar Chart
                      2
4.1
         Stacked Bar Chart
4.2
                              2
4.3
         Pie Chart
     Two Dimensions of Data (program X gender)
5
                                                       2
         Stacked Bar Chart
                              2
5.1
5.2
         Unstack the Bars
                             3
5.3
         Pie Chart
```

1 Background

A quick look at moving from bar charts to pie charts.

A longer explanation of some issues is here: https://agrogan1.

github.io/myposts/bar_charts_in_ggplot2.html

2 Get Data

load("social_service_agency.RData")

```
## age program gender
## 1 26.79480 Program B Male
## 2 24.86283 Program B Male
## 3 24.47185 Program C Male
## 4 23.53132 Program C Female
## 5 18.71005 Program C Other Identity
```

3 Call ggplot

```
library(ggplot2)
```

4 One Dimension of Data (program)

4.1 Bar Chart

```
ggplot(clients, # data I am using
      aes(x = program, # x is program
           fill = program)) + # fill is also program
 geom_bar() # use bars
```

4.2 Stacked Bar Chart

```
ggplot(clients, # data I am using
       aes(x = 1, # x is now 1 for everyone)
           fill = program)) + # fill is program
 geom_bar() # use bars
```


4.3 Pie Chart


```
ggplot(clients, # data I am using
      aes(x = 1, # x is now 1 for everyone
           fill = program)) + # fill is program
  geom_bar() + # use bars
  coord_polar(theta = "y") + # use polar coordinates
 theme_void() # blank theme for pie charts
```


5 Two Dimensions of Data (program X gender)


5.1 Stacked Bar Chart

```
ggplot(clients, # data I am using
       aes(x = program, # x is back to program
           fill = gender)) + # fill is gender
 geom_bar() # use bars
```










5.2 Unstack the Bars

```
ggplot(clients, # data I am using
      aes(x = program, # x is back to program
          fill = gender)) + # fill is gender
 geom_bar(position = "dodge2") # unstack ('dodge') the bars
```



5.3 Pie Chart

One approach ...

```
# position = position_fill() makes the slices
# fill the pie in each facet
ggplot(clients, # data I am using
      aes(x = 1, # x is back to 1)
           fill = gender)) + # fill is gender
  geom_bar(position = position_fill()) + # use bars
  coord_polar(theta = "y") + # polar coordinates
 facet_wrap(~program) + # facet wrap on program
 theme_void() # blank theme for pie charts
```

