

Four Page dplyr

Andy Grogan-Kaylor

2019-02-05

Contents

1	Background	1
2	Sample Data	1
3	Piping	2
4	Select A Subset of Variables: <code>select()</code>	2
5	Filter A Subset of Rows: <code>filter()</code>	2
6	Create New Variables: <code>mutate()</code>	2
7	Recode Variables: <code>mutate()</code>	3
7.1	Continuous Into Categorical: <code>mutate()</code> & <code>cut()</code>	3
7.2	Categorical Into Categorical: <code>mutate()</code> & <code>recode()</code>	3
8	Rename Variables: <code>rename()</code>	3
9	Drop Missing Values: <code>filter()</code>	4
10	Connecting To Other Packages Like <code>ggplot</code>	4

1 Background

`dplyr` is a very powerful R library for managing and processing data.

While `dplyr` is very powerful, learning to use `dplyr` can be very confusing. This guide aims to present some of the most common `dplyr` functions and commands in the form of a brief cheatsheet.

```
library(dplyr)
```

2 Sample Data

year	x	y	z
2005	NA	Group B	89.48
2009	54.51	Group A	110.3
2010	41.54	Group B	94.54
2015	38.86	Group A	106.7
2007	46.99	Group B	89.39

3 Piping

Pipes `%>%` connect pieces of a command e.g. *data to data wrangling to a graph command*.

4 Select A Subset of Variables: `select()`

```
mynewdata <- mydata %>% select(x, y) # select only x and y
```

x	y
NA	Group B
54.51	Group A
41.54	Group B
38.86	Group A
46.99	Group B

5 Filter A Subset of Rows: `filter()`

```
mynewdata <- mydata %>% filter(year > 2010) # filter on year
```

year	x	y	z
2015	38.86	Group A	106.7

6 Create New Variables: `mutate()`

```
mynewdata <- mydata %>% mutate(myscale = x + z) # create a new variable e.g. a scale
```

year	x	y	z	myscale
2005	NA	Group B	89.48	NA
2009	54.51	Group A	110.3	164.8
2010	41.54	Group B	94.54	136.1
2015	38.86	Group A	106.7	145.6
2007	46.99	Group B	89.39	136.4

7 Recode Variables: mutate()

7.1 Continuous Into Categorical: mutate() & cut()

```
mynewdata <- mydata %>%
  mutate(zcategorical = cut(z, # cut at breaks
                           breaks=c(-Inf, 100, Inf),
                           labels = c("low", "high")))
```

year	x	y	z	zcategorical
2005	NA	Group B	89.48	low
2009	54.51	Group A	110.3	high
2010	41.54	Group B	94.54	low
2015	38.86	Group A	106.7	high
2007	46.99	Group B	89.39	low

7.2 Categorical Into Categorical: mutate() & recode()

```
mynewdata <- mydata %>%
  mutate(yrecoded = dplyr::recode(y, # recode values
                                   "Group A" = "Red Group",
                                   "Group B" = "Blue Group"))
```

year	x	y	z	yrecoded
2005	NA	Group B	89.48	Blue Group
2009	54.51	Group A	110.3	Red Group
2010	41.54	Group B	94.54	Blue Group
2015	38.86	Group A	106.7	Red Group
2007	46.99	Group B	89.39	Blue Group

8 Rename Variables: rename()

```
newdata <- mydata %>%
  rename(age = x, # rename
         mental_health = z)
```

year	age	y	mental_health
2005	NA	Group B	89.48
2009	54.51	Group A	110.3
2010	41.54	Group B	94.54

year	age	y	mental_health
2015	38.86	Group A	106.7
2007	46.99	Group B	89.39

9 Drop Missing Values: `filter()`

```
newdata <- mydata %>% filter(!is.na(x)) # filter by x is not missing
```

year	x	y	z
2009	54.51	Group A	110.3
2010	41.54	Group B	94.54
2015	38.86	Group A	106.7
2007	46.99	Group B	89.39

10 Connecting To Other Packages Like `ggplot`

Notice how, in the code below, I never actually create the new data set `mynewdata`. I simply pipe `mydata` into a `dplyr` command, and pipe the result directly to `ggplot2`.

```
library(ggplot2)
```

```
mydata %>% # my data
  mutate(myscale = x + z) %>% # dplyr command to make new variable
  ggplot(aes(x = year, # the rest is ggplot
             y = myscale)) +
  geom_point() + # points
  geom_smooth(se = FALSE) + # smoother without confidence interval
  labs(title = "My Scale By Year") + # labels
  theme(axis.text.x = element_text(size = 10, # tweak theme
                                     angle = 90))
```

