

# Ordinal and Multinomial Logistic Regression

A New Example Using Data From *Multilevel Thinking*

Andy Grogan-Kaylor

2023-10-15

## Table of contents

1	The Data	1
2	Setup	2
3	Ordinal Logistic Regression	2
4	Multinomial Logistic Regression	4

## 1 The Data

Data are simulated data on parent behaviors and child outcomes from [Multilevel Thinking](#).

```
use "https://github.com/agrogan1/multilevel-thinking/raw/main/simulate-and-analyze-multilevel-data"
describe
```

```
Contains data from https://github.com/agrogan1/multilevel-thinking/raw/main/simulate-and-analyze
> -multilevel-data/simulated_multilevel_data.dta
```

```
Observations:      3,000
Variables:         8                21 Apr 2023 12:38
```

Variable name	Storage type	Display format	Value label	Variable label
country	float	%9.0g		country id
HDI	float	%9.0g		Human Development Index
family	float	%9.0g		family id
id	str7	%9s		unique country family id
group	float	%9.0g		arbitrary group variable
physical_punish	float	%9.0g		physical punishment in past week
warmth	float	%9.0g		parental warmth in past week
outcome	float	%9.0g		beneficial outcome

Sorted by: country family

## 2 Setup

We need to create a categorical outcome variable for demonstration purposes.

```
* create an outcome_group variable

egen outcome_group = cut(outcome), group(3) // divide outcome into groups

label define outcome_group 0 "low" 1 "medium" 2 "high" // define value labels

label values outcome_group outcome_group // attach value labels

tabulate outcome_group
```

outcome_group	Freq.	Percent	Cum.
low	1,000	33.33	33.33
medium	1,000	33.33	66.67
high	1,000	33.33	100.00
Total	3,000	100.00	

## 3 Ordinal Logistic Regression

Because the data are clustered by countries, we will use the `cluster(country)` option in each model. The `brant` command can be installed by typing `findit brant`, and installing the Long & Freese `spost` utilities.

```
ologit outcome_group physical_punishment warmth HDI i.group, or cluster(country) // ordinal logit

brant // brant test

margins, at(warmth = (1(1)7)) // margins at different values of warmth

marginsplot, title("Predicted Probabilities From Ordinal Logit") ///
plot(_outcome, labels("low" "medium" "high")) // graph w/ manual labels

graph export myologit.png, replace
```

```
Iteration 0:  Log pseudolikelihood = -3295.8369
Iteration 1:  Log pseudolikelihood = -3157.4676
Iteration 2:  Log pseudolikelihood = -3157.0335
Iteration 3:  Log pseudolikelihood = -3157.0333
```

Ordered logistic regression

```
Number of obs = 3,000
Wald chi2(4)   = 242.78
Prob > chi2    = 0.0000
```

Log pseudolikelihood = -3157.0333

Pseudo R2 = 0.0421

(Std. err. adjusted for 30 clusters in country)

		Robust				
outcome_group		Odds ratio	std. err.	z	P> z	[95% conf. interval]
physical_punishment		.7962002	.0197074	-9.21	0.000	.7584964 .8357781
warmth		1.282995	.026044	12.28	0.000	1.232951 1.335069
HDI		1.00389	.0058436	0.67	0.505	.9925017 1.015409
2.group		1.322192	.0754851	4.89	0.000	1.182221 1.478735
/cut1		-.04647	.4096606			-.84939 .7564499
/cut2		1.446814	.426558			.610776 2.282853

Note: Estimates are transformed only in the first equation to odds ratios.

Brant test of parallel regression assumption

	chi2	p>chi2	df
All	1.98	0.739	4
physical_punishment	1.45	0.229	1
warmth	0.20	0.656	1
HDI	0.05	0.818	1
2.group	0.18	0.672	1

A significant test statistic provides evidence that the parallel regression assumption has been violated.

Predictive margins

Number of obs = 3,000

Model VCE: Robust

1.\_predict: Pr(outcome\_group==0), predict(pr outcome(0))  
2.\_predict: Pr(outcome\_group==1), predict(pr outcome(1))  
3.\_predict: Pr(outcome\_group==2), predict(pr outcome(2))

1.\_at: warmth = 1  
2.\_at: warmth = 2  
3.\_at: warmth = 3  
4.\_at: warmth = 4  
5.\_at: warmth = 5  
6.\_at: warmth = 6  
7.\_at: warmth = 7

		Delta-method				
	Margin	std. err.	z	P> z	[95% conf. interval]	
_predict#_at						

1	1		.4715116	.0239632	19.68	0.000	.4245446	.5184785
1	2		.411902	.0219914	18.73	0.000	.3687996	.4550044
1	3		.3547047	.0204707	17.33	0.000	.3145829	.3948265
1	4		.3012864	.0194346	15.50	0.000	.2631953	.3393776
1	5		.2526558	.0187163	13.50	0.000	.2159724	.2893391
1	6		.2094156	.0180743	11.59	0.000	.1739907	.2448405
1	7		.1717793	.0173168	9.92	0.000	.137839	.2057196
2	1		.3210415	.0100789	31.85	0.000	.3012872	.3407958
2	2		.3376888	.0091914	36.74	0.000	.3196739	.3557037
2	3		.3465153	.0092644	37.40	0.000	.3283575	.3646731
2	4		.3467361	.010075	34.42	0.000	.3269895	.3664827
2	5		.3383307	.0114619	29.52	0.000	.3158658	.3607955
2	6		.3220464	.0133672	24.09	0.000	.2958472	.3482456
2	7		.2992734	.0156422	19.13	0.000	.2686153	.3299314
3	1		.207447	.0183764	11.29	0.000	.1714298	.2434641
3	2		.2504092	.0196723	12.73	0.000	.2118522	.2889661
3	3		.29878	.021223	14.08	0.000	.2571838	.3403763
3	4		.3519775	.0231631	15.20	0.000	.3065787	.3973762
3	5		.4090136	.0255026	16.04	0.000	.3590294	.4589977
3	6		.468538	.0280772	16.69	0.000	.4135078	.5235682
3	7		.5289473	.0305829	17.30	0.000	.469006	.5888886

---

Variables that uniquely identify margins: warmth

```
file
/Users/agrogan/Desktop/GitHub/newstuff/categorical/ordinal-multinomial-logistic-regression
> -2/myologit.png saved as PNG format
```




Figure 1: marginsplot from ologit

## 4 Multinomial Logistic Regression

Because the *Brant* test was insignificant, the results below are likely to look similar. Imagine, however, if the *Brant* test were statistically significant, suggesting that we should estimate separate regression coefficients for each value of the outcome. Imagine, in addition, if we were estimating an outcome

that were truly multinomial in nature, such as *post-secondary* education pursued: *none, vocational, university*. For heuristic purposes, we will relabel the outcome accordingly.

```
label define outcome_group2 0 "none" 1 "vocational" 2 "university" // define value labels

label values outcome_group outcome_group2 // attach NEW value labels

tabulate outcome_group

mlogit outcome_group physical_punishment warmth HDI i.group, rr cluster(country)

margins, at(warmth = (1(1)7)) // margins at different values of warmth

marginsplot, title("Predicted Probabilities From Multinomial Logit") ///
plot(_outcome, labels("none" "vocational" "university")) // graph w/ manual labels

graph export mymlogit.png, replace
```

outcome_gro up	Freq.	Percent	Cum.
none	1,000	33.33	33.33
vocational	1,000	33.33	66.67
university	1,000	33.33	100.00
Total	3,000	100.00	

Iteration 0: Log pseudolikelihood = -3295.8369  
Iteration 1: Log pseudolikelihood = -3159.3121  
Iteration 2: Log pseudolikelihood = -3157.2541  
Iteration 3: Log pseudolikelihood = -3157.2532  
Iteration 4: Log pseudolikelihood = -3157.2532

Multinomial logistic regression

Number of obs = 3,000  
Wald chi2(8) = 216.92  
Prob > chi2 = 0.0000  
Pseudo R2 = 0.0420

Log pseudolikelihood = -3157.2532

(Std. err. adjusted for 30 clusters in country)

outcome_group	RRR	Robust std. err.	z	P> z	[95% conf. interval]	
none	(base outcome)					
vocational						
physical_punishment	.8284144	.0268834	-5.80	0.000	.7773647	.8828166
warmth	1.172042	.0323704	5.75	0.000	1.110284	1.237235
HDI	1.003045	.0039244	0.78	0.437	.9953822	1.010766
2.group	1.244621	.1034633	2.63	0.008	1.057495	1.46486
_cons	.7248303	.2045156	-1.14	0.254	.4169312	1.26011

university							
physical_punishment		.733425	.0260105	-8.74	0.000	.6841767	.7862183
warmth		1.402776	.0404291	11.74	0.000	1.325733	1.484296
HDI		1.005061	.0080327	0.63	0.528	.9894402	1.020929
2.group		1.454744	.1119325	4.87	0.000	1.251102	1.691534
_cons		.3950266	.227379	-1.61	0.107	.1278413	1.220623

Note: \_cons estimates baseline relative risk for each outcome.

Predictive margins  
Model VCE: Robust

Number of obs = 3,000

1.\_predict: Pr(outcome\_group==none), predict(pr outcome(0))  
2.\_predict: Pr(outcome\_group==vocational), predict(pr outcome(1))  
3.\_predict: Pr(outcome\_group==university), predict(pr outcome(2))

1.\_at: warmth = 1  
2.\_at: warmth = 2  
3.\_at: warmth = 3  
4.\_at: warmth = 4  
5.\_at: warmth = 5  
6.\_at: warmth = 6  
7.\_at: warmth = 7

		Delta-method					
		Margin	std. err.	z	P> z	[95% conf. interval]	
_predict#_at							
1 1		.4655491	.0256453	18.15	0.000	.4152852	.515813
1 2		.4108856	.0225268	18.24	0.000	.3667338	.4550374
1 3		.3566849	.020455	17.44	0.000	.3165938	.3967761
1 4		.3043247	.0194768	15.62	0.000	.2661507	.3424986
1 5		.2551027	.0192162	13.28	0.000	.2174397	.2927657
1 6		.210102	.0191257	10.99	0.000	.1726162	.2475877
1 7		.170087	.0187808	9.06	0.000	.1332774	.2068966
2 1		.3312655	.0149681	22.13	0.000	.3019286	.3606025
2 2		.3403628	.010943	31.10	0.000	.318915	.3618106
2 3		.3438888	.0090929	37.82	0.000	.3260671	.3617104
2 4		.3414688	.010569	32.31	0.000	.3207539	.3621838
2 5		.3331582	.014179	23.50	0.000	.3053679	.3609485
2 6		.3194468	.0184628	17.30	0.000	.2832603	.3556333
2 7		.301194	.0227261	13.25	0.000	.2566517	.3457363
3 1		.2031854	.0183179	11.09	0.000	.1672829	.2390879
3 2		.2487516	.0194812	12.77	0.000	.2105691	.2869341
3 3		.2994263	.0210267	14.24	0.000	.2582148	.3406379
3 4		.3542065	.0231943	15.27	0.000	.3087464	.3996666
3 5		.4117391	.0260214	15.82	0.000	.3607381	.4627401
3 6		.4704512	.0292975	16.06	0.000	.4130291	.5278733
3 7		.528719	.0326555	16.19	0.000	.4647153	.5927227

Variables that uniquely identify margins: warmth

file

```
/Users/agrogan/Desktop/GitHub/newstuff/categorical/ordinal-multinomial-logistic-regression  
> -2/mymlogit.png saved as PNG format
```




Figure 2: marginsplot from mlogit