Workflow

Andy Grogan-Kaylor
University of Michigan

2024-02-21

Table of contents

1 Introduction

I have increasingly been thinking about the idea of *workflow* in data science / data analysis work.

So many workflows follow the same conceptual pattern.

2 Visually and Conceptually



3 Characteristics of Good Workflows

Increasingly, we want to think about workflows that are

- **documentable**, **transparent**, and **auditable**: We have a record of what we did if we want to double check our work, clarify a result, or develop a new project with a similar process. We, or others, can find the inevitable errors in our work, **and correct them**.
- **replicable**: Others can replicate our findings with the same or new data.

- **scalable**: We are developing a process that can be as easily used with *thousands* or *millions* of rows of data as it can with *ten* rows of data. We are developing a process that can be easily repeated if we are *constantly getting new or updated data*, e.g. getting new data every week, or every month.

4 Complex Workflows

For **complex workflows**, we will often want to write a script.

> Complex Workflows Benefit From Scripts or Code
>
> The more graphs or calculations I have to make, the more complex the project, the more the desires of the client are likely to change, the more frequently the data is being updated, the more team members that are involved in the workflow, and/or the more mission critical the results (i.e. I need auditability, documentation, and error correction) the more likely I am to use a scripting tool like Stata or R.

	Simple Process: Single Graph or Calculation	Complex Process: Multiple Graphs or Calculations.
Process Run Only Once	Spreadsheet: Excel or Google	Scripting Tool: Stata or R
Process Run Multiple Times (Perhaps As Data Are Regularly Updated)	Scripting Tool: Stata or R	Scripting Tool: Stata or R

Table 1: Tools for Different Workflows

> Start With The Raw Data, And Document Your Thinking In Code
>
> Always (or usually) beginning with the raw data, and then writing and running a script that generates our results allows us to develop a process that is **documentable**, **auditable**, **replicable** and **scalable**.

> Data Are Often Best Stored In Statistical Formats
>
> It is usually best to store quantitative data in a statistical format such as R, Stata, or SPSS. Spreadsheets are likely to be a bad tool for storing quantitative data.

> ! Good Workflows Require Safe Workspaces
>
> It is also *very important* to be aware that good complex workflows are *highly iterative* and *highly collaborative*. Good complex workflows require a *safe workspace* in which team members feel free to admit their own errors, and help with others' mistakes in a non-judgmental fashion. Such a *safe environment* is necessary to build an environment where the *overall error rate* is low.

5 Example

Below is an example that uses the Palmer Penguins data set.

> The example below is in Stata, due to Stata's ease of readability, but could as easily be written in any other language that has scripting, such as SPSS, SAS, R, or Julia.

```
* Learning About Penguins

* Ask A Question

* What can I learn about penguins?
```

```
* Open The Raw Data

use "https://github.com/agrogan1/Stata/raw/main/do-files/penguins.dta", clear

* Clean and Wrangle Data

generate big_penguin = body_mass_g > 4000 // create a big penguin variable
```

```
* Descriptive Statistics

use "https://github.com/agrogan1/Stata/raw/main/do-files/penguins.dta", clear

summarize culmen_length_mm culmen_depth_mm flipper_length_mm body_mass_g

tabulate species
```

```

```

```
    Variable |        Obs        Mean    Std. dev.       Min        Max
-------------+---------------------------------------------------------
culmen_len~m |        342    43.92193    5.459584       32.1       59.6
culmen_dep~m |        342    17.15117    1.974793       13.1       21.5
flipper_le~m |        342    200.9152    14.06171        172        231
 body_mass_g |        342    4201.754    801.9545       2700       6300

    species |      Freq.     Percent        Cum.
------------+-----------------------------------
     Adelie |        152       44.19       44.19
  Chinstrap |         68       19.77       63.95
     Gentoo |        124       36.05      100.00
------------+-----------------------------------
      Total |        344      100.00
```

```
* Visualize The Data

use "https://github.com/agrogan1/Stata/raw/main/do-files/penguins.dta", clear

graph bar body_mass_g, over(species) scheme(s1color) // bar graph

quietly graph export "mybargraph.png", replace

twoway scatter culmen_length_mm body_mass_g, scheme(s1color) // scatterplot

quietly graph export "myscatterplot.png", replace
```



Figure 1: Bar Graph of Penguin Species



Figure 2: Scatterplot of Culmen Length by Body Mass

```
* Analyze

use "https://github.com/agrogan1/Stata/raw/main/do-files/penguins.dta", clear

regress culmen_length_mm body_mass_g // regress culmen length on body mass
```

```
      Source |       SS           df       MS      Number of obs   =       342
-------------+----------------------------------   F(1, 340)       =    186.44
       Model |  3599.71136         1  3599.71136   Prob > F        =    0.0000
    Residual |  6564.49417       340  19.3073358   R-squared       =    0.3542
-------------+----------------------------------   Adj R-squared   =    0.3523
       Total |  10164.2055       341  29.8070543   Root MSE        =     4.394

------------------------------------------------------------------------------
culmen_len~m | Coefficient  Std. err.      t    P>|t|     [95% conf. interval]
-------------+----------------------------------------------------------------
 body_mass_g |   .0040514   .0002967    13.65   0.000     .0034678     .004635
       _cons |   26.89887   1.269148    21.19   0.000      24.4025    29.39524
------------------------------------------------------------------------------
```

6 Multiple Person Workflows

When workflows involve multiple people, all of the above considerations apply, but the situation often becomes more complex. Two hypothetical multiple person workflows are illustrated below.

In the diagram below, the workflow on the left is *uncoordinated*. Each person's work is not available to the others, which may cause difficulties if people's work is supposed to build on the work of others. If one team member makes updates or corrects errors, the results of these efforts are not automatically available to the others.

In contrast, in the diagram below, the workflow on the right is *coordinated*. Each person's work is available to the others so that updates and corrections to errors are propagated through the workflow, and into final analyses and visualizations.

It is often the case that a *coordinated* workflow requires more *coordination*, *time* and *energy* to implement than an *uncoordinated* workflow, but a *coordinated* workflow is likely to pay benefits in terms of all of the advantages of good workflows listed above.


COORDINATED Multiperson Workflow
raw data
person 1
cleans the data
person 2
creates scale 1
person 3
creates scale 2
person 4
complex analysis and visualization


UNCOORDINATED Workflow
raw data
person 1
person 2
person 3
person 4
cleans the data
creates scale 1
creates scale 2
complex analysis and visualization