

Geodesic Paths and Distances on Meshes: PDE and Computational Geometry Approaches

Matthieu Pierre Boyer & Antoine Groudiev

École Normale Supérieure

December 16, 2025

Introduction




Figure: Geodesic paths from a source point on a bunny, a bust and a icosahedron.

Problem Positioning

Given a mesh of a 2-manifold embedded in \mathbb{R}^3 and two points on the mesh, what is the shortest path between the points?

Problem Positioning

Given a mesh of a 2-manifold embedded in \mathbb{R}^3 and two points on the mesh, what is the shortest path between the points?

2-Manifold: a surface that looks locally like \mathbb{R}^2 ;

Problem Positioning

Given a mesh of a 2-manifold embedded in \mathbb{R}^3 and two points on the mesh, what is the shortest path between the points?

2-Manifold: a surface that looks locally like \mathbb{R}^2 ;

Mesh: a set \mathbb{V} of vertices, a set \mathcal{F} of faces in \mathbb{V}^3 .




Figure: Examples of a 2-manifold (left) and non-manifold (right) mesh.

Discrete Differential Geometry

The Laplace-Beltrami operator of a function u is given by:

$$(\Delta u)_i = \frac{1}{2A_i} \sum_{e=(i,j)} (\cot \alpha_{i,j} + \cot \beta_{i,j}) (u_i - u_j). \quad (1)$$

It quantifies the symmetric deviation of the variation of the value at a point.

Physical Equations

We base ourselves on equations modelling the propagation of a phenomenon:


Heat Equation $\Delta u_t = \frac{d}{dt} u_0$;

Poisson Equation $\Delta u = u_0$ for a fixed distribution u_0 ;

Spectral Embedding ℓ^2 distance based on eigenspaces of the laplacian Δ .

Fast Marching

We compute a variation of Dijkstra's algorithm based on the Eikonal equation $|\nabla u| = 1$ for wavefront propagation.



Improved Chen-Han (ICH) Algorithm

Idea: Propagate **windows** accross edges of the mesh, encoding shortest paths from a source.




Figure: Illustration of a window $w = (s, p, e, b_0, b_1, d_0, d_1, \sigma)$.

One Angle, One Split Rule





Figure: Illustration of the “one angle, one split” pruning rule: only keep three out of four windows.

Window Filtering



We can discard a window w if:

- $d + \|pb_0\| > d_0 + \|v_0b_1\|$
- $d + \|pb_1\| > d_1 + \|v_1b_1\|$
- $d + \|pb_0\| > d_2 + \|v_2b_0\|$

Compute time: Heat Method




Figure: Benchmark of the *Heat method* as a function of the number of vertices. Slope: 2.63, r^2 : 0.99.

Compute time: Fast Marching




Figure: Benchmark of the *Fast Marching algorithm* as a function of the number of vertices. Slope: 1.51, r^2 : 0.98.

Compute time: ICH




Figure: Benchmark of the *ICH* algorithm as a function of the number of vertices. Slope: 1.60, r^2 : 0.96.

Comparison of methods

Method	Theoretical Runtime	Actual Runtime	Precision	Main limits
Heat	$\mathcal{O}(n_V^\omega)$	$\mathcal{O}(n_V^\omega)$	Approx.	No paths
Poisson	$\mathcal{O}(n_V^\omega)$		Approx.	Not geodesics
Spectral	$\mathcal{O}(n_V^\omega)$		Approx.	Not geodesics
Fast Marching	$\mathcal{O}(n_V \log n_V)$	$\mathcal{O}(n_V^{1.5})$	Approx.	Fixed sources
ICH	$\mathcal{O}(n_V^2 \log n_V)$	$\mathcal{O}(n_V^{1.6})$	Exact	Limited to meshes

Bibliography I

- [BN03] Mikhail Belkin **and** Partha Niyogi. “Laplacian Eigenmaps for Dimensionality Reduction and Data Representation”. *in* *Neural Computation*: (2003).
- [BR06] Folkmar Bornemann **and** Christian Rasch. “Finite-element Discretization of Static Hamilton-Jacobi Equations based on a Local Variational Principle”. *in* *Computing and Visualization in Science*: (2006).

Bibliography II

- [CH90] Jindong Chen **and** Yijie Han. “Shortest paths on a polyhedron”. *in Proceedings of the sixth annual symposium on Computational geometry*: 1990.
- [Cra+20] Keenan Crane **and others**. *A Survey of Algorithms for Geodesic Paths and Distances*. 2020.
- [CWW17] Keenan Crane, Clarisse Weischedel **and** Max Wardetzky. “The Heat Method for Distance Computation”. *in Commun. ACM*: (2017).

Bibliography III

- [KR93] Douglas Klein **and** Milan Randic. “Resistance Distance”. *in Journal of Mathematical Chemistry*: (1993).
- [KS98] Ron Kimmel **and** JA Sethian. “Computing Geodesic Paths on Manifolds”. *in Proceedings of the National Academy of Sciences of the United States of America*: (1998).
- [MMP87] Joseph SB Mitchell, David M Mount **and** Christos H Papadimitriou. “The discrete geodesic problem”. *in SIAM Journal on Computing*: (1987).

Bibliography IV

- [SK17] Gil Shamai **and** Ron Kimmel. “Geodesic distance descriptors”. *in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition: 2017*.
- [XW09] Shi-Qing Xin **and** Guo-Jin Wang. “Improving Chen and Han’s algorithm on the discrete geodesic problem”. *in ACM Transactions on Graphics (TOG): (2009)*.
- [ZJ16] Qingnan Zhou **and** Alec Jacobson. *Thingi10K: A Dataset of 10,000 3D-Printing Models*. 2016.