

# Lecture 10

# Complexity

FIT 1008  
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA  
Copyright Regulations 1969  
WARNING

# Running Time and RAM

Insertion sort

Binary Search

Big O


Growth rates

# Running Time

Depends on a number of factors including:

- The **input**
- The quality of the code generated by the **compiler**
- The nature and **speed** of the instructions on the **machine** used to execute the program
- The **time complexity of the algorithm**





# Simple computation model

- Each simple operation takes one step (e.g., **assignment**, **print** or **return** statement).
- Each **comparison** takes one time step.
- Running time of **a sequence of statements** = **Sum** of the running time of the **statements**.
- **Loops** and **modules**
  - Composition of many simple operations, and their running time
  - Depends on how many times each of these simple operations are performed.

**RAM model = abstract machine**

# Algorithm FindMin(L[0..n-1])

**Finds minimum element in a list**

**Input:** A list L[0, n-1] of real numbers

**Output:** A list sorted in ascending order.

```
min ← list[0]
k ← 0
while (k < n) do {
    if list[k] < min do {
        min ← list[k]
    }
    k ← k+1
}
return min
```

**2 assignments**

n-1 times

**Does running time  
depend only on n?**

*If it always enters the if:*  $2 + 4(n-1) + 1 + 1 = 4 + 3(n-1)$

*If it never enters the if:*  $2 + 3(n-1) + 1 + 1 = 4 + 2(n-1)$

**This difference is unimportant, when considering the big picture**  
(we will discuss this again at the end)

# Insertion sort





(take last, put slowly in correct position, enlarge)

L






# Loop 1 – I bring another into our home



Loop 2 – I find each item a bed to stay in




# Algorithm InsertionSort( $L[0..n-1]$ )

**Sorts a list using insertion sort.**

**Input:** A list  $L[0, n-1]$  of real numbers

**Output:** A list sorted in ascending order.



Running time does not depend on **n** only

Best and Worst Case

# Insertion Sort: Time complexity


```
k ← 1
while (k < n) do {
    tmp ← list[k]
    j ← k-1
    while (j ≥ 0 and tmp < list[j]) do {
        list[j+1] ← list[j]
        j ← j - 1
    }

    list[j+1] ← tmp
    k ← k + 1
}
```

- Can we stop any of the two loops early?
  - Yes, the second one, when  $\text{tmp} \geq \text{list}[j]$
  - Best and worst cases are going to be different
  - The average case lies in between them.
- Best case?
  - [1, 2, 3, 4]
- Worst case?
  - [4, 3, 2, 1]

We often refer to best  
AND worst case complexities

# Best case



$$1 + 7(n-1) + 1$$

$$7n - 5$$

# Worst case

$k \leftarrow 1$  **1**

**while** ( $k < n$ ) **do** { **1**

$\text{tmp} \leftarrow \text{list}[k]$

$j \leftarrow k-1$

**while** ( $j \geq 0$  and  $\text{tmp} < \text{list}[j]$ ) **do** { **2**

$\text{list}[j+1] \leftarrow \text{list}[j]$

$j \leftarrow j-1$

    }

$\text{list}[j+1] \leftarrow \text{tmp}$

$k \leftarrow k+1$

}

}


**2**

**4**


$k$   
times  
max

$n-1$   
times


**1**



$k = 1$




$k = 2$



$k = 3$


⋮



$k = n-1$

**+1**

# Worst case




$$5(n-1) + (1 \times 4 + 2 \times 4 + 3 \times 4 + \dots + (n-1) \times 4) \quad \mathbf{+2}$$

$$5(n-1) + (2n(n-1)) \mathbf{+2}$$

$$\boxed{2n^2 + 3n - 3}$$

# Insertion Sort running time



- Select **how to measure the input size**.
- If running time depends only on the input size, then that's great.
- If running time depends on input size **and other characteristics** of the input:
  - Analyse best case separately (*can I leave any loops early*).
  - Analyse worst case separately.
  - Together best and worst case are informative.



# Insertion Sort: Code

```
k ← 1
while (k < n) do {
    tmp ← list[k]
    j ← k-1
    while (j ≥ 0 and tmp < list[j]) do {
        list[j+1] ← list[j]
        j ← j - 1
    }

    list[j+1] ← tmp
    k ← k + 1
}
```

```
def insertion_sort(the_list):
    n = len(the_list)
    for k in range(1, n):
        temp = the_list[k]
        i = k - 1
        while i >= 0 and the_list[i] > temp:
            the_list[i + 1] = the_list[i]
            i -= 1
        the_list[i + 1] = temp
```

# Binary Search Assumptions



- The list is sorted
- We can random access the list  
(you can get the value of any position in the list)

# Binary Search

item  $\leftarrow$  the item in the middle of the list

if (item = target)

{

    return index of item

}

if (target < item)

{

    search the first part of the list


}

if (target > item)

{

    search the second part of the list

}



item

**item < target**

item = target

**item > target**

# Binary Search

## **Algorithm BinarySearch(target, L[0..n-1])**

// Find the index such that  $L[\text{index}] = \text{target}$   
// Input: target and list  $L[0..n-1]$   
// Output: If target is in L, return the index of the first  
// item with that value. Otherwise return -1.

```
lower ← 0
upper ← n-1
while (lower ≤ upper) do {
    mid = ⌊ (lower + upper)/2 ⌋
    if (target == L[mid])
        return mid
    if (target < L[mid])
        upper = mid - 1
    if (target > L[mid])
        lower = mid + 1
}
return -1
```

# Worst case

$$6 \log_2(n) + 4$$

$$2 + \log_2(n) (1 + 1 + 1 + 3) + 1 + 1$$

```
lower ← 0  
upper ← n-1
```

} 2 assignments

```
while (lower ≤ upper) {
```

1 comparison

```
    mid ← ⌊ (lower + upper)/2 ⌋
```

1 assignment

```
    if (target = L[mid])
```

1 comparison

```
        return mid
```

1 return

```
    if (target < L[mid])
```

```
        upper ← mid - 1
```

```
    if (target > L[mid])
```

```
        lower ← mid + 1
```

} 3 operations

```
}
```

```
return -1
```

1 return


Target not in List

at most  
 $\log_2(n)$   
times

Big O

Focus on the big picture

# Binary Search running time



$$6 \log_2(n) + 4$$

average case must  
be somewhere in the  
middle

6



$$6 \log_2(n) + 4$$

$$n = 1, 4.0 = 0.0 + 4.0$$

$$n = 2, 10.0 = 6.0 + 4.0$$

$$n = 3, 13.5 = 9.5 + 4.0$$

$$n = 5, 17.9 = 13.9 + 4.0$$

$$n = 10, 23.9 = 19.9 + 4.0$$

$$n = 100, 43.9 = 39.9 + 4.0$$

$$n = 1000, 63.8 = 59.8 + 4.0$$

$$n = 10000, 83.7 = 79.7 + 4.0$$

$$n = 100000, 103.7 = 99.7 + 4.0$$


$$n = 1000000, 123.6 = 119.6 + 4.0$$

**Ignore parts that do not contribute significantly, when the input is large**

# Big O notation


Function  **$g(n)$**  is said to be  **$O(f(n))$**  if there exist constants  **$k$**  and  **$L$**  such that:

$$g(n) < k \cdot f(n) \text{ for all } n > L$$



# Big O notation

**$g(n)$  is  $O(f(n))$**



- Intuitively:  
 $f(n)$  gives an **upper bound** to running time  $g(n)$ , which:
- ignores parts of the algorithm that do not contribute significantly to the total running time
- bounds the error made when ignoring small terms in  $g$

Big O gives us an idea of  $g(n)$ 's behaviour for **large inputs**. Simple but formal.

# Big O notation

Ignore constants

Ignore parts that do not  
contribute significantly

# Algorithm FindMin(L[0..n-1])

**Finds minimum element in a list**

**Input:** A list L[0, n-1] of real numbers

**Output:** A list sorted in ascending order.

```
min ← list[0]
k ← 0
while (k < n) do {
    if list[k] < min do {
        min ← list[k]
    }
    k ← k+1
}
return min
```

2 assignments

**In Big O best = worst**  
 **$O(n)$**


n-1 times

*If it always enters the if:*  $2 + 3(n-1) + 1 + 1 = 4 + 3(n-1)$

*If it never enters the if:*  $2 + 2(n-1) + 1 + 1 = 4 + 2(n-1)$

**This difference is unimportant, when considering the big picture**  
(we will discuss this again at the end)


# Insertion Sort running time



**Best case  $O(n)$**

**Worst case  $O(n^2)$**

# Binary Search running time











**Best case  $O(1)$**

**Worst case  $O(\log n)$**

# Basic efficiency classes

In order of increasing time complexity:

- Constant  $O(1)$  
- Logarithmic  $O(\log N)$  
- Linear  $O(N)$  
- Superlinear  $O(N \log N)$  
- Quadratic  $O(N^2)$  
- Exponential  $O(2^N)$  
- Factorial  $O(N!)$    




Constant	$O(1)$	Running time does not depend on N	N doubles, T remains constant
Logarithmic	$O(\log N)$	Problem is broken up into smaller problems and solved independently. <sup>[1]</sup> <sub>SEP</sub> Each step cuts the size by a constant factor.	If N doubles, running time T gets slightly slower
Linear	$O(N)$	Each element requires a certain (fixed) amount of processing	If N doubles, running time T doubles ( $2 \cdot T$ )
Superlinear	$O(N \log N)$	Problem is broken up in sub-problems. Each step cuts the size by a constant factor and the final solution is obtained by combining the solutions.	If N doubles, running time T gets slightly bigger than double ( $2 \cdot T$ and a bit)
Quadratic	$O(N^2)$	Processes pairs of data items. Often occurs when you have double nested loop	If N doubles, running time T increases four times ( $4 \cdot T$ )
Exponential	$O(2^N)$	Combinatorial explosion <sup>[1]</sup> <sub>SEP</sub> (think about a family tree)	If N doubles, running time T squares ( $T \cdot T$ )
Factorial	$O(N!)$	Finding all the permutations of N items	

# Growth Rates

N	log(N)	N	Nlog(N)	N <sup>2</sup>	2 <sup>N</sup>	N!
10	0.003 μs	0.01 μs	0.033 μs	0.1 μs	1 μs	3.63 ms
20	0.004 μs	0.02 μs	0.086 μs	0.4 μs	1 ms	77.1 years
30	0.005 μs	0.03 μs	0.147 μs	0.9 μs	1 sec	8.4x10 <sup>15</sup> years
40	0.005 μs	0.04 μs	0.213 μs	1.6 μs	18.3 min	
50	0.006 μs	0.05 μs	0.282 μs	2.5 μs	13 days	
100	0.007 μs	0.1 μs	0.644 μs	10 μs	4x10 <sup>13</sup> years	
1,000	0.010 μs	1 μs	9.966 μs	1 ms		
10,000	0.013 μs	10 μs	130 μs	100 ms		
100,000	0.017 μs	100 μs	1.67 ms	10 sec		
1,000,000	0.020 μs	1 ms	19.93 ms	16.7 min		
10,000,000	0.023 μs	10 ms	0.23 sec	1.16 days		
100,000,000	0.027 μs	0.1 sec	2.66 sec	115.7 days		
1,000,000,000	0.030 μs	1 sec	29.90 sec	31.7 years		

Measured in nanoseconds (10<sup>-9</sup> secs)

# Points to keep in mind

- Big-O gives an **upper bound**, which may be much larger than the actual value.
- The input that produces the **worst case may be very unlikely** to occur.
- Big-O **ignores constants**, which in practice may be very large.
- If a program is **used only a few times**, then the actual running time may not be a big factor in the overall costs.
- If a program is only **used on small inputs**, the growth rate of the running time may be less important than other factors.
- A **complicated but efficient algorithm may be less desirable** than a simpler algorithm.
- **Other criteria:** In numerical algorithms, accuracy and stability are just as important as efficiency.
- The **average case** complexity is always between the best and the worst cases.