

Table of Contents

1. Paths	1
1.1. Get PUDO list based on address	1
1.1.1. Parameters	1
1.1.2. Responses	4
1.1.3. Produces	4
1.1.4. Tags	4
1.2. Get PUDO list based on coordinates	5
1.2.1. Parameters	5
1.2.2. Responses	7
1.2.3. Produces	8
1.2.4. Tags	8
1.3. GET details of a PUDO	8
1.3.1. Parameters	8
1.3.2. Responses	8
1.3.3. Produces	9
1.3.4. Tags	9

Chapter 1. Paths

1.1. Get PUDO list based on address

```
GET /pudo/v1/open/pickup/get-pudo-by-address
```

1.1.1. Parameters

Type	Name	Description	Schema	Default
Header	X-API-Auth <i>required</i>	UUID Token Authentication	string	
Query	address <i>optional</i>	The expected informations are : - Road number - Kind of road (street, place, avenue, boulevard...) - Name of the road (des alouettes, du général de Gaulle,...) You can improve the quality of the keying by different ways: - address recovery - Keying in 3 distinct fields: house number/ type of road / name of road, with a pull-down list for the type of road. Default : none	string	
Query	category <i>optional</i>	Parcel dimension category. Available value : 1, 2 ou 3 Get in touch with the logistic department: those categories have been defined with Pickup from your product catalogues. It is important that this value is filled in reliable way as some PUDO refuse parcels that are over certain dimensions. In case of doubt, let the filed blank. This call parameter is for future use and is not functional at the date of the writing of this document Default : ALL	integer (int32)	

Type	Name	Description	Schema	Default
Query	city <i>required</i>	City You can improve the quality of the keying by different ways: - recovery - city suggestion via a dynamic pull-down list using the Zip Code	string	
Query	countryCode <i>required</i>	Research address country ISO 3166-1 alpha-3. Eg : DEU (alpha-2 is only compliant for old version)	string	
Query	date_from <i>optional</i>	Theoretical earliest delivery date at the parcel shop At minimum 24 hours, according to the shipper stock, the preparation time, the carrier cut-off and the transport time. It is important to fill in this date in order to avoid displaying PUDOs that are on vacations at the delivery/reception of the parcel. Default : Calling date+1 Min value : Calling date+1 Max value : parameter in the account	string (date-time)	
Query	destcountry code <i>optional</i>	List of the Pudos location's country codes to filter the response of the PUDO. Data separated by semicolon. Separator are considered as OR operator CountryCode needs to be found in this list again. (ISO 3166) alpha-3 = Ex : FRA;DEU;NLD;BEL Default : ALL	string	
Query	holiday_tolerant <i>optional</i>	0 = non tolerant on vacations (always take 0 if date_from is not reliable) 1 = tolerant on vacations Default : 1	integer (int32)	

Type	Name	Description	Schema	Default
Query	language <i>optional</i>	Address language wished for the display ISO 639-1 alpha-2 Norm Default: If the language requested is not possible on a PUDO Shop, the address is in the language of the PUDO Shop. The default value can be customized in the MyPudo account	string	
Query	maxDistanceSearch <i>optional</i>	Maximal distance in meters to the research of points. To be more efficient, we advise to put a value by default. Default : 40000 Min value : 100 Max value : 50000 depending on account parameter	integer (int32)	
Query	max_pudo_number <i>optional</i>	Max numbers of wished PUDOs. To be more efficient, we advise to put a value by default. Default : 10 Min value : 1 Max value : 25 depending on account parameter	integer (int32)	25
Query	pudotype <i>optional</i>	List of Pudo Type to filter. Data separated by semicolon (;). Empty field means no filter. Separator is considered as OR operator Available values are: ALL, SHOP, LOCKER Default : ALL	string	"ALL"
Query	servicePudo <i>optional</i>	List of specific services operated by the ParcelShop to filter.Data separated by semicolon. Empty field means no filter. Separator are considered as AND operator Default : ALL	string	
Query	servicePudo_display <i>optional</i>	0 = not display in the answer 1=display Default : 0	integer (int32)	

Type	Name	Description	Schema	Default
Query	weight <i>optional</i>	Weight in grams for the order In case of multi-parcel order, indicate the weight of the heaviest parcel. By default, indicate the weight of the order It is important that this value is filled in reliable way as some PUDO refuse parcels that are over a certain weight. In case of doubt, let the field blank N.B: parcels will be weighed once again by the carrier, but the carrier does not know the tolerance of the PUDOs. Default : ALL	string	
Query	zipCode <i>required</i>	Zip Code If the address is not recognized, the suggestion of the PUDOs will be done thanks to the Zip Code that is less accurate.	string	

1.1.2. Responses

HTTP Code	Description	Schema
200	OK	PUSResponse
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

1.1.3. Produces

- `application/json`

1.1.4. Tags

- OpenPickUp

1.2. Get PUDO list based on coordinates

GET /pudo/v1/open/pickup/get-pudo-by-lat-lng

1.2.1. Parameters

Type	Name	Description	Schema	Default
Header	X-API-Auth <i>required</i>	UUID Token Authentication	string	
Query	category <i>optional</i>	Parcel dimension category. Available value : 1, 2 ou 3 Get in touch with the logistic department: those categories have been defined with Pickup from your product catalogues. It is important that this value is filled in reliable way as some PUDO refuse parcels that are over certain dimensions. In case of doubt, let the filed blank. This call parameter is for future use and is not functional at the date of the writing of this document Default : ALL	integer (int32)	
Query	date_from <i>optional</i>	Theoretical earliest delivery date at the parcel shop At minimum 24 hours, according to the shipper stock, the preparation time, the carrier cut-off and the transport time. It is important to fill in this date in order to avoid displaying PUDOs that are on vacations at the delivery/reception of the parcel. Default : Calling date+1 Min value : Calling date+1 Max value : parameter in the account	string (date-time)	

Type	Name	Description	Schema	Default
Query	destcountry code <i>optional</i>	List of the Pudos location's country codes to filter the response of the PUDO. Data separated by semicolon. Separator are considered as OR operator CountryCode needs to be found in this list again. (ISO 3166) alpha-3 = Ex : FRA;DEU;NLD;BEL Default : ALL	string	
Query	holiday_tolerant <i>optional</i>	0 = non tolerant on vacations (always take 0 if date_from is not reliable) 1 = tolerant on vacations Default : 1	integer (int32)	
Query	language <i>optional</i>	Address language wished for the display ISO 639-1 alpha-2 Norm Default: If the language requested is not possible on a PUDO Shop, the address is in the language of the PUDO Shop. The default value can be customized in the MyPudo account	string	
Query	latitude <i>required</i>	Latitude, in degree decimal, conform to coordinate system WGS84-EPG4326 The Decimal separator is a dot	string	
Query	longitude <i>required</i>	Longitude, in degree decimal, conform to coordinate system WGS84-EPG4326 The Decimal separator is a dot	string	
Query	maxDistanceSearch <i>optional</i>	Maximal distance in meters to the research of points. To be more efficient, we advise to put a value by default. Default : 40000 Min value : 100 Max value : 50000 depending on account parameter	integer (int32)	

Type	Name	Description	Schema	Default
Query	max_pudo_number <i>optional</i>	Max numbers of wished PUDOs. To be more efficient, we advise to put a value by default. Default : 10 Min value : 1 Max value : 25 depending on account parameter	integer (int32)	25
Query	pudotype <i>optional</i>	List of Pudo Type to filter. Data separated by semicolon (;). Empty field means no filter. Separator is considered as OR operator Available values are: ALL, SHOP, LOCKER Default : ALL	string	"ALL"
Query	servicePudo <i>optional</i>	List of specific services operated by the ParcelShop to filter.Data separated by semicolon. Empty field means no filter. Separator are considered as AND operator Default : ALL	string	
Query	servicePudo_display <i>optional</i>	0 = not display in the answer 1=display Default : 0	integer (int32)	
Query	weight <i>optional</i>	Weight in grams for the order In case of multi-parcel order, indicate the weight of the heaviest parcel. By default, indicate the weight of the order It is important that this value is filled in reliable way as some PUDO refuse parcels that are over a certain weight. In case of doubt, let the field blank N.B: parcels will be weighed once again by the carrier, but the carrier does not know the tolerance of the PUDOs. Default : ALL	string	

1.2.2. Responses

HTTP Code	Description	Schema
200	OK	PUSResponse
401	Unauthorized	No Content
403	Forbidden	No Content
404	Not Found	No Content

1.2.3. Produces

- [application/json](#)

1.2.4. Tags

- OpenPickUp

1.3. GET details of a PUDO

GET /pudo/v1/open/pickup/get-pudo-details

1.3.1. Parameters

Type	Name	Description	Schema
Header	X-API-Auth <i>required</i>	UUID Token Authentication	string
Query	language <i>optional</i>	Address language wished for the display ISO 639-1 alpha-2 Norm	string
Query	pudoId <i>required</i>	ID of the ParcelShop	string

1.3.2. Responses

HTTP Code	Description	Schema
200	OK	PUSResponse
401	Unauthorized	No Content

HTTP Code	Description	Schema
403	Forbidden	No Content
404	Not Found	No Content

1.3.3. Produces

- `application/json`

1.3.4. Tags

- OpenPickUp