

# emptyDir Volume

# Concept



# Objectives

### Concept

a. emptyDir

### **Review Demo**

- a. Manifest file
- b. Create and display
- c. Test usecases
- d. Clean up

### Demo

### emptyDir

- Creates empty directory first created when a Pod is assigned to a Node
- Stays as long as pod is running
- Once pod is removed from a node, emptyDir is deleted forever

### Use cases:

• Temporary space.

# Review Demo

- a. Manifest file
- b. Create DaemonSet

- d. Display & Validate
- e. Clean up

### emptyDir - Config

```
# test-ed.yaml
apiVersion: v1
kind: Pod
metadata:
  name: test-ed
spec:
  containers:
  - image: k8s.gcr.io/test-webserver
    name: test-container
    volumeMounts:
    - name: cache-volume
      mountPath: /cache
  volumes:
  - name: cache-volume
    emptyDir: {}
```

### emptyDir - Create & Display

```
[srinath@master ~]$ kubectl create -f test-ed.yaml
pod/test-ed created
```

```
[srinath@master ~]$ kubectl get po
NAME READY STATUS RESTARTS AGE
test-ed 1/1 Running 0 49s
```

```
[srinath@master ~]$ kubectl exec test-ed df /cache
Filesystem 1K-blocks Used Available Use% Mounted on
/dev/sda1 10474496 5389664 5084832 52% /cache
```

### emptyDir - Describe

```
[srinath@master ~]$ kubectl describe pod test-ed
Name:
                   test-ed
                    default
Namespace:
Priority:
PriorityClassName:
                    <none>
Node:
                    node2/10.128.0.7
                    Thu, 30 Aug 2018 13:39:17 +0000
Start Time:
Labels:
                    <none>
Annotations:
                    <none>
Status:
                    Running
IP:
                    10.240.2.162
Containers:
  redis-container:
    Container ID:
                    docker://bb2c13c35729e303428e30fe4aa06e724d1b9ef78677187af41082d763aab705
                    redis
    Image:
    . . .
    Mounts:
     /cache from cache-volume (rw)
      /var/run/secrets/kubernetes.io/serviceaccount from default-token-mdxv9 (ro)
    . . .
Volumes:
  cache-volume:
    Type:
             EmptyDir (a temporary directory that shares a pod's lifetime)
```

### emptyDir – Delete

```
[srinath@master ~]$ kubectl delete po test-ed
pod "test-ed" deleted
```

# Objectives

### Concept

a. emptyDir

### **Review Demo**

- a. Manifest file
- b. Create and display
- c. Test usecases
- d. Clean up

Coming up...

Demo emptyDir