

API Specs - External

1. Ads

1.1 Create Ad

Creates a new ad.

HTTP Request

POST /api/v5/p2p/ad/create

Request Parameters

Parameter	Type	Required	Description
automatedMessage	String	No	Message that is sent to taker when an order is placed on this ad
cryptoAmount	String	Yes	The quantity of cryptocurrency
cryptoCurrency	String	Yes	The crypto currency symbol. Example: BTC
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD
isProofRequired	Boolean	No	Indicates whether a proof (e.g., bank statement) is required for CNY ads. Valid values: true, false
isPublic	Boolean	No	Indicates whether the ad is targeted for public or private marketplace. Valid values: true,false
maxOrderLimit	String	Yes	The maximum order limit. Example: 990.00
maxPaymentDurationInMinutes	String	No	The maximum time allowed for payment in minutes before timeout happens. Valid values can be fetched from the /config API from maxPaymentDurationAllowedValues field. Examples: 5,10,15,30,60,120
minAccountAge	String	No	The number of days since the user has registered (sign-up date). Valid values are: 30, 60, 180, 365

minCompletedOrders	String	No	The minimum number of completed orders by the transaction party
minCompletionRate	String	No	The minimum order completion rate of the taker. Example: 0.95
minKycLevel	String	No	The minimum identity verification level of the taker. Valid values: 1,2,3
minOrderLimit	String	Yes	The minimum order limit. Example: 890.00
minSellOrders	String	No	The minimum number of sell orders completed by the taker. Example: 5
paymentMethodIds	Array of String	No	The Ids of payment methods which maker accepts for payments. Applicable only for 'sell' ads. Example: [1234]
paymentMethods	String	No	The payment methods which maker can transact in. Applicable only for 'buy' ads. Example: bank
priceFloor	String	No	The lowest price before the user's ad is hidden. Applicable only for ads with price type as floating_market. Example: 890.00
priceMargin	String	No	The price margin ratio for floating type ads. Applicable only for ads with price type as floating_market. Example: 0.01
remark	String	No	Additional information or trading instructions for the ad for taker
side	String	Yes	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction.
targetGroup	String	Yes	User target group for the ad. Valid values: common,certified,diamond,all
type	String	Yes	Ad price type. Valid values are: limit, floating_market
unitPrice	String	Yes	The unit price in fiat currency. Applicable only for ads with price type as fixed price. Example: 1.1
verificationType	String	No	Verification type for overseas ads excluding CNY. Valid values: 0 (No verification), 1 (Verification)
verificationNotes	Array of Object	No	Notes set by the maker for Verification Ads to be shown as a prompt to the taker

> id	String	No	Verification note Id. Valid values (CNY): 1 (Provide proof that the account funds used for payment have been credited for more than X days) Valid values (Overseas): 10 (Chat before payment) 11 (No 3rd party payment) 12 (Provide payment proof) 13 (ID verification)
> constraints	Object	No	Constraints specified by the user
>> min	String	No	Min constraint value. Example: 1
>> max	String	No	Max constraint value. Example: 2
>> maxLength	String	No	Max length constraint value. Example: 10
>> isActive	Boolean	No	Specifies whether the constraint is active. Valid values: true, false
> variables	Object	No	Variables specified by the user for verification notes
>> num	String	No	Number
>> others	String	No	Miscellaneous
whitelistedCountries	Array of String	No	Regions that the taker must be from. Use ALL_COUNTRIES for including all countries. For other countries use the two-digit Id. Example: [US,UK,CA]

Response Parameters

Parameter	Type	Description
adId	String	Id of the created ad

1.2 Get Ad

Gets the ad information by ad id.

HTTP Request

GET /api/v5/p2p/ad

Request Parameters

Parameter	Type	Required	Description
adId	String	Yes	Ad id

Response Parameters

Parameter	Type	Description	
adId	String	Ad id	
automatedMessage	String	Message that is sent to taker when an order is placed on this ad	
availableAmount	String	The available crypto quantity currently available for buying and selling	
blacklistStatus	String	Blacklist status. Valid values: NO_BLACK (<i>No blacklist relationship</i>) BLACK_OTHER (<i>Current user blacklisted the other side</i>) BLACKED (<i>The other side blacklisted current user</i>) BLACK_EACH_OTHER (<i>Current user and other use blacklisted each other</i>)	
blockedReasons	Array of strings	Collection of all blocked reasons. Example: Your completion rate is less than 0.5. We encourage you to increase it	
completedOrderCryptoAmount	String	The amount of crypto that has been traded till now	
completedOrderFiatAmount	String	The amount of fiat that has been traded till now	
configuredPaymentMethodDetails	Array of objects	Collection of maker payment information	
> paymentMethod	String	Payment method	

> openStatus	String	Payment method switch state. Valid values: open close unbound	
> paymentMethodDetails	Array of objects	Collection of payment method details	
>> paymentMethodId	String	Payment method Id	
>> accountNo	String	The account number of payment method	
>> bankName	String	Bank name	
createdTimestamp	String	Creation time of the ad	
creator	Object	Ad creator details	
> id	String	User Id	
> nickName	String	Nick name of the user	
> realName	String	Real name of the user	
> type	String	User type for the ad. Valid values: common certified diamond	
> completedOrders	String	The number of orders completed by the user	
> cancelledOrders	String	The number of orders canceled by the user	
> completedSellOrders	String	The number of sell orders completed by the user	
> completionRate	String	The order completion rate of the user	
> kycLevel	String	The identity verification level of the user. Valid values: 1, 2, 3	
> acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)	
	String	Average payment time in seconds	

> avgPaymentTimeIn Seconds			
> avgCompletionTimeInSeconds	String	Average completion time in seconds	
> createdTimestamp	String	User joining timestamp in milliseconds	
> hasAlreadyTraded	Boolean	Specifies whether the user has traded in the past with the requester. Valid values: true, false	
cryptoCurrency	String	Crypto currency symbol	
cryptoScale	String	Crypto currency decimal places	
fiatCurrency	String	Fiat currency symbol	
fiatPriceIncrement	String	Fiat currency increasing unit price gradient	
fiatPriceScale	String	Decimal places reserved for fiat currency	
fiatScale	String	Fiat Currency decimal places	
hiddenCategory	String	Hidden Category. Valid values are: 1 (hide one) 0 (not hidden) 3 (out of stock)	
hiddenReason	String	All ads hidden reasons	
hiddenType	String	Order offline type. Valid values: 0 1	
isBlockTradeCategory	Boolean	Specifies whether the ad is a block trade ad (ad dealing with large amount)	
isCreatorBlockedByCurrentUser	Boolean	Specifies whether blocked by the current user	
isHidden	Boolean	Specifies whether the ad is hidden or not	
isListedOnMarketplace	Boolean	Specifies whether the ad is listed on marketplace	
isOwner	Boolean	Specifies whether the ad belongs to the user	

isPriceOutOfRange	Boolean	Specifies whether index rate deviates too much	
isProofRequired	Boolean	Specifies whether proof is required	
isSecurityLimitApplicable	Boolean	Specifies whether T+1 order	
latestUserRegisteredTimestamp	String	Transaction party user maximum registration time. Example: 1686652358497	
maxCompletedOrders	String	The maximum number of orders completed by the taker	
maxOrderSize	String	Order upper limit	
maxAvgCompleteTime	String	The maximum average completion time of the transaction parties	
maxPaymentDurationInMinutes	String	The maximum time allowed for payment in minutes before timeout happens.	
merchantId	String	Merchant Id	
minAccountAge	String	The number of days since the user has registered (sign-up date). Example: 30	
minCompletedOrders	String	The minimum number of orders completed by the taker	
minCompletionRate	String	The minimum order completion rate of the taker	
minKycLevel	String	The minimum identity verification level of the taker. Valid values: 1,2,3	
minOrderSize	String	Order lower limit	
minSellOrders	String	The minimum number of sell orders completed by the taker	
onHoldAmount	String	The quantity that has been frozen but the order has not been completed till now	
paymentMethodBasicInfoList	Array of Object	Collection of payment method basic info set by the maker. Applicable for buy ads.	
> paymentMethod	String	Payment method name	
	Boolean	Indicate whether the payment method instantly settle	

> isInstantSettlePayment			
> transferSpeed	String	Indicates the speed of the payment method. Valid values: 0 (nil): No specific speed requirement or processing time mentioned. 1 (real time): Payment is expected to be processed immediately or in real-time. 2 (instant crypto release): Payment release or confirmation is expected to be instant for cryptocurrency transactions. 3 (up to X days): Payment processing may take up to a certain number of days, where X represents the specific number of days mentioned.	
platformCommissionRate	String	Commission rate charged by the platform	
priceMargin	String	The price margin ratio for floating type ads. Applicable only for ads with price type as floating price	
realFiatMaxAmountPerOrder	String	Original order maximum amount	
remark	String	Additional information or instructions for the ad for taker	
side	String	Specifies the transaction side or direction. Valid values: buy sell	
status	String	Order status. Valid values: new canceled completed creating create_fail canceled cancel_fail	
targetGroup	String	User target group for the ad. Valid values:	

		common certified diamond all	
type	String	Ad price type. Valid values: limit floating_market	
unitPrice	String	Unit price	
unpaidOrderTimeoutInMinutes	String	Payment time in minutes	
updatedTimestamp	String	Timestamp of latest modification of ad. Example: 1686652358497	
userRegisteredIntervalInDays	String	Maximum registration interval in days	
verificationNotes	Array of Object	Notes for Verification Ads to be shown as a prompt to the taker	
>id	Integer	Verification note Id. Valid values (CNY): 1 (Provide proof that the account funds used for payment have been credited for more than X days) Valid values (Overseas): 10 (Chat before payment) 11 (No 3rd party payment) 12 (Provide payment proof) 13 (ID verification)	
>description	String	Text description of verification type	
>viewType	String	For UI display can ignore for OpenAPI	
> constraints	Object	Constraints specified by the user	
>> active	Boolean	Specifies whether the constraint is active	
>> max	Integer	Max payment account duration value	

>> min	Integer	Min payment account duration value	
>> maxLength	Integer	Max length for others constraint value	
>variables	Object	Variables specified by the user for verification notes	
>> num	Integer	Number	
>> others	String	Miscellaneous	
verificationType	String	Specifies the verification type. Applies for Overseas Ads. Valid values: 0 (no verification required) 1 (verification required)	
whitelistedCountries	String	Regions that the taker must be from, as set by the maker of the ad	

1.3 Update Ad

This operation would cancel the existing order and create a new one. If the required parameters are not passed, then we default to using the old ad values.

HTTP Request

POST /api/v5/p2p/ad/update

Request Parameters

Parameter	Type	Required	Description
adId	String	Yes	Id of the Ad which needs to be updated
online	String	No	Status of the ad: true (online), false (offline)
minOrderLimit	String	No	The minimum order limit. Example: 890.00
maxOrderLimit	String	No	The maximum order limit. Example: 990.00
type	String	No	Ad price type. Valid values are: limit, floating_market
priceMargin	String	No	The price margin ratio for floating type ads. Applicable only for ads with price type as floating price. Example: 0.01
unitPrice	String	No	The unit price in fiat currency. Applicable only for ads with price type as fixed price. Example: 1.1

cryptoAmount	String	No	The quantity of cryptocurrency
priceFloor	String	No	The lowest price before the user's ad is hidden. Example: 890.00
isPublic	Boolean	No	Indicates whether the ad is targeted for public or private marketplace. Valid values: true,false
paymentMethodIds	Array of String	No	The Ids of payment methods which maker accepts for payments. Applicable only for 'sell' ads. Example: [1234]
paymentMethods	String	No	The payment methods which maker can transact in. Applicable only for 'buy' ads. Example: bank
minCompletedOrders	String	No	The minimum number of completed orders by the taker
minKycLevel	String	No	The minimum identity verification level of the taker. Valid values: 1,2,3
minSellOrders	String	No	The minimum number of sell orders completed by the taker. Example: 5
minCompletionRate	String	No	The minimum order completion rate of the taker. Example: 0.95
minAccountAge	String	No	The number of days since the user has registered (sign-up date). Valid values are: 30, 60, 180, 365
targetGroup	String	No	User target group for the ad. Valid values: common,certified,diamond,all
maxPaymentDurationInMinutes	String	No	The maximum time allowed for payment in minutes before timeout happens. Valid values: 5,10,15,30,60,120
isProofRequired	Boolean	No	Indicates whether proof (e.g., bank statement) is required for CNY ads. Valid values: true, false
whitelistedCountries	Array of String	No	Regions that the taker must be from. Use ALL_COUNTRIES for including all countries. For other countries use the two-digit Id. Example: [US,UK,CA]
verificationType	String	No	Verification type for overseas ads excluding CNY. Example: 0 (No verification), 1 (Verification))
verificationNotes	Array of Object	No	Notes set by the maker for Verification Ads to be shown as a prompt to the taker Valid values (CNY):

			1 (Provide proof that the account funds used for payment have been credited for more than X days) Valid values (Overseas): 10 (Chat before payment) 11 (No 3rd party payment) 12 (Provide payment proof) 13 (ID verification)
> id	String	No	Verification note Id. Valid values: 1 (Provide proof that the account funds used for payment have been credited for more than X days)
> constraints	Object	No	Constraints specified by the user
>> min	String	No	Min payment account duration value. Example: 1
>> max	String	No	Max payment account duration value. Example: 2
>> maxLength	String	No	Max length constraint value. Example: 10
>> isActive	Boolean	No	Specifies whether the constraint is active. Valid values: true, false
> variables	Object	No	Variables specified by the user for verification notes
>> num	String	No	Number
>> others	String	No	Miscellaneous
remark	String	No	Additional information or trading instructions for the ad for taker
automatedMessage	String	No	Message that is sent to taker when an order is placed on this ad

Response Parameters

Parameter	Type	Description
oldAdId	String	Id of the cancelled ad
newAdId	String	Id of the newly created ad

1.4 Update Ad Active Status

Updates the ad status to be online or offline.

HTTP Request

POST /api/v5/p2p/ad/update-active-status

Request Parameters

Parameter	Type	Required	Description
adId	String	Yes	Id of the Ad for which status needs to be modified
status	String	Yes	New online status of the Ad. Valid values: hidden, show

Response Parameters

Parameter	Type	Description
adId	String	Id of the Ad for which status got modified

1.5 Cancel Ad

Cancel an ad

HTTP Request

POST /api/v5/p2p/ad/cancel

Request Parameters

Parameter	Type	Required	Description
adId	String	Yes	Id of the Ad to be canceled

Response Parameters

Parameter	Type	Description
-----------	------	-------------

adId	String	Id of the cancelled Ad
------	--------	------------------------

1.6 Get Optimal Ad Price

Get top buy top sell price

HTTP Request

GET /api/v5/p2p/ad/optimal-price

Request Parameters

Parameter	Type	Required	Description
cryptoCurrency	String	Yes	Crypto currency symbol
fiatCurrency	String	Yes	Fiat currency symbol

Response Parameters

Parameter	Type	Description
currentHighestBuyAd Price	String	Current highest buy ad price
currentLowestSellAd Price	String	Current lowest sell ad price

1.7 Get Marketplace List

Get buy and sell ad list. Return similar ads which are visible on the marketplace on app/website.

HTTP Request

GET /api/v5/p2p/ad/marketplace-list

Request Parameters

Parameter	Type	Required	Description

side	String	No	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction, or all to include both buy and sell transactions.
cryptoCurrency	String	Yes	Crypto currency symbol
fiatCurrency	String	Yes	Fiat currency symbol
targetGroup	String	No	User target group for the ad. Valid values: common,certified,diamond,all,blockTrade,flashtrade
minCryptoAmount	String	No	Minimum amount of crypto
cryptoQuota	String	No	The crypto currency limit, which is the amount of crypto currency multiplied by the unit price and the comparison of the limit of the order. Example: 5.9
minFiatAmount	String	No	Fiat currency quantity (ads with fiat amount less than this number would be filtered out)
maxFiatAmount	String	No	Fiat currency quantity (ads with fiat amount greater than this number would be filtered out)
minFiatAmountPerOrder	String	No	The minimum fiat amount required for a single order. Any ads with orders placed for an amount less than this threshold will be filtered out
maxFiatAmountPerOrder	String	No	The maximum fiat amount required for a single order. Any ads with orders placed for an amount greater than this threshold will be filtered out
paymentMethod	String	No	Payment method. Default: all. Examples: all, bank, aliPay, wxPay
isTradable	Boolean	No	Specifies whether the ad is tradable or not. Default: false
isSecurityLimitApplicable	Boolean	No	Specifies whether to show T+1 ads. Default: false
shouldShowOnlyFollow	Boolean	No	Specifies whether to fetch ads from users which the current user follows. Default: false. Valid values: true, false
showAlreadyTraded	Boolean	No	Specifies whether to fetch ads which have already been traded with the user. Default: false. Valid values: true, false
isProofRequired	Boolean	No	Specifies whether verification is required for the ads. Default: false. Valid values: true, false

hideOverseasVerificationAds	Boolean	No	Specifies whether to hide overseas verification ads. Default: false. Applies only for non-CNY regions. Valid values: true, false
limit	String	No	Maximum number of items returned
sortType	String	No	Sort type for the ads. Valid values: default,recommended,price_asc,price_desc

Response Parameters

Parameter	Type	Description
sellAds	Array of Object	Collection of sell ad details
buyAds	Array of Object	Collection of buy ad details
> adId	String	Ad Id
> minSellOrders	String	Minimum number of sell orders completed by the trading party
> side	String	Specifies the transaction side or direction. Valid values: buy,sell,block_buy,block_sell
> cryptoCurrency	String	Crypto currency symbol
> fiatCurrency	String	Fiat currency symbol
> minOrderSize	String	Order lower limit
> maxOrderSize	String	Order upper limit
> availableAmount	String	The available current quantity that can be bought/sold
> unitPrice	String	The unit price in fiat currency. Applicable only for ads with price type as fixed price. Example: 1.1
> creator	Object	Information about the ad creator.
>> hasAlreadyTraded	Boolean	Specifies whether the ad creator has already traded with the user
>> nickName	String	Nick name of the ad creator

>> userId	String	Id of the ad creator
>> cancelledOrders	String	Number of orders cancelled by the user
>> merchantId	String	Merchant Id
>> type	String	Ad creator type. Valid values: all, common (non-authenticated), certified (authenticated)
>> completedOrders	String	Total orders completed by the ad creator
>> completionRate	String	Completion rate of the ad creator
>> isBlacklistedByUser	Boolean	Specifies whether the ad creator is blocked by the user
> paymentMethods	Array of String	Collection of payment methods. Example: bank, aliPay, wxPay
> paymentMethodBasicInfoList	Array of Object	Collection of payment method basic info set by the maker. Applicable for buy ads
>> paymentMethod	String	Payment method name
>> isInstantSettlePayment	Boolean	Indicate whether the payment method instantly settle
>> transferSpeed	String	Indicates the speed of the payment method. Valid values: 0 (nil): No specific speed requirement or processing time mentioned. 1 (real time): Payment is expected to be processed immediately or in real-time. 2 (instant crypto release): Payment release or confirmation is expected to be instant for cryptocurrency transactions. 3 (up to X days): Payment processing may take up to a certain number of days, where X represents the specific number of days mentioned.
> fiatScale	String	Fiat Currency decimal places
> isOwner	Boolean	Specifies whether the ad belongs to the user
> minCompletedOrders	String	The minimum number of completed orders specified by the ad creator
> maxCompletedOrders	String	The maximum number of completed orders specified by the ad creator

> minCompletionRate	String	The minimum completion rate of the taker specified by the ad creator
> targetGroup	String	User target group for the ad. Valid values: common certified diamond all
> maxAvgCompletionTime	String	The maximum average completion time of the taker
> isSecurityLimitApplicable	Boolean	Specifies whether T+1 ad
> isProofRequired	Boolean	Indicates whether a proof (e.g., bank statement) is required for CNY ads. Valid values: true, false
> verificationType	String	Verification type for overseas ads excluding CNY. Valid values: 0 (No verification), 1 (Verification)
> fiatSymbol	String	Fiat currency symbol. Examples: ¥,\$
recommendedAd	Array of Object	Recommended ads
> userGroup	String	User group that can see ad. Valid values: 0 (new users), 1 (returning users), 2 (both)
> ad	Object	Ad details. Schema is the same as what it is for buy/sell ads

Sample Response:

```

1  {
2    "code": 0,
3    "data": [
4      {
5        "buyAds": [
6
7          {
8            "adId": "230206170034022",
9            "availableAmount": "154.00",
10           "creator": {

```

```
11      "cancelledOrders": "7",
12      "completedOrders": "200001",
13      "completionRate": "0.9999",
14      "hasAlreadyTraded": false,
15      "isBlacklistedByUser": false,
16      "merchantId": "bba0ea46b8",
17      "nickName": "1234424",
18      "type": "diamond",
19      "userId": "2460c7a78d"
20  },
21  "cryptoCurrency": "usdt",
22  "fiatCurrency": "cny",
23  "fiatScale": "2",
24  "fiatSymbol": "¥",
25  "isOwner": "false",
26  "isProofRequired": false,
27  "isSecurityLimitApplicable": false,
28  "maxAvgCompletionTime": "",
29  "maxCompletedOrders": "0",
30  "maxOrderSize": "646.00",
31  "minCompletedOrders": "0",
32  "minCompletionRate": "0.0",
33  "minKycLevel": "1",
34  "minOrderSize": "1.00",
35  "minSellOrders": "0",
36  "paymentMethodBasicInfoList": [],
37  "paymentMethods": [
38      "bank"
39  ],
40  "remark": "",
41  "side": "buy",
42  "targetGroup": "all",
43  "unitPrice": "6.4600",
44  "verificationType": "0"
45  },
46  {
47      "adId": "230208145147869",
48      "availableAmount": "29.00",
49      "creator": {
50          "cancelledOrders": "2",
51          "completedOrders": "0",
52          "completionRate": "0.0000",
53          "hasAlreadyTraded": false,
54          "isBlacklistedByUser": false,
55          "merchantId": "ceb26b15e6",
56          "nickName": "Test@1675838705282",
57          "type": "certified",
```

```
58         "userId": "e436507906"
59     },
60     "cryptoCurrency": "usdt",
61     "fiatCurrency": "cny",
62     "fiatScale": "2",
63     "fiatSymbol": "¥",
64     "isOwner": "false",
65     "isProofRequired": false,
66     "isSecurityLimitApplicable": false,
67     "maxAvgCompletionTime": "",
68     "maxCompletedOrders": "0",
69     "maxOrderSize": "187.34",
70     "minCompletedOrders": "0",
71     "minCompletionRate": "0.0",
72     "minKycLevel": "1",
73     "minOrderSize": "1.00",
74     "minSellOrders": "0",
75     "paymentMethodBasicInfoList": [],
76     "paymentMethods": [
77         "bank"
78     ],
79     "remark": "",
80     "side": "buy",
81     "targetGroup": "all",
82     "unitPrice": "6.4600",
83     "verificationType": "0"
84 }
85 ],
86 "recommendedAd": {
87     "ad": {
88         "adId": "230710173636129",
89         "availableAmount": "999999.00",
90         "creator": {
91             "cancelledOrders": "0",
92             "completedOrders": "0",
93             "completionRate": "0.0000",
94             "hasAlreadyTraded": false,
95             "isBlacklistedByUser": false,
96             "merchantId": "9a9aa9acc9",
97             "nickName": "ftt maker",
98             "type": "diamond",
99             "userId": "4f9054eaf1"
100         },
101         "cryptoCurrency": "usdt",
102         "fiatCurrency": "cny",
103         "fiatScale": "2",
104         "fiatSymbol": "¥",
```

```
105     "isOwner": "false",
106     "isProofRequired": false,
107     "isSecurityLimitApplicable": false,
108     "maxAvgCompletionTime": "",
109     "maxCompletedOrders": "0",
110     "maxOrderSize": "6999993.00",
111     "minCompletedOrders": "0",
112     "minCompletionRate": "0.0",
113     "minKycLevel": "1",
114     "minOrderSize": "1.00",
115     "minSellOrders": "0",
116     "paymentMethodBasicInfoList": [],
117     "paymentMethods": [
118         "bank"
119     ],
120     "remark": "",
121     "side": "sell",
122     "targetGroup": "all",
123     "unitPrice": "7.0000",
124     "verificationType": "0"
125 },
126 "userGroup": "0"
127 },
128 "sellAds": [
129     {
130         "adId": "230710173636129",
131         "availableAmount": "999999.00",
132         "creator": {
133             "cancelledOrders": "0",
134             "completedOrders": "0",
135             "completionRate": "0.0000",
136             "hasAlreadyTraded": false,
137             "isBlacklistedByUser": false,
138             "merchantId": "9a9aa9acc9",
139             "nickName": "ftt maker",
140             "type": "diamond",
141             "userId": "4f9054eaf1"
142         },
143         "cryptoCurrency": "usdt",
144         "fiatCurrency": "cny",
145         "fiatScale": "2",
146         "fiatSymbol": "¥",
147         "isOwner": "false",
148         "isProofRequired": false,
149         "isSecurityLimitApplicable": false,
150         "maxAvgCompletionTime": "",
151         "maxCompletedOrders": "0",
```

```

152         "maxOrderSize": "6999993.00",
153         "minCompletedOrders": "0",
154         "minCompletionRate": "0.0",
155         "minKycLevel": "1",
156         "minOrderSize": "1.00",
157         "minSellOrders": "0",
158         "paymentMethodBasicInfoList": [],
159         "paymentMethods": [
160             "bank"
161         ],
162         "remark": "",
163         "side": "sell",
164         "targetGroup": "all",
165         "unitPrice": "7.0000",
166         "verificationType": "0"
167     }
168 ]
169 }
170 ],
171 "msg": ""
172 }

```

1.8 Get Ad share info

Gets Ad sharing info with QRcode, url, ad details. This is similar to the ad share feature on web/mobile.

HTTP Request

GET /api/v5/p2p/ad/share-info

Request Parameters

Parameter	Type	Required	Description
adId	String	No	Ad id for which sharing info needs to be generated

Response Parameters

Parameter	Type	Description
adId	String	Ad id for which sharing info is generated
side	String	

		Specifies the transaction side or direction. Valid values: buy,sell,block_buy,block_sell
cryptoCurrency	String	Crypto currency symbol
fiatCurrency	String	Fiat currency symbol
cryptoDecimalPlaces	String	Crypto currency decimal places
fiatDecimalPlaces	String	Fiat currency decimal places
minOrderLimit	String	The minimum order limit. Example: 890.00
maxOrderLimit	String	The maximum order limit. Example: 990.00
unitPrice	String	The unit price in fiat currency. Applicable only for ads with price type as fixed price. Example: 1.1
fiatPriceScale	String	Decimal places reserved for fiat currency
fiatPriceIncrement	String	Fiat currency increasing unit price gradient
paymentMethods	Array of String	The payment methods which maker can transact in. Applicable only for 'buy' ads. Examples: bank,aliPay,wxPay
depositPaymentMethods	Array of Object	Collection of deposit payment methods
> paymentMethod	String	Payment method code. Example: bank
> description	String	Description of payment method
remark	String	Additional information or instructions for the ad for taker
minKycLevel	String	The minimum identity verification level of the taker. Valid values: 1,2,3
targetGroup	String	User target group for the ad. Valid values: common,certified,diamond,all
availableAmount	String	The available crypto quantity currently available for buying and selling
nickName	String	Nick name of the creator
minCompletionRate	String	The minimum order completion rate of the taker. Example: 0.95
minCompletedOrders	String	The minimum number of completed orders specified by the ad creator
	String	

maxCompletedOrders		The maximum number of completed orders specified by the ad creator
isPublic	Boolean	Indicates whether the ad is targeted for public or private marketplace. Valid values: true,false
userLevel	String	Ad creator level. Valid values: common, certified, diamond
minKycLevel	String	The minimum identity verification level of the taker. Valid values: 1,2,3

1.9 Get Active ads

Get active ads for the user. Schema is similar to Get Ad API.

HTTP Request

GET /api/v5/p2p/ad/active-list

Request Parameters

Parameter	Type	Required	Description
side	String	Yes	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction.
cryptoCurrency	String	Yes	The crypto currency symbol. Example: BTC
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD

Response Parameters

Parameter	Type	Description
adId	String	Ad id
type	String	Ad price type. Valid values: limit floating_market
side	String	Specifies the transaction side or direction. Valid values: buy

		sell
cryptoCurrency	String	Crypto currency symbol
fiatCurrency	String	Fiat currency symbol
minOrderSize	String	Order lower limit
maxOrderSize	String	Order upper limit
availableAmount	String	The available crypto quantity currently available for buying and selling
completedOrderCryptoAmount	String	The amount of crypto that has been traded till now
completedOrderFiatAmount	String	The amount of fiat that has been traded till now
onHoldAmount	String	The quantity that has been frozen but the order has not been completed till now
unitPrice	String	Unit price
priceMargin	String	The price margin ratio for floating type ads. Applicable only for ads with price type as floating price
creator	Object	Details of the ad creator
> userId	String	User Id
> nickName	String	Nick name of the user
> realName	String	Real name of the user
> type	String	User type. Valid values: common certified diamond all
> completedOrders	String	The number of orders completed by the user
> cancelledOrders	String	The number of orders canceled by the user
> completedSellOrders	String	The number of sell orders completed by the user
> completionRate	String	The order completion rate of the user

> kycLevel	String	The identity verification level of the user
> acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)
> avgPaymentTimeInSeconds	String	Average payment time in seconds
> avgCompletionTimeInSeconds	String	Average completion time in seconds
> createdTimestamp	String	User joining timestamp in milliseconds
> hasAlreadyTraded	Boolean	Specifies whether the user has traded in the past with the requester. Valid values: true, false
> paymentMethodBasicInfoList	Array of Object	Collection of payment method basic info set by the maker. Applicable for buy ads.
>> paymentMethod	String	Payment method name
>> isInstantSettlePayment	Boolean	Indicate whether the payment method instantly settle
>> transferSpeed	String	Indicates the speed of the payment method. Valid values: 0 (nil): No specific speed requirement or processing time mentioned. 1 (real time): Payment is expected to be processed immediately or in real-time. 2 (instant crypto release): Payment release or confirmation is expected to be instant for cryptocurrency transactions. 3 (up to X days): Payment processing may take up to a certain number of days, where X represents the specific number of days mentioned.
minKycLevel	String	The minimum identity verification level of the taker. Valid values: 1,2,3
remark	String	Additional information or instructions for the ad for taker
createdTimestamp	String	Creation time of the ad
isHidden	Boolean	Specifies whether the ad is hidden or not

fiatPriceScale	String	Decimal places reserved for fiat currency
fiatPriceIncrement	String	Fiat currency increasing unit price gradient
fiatScale	String	Fiat Currency decimal places
cryptoScale	String	Crypto currency decimal places
isOwner	Boolean	Specifies whether the ad belongs to the user
minCompletedOrders	String	The minimum number of orders completed by the taker
maxCompletedOrders	String	The maximum number of orders completed by the taker
minSellOrders	String	The minimum number of sell orders completed by the taker
minCompletionRate	String	The minimum order completion rate of the taker
targetGroup	String	User target group for the ad. Valid values: common certified diamond all
maxAvgCompleteTime	String	The maximum average completion time of the transaction parties
isBlockTradeCategory	Boolean	Specifies whether the ad is a block trade ad (ad dealing with large amount)
isPriceOutOfRange	Boolean	Specifies whether index rate deviates too much
maxPaymentDurationInMinutes	String	The maximum time allowed for payment in minutes before timeout happens.
status	String	Order status. Valid values: new canceled completed creating create_fail canceling cancel_fail

blacklistStatus	String	Blacklist status
merchantId	String	Merchant Id
status	String	
platformCommissionRate	String	Commission rate charged by the platform
isListedOnMarketplace	Boolean	Specifies whether the ad is listed on marketplace
unpaidOrderTimeoutInMinutes	String	Payment time in minutes
realFiatMaxAmountPerOrder	String	Original order maximum amount
isSecurityLimitApplicable	Boolean	Specifies whether T+1 order
isProofRequired	Boolean	Specifies whether proof is required
verificationType	String	Specifies the verification type. Applies for Overseas Ads. Valid values: 0 (no verification required) 1 (verification required)
verificationNotes	Array of Object	Notes for Verification Ads to be shown as a prompt to the taker
>id	Integer	Verification note Id. Valid values (CNY): 1 (Provide proof that the account funds used for payment have been credited for more than X days) Valid values (Overseas): 10 (Chat before payment) 11 (No 3rd party payment) 12 (Provide payment proof) 13 (ID verification)
>description	String	Text description of verification type

>viewType	String	For UI display can ignore for OpenAPI
> constraints	Object	Constraints specified by the user
>> active	Boolean	Specifies whether the constraint is active
>> max	Integer	Max payment account duration value
>> min	Integer	Min payment account duration value
>> maxLength	Integer	Max length for others constraint value
>variables	Object	Variables specified by the user for verification notes
>> num	Integer	Number
>> others	String	Miscellaneous
configuredPaymentMethodDetails	Array of objects	Collection of maker payment information
> paymentMethod	String	Payment method
> openStatus	String	Payment method switch state. Valid values: open close unbound
> paymentMethodDetails	Array of objects	Collection of payment method details
>> paymentMethodId	String	Payment method Id
>> accountNo	String	The account number of payment method
>> bankName	String	Bank name
minAccountAge	String	The number of days since the user has registered (sign-up date). Example: 30
hiddenType	String	Order offline type. Valid values: 0 1
updatedTimestamp	String	Timestamp of latest modification of ad. Example: 1686652358497
	String	Maximum registration interval in days

userRegisteredIntervalInDays		
latestUserRegisteredTime stamp	String	Transaction party user maximum registration time. Example: 1686652358497
whitelistedCountries	String	Regions that the taker must be from, as set by the maker of the ad
hiddenReason	String	All ads hidden reasons
hiddenCategory	String	Hidden Category. Valid values are: 1 (hide one) 0 (not hidden) 3 (out of stock)
blockedReasonList	Array of strings	Collection of all blocked reasons. Example: Your completion rate is less than 0.5. We encourage you to increase it

1.10 Get Ad Config

Gets the ad config which is used to tell valid values for ad creation.

HTTP Request

GET /api/v5/p2p/ad/config

Request Parameters

Parameter	Type	Required	Description
side	String	Yes	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction.
cryptoCurrency	String	Yes	The crypto currency symbol. Example: BTC
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD
isPublic	Boolean	No	Indicates whether the ad is targeted for public or private marketplace. Valid values: true,false

Response Parameters

Parameter	Type	Description
-----------	------	-------------

blockTradeForUserAllowed	Boolean	Specifies whether the user is eligible to place block trades. Valid values: true/false
blockTradeForFiatAllowed	Boolean	Specifies whether block trade is allowed for this fiat currency. Valid values: true/false
minBlockTradeAmount	String	Specifies the transaction side or direction. Valid values: buy sell
orderLimits	String	Crypto currency symbol
> min	String	Limit lower value. Ad min and max values should be greater than this value.
> max	String	Limit upper value. Ad min and max values should be less than this value.
optimalPrice	String	Optimal price for buy/sell ads
tradableFiatCurrencies	Array of Object	Tradable fiat currencies based on kyc level of the user
> currency	String	Fiat currency code. Examples: CNY, VND, USD
> symbol	String	Symbol of fiat currency. Examples: ¥, \$
maxPaymentMethodsAllowed	String	Maximum number of payment methods allowed. Applicable only for buy ads
maxDepositPaymentMethodsAllowed	String	Maximum number of payment methods allowed. Applicable only for sell ads
maxPaymentDurationAllowedValues	String	Provides possible values for maximum payment duration (mayPaymentDuration in create ad API)
verificationNoteOptions	Array of Object	Type of verification options that the maker can set to be shown to the taker for verification Ads. Only applicable for the CNY region for now
optimalPrices	Object	Top buy top sell price
> currentHighestBuyAdPrice	String	Current highest buy ad price
> currentLowestSellAdPrice	String	Current lowest sell ad price

2. Order

2.1 Create Order

Creates a new ad.

HTTP Request

POST /api/v5/p2p/order/create

Request Parameters

Parameter	Type	Required	Description
adId	String	Yes	Ad id for which order would be placed against
cryptoAmount	String	Yes	Crypto amount. Example: 1.1
cryptoCurrency	String	Yes	Crypto currency for the ad. Example: "BTC"
fiatCurrency	String	Yes	Fiat currency for the ad. Example: "USD"
makerPayment MethodId	String	No	Maker payment method Id
paymentMethod	String	Yes	Payment method of the counterparty. When buying crypto, it's the payment method of the maker.
totalFiatAmount	String	No	Total fiat amount for the order. Example: 100.2

Response Parameters

Parameter	Type	Description
orderId	String	Id of the created order
status	String	Order status. Valid values: 2 (new), 3 (cancelled), 4 (completed)
orderProcessStatus	String	Order process status. Valid values: 2 (new) 3 (cancelled)

	4 (completed)
	5 (creation in progress)
	6 (creation failed)
	7 (canceling)
	8 (cancellation failed)
	9 (completion in progress)
	10 (completion failed)

2.2 Get Order

Gets the order information by order id.

HTTP Request

GET /api/v5/p2p/order

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id

Response Parameters

Parameter	Type	Description
orderId	String	Order Id
side	String	Specifies the transaction side or direction. Valid values: buy, sell
isBlockTradeCategory	Boolean	Indicates whether the transaction is classified as a block trade
orderStatus	String	Order status. Valid values: new, cancelled, completed
isFrozen	Boolean	Indicates whether the order is frozen
cryptoCurrency	String	Crypto currency symbol
fiatCurrency	String	Fiat currency symbol
unitPrice	String	The unit price of the order

priceMargin	String	The price margin ratio for floating type ads. Applicable only for ads with price type as floating price
exchangeRate	String	Exchange rate
cryptoAmount	String	The amount of crypto currency traded
fiatAmount	String	The amount of fiat currency traded
paymentStatus	String	The payment status of the order. Valid values: unpaid, paid, unreceived, confirmed, rejected
createdTimestamp	String	The timestamp when the order was created
completionTimestamp	String	The timestamp when the order was completed
updatedTimestamp	String	The timestamp of the last change made to the order
completionType	String	The type of completion for the order. Example: cancelled_by_buyer
expiredInSeconds	String	The expiration time of the order in seconds
expiredAfterInSeconds	String	The expiration duration after completion in seconds
frozenType	String	The type of freeze applied to the order. Valid values: sellerRejectPaid, customerService, sellerArbitration, appealFreeze
disputeStatus	String	The dispute status of the order. Valid values: 0 (not appealed), 1 (maker appealed), 2 (taker appealed), 3 (cancelled), 4 (completed)
disputeType	String	The type of dispute
disputeSubType	String	The subtype of dispute
disputeResult	String	The result of the dispute
disputeTime	String	The time of the dispute
hasMakerBeenReminded	Boolean	Indicates whether the maker has been reminded
canRaiseDispute	Boolean	Indicates whether it is possible to raise dispute
reviewStatus	String	The review status of the order. Valid values: '1' (pending), '2' (submitted), '3' (finalised), '4' (expired)
counterpartyDetail	Object	Counterparty details
> merchantId	String	Merchant id

> takerPaymentMethod	Object	Taker collection payment method information
>> paymentMethodId	String	Payment method Id
>> bankCode	String	Bank code
>> bankName	String	Bank name
>> bankBranchName	String	Bank branch name
>> accountNo	String	Payment method number. This could be bank card number, Alipay account number, WeChat Id etc
>>paymentMethodName	String	Payment method name. It could be nick name of the user
>> paymentMethodQrCodeUrl	String	WeChat QR code, Alipay QR code
>>type	String	Payment method type. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
>> > currency	String	Fiat currency symbol. Example: CNY, USD
>> isDisabled	Boolean	Specifies whether the payment method is disabled
>>decodingUrl	String	Payment method QR code decoding URL
>>paymentDescription	String	Payment method description. Example: bank payment, WeChat, Alipay
>> adsLinkedCount	String	Number of ads linked to this payment method
>>isInstantSettlement	Boolean	Indicate whether the payment method instantly settle
> orders	String	Number of buy/sell orders that the user has completed. Example: 10
> estimatedReleaseTime	String	Estimated crypto release time
> userId	String	User Id
>nickName	String	Nick name of the user

> realName	String	Real name of the user
> type	String	User type. Valid values: common certified diamond
> completedOrders	String	The number of orders completed by the user
> cancelledOrders	String	The number of orders canceled by the user
> completedSellOrders	String	The number of sell orders completed by the user
> completionRate	String	The order completion rate of the user
> kycLevel	String	The identity verification level of the user
> acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)
> avgPaymentTimeInSeconds	String	Average payment time in seconds
> avgCompletionTimeInSeconds	String	Average completion time in seconds
> createdTimestamp	String	User joining timestamp in milliseconds
> hasAlreadyTraded	Boolean	Specifies whether the user has traded in the past with the requester. Valid values: true, false

2.3 Get Orders by Filters

Get the order list filtered by parameters. Users can get the order list for the last 6 months.

HTTP Request

GET /api/v5/p2p/order/list

Request Parameters

Parameter	Type	Required	Description

side	String	No	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction, or all to include both buy and sell transactions. Default: all
pageIndex	String	Yes	Page index starting from 1. Default: 1
pageSize	String	Yes	Number of orders to fetch. Default: 20
cryptoCurrencies	String	No	Specifies crypto currencies. Valid values are comma-separated crypto currency symbols. Example: BTC, ETH
fiatCurrencies	String	No	Specifies fiat currencies. Valid values are comma-separated fiat currency symbols. Example: CNY,USD
start	String	No	Search start timestamp. Unix timestamp format in milliseconds.
end	String	No	Search end timestamp. Unix timestamp format in milliseconds.
completionStatus	String	No	Specifies completion status category. Valid values: all - all types of order are needed pending - orders which aren't completed/cancelled completed - orders which are completed/cancelled Default: all
searchKeyword	String	No	Search orders by either Order Id or User nickname

Response Parameters

Parameter	Type	Description	
adId	String	Id of the Ad against which order was placed	
orderId	String	Order Id	
side	String	Specifies the transaction side or direction. Valid values: buy, sell	
isBlockTradeCategory	Boolean	Indicates whether the transaction is classified as a block trade	
orderStatus	String	Order status. Valid values: new, cancelled, completed	
isFrozen	Boolean	Indicates whether the order is frozen	

cryptoCurrency	String	Crypto currency symbol	
fiatCurrency	String	Fiat currency symbol	
unitPrice	String	The unit price of the order	
priceMargin	String	The price margin ratio for floating type ads. Applicable only for ads with price type as floating price	
exchangeRate	String	Exchange rate	
cryptoAmount	String	The amount of crypto currency traded	
fiatAmount	String	The amount of fiat currency traded	
paymentStatus	String	The payment status of the order. Valid values: unpaid, paid, unreceived, confirmed, rejected	
createdTimestamp	String	The timestamp when the order was created	
completedTimestamp	String	The timestamp when the order was completed	
updatedTimestamp	String	The timestamp of the last change made to the order	
completionType	String	The type of completion for the order. Example: cancelled_by_buyer	
expiredInSeconds	String	The expiration time of the order in seconds	
expiredAfterInSeconds	String	The expiration duration after completion in seconds	
frozenType	String	The type of freeze applied to the order. Valid values: sellerRejectPaid, customerService, sellerArbitration, appealFreeze	
disputeStatus	String	The dispute status of the order. Valid values: 0 (not appealed), 1 (maker appealed), 2 (taker appealed), 3 (cancelled), 4 (completed)	
disputeType	String	The type of dispute	
disputeSubType	String	The subtype of dispute	
disputeResult	String	The result of the dispute	
disputeTime	String	The time of the dispute	

hasMakerBeenReminded	Boolean	Indicates whether the maker has been reminded	
canRaiseDispute	Boolean	Indicates whether it is possible to raise dispute	
reviewStatus	String	The review status of the order. Valid values: '1' (pending), '2' (submitted), '3' (finalised), '4' (expired)	
counterpartyDetail	Object	Counterparty details	
>merchantId	String	Merchant id	
>takerPaymentMethod	Object	Taker collection payment method information	
>>paymentMethodId	String	Payment method Id	
>>bankCode	String	Bank code	
>>bankName	String	Bank name	
>>bankBranchName	String	Bank branch name	
>>paymentMethodNumber	String	Payment method number. This could be bank card number, Alipay account number, WeChat Id etc	
>>paymentMethodName	String	Payment method name. It could be nick name of the user	
>>paymentMethodQrCodeUrl	String	WeChat QR code, Alipay QR code	
>>type	String	Payment method type. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI	
>>>currency	String	Fiat currency symbol. Example: CNY, USD	
>>isDisabled	Boolean	Specifies whether the payment method is disabled	
>>decodingUrl	String	Payment method QR code decoding URL	
>>paymentDescription	String	Payment method description. Example: bank payment, WeChat, Alipay	
>>adsLinkedCount	String	Number of ads linked to this payment method	

>>isInstantSettlePayment	Boolean	Indicate whether the payment method instantly settle	
>orders	String	Number of buy/sell orders that the user has completed. Example: 10	
>estimatedReleaseTime	String	Estimated crypto release time	
>id	String	User Id	
>nickName	String	Nick name of the user	
>realName	String	Real name of the user	
>targetGroup	String	User target group for the ad. Valid values: common certified diamond all	
>completedOrders	String	The number of orders completed by the user	
>cancelledOrders	String	The number of orders canceled by the user	
>completedSellOrders	String	The number of sell orders completed by the user	
>completionRate	String	The order completion rate of the user	
>kycLevel	String	The identity verification level of the user	
>acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)	
>avgPaymentTimeInSeconds	String	Average payment time in seconds	
>avgCompletionTimeInSeconds	String	Average completion time in seconds	
>createdTimestamp	String	User joining timestamp in milliseconds	
>hasAlreadyTraded	Boolean	Specifies whether the user has traded in the past with the requester. Valid values: true, false	

2.4 Get Counterparty User Details

Obtain counterparty user information for the order.

HTTP Request

GET /api/v5/p2p/order/counterparty-user-info

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order id

Response Parameters

Parameter	Type	Description
merchantId	String	Merchant id
takerPaymentMethod	Object	Taker collection payment method information
>paymentMethodId	String	Payment method Id
>bankCode	String	Bank code
>bankName	String	Bank name
>bankBranchName	String	Bank branch name
>paymentMethodNumber	String	Payment method number. This could be bank card number, Alipay account number, WeChat Id etc
>paymentMethodName	String	Payment method name. It could be nick name of the user
>paymentMethodQRCodeUrl	String	WeChat QR code, Alipay QR code
>type	String	Payment method type. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
>currency	String	Fiat currency symbol. Example: CNY, USD

>isDisabled	String	Specifies whether the payment method is disabled
>decodingUrl	String	Payment method QR code decoding URL
>paymentDescription	String	Payment method description. Example: bank payment, WeChat, Alipay
>adsLinkedCount	String	Number of ads linked to this payment method
>isInstantSettlePayment	String	Indicate whether the payment method instantly settle
orders	String	Number of buy/sell orders that the user has completed. Example: 10
estimatedReleaseTime	String	Estimated crypto release time
userId	String	User Id
nickName	String	Nick name of the user
realName	String	Real name of the user
type	String	User type. Valid values: common certified diamond
completedOrders	String	The number of orders completed by the user
cancelledOrders	String	The number of orders canceled by the user
completedSellOrders	String	The number of sell orders completed by the user
completionRate	String	The order completion rate of the user
kycLevel	String	The identity verification level of the user
acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)
avgPaymentTimeInSeconds	String	Average payment time in seconds
avgCompletionTimeInSeconds	String	Average completion time in seconds
createdTimestamp	String	User joining timestamp in milliseconds

hasAlreadyTraded	Boolean	Specifies whether the user has traded in the past with the requester. Valid values: true, false
------------------	---------	--

2.5 Get Batch Counterparty Details for Orders

Obtain multiple counterparty user information for the orders.

HTTP Request

POST /api/v5/p2p/order/counterparty-user-list

Request Parameters

Parameter	Type	Required	Description
orderIds	String	Yes	Order Ids

Response Parameters

Parameter	Type	Description
orderId	String	Order Id
realName	Object	Actual name of the counterparty

2.6 Get Trade Summary with User

Get a list of order cancellation reasons.

HTTP Request

GET /api/v5/p2p/order/trade-info

Request Parameters

Parameter	Type	Required	Description
userId	String	Yes	Id of the user for which trade info is needed

Response Parameters

--	--	--

Parameter	Type	Description
tradeCount	String	Number of trades
tradeAmount	String	Total amount traded
side	String	Specifies the transaction side or direction.

2.7 Get Pending Order Details

Obtain pending order details for an ad.

HTTP Request

GET /api/v5/p2p/order/pending-order

Request Parameters

Parameter	Type	Required	Description
adId	String	Yes	Ad id

Response Parameters

Parameter	Type	Description
orderId	String	Order Id
side	String	Specifies the transaction side or direction. Valid values: buy, sell
isBlockTradeCategory	Boolean	Indicates whether the transaction is classified as a block trade
orderStatus	String	Order status. Valid values: new, cancelled, completed
isFrozen	Boolean	Indicates whether the order is frozen
cryptoCurrency	String	Crypto currency symbol
fiatCurrency	String	Fiat currency symbol
unitPrice	String	The unit price of the order
priceMargin	String	

		The price margin ratio for floating type ads. Applicable only for ads with price type as floating price
exchangeRate	String	Exchange rate
cryptoAmount	String	The amount of crypto currency traded
fiatAmount	String	The amount of fiat currency traded
paymentStatus	String	The payment status of the order. Valid values: unpaid, paid, unreceived, confirmed, rejected
createdTimestamp	String	The timestamp when the order was created
completionTimestamp	String	The timestamp when the order was completed
updatedTimestamp	String	The timestamp of the last change made to the order
completionType	String	The type of completion for the order. Example: cancelled_by_buyer
expiredInSeconds	String	The expiration time of the order in seconds
expiredAfterInSeconds	String	The expiration duration after completion in seconds
frozenType	String	The type of freeze applied to the order. Valid values: sellerRejectPaid, customerService, sellerArbitration, appealFreeze
disputeStatus	String	The dispute status of the order. Valid values: 0 (not appealed), 1 (maker appealed), 2 (taker appealed), 3 (cancelled), 4 (completed)
disputeType	String	The type of dispute
disputeSubType	String	The subtype of dispute
disputeResult	String	The result of the dispute
disputeTime	String	The time of the dispute
hasMakerBeenReminded	Boolean	Indicates whether the maker has been reminded
canRaiseDispute	Boolean	Indicates whether it is possible to raise dispute
reviewStatus	String	The review status of the order. Valid values: '1' (pending), '2' (submitted), '3' (finalised), '4' (expired)
counterpartyDetail	Object	Counterparty details
>merchantId	String	Merchant id
>takerPaymentMethod	Object	Taker collection payment method information

>>paymentMethodId	String	Payment method Id
>>bankCode	String	Bank code
>>bankName	String	Bank name
>>bankBranchName	String	Bank branch name
>>paymentMethodNumber	String	Payment method number. This could be bank card number, Alipay account number, WeChat Id etc
>>paymentMethodName	String	Payment method name. It could be nick name of the user
>>paymentMethodQrCodeUrl	String	WeChat QR code, Alipay QR code
>>type	String	Payment method type. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
>>>currency	String	Fiat currency symbol. Example: CNY, USD
>>isDisabled	Boolean	Specifies whether the payment method is disabled
>>decodingUrl	String	Payment method QR code decoding URL
>>paymentDescription	String	Payment method description. Example: bank payment, WeChat, Alipay
>>adsLinkedCount	String	Number of ads linked to this payment method
>>isInstantSettlePayment	String	Indicate whether the payment method instantly settle
>orders	String	Number of buy/sell orders that the user has completed. Example: 10
>estimatedReleaseTime	String	Estimated crypto release time
>userId	String	User Id
>nickName	String	Nick name of the user
>realName	String	Real name of the user
>targetGroup	String	User target group for the ad. Valid values: common certified diamond

		all
>completedOrders	String	The number of orders completed by the user
>cancelledOrders	String	The number of orders canceled by the user
>completedSellOrders	String	The number of sell orders completed by the user
>completionRate	String	The order completion rate of the user
>kycLevel	String	The identity verification level of the user
>acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)
>avgPaymentTimeInSeconds	String	Average payment time in seconds
>avgCompletionTimeInSeconds	String	Average completion time in seconds
>createdTimestamp	String	User joining timestamp in milliseconds
>hasAlreadyTraded	Boolean	Specifies whether the user has traded in the past with the requester. Valid values: true, false

2.8 Mark Order as Paid

Lets buyer mark the order as paid.

HTTP Request

POST /api/v5/p2p/order/mark-as-paid

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Id of the order for which payment is made
paymentProofFileUrls	String	No	Collections of payment proof file url
makerPaymentMethodId	String	No	Maker payment method id
rrnCode	String	No	Retrieval Reference Number

Response Parameters

Parameter	Type	Description
orderId	String	Id of the order for which payment is made

2.9 Cancel Order

Cancels the order. Buyers cancel pending, unpaid, paid, or rejected orders, and sellers cancel pending orders

HTTP Request

POST /api/v5/p2p/order/cancel

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Id of the Order to be canceled
verificationType	String	Yes	Valid values: 1, 2 Use 2 currently
amount	String	No	Amount for which the order was placed. Example: 1.2

Response Parameters

Parameter	Type	Description
orderId	String	Id of the order which got cancelled

2.10 Mark Order as Unpaid

Lets seller mark the order as unpaid.

HTTP Request

POST /api/v5/p2p/order/mark-as-unpaid

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Id of the order for which payment should be marked as unpaid

Response Parameters

Parameter	Type	Description
orderId	String	Id of the order for which payment is marked as unpaid

2.11 Release Crypto

Seller can release the crypto upon confirming the payment.

HTTP Request

POST /api/v5/p2p/order/release-crypto

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Id of the order for which crypto should be released
paymentProofFileUrls	String	No	Collections of payment proof file url
verificationType	String	Yes	Valid values: 1, 2 Use 2 currently
amount	String	No	Amount received from the buyer. Example: 1.2

Response Parameters

Parameter	Type	Description
-----------	------	-------------

orderId	String	Id of the order for which crypto is released
---------	--------	--

2.12 Get Cancellation Reasons

Get a list of order cancellation reasons.

HTTP Request

GET /api/v5/p2p/order/cancel-reason-list

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id

Request Parameters

Parameter	Type	Description
reasonId	String	Reason Id
reason	String	Cancellation reason
subReasons	Array of Object	Sub reasons
>reasonId	String	Sub-reason Id
>reason	String	Cancellation sub-reason

2.13 Get Unreleased Orders

Get order ids that haven't been processed for a long time.

HTTP Request

GET /api/v5/p2p/order/unreleased-orders

Response Parameters

Parameter	Type	Description
-----------	------	-------------

orderIds	Array of String	Unreleased order Ids
waitingTimeInMinutes	String	Waiting time in minutes

3. Payment Method

3.1 Add Payment Method

Adds a new payment method.

HTTP Request

GET /api/v5/p2p/payment-method/add

Request Parameters

Parameter	Type	Required	Description
currency	String	Yes	Fiat currency symbol. Examples: CNY, VND
type	String	Yes	Type of payment method. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
isEnabled	Boolean	Yes	Specifies whether payment method should be enabled. Valid values: true, false
applicationType	String	Yes	Type of application. Valid values: -1: (Disabled) 0 (Enabled), 1 (Deposit payment method, used for receiving payment), 2 (Withdrawal Payment method, used for paying)
details	Object	Yes	Key-value pairs of fields required for adding payment method where key is field name and value is field value. Example: {"accountNo": "1234"}

Response Parameters

Parameter	Type	Description
paymentMethodId	String	Id of the added Payment method

3.2 Get Payment Method

Get payment method info.

HTTP Request

GET /api/v5/p2p/payment-method

Request Parameters

Parameter	Type	Required	Description
paymentMethodId	String	Yes	Payment method id

Response Parameters

Parameter	Type	Description
paymentMethodId	String	Payment method Id
bankCode	String	Bank code
bankName	String	Bank name
bankBranchName	String	Bank branch name
paymentMethodNumber	String	Payment method number. This could be bank card number, Alipay account number, WeChat Id etc
paymentMethodName	String	Payment method name. It could be nick name of the user
paymentMethodQrCodeUrl	String	WeChat QR code, Alipay QR code
type	String	

		Payment method type. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
currency	String	Fiat currency symbol. Example: CNY, USD
isDisabled	Boolean	Specifies whether the payment method is disabled
decodingUrl	String	Payment method QR code decoding URL
paymentDescription	String	Payment method description. Example: bank payment, WeChat, Alipay
adsLinkedCount	String	Number of ads linked to this payment method
isInstantSettlePayment	Boolean	Indicate whether the payment method instantly settle

3.3 Get Payment Methods

Get all payment methods.

HTTP Request

GET /api/v5/p2p/payment-method/list

Response Parameters

Parameter	Type	Description
paymentMethodId	String	Payment method Id
bankCode	String	Bank code
bankName	String	Bank name
bankBranchName	String	Bank branch name
paymentMethodN	String	Payment method number. This could be bank card number, Alipay account number, WeChat Id etc

number		
paymentMethodName	String	Payment method name. It could be nick name of the user
paymentMethodQrCodeUrl	String	WeChat QR code, Alipay QR code
type	String	Payment method type. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
currency	String	Fiat currency symbol. Example: CNY, USD
isDisabled	Boolean	Specifies whether the payment method is disabled
decodingUrl	String	Payment method QR code decoding URL
paymentDescription	String	Payment method description. Example: bank payment, WeChat, Alipay
adsLinkedCount	String	Number of ads linked to this payment method
isInstantSettlePayment	Boolean	Indicate whether the payment method instantly settle

3.4 Update Payment Method

Update the payment method.

HTTP Request

POST /api/v5/p2p/payment-method/update

Request Parameters

Parameter	Type	Required	Description
paymentMethodId	String	Yes	Id of the Payment Method which needs to be updated

currency	String	Yes	Fiat currency symbol. Examples: CNY, VND
type	String	Yes	Type of payment method. Examples: BANK, ALIPAY, WXPAY, WESTERN_UNION, PAY_PAL, SWIFT, PAY_NOW, PAYTM, QIWI
isEnabled	Boolean	Yes	Specifies whether payment method should be enabled. Valid values: true, false
application Type	String	Yes	Type of application. Valid values: -1: (Disabled) 0 (Enabled), 1 (Deposit payment method, used for receiving payment), 2 (Withdrawal Payment method, used for paying)
details	Object	Yes	Key-value pairs of fields required for adding payment method where key is field name and value is field value. Example: {"accountNo": "1234"}

Response Parameters

Parameter	Type	Description
payment MethodId	String	Id of the updated Payment method

3.5 Delete Payment Method

Delete the payment method.

HTTP Request

GET /api/v5/p2p/payment-method/delete

Request Parameters

Parameter	Type	Required	Description
paymentMethodId	String	Yes	Id of the Payment Method which needs to be deleted

Response Parameters

Parameter	Type	Description
-----------	------	-------------

paymentMethodId	String	Id of the Payment Method which got deleted
-----------------	--------	--

3.6 Update Payment Method Status

Delete the payment method.

HTTP Request

GET /api/v5/p2p/payment-method/update-status

Request Parameters

Parameter	Type	Required	Description
paymentMethodId	String	Yes	Payment Method Id for which status needs to be updated
disable	Boolean	Yes	Specifies whether to disable the payment method

Response Parameters

Parameter	Type	Description
paymentMethodId	String	Id of the Payment Method for which status got updated

3.7 Get Supported Payment Methods

Get all payment methods which are supported by the currencies specified.

HTTP Request

GET /api/v5/p2p/payment-method/supported-list

Request Parameters

Parameter	Type	Required	Description
currencies	String	Yes	Fiat currencies for which supported payment methods are needed. Valid values are comma-separated fiat currency symbols. Example:

CNY,USD

Response Parameters

Parameter	Type	Description
paymentMethod	String	Payment method
icon	String	Icon for the payment method
applicationType	String	Type of application. Valid values: -1: (Disabled) 0 (Enabled), 1 (Deposit payment method, used for receiving payment), 2 (Withdrawal Payment method, used for paying)
currency	String	Fiat currency symbol

4. P2P Ticker

4.1 Get Swap Price

Get Swap Price.

HTTP Request

GET /api/v5/p2p/p2p-ticker/swap

Request Parameters

Parameter	Type	Required	Description
cryptoCurrency	String	Yes	The crypto currency symbol. Example: BTC
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD
usdtAmount	String	Yes	Amount of USDT

Response Parameters

	Type	Description
--	------	-------------

Parameter		
price	String	Price
swapFiatId	String	Swap fiat Id
swapAmount	String	Exchange amount
swapFiatScale	String	Conversion quantity accuracy
fiatSymbol	String	Fiat currency symbol. Examples: ¥,\$

4.2 Get All Crypto prices

Get all crypto prices for a fiat currency.

HTTP Request

GET /api/v5/p2p/p2p-ticker/all

Request Parameters

Parameter	Type	Required	Description
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD

Response Parameters

Parameter	Type	Description
prices	String	Mapping of Crypto currency symbol to price. Example: BTC -> 0.01

4.3 Get Platform ticker price

Get the price for the currency pair.

HTTP Request

GET /api/v5/p2p/p2p-ticker/platform-ticker

Request Parameters

Parameter	Type	Required	Description
price	String	Yes	Price

Response Parameters

Parameter	Type	Description
price	String	Price for the currency pair

4.4 Get Estimated price

Get estimated trading price for the currency pair.

HTTP Request

GET /api/v5/p2p/p2p-ticker/estimated-price

Request Parameters

Parameter	Type	Required	Description
cryptoCurrency	String	Yes	The crypto currency symbol. Example: BTC
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD
side	String	No	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction.
depositName	String	No	Deposit name. Example: 'OKEX P2P'
paymentMethod	String	No	Payment method. Example: bank

Response Parameters

Parameter	Type	Description
price	String	Price for the currency pair

5. User

5.1 Get Basic Information

Gets the basic information for the user.

HTTP Request

GET /api/v5/p2p/user/basic-info

Response Parameters

Parameter	Type	Description
userId	String	User Id
nickName	String	Nick name of the user
realName	String	Real name of the user
phoneNumber	String	Phone number of the user
email	String	Email of the user
type	String	User type. Valid values: common certified diamond
completedOrders	String	The number of orders completed by the user
completedSellOrders	String	The number of sell orders completed by the user
cancelledOrders	String	The number of orders canceled by the user
completionRate	String	The order completion rate of the user
kycLevel	String	The identity verification level of the user. Valid values: 1, 2, 3

acceptStatus	String	Order acceptance status of the user. Valid values: 0 (do not accept order), 1 (accept order)
avgPaymentTimeInSeconds	String	Average payment time in seconds
avgCompletionTimeInSeconds	String	Average completion time in seconds
createdTimestamp	String	User joining timestamp in milliseconds

5.2 Get Id for UID

Get P2P user Id by UID (visible on Web/Mobile).

HTTP Request

GET /api/v5/p2p/user/id

Request Parameters

Parameter	Type	Required	Description
uid	String	Yes	UID of the user

Response Parameters

Parameter	Type	Description
userId	String	User Id of the user

5.3 Get Balance

Get balance for the user.

HTTP Request

GET /api/v5/p2p/user/balance

Request Parameters

Parameter	Type	Required	Description
-----------	------	----------	-------------

currencySymbol	String	Yes	Currency symbol. Example: BTC
----------------	--------	-----	-------------------------------

Response Parameters

Parameter	Type	Description
availableAmount	String	The available crypto quantity currently available for buying and selling
onHoldAmount	String	The quantity that has been frozen but the order has not been completed till now
sellOrTransferLimit	String	Sell or transfer limit
currencySymbol	String	Currency symbol. Example: BTC
isSecurityLimitApplicable	Boolean	Specifies whether the ad is T+1 ad

5.4 Get Blacklist Users

Get details of blacklisted users.

HTTP Request

GET /api/v5/p2p/user/blacklist-users

Request Parameters

Parameter	Type	Required	Description
currencySymbol	String	Yes	Currency symbol. Example: BTC

Response Parameters

Parameter	Type	Description
userName	String	User name
createdTimestamp	String	Timestamp of the blacklisted action. Unix timestamp format in milliseconds

buyerAvgPaidTime	String	The buyer average payment time in minutes
sellerAvgCompletedTime	String	The seller's average release time in minutes
userType	String	User type. Valid values: common,certified,diamond
completionRate	String	Completion rate
orders	String	Number of total order. Includes completed and cancelled orders
userId	String	User Id

5.5 Add Blacklist User

Add user to the blacklist.

HTTP Request

POST /api/v5/p2p/user/add-user-to-blacklist

Request Parameters

Parameter	Type	Required	Description
userId	String	Yes	Id of the user who needs to be blacklisted
reasons	String	No	Reasons for blacklisting. Comma separated reasons can be provided
otherReason	String	No	Any other reason for blocking
orderId	String	No	Order Id

Response Parameters

Parameter	Type	Description
userId	String	Id of the user who got blacklisted

5.6 Remove User from Blacklist

Add user to the blacklist.

HTTP Request

POST /api/v5/p2p/user/remove-user-from-blacklist

Request Parameters

Parameter	Type	Required	Description
userId	String	Yes	Id of the user who needs to be removed from the blacklist

Response Parameters

Parameter	Type	Description
userId	String	Id of the user who got removed from the blacklist

5.7 Get User statistics

Get current user badge related information.

HTTP Request

GET /api/v5/p2p/user/statistics

Response Parameters

Parameter	Type	Description
newOrders	String	Number of Orders in progress
newAds	String	Number of ads in progress
appealOrders	String	Number of orders in appeal
completedAppealOrders	String	Number of completed orders with appeal
cancelledAppealOrders	String	Number of cancelled orders with appeal
waitPaidOrders	String	Number of orders pending payment
waitReleaseOrder	String	Number of to-be-released orders
cancelledOrders	String	Number of orders canceled by the user
completedOrders	String	Number of orders the user has completed

pendingActions	String	Number of user's pending actions
----------------	--------	----------------------------------

5.8 Update Online Status

Updates user online status. If the user chooses to be offline, no ad can be placed against the ads created by the user.

HTTP Request

POST /api/v5/p2p/user/update-online-status

Request Parameters

Parameter	Type	Required	Description
status	String	Yes	User online status. Valid values: hidden (makes user offline), show (makes user online)

Response Parameters

Parameter	Type	Description
status	String	Updated online status

6. Merchant

6.1 Get Basic Information

Gets the basic information of the merchant.

HTTP Request

GET /api/v5/p2p/merchant/basic-info

Response Parameters

Parameter	Type	Description
nickname	String	Nick name of the user
avatarImage	String	User image URL
description	String	Description of the merchant

status	String	Status of the merchant. Valid values: 0 (under review), 1 (passed review), -1 (rejected)
remark	String	Remark

6.2 Get Merchant info by share code

Get shared information by sharing code.

HTTP Request

GET /api/v5/p2p/merchant/share-info

Request Parameters

Parameter	Type	Required	Description
shareCode	String	Yes	Share Code

Response Parameters

Parameter	Type	Description
realName	String	Real name of the user
userId	String	Id of the user
completedOrders	String	Number of orders completed by the user
completionRate	String	Completion rate
isSelf	Boolean	Specifies whether the user is the requester

6.3 Get sharable basic info

Gets the basic information of the merchant along with the QR code which can be shared.

HTTP Request

GET /api/v5/p2p/merchant/share-profile

Response Parameters

Parameter	Type	Description
merchantId	String	Id of the Merchant
avatarImage	String	User image URL
totalOrders	String	Total orders
tradedUsers	String	Number of people merchant traded with
currencyPairs	Array of Object	Collection of currencies the merchant traded in.
> cryptoCurrency	String	The crypto currency symbol. Example: BTC
> fiatCurrency	String	The fiat currency symbol. Example: USD
qrCode	String	Share link
password	String	Share password

6.4 Get Profile Information

Get merchant's profile (from the merchant himself/herself, or from others).

HTTP Request

GET /api/v5/p2p/merchant/profile

Request Parameters

Parameter	Type	Required	Description
userId	String	No	Id of the user for which information is required

Response Parameters

Parameter	Type	Description
merchantId	String	Id of the Merchant
avatarImage	String	User image URL
auditStatus	String	Audit status. Valid values: -1 (audit failed), 0 (audit in progress), 1 (audit passed), 2 (initialization completed, after N hours of audit passed, the status changes to this status)

completedBuyOrders	String	Total completed buy orders
tradedUsers	String	Number of people merchant traded with
merchantInfo30DayOrderInfo	Array of Object	30 day order info
> completedOrders30Day	String	30 day completed orders count
> servedUsersCompletedOrders30Day	String	The number of users served for completed orders within 30 days
> completionRate30Day	String	30 day completion rate
> completionRateBuyOrders30Day	String	30 day completion rate for buy orders
> completionRateSellOrders30Day	String	30 day completion rate for sell orders
positiveReviews	String	Number of positive reviews
negativeReviews	String	Number of negative reviews
positiveReviewPercentage	String	Positive review percentage
totalReviews	String	Number of reviews given for the user
commonOrderTotal	String	The total transaction amount of the current site within half a year (usd)
blacklistUserCount	String	Number of times the user has been blocked
followerCount	String	Followers count
isDisabled	Boolean	Specifies whether the account is frozen
countryId	String	KYC country
merchantRegisteredTimestamp	String	Merchant registration timestamp. Unix timestamp format in milliseconds

countryName	String	Country name
countryIcon	String	Country flag
isKycVerified	Boolean	Specifies whether the merchant is KYC verified
isPhoneVerified	Boolean	Specifies whether the user has completed phone verification
isEmailVerified	Boolean	Specifies whether the user has completed email verification
blacklistStatus	String	Blacklist status of the user. Valid values: NO_BLACK (No blacklist relationship), BLACK_OTHER (Current user blacklisted the other side), BLACKED (The other side blacklisted current user), BLACK_EACH_OTHER (Current user and other use blacklisted each other)
isFollowingUser	Boolean	Specifies whether the requester follows the user
isSelf	Boolean	Specifies whether the requester is the user itself
depositAmount	String	Merchant's deposit amount
depositCurrency	String	Merchant's deposit currency

6.5 Get Merchant Ads

Get merchant's add list (not for merchant himself/herself).

HTTP Request

GET /api/v5/p2p/merchant/ads

Request Parameters

Parameter	Type	Required	Description
userId	String	Yes	Id of the user for which ads are required

Response Parameters

Parameter	Type	Description
sellAds	String	Collection of sell ads. Schema is same as that of buy ads.
buyAds	String	Collection of buy ads.

> adId	String	Ad id
> type	String	Ad price type. Valid values: limit floating_market
> side	String	Specifies the transaction side or direction. Valid values: buy sell
> cryptoCurrency	String	Crypto currency symbol
> fiatCurrency	String	Fiat currency symbol
> minOrderSize	String	Order lower limit
> maxOrderSize	String	Order upper limit
> availableAmount	String	The available crypto quantity currently available for buying and selling
> unitPrice	String	Unit price
> priceMargin	String	The price margin ratio for floating type ads. Applicable only for ads with price type as floating price
> minKycLevel	String	The minimum identity verification level of the taker. Valid values: 1,2,3
> remark	String	Additional information or instructions for the ad for taker
> createdTimestamp	String	Creation time of the ad
> isHidden	Boolean	Specifies whether the ad is hidden or not
> fiatPriceScale	String	Decimal places reserved for fiat currency
> fiatPriceIncrement	String	Fiat currency increasing unit price gradient
> fiatScale	String	Fiat Currency decimal places
> cryptoScale	String	Crypto currency decimal places
> minCompletedOrders	String	The minimum number of orders completed by the taker
> maxCompletedOrders	String	The maximum number of orders completed by the taker
> minSellOrders	String	The minimum number of sell orders completed by the taker

> minCompletionRate	String	The minimum order completion rate of the taker
> maxPaymentDurationInMinutes	String	The maximum time allowed for payment in minutes before timeout happens.
> targetGroup	String	User target group for the ad. Valid values: common certified diamond all
> isSecurityLimitApplicable	Boolean	Specifies whether T+1 order
> isProofRequired	Boolean	Specifies whether proof is required
> verificationType	String	Specifies the verification type. Applies for Overseas Ads. Valid values: 0 (no verification required) 1 (verification required)
paymentMethods	String	Collection of payment methods. Example: bank, aliPay, wxPay
fiatSymbol	String	Fiat symbol. Examples: ¥,\$

6.6 Get Followings

Gets the following list for the merchant.

HTTP Request

GET /api/v5/p2p/merchant/followings

Request Parameters

Parameter	Type	Required	Description
pageIndex	String	Yes	Current page index. Index starts from 1. Default value: 1
pageLength	String	Yes	Size of each page. Default value: 20

Response Parameters

Parameter	Type	Description
userId	String	Current page index. Index starts from 1. Default value: 1
merchantId	String	Size of each page. Default value: 20
nickname	String	Nick name of the merchant
realName	String	Real name of the merchant
avatarImage	String	Avatar image URL
registeredTimestamp	String	Registration timestamp. Unix timestamp format in milliseconds
userType	String	Type of the user. Valid values: common, certified, diamond
kycLevel	String	The identity verification level of the user. Valid values: 1, 2, 3
hasAlreadyTraded	Boolean	Specifies whether requester has traded with the following merchant
hasOnlineAd	Boolean	Specifies whether the merchant has online ad

6.7 Update following status

Follow/unfollow a user.

HTTP Request

POST /api/v5/p2p/merchant/update-following-status

Request Parameters

Parameter	Type	Required	Description
userId	String	Yes	Id of the user who should be followed/unfollowed
shouldFollow	Boolean	Yes	Specifies whether to follow the user. Valid values: true (to follow), false (un-follow)

Response Parameters

Parameter	Type	Description

userId	String	Id of the user who was followed/unfollowed
--------	--------	--

6.8 Update Basic Information

Update merchant's basic information.

HTTP Request

POST /api/v5/p2p/merchant/update-basic-info

Request Parameters

Parameter	Type	Required	Description
avatarImage	String	Yes	Merchant image URL
description	String	Yes	Description of the merchant

7. Currency

7.1 Get Fiat Currencies

Retrieve supported Fiat Currencies for P2P.

HTTP Request

GET /api/v5/p2p/currency/fiat-currency-list

Response Parameters

Parameter	Type	Description
currency	String	The fiat symbol. Example: USD
name	String	Full name of currency
symbol	String	Fiat currency symbol. Examples: ¥,\$
countryIcon	String	Country Icon
isBlockTradeSupported	Boolean	Specifies whether block trade is supported

7.3 Get Currency Pair information

Retrieve supported Crypto currency pairs for a P2P fiat market.

HTTP Request

GET /api/v5/p2p/currency/currency-pair-list

Request Parameters

Parameter	Type	Required	Description
fiatCurrency	String	Yes	The fiat currency symbol. Example: USD

Response Parameters

Parameter	Type	Description
cryptoCurrency	String	The crypto currency symbol. Example: BTC
fiatCurrency	String	The fiat currency symbol. Example: USD
cryptoSymbol	String	Crypto currency symbol
fiatName	String	Full name of fiat currency
fiatSymbol	String	Fiat currency symbol. Examples: ¥,\$
fiatPriceScale	String	Decimal places reserved for fiat currency
fiatPriceIncrement	String	Fiat currency increasing unit price gradient
fiatScale	String	Fiat Currency decimal places
cryptoScale	String	Crypto currency decimal places
cryptoName	String	Full name of crypto currency
countryIcon	String	Country icon

8. Dispute

8.1 Get Dispute Types

Get available dispute types based on order.

HTTP Request

GET /api/v5/p2p/dispute/types

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id
side	String	No	Specifies the transaction side or direction. Use buy to indicate a buy transaction, sell for a sell transaction.

Response Parameters

Parameter	Type	Description
disputeId	String	Dispute id
subReason	String	Dispute subreason
code	String	Dispute code
hasSubType	Boolean	Specifies whether the dispute has sub-type
subType	String	Collections of sub-types if dispute has any
suggestions	Array of Object	Collection of suggestions. Schema is the same as the original object.
> suggestText	String	Main suggestion message
> children	Array of String	Sub-points for each suggestion
videoSuggestion	String	Video proof request suggestion message
imageSuggestion	String	Image proof request suggestion message
isImageSubmissionNeeded	Boolean	Indicates if the user needs to submit an image
isRemarkSubmissionNeeded	Boolean	Indicates if the user needs to submit a remark
isVideoSubmissionNeeded	Boolean	Indicates if the user needs to submit video

Sample response:

```
1  {
2    "code": 0,
3    "data": [
4      {
5        "sell": [
6          {
7            "code": "14",
8            "disputeId": "SX14",
9            "hasSubType": true,
10           "imageSuggestion": "",
11           "isImageSubmissionNeeded": false,
12           "isRemarkSubmissionNeeded": true,
13           "isVideoSubmissionNeeded": true,
14           "subReason": "I received the payment but the order is
canceled",
15           "subType": [
16             {
17               "code": "2",
18               "disputeId": "SX1402",
19               "hasSubType": false,
20               "imageSuggestion": "",
21               "isImageSubmissionNeeded": false,
22               "isRemarkSubmissionNeeded": true,
23               "isVideoSubmissionNeeded": true,
24               "subReason": "Transfer the crypto to the buyer",
25               "subType": [],
26               "suggestions": [
27                 {
28                   "children": [],
29                   "suggestText": "Try reaching out to the
other party to see if you can resolve the issue\n"
30                 },
31                 {
32                   "children": [],
33                   "suggestText": "Raise a dispute if you're
unable to resolve it."
34                 }
35               ],
36               "videoSuggestion": ""
37             },
38             {
39               "code": "3",
40               "disputeId": "SX1403",
41               "hasSubType": false,
```

```

42         "imageSuggestion": "",
43         "isImageSubmissionNeeded": false,
44         "isRemarkSubmissionNeeded": true,
45         "isVideoSubmissionNeeded": true,
46         "subReason": "Customer Support to get account
information for refund",
47         "subType": [],
48         "suggestions": [
49             {
50                 "children": [],
51                 "suggestText": "Try reaching out to the
other party to see if you can resolve the issue\n"
52             },
53             {
54                 "children": [],
55                 "suggestText": "Raise a dispute if you're
unable to resolve it."
56             }
57         ],
58         "videoSuggestion": ""
59     }
60 ],
61     "suggestions": [
62         {
63             "children": [],
64             "suggestText": "Try reaching out to the other
party to see if you can resolve the issue\n"
65         },
66         {
67             "children": [],
68             "suggestText": "Raise a dispute if you're unable
to resolve it."
69         }
70     ],
71     "videoSuggestion": ""
72 }
73 ],
74     "buy": [
75         {
76             "code": "10",
77             "disputeId": "BX10",
78             "hasSubType": true,
79             "imageSuggestion": "",
80             "isImageSubmissionNeeded": false,
81             "isRemarkSubmissionNeeded": true,
82             "isVideoSubmissionNeeded": true,
83             "subReason": "I have paid but order is canceled",

```

```

84         "subType": [
85             {
86                 "code": "1",
87                 "disputeId": "BX1001",
88                 "hasSubType": false,
89                 "imageSuggestion": "",
90                 "isImageSubmissionNeeded": false,
91                 "isRemarkSubmissionNeeded": true,
92                 "isVideoSubmissionNeeded": true,
93                 "subReason": "I can't contact the counterparty",
94                 "subType": [],
95                 "suggestions": [
96                     {
97                         "children": [],
98                         "suggestText": "If you have made the
payment but did not mark the order as paid, the seller has the obligation to
refund you or accept your new order. Refund fee asked by the seller is at
your own cost.\n"
99                     },
100                     {
101                         "children": [],
102                         "suggestText": "You can send ^the payment
proof^ and reach a mutual agreement with the seller using our chat."
103                     },
104                     {
105                         "children": [],
106                         "suggestText": "If you can't reach the
buyer, you can continue your dispute submission to our Customer Support."
107                     }
108                 ],
109                 "videoSuggestion": "If you have already made
payment for the order, please send us video proofs that contain the following
information:\n\n1. Your bank account or payment platform used for the
order.\n\n2. Your name and bank account number.\n\n3. The transaction date
and the order amount.\n\n4. The P2P order page on the app (not on a separate
bank statement).\n\n5. The seller's bank account number or email ID used for
the order."
110             },
111         ],
112         "suggestions": [
113             {
114                 "children": [],
115                 "suggestText": "If you have made the payment but
did not mark the order as paid, the seller has the obligation to refund you
or accept your new order. Refund fee asked by the seller is at your own
cost.\n"
116             },

```

```

117         {
118             "children": [],
119             "suggestText": "You can send ^the payment proof^
and reach a mutual agreement with the seller using our chat."
120         },
121         {
122             "children": [],
123             "suggestText": "If you can't reach the buyer, you
can continue your dispute submission to our Customer Support."
124         }
125     ],
126     "videoSuggestion": "If you have already made payment for
the order, please send us video proofs that contain the following
information:\n\n1. Your bank account or payment platform used for the
order.\n\n2. Your name and bank account number.\n\n3. The transaction date
and the order amount.\n\n4. The P2P order page on the app (not on a separate
bank statement).\n\n5. The seller's bank account number or email ID used for
the order."
127     }
128 ],
129     "appealUrge": []
130 }
131 ],
132     "msg": ""
133 }

```

8.2 Create Dispute

Creates dispute for an order.

HTTP Request

POST /api/v5/p2p/dispute/create

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id for which dispute should be created
disputeType	String	Yes	Type of dispute

subDisputeType	String	No	Type of sub-dispute
messageText	String	No	Remark, necessary when dispute type is others
imageUrls	Array of String	No	Image proof urls
videoUrls	Array of String	No	Video proof urls
disputeTypeUid	String	No	Dispute type UID

Response Parameters

Parameter	Type	Description
disputeId	String	Id of the created dispute

8.3 Get Dispute Details

Get dispute details including messages.

HTTP Request

GET /api/v5/p2p/dispute/dispute-details

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Id of the order for which dispute information is needed

Response Parameters

Parameter	Type	Description
disputerSide	String	Specifies disputer side. Valid values: 0 (buyer), 1 (seller)
isDisputer	String	Specifies whether the current user is the disputer. Valid values: true, false

disputeReason	String	Reason for the dispute
disputeSubReason	String	Sub-reason for the dispute
userLastReadTimestamp	String	Last read timestamp of the user
messages	Array of Object	Collections of message details
> message	String	Message text
> sender	String	Sender of the message. Valid values: 0 (Self), 1 (Customer Support), 2 (Counterparty)
> senderName	String	Name of the message sender
> imageUrls	String	Image urls
> videoUrls	String	Video urls
> timestamp	String	Message sent timestamp. Unix timestamp format in milliseconds

Sample Response:

```

1  {
2      "code": 0,
3      "data": [
4          {
5              "disputeReason": "I received the payment but the order is
6              canceled",
7              "disputeSubReason": "Transfer the crypto to the buyer",
8              "disputerSide": "1",
9              "isDisputer": true,
10             "messages": [
11                 {
12                     "imageUrls": [],
13                     "message": "",
14                     "sender": "0",
15                     "senderName": "",
16                     "timestamp": "1721269451000",
17                     "translatedMessage": "",
18                     "videoUrls": []
19                 },
20                 {
21                     "imageUrls": [],
22                     "message": "",

```

```

22         "sender": "1",
23         "senderName": "abcd",
24         "timestamp": "1721269451000",
25         "translatedMessage": "",
26         "videoUrls": [
27             "https://static.coinall.ltd/cdn/oksupport/c2c/20240718_a8005793-9826-4c95-
b25d.mp4"
28         ]
29     },
30     {
31         "imageUrls": [],
32         "message": "",
33         "sender": "0",
34         "senderName": "",
35         "timestamp": "1721269431000",
36         "translatedMessage": "",
37         "videoUrls": []
38     },
39     {
40         "imageUrls": [],
41         "message": "",
42         "sender": "1",
43         "senderName": "test4fiat2",
44         "timestamp": "1721269431000",
45         "translatedMessage": "",
46         "videoUrls": [
47             "https://static.coinall.ltd/cdn/oksupport/c2c/20240718_f42ce0bb-a2c0-4c43-
9e2.mp4"
48         ]
49     }
50 ]
51 }
52 ],
53 "msg": ""
54 }

```

8.4 Send message

Send a message for the dispute.

HTTP Request

POST /api/v5/p2p/dispute/sendMessage

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id
message	String	No	Message text
imageUrls	Array of String	No	User-uploaded image URLs
videoUrls	Array of String	No	User-uploaded video URLs

Response Parameters

Parameter	Type	Description
id	String	Order Id for which evidence got updated

8.5 Cancel Dispute

Cancels the dispute.

HTTP Request

POST /api/v5/p2p/dispute/cancel

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id

Response Parameters

Parameter	Type	Description
orderId	String	Id of the order for which dispute got cancelled

9. Chat

9.1 Get Chat history for order

Get chat history based on order. The messages are ordered from the latest to the oldest. System-generated messages are not returned.

HTTP Request

GET /api/v5/p2p/chat/history

Request Parameters

Parameter	Type	Required	Description
orderId	String	Optional	- If the <code>orderId</code> is specified, the API will return all chat messages related to that specific order. Note that once the order is completed, no further chat messages can be retrieved for that order. - If the <code>orderId</code> is not provided, the API will return all available chat messages between the counterparty
lastMessageSequence	String	No	Specifies the last message sequence number. Eg: "123" This param is required if messages are required to be fetched backward.
pageSize	String	Yes	Specifies the number of messages to be retrieved.

Response Parameters

Parameter	Type	Description
sentTimestamp	String	Epoch timestamp for the message sent time
isSentBySelf	String	Specifies whether requestor is the sender as well
content	String	Text of the content. Eg: "Hello"
contentUrl	Boolean	If the message is of a media type (like an image/video, etc.), the URL is returned. Content present at this URL can be retrieved for 30 days from the time the content is uploaded.
lastMessageSequence	String	The sequence number of the message. Eg: "123"

9.2 Send message

Send message for the order to the counterparty.

HTTP Request

POST /api/v5/p2p/chat/send-message

Request Parameters

Parameter	Type	Required	Description
orderId	String	Yes	Order Id. Eg: "12345"
content	String	No	Text of the content. Eg: "Hello"
contentUrl	String	No	If the message is of a media type (like an image/video, etc.), then specify the url. URL can be generated by calling file upload API.
contentType	String	Yes	Type of content. 101 => Text 102 => Image 112 => Video

Response Parameters

Parameter	Type	Description
isSentSuccessfully	Boolean	Specifies whether the message was sent successfully to the other user or not.

10. File

10.1 Upload file

HTTP Request

POST /api/v5/p2p/file/upload

The input is multipart file.

Request Parameters

Parameter	Type	Required	Description
-----------	------	----------	-------------

file	Multipart	Yes	
------	-----------	-----	--

Response Parameters

Parameter	Type	Description
path	String	Path of the uploaded file. Eg: " http://abc.com/xyz "