

Cloud Native Streaming Platform Netflix-inspired

Santiago Antonio Gualteros Bustos

Nicolas Castro Rivera

Andrés Julian Vargas Medina

Erick Santiago Buitrago Peña

1 Executive Summary

Netflix is a streaming platform that provides this service for subscriptions. Whose vision is entertaining customers through series and movies. This content can be accessed around the world by millions of customers those who want to watch their favorites shows at any time. For that reason is an application demands great availability, good performance with heavy content such as multimedia and personalized experience with assertive recommendations.

2 System Description

Business problem, actor catalog, use case definitions, and system boundary diagram

2.1 Business Problem

Netflix solves the problem of providing a large amount of audiovisual content to millions of users through the internet while giving each user a convenient and personalized experience.

Users want to watch movies and series whenever and wherever they want without having to download the entire content beforehand. At the same time, Netflix needs to help users find something they want to watch among a very large catalog.

The platform provide another services that not will be consider in this project like: Option for subtitles, interactive experiences or content preview.

2.2 Actors

The application has 4 users represented by a person, each of this person has a particular function and use the application for different purposes. Also there are some system actor that provide services for the application.

Table 1: Actors, Roles, Interaction Frequency, and Expectations

Actor	Role	Frequency of interaction	Expectation
Customer	A person who has a monthly membership plan with the platform.	High	Be able to watch series and movies without interruptions and receive relevant recommendations.
Operational user	A member of the operations team responsible for managing content within the system.	Medium	Be able to manage all the content without problems.
Data analyst	A member of the Data & Insights area who can access data and statistics.	Medium	Have access to useful data with clear statistics.
Platform administrator	Is responsible for managing users and the business model.	Low	Be able to manage the users of the system and membership configurations.
Media Convert service	It allows videos to be sent in small segments.	High	The user does not need to download the entire video; it is stored in fragments in the device buffer.
CDN service	Servers that help reduce latency by delivering content from the nearest server.	High	Ensure rapid response to high volumes of requests.
Storage	Storage for multimedia content and metadata, useful for performing queries.	High	Persist all data over time.

2.3 Main Use Cases

Subsection example 2

2.4 System Boundaries

Subsection example 2

3 Functional Requirements

This requirements specify what application does. There are 12 functional requirements divided in 7 domains. To define the functional scope for this section, an analysis of Netflix's business model and

official domain vision was conducted to establish a comprehensive understanding of the operational context. Building upon this business domain baseline, an actor-driven requirement elicitation process was executed. System actors, ranging from end-customers to operational staff and data analysts, were identified and evaluated based on their operational responsibilities and system interactions. Each actor’s functional needs, such as secure authentication, uninterrupted media streaming, content curation, and platform analytics, were systematically mapped to define the required system capabilities.

Subsequently, Domain-Driven Design (DDD) strategic design principles were applied to analyze and categorize the elicited requirements. The requirements were grouped into distinct Bounded Contexts, acknowledging that domain entities and ubiquitous language terms carry specialized business semantics and rules depending on their contextual boundary. Through this domain decomposition, the following core Bounded Contexts were identified:

- **Identity and Access Management (IAM):** Manages user accounts, authentication credentials, and access control policies across the platform.
- **Subscription Management:** Governs membership plans, billing processing, and subscription lifecycle states.
- **Streaming Core:** Serves as the primary domain service responsible for video playback orchestration and real-time media streaming delivery.
- **Recommendation Engine:** Leverages user consumption history, search queries, and contextual metadata to generate personalized content suggestions.
- **Content Management:** Facilitates the complete lifecycle management (CRUD operations) for media assets and metadata across staging and release workflows.
- **Data & Insights:** Captures, aggregates, and processes platform-wide performance and streaming metrics for analytical insights.
- **Catalog & Discovery:** Handles content indexing, search queries, and catalog exploration to enable seamless user discovery.

“latex

Table 2: System Requirements Matrix Categorized by Domain / Bounded Context

ID	Requirement (The system shall...)	Inputs	Outputs	Domain / Context
RF - 01	Allow customer registration through paid membership.	Email, password, payment details	Customer account creation notification	Subscription Management

Continued on next page

ID	Requirement (The system shall...)	Inputs	Outputs	Domain / Context
RF - 02	Allow membership payment processing using online payment methods.	Payment method info (card/gateway)	Payment confirmation or error message	(Subscription)
RF - 05	Allow customers to cancel their active membership subscription.	Cancellation request and reason	Membership cancellation status confirmation	(Subscription)
RF - 03	Allow any user to authenticate using email and password credentials.	Email and password credentials	Access granted to appropriate user dashboard	Identity & Access Management (IAM)
RF - 04	Allow users to update their access credentials.	Registered email, current and new credentials	Credential update success or failure notice	
RF - 06	Allow any user to update their personal profile information.	Authenticated session, updated attributes	Updated profile status or error message	
RF - 10	Allow platform administrators to manage user accounts and roles.	Admin request parameters and action payload	Success/failure message and updated user state	
RF - 07	Allow customers to stream movie or episode content instantly without prior downloading.	Chapter/movie selection	Instant video playback stream	Streaming Core
RF - 08	Provide personalized and timely content recommendations to customers.	Contextual data, watch history, search queries	Personalized content feed on main screen	Recommendation Engine
RF - 09	Allow operations personnel to manage media content catalog items.	Metadata creation, update, query, or deletion requests	Action result message and updated catalog state	Content Management
RF - 11	Allow data analysts to query and view streaming usage analytics.	Time range and metric filter parameters	Processed analytical reports and metrics	Data & Insights

Continued on next page

ID	Requirement (The system shall...)	Inputs	Outputs	Domain / Context
RF - 12	Allow customers to search for movies or series in the catalog.	Search query string	List of matching movies/series and metadata	Catalog & Discovery

4 Non-Functional Requirements

The non-functional requirements were estimated of some public Netflix values. The values for our application are approximately 5 times less, but congruent.

Table 3: RNF – Expected Users

Identifier	Description	RF associated
RNF-01	The system shall support up to 50.000.000 registered customer accounts while maintaining normal operation and the defined performance targets.	RF-01, RF-03
RNF-02	The system shall support up to 10.000.000 concurrently active users under normal operating conditions.	RF-03, RF-07, RF-08, RF-12
RNF-03	The system shall support up to 40.000.000 concurrently active users during peak operating periods without service degradation below the defined performance and availability targets.	RF-03, RF-07, RF-08, RF-12

Table 4: RNF – Average Requests per Hour

Identifier	Description	RF associated
RNF-04	The system shall support an average of at least 120.000.000 application requests per hour during normal operating conditions, including authentication, catalog browsing, searches, recommendations, profile operations, and administrative operations.	RF-03, RF-06, RF-08, RF-09, RF-10, RF-12
RNF-05	The system shall process at least 40.000 requests per second on average during normal operating conditions while maintaining the defined response-time targets.	RF-03, RF-07, RF-08, RF-09, RF-12

Table 5: RNF – Peak Requests per Hour

Identifier	Description	RF associated
RNF-06	The system shall support at least 600.000.000 application requests per hour during peak periods, equivalent to approximately 160.000 requests per second.	RF-03, RF-07, RF-08, RF-12
RNF-07	The system shall maintain successful processing of authentication, catalog, search, recommendation, and content-access requests during peak periods without exceeding the defined response-time thresholds.	RF-03, RF-07, RF-08, RF-12

Table 6: RNF – Peak Duration

Identifier	Description	RF associated
RNF-08	The system shall sustain the defined peak workload continuously for at least 4 hours without exceeding the established response-time or availability thresholds.	RF-03, RF-07, RF-08, RF-12
RNF-09	The system shall support sustained high-demand periods during evenings, weekends, and periods following the publication of new content without requiring manual intervention to maintain the defined service levels.	RF-07, RF-08, RF-09, RF-12

Table 7: RNF – Response-Time Targets

Identifier	Description	RF associated
RNF-10	At least 95% of authentication, profile, subscription, and standard API requests shall receive a response within 500 ms under normal operating conditions.	RF-01, RF-02, RF-03, RF-04, RF-05, RF-06
RNF-11	At least 95% of catalog browsing and content-search requests shall return the initial result set within 1 second under normal operating conditions.	RF-09, RF-12
RNF-12	At least 99% of catalog browsing and content-search requests shall return the initial result set within 2 seconds under normal operating conditions.	RF-09, RF-12
RNF-13	At least 95% of recommendation requests shall return the personalized content feed within 2 seconds under normal operating conditions.	RF-08
RNF-14	At least 95% of successful video playback requests shall initiate playback within 3 seconds, excluding delays attributable to the user's Internet connection or external content-delivery infrastructure.	RF-07

Table 8: RNF – Availability

Identifier	Description	RF associated
RNF-15	The system shall maintain a monthly availability of at least 99.9% for customer-facing services, excluding previously announced maintenance periods.	RF-03, RF-07, RF-08, RF-09, RF-12
RNF-16	The maximum accumulated unplanned downtime of customer-facing services shall not exceed approximately 43.2 minutes per calendar month.	RF-03, RF-07, RF-08, RF-12
RNF-17	The system shall preserve access to authentication, catalog discovery, and content playback whenever the corresponding service dependencies remain operational.	RF-03, RF-07, RF-12

Table 9: RNF – Data Volume

Identifier	Description	RF associated
RNF-18	The system shall support up to 5 TB of application-managed data at launch, including user accounts, subscriptions, content metadata, viewing history, recommendation data, search records, and analytics data.	RF-01, RF-02, RF-05, RF-06, RF-08, RF-09, RF-11, RF-12
RNF-19	The system shall support a media catalog of at least 5,000 movie and episode entries, including their associated metadata required for catalog discovery and playback.	RF-07, RF-09, RF-12
RNF-20	The system shall allow storage capacity to be expanded beyond the initial 5 TB without requiring a fundamental redesign of the application’s data-management architecture.	RF-07, RF-08, RF-09, RF-11

Table 10: RNF – Data Growth

Identifier	Description	RF associated
RNF-21	The system shall accommodate an estimated annual growth of up to 2 TB of application-managed data without degradation of the defined performance targets.	RF-07, RF-08, RF-09, RF-11, RF-12
RNF-22	The system shall support continuous growth of user activity data, including viewing history, searches, recommendations, and analytics, while maintaining access to data generated during previous years.	RF-08, RF-11, RF-12
RNF-23	The system shall allow storage resources to be increased independently from application services as data volume grows.	RF-09, RF-11

Table 11: RNF – Geographic Scope

Identifier	Description	RF associated
RNF-24	The system shall initially provide its services to users located in Colombia through the public Internet.	RF-01, RF-02, RF-03, RF-07, RF-08, RF-09, RF-12
RNF-25	At least 95% of customer-facing API requests originating from Colombia shall achieve a response time below 500 ms under normal operating conditions, excluding delays caused by the user’s local network or Internet service provider.	RF-03, RF-06, RF-08, RF-09, RF-12
RNF-26	The system architecture shall permit expansion to additional Latin American countries without requiring a fundamental re-design of the core application architecture.	RF-01, RF-02, RF-03, RF-07, RF-08, RF-09, RF-12

5 Workload Model

Structured table with all workload parameters and justification for each value

References

- [1] Rummery, G. A., & Niranjana, M. (1994). On-line Q-learning using connectionist systems. *Technical Report*, Cambridge University Engineering Department.