New York City Taxi Fare Prediction

Arijit Guchhait

Research Objectives

For each key in the test set, you must predict a value for the fare_amount variable. The evaluation metric for this competition is the root mean-squared error or RMSE.

Data Wrangling

Loading library & Data

- train.csv - Input features and target fare_amount values for the training set. Only 01 Million rows are seleted out of 55 M due to memory restriction on local machine.
- test.csv - Input features for the test set (about 10K rows). Goal is to predict fare_amount for each row.
- sample_submission.csv - a sample submission file in the correct format (columns key and fare_amount). This file 'predicts' fare_amount to be $11.35 for all rows, which is the mean fare_amount from the training set.

```
import pandas as pd
import numpy as np
from scipy import stats
import matplotlib.pyplot as plt
import seaborn as sns
import sklearn
from sklearn.pipeline import Pipeline
from sklearn.linear_model import LinearRegression, ElasticNet, Ridge,Lasso
from sklearn.preprocessing import StandardScaler
from sklearn.metrics import roc_auc_score,f1_score,mean_squared_error
from xgboost import XGBRegressor
from sklearn.model_selection import train_test_split
from sklearn.model_selection import KFold, cross_val_score, StratifiedKFold
```

```python
from sklearn.metrics import mean_squared_error
sns.set_theme(palette="viridis",rc={"figure.figsize": (8, 5)},style="darkgrid")
```

```python
train = pd.read_csv('data.nosync/train.csv', nrows=1000000)
test = pd.read_csv('data.nosync/test.csv')
```

Data Cleaning & Feature Engineering

```python
print("--- Missing Values Per Column ---")

print(train.isna().sum())

print("--- Data Types ---")
print(train.dtypes)
```

```
--- Missing Values Per Column ---
key                  0
fare_amount          0
pickup_datetime      0
pickup_longitude     0
pickup_latitude      0
dropoff_longitude   10
dropoff_latitude    10
passenger_count      0
dtype: int64
--- Data Types ---
key                     str
fare_amount         float64
pickup_datetime         str
pickup_longitude    float64
pickup_latitude     float64
dropoff_longitude   float64
dropoff_latitude    float64
passenger_count       int64
dtype: object
```

```python
print("--- Descriptive Summary ---")
print(train.describe())
```

```
--- Descriptive Summary ---
          fare_amount  pickup_longitude  pickup_latitude  dropoff_longitude  \
count  1000000.000000    1000000.000000   1000000.000000      999990.000000
mean        11.348079        -72.526640        39.929008         -72.527860
std          9.822090         12.057937         7.626154          11.324494
min        -44.900000      -3377.680935     -3116.285383       -3383.296608
25%          6.000000        -73.992060        40.734965         -73.991385
50%          8.500000        -73.981792        40.752695         -73.980135
75%         12.500000        -73.967094        40.767154         -73.963654
max        500.000000       2522.271325      2621.628430          45.581619

       dropoff_latitude  passenger_count
count     999990.000000   1000000.000000
mean          39.919954         1.684924
std            8.201418         1.323911
min        -3114.338567         0.000000
25%           40.734046         1.000000
50%           40.753166         1.000000
75%           40.768129         2.000000
max         1651.553433       208.000000
```

```python
upper_limit = train["fare_amount"].quantile(0.75)+1.5*stats.iqr(train["fare_amount"])
lower_limit = train["fare_amount"].quantile(0.25)-1.5*stats.iqr(train["fare_amount"])
outliers = (train["fare_amount"]<=lower_limit) & (train["fare_amount"]>=upper_limit)
print(f"""
----  Fare  Amount Analysis  ----

    Upper limit: {upper_limit},
    Lower limit: {lower_limit},
    Outliers percentage: {len(train[outliers])*100.00/len(train)},
    Negative price in : {len(train[train["fare_amount"]<0])} Rows
    """)
```

```
----  Fare  Amount Analysis  ----

    Upper limit: 22.25,
    Lower limit: -3.75,
    Outliers percentage: 0.0,
    Negative price in : 38 Rows
```

```
print("--- Removing negative 38 rows ---\n")
train_clean =train[train["fare_amount"]>=0]
train_clean["pickup_datetime"]=pd.to_datetime(train_clean["pickup_datetime"],errors="coerce")
train_clean["year"]=train_clean["pickup_datetime"].dt.year
train_clean["month"]=train_clean["pickup_datetime"].dt.month
train_clean["hour"]=train_clean["pickup_datetime"].dt.hour
```

```
--- Removing negative 38 rows ---
```

Exploratory Data Analysis (EDA)

```
sns.heatmap(train_clean.corr(numeric_only=True,method="kendall"),annot=True)
plt.show()
```



```
sns.relplot(x="year",y="fare_amount",data=train_clean,kind="line",errorbar=None)
plt.title("Rise of fare from 2009 to 2015")
plt.show()
```




```
sns.lineplot(x="hour",y="fare_amount",data=train_clean,estimator="median",marker="o",errorba
plt.xlabel('Hour')
plt.ylabel('Median fare amount')
plt.xticks(range(24))
plt.title('Fare amount based on time')
plt.show()
```

```
train_clean["passenger_count"].value_counts(ascending=True).plot(kind="barh")
plt.title("Passengers per Ride")
plt.show()
```




```
print(f"Number of rows with either 0 and one instance of 208 passengers are : \
{len(train_clean[train_clean['passenger_count'].isin([208,0])])}\n")

print("--- Removing thses outliers ---\n")
train_clean=train_clean[~train_clean["passenger_count"].isin([208,0])]
```

```
Number of rows with either 0 and one instance of 208 passengers are : 3566

--- Removing thses outliers ---
```

```
sns.histplot(x="fare_amount",bins=np.linspace(0,100,21),data=train_clean)
plt.title("Distribution of fare")
plt.show()
```




```
def haversign_distance(lat1,lat2,lon1,lon2):
    """
    d = 2R · arcsin( √[ sin²((lat  - lat )/2) + cos(lat )·cos(lat )·sin²((lon  - lon )/2) ] )
    6371 is earth radius in Km
    """
    lat1,lat2,lon1,lon2 = map(np.radians,[lat1,lat2,lon1,lon2])
    dlat = lat2-lat1
    dlon = lon2-lon1
    # Haversine formula
    a = np.sin(dlat/2)**2 + np.cos(lat1) * np.cos(lat2) * np.sin(dlon/2)**2
    c = 2 * np.arcsin(np.sqrt(a))
    return c* 6371
train_clean["distance_km"]= haversign_distance(train_clean['pickup_latitude'],
                                               train_clean['dropoff_latitude'],
                                               train_clean['pickup_longitude'],
                                               train_clean['dropoff_longitude'])
```

```
sns.scatterplot(y="distance_km",x="fare_amount",size="fare_amount",data=train_clean)
sns.regplot(y="distance_km",x="fare_amount",data=train_clean,scatter=False,color="black")
plt.title('Fare amount based on the distance')
```

```
plt.ylim([0,50])
plt.show()
```




```
latitute_range = (40.5, 41.0)
longitude_range = (-74.3, -73.7)
coordinate_outliers = ~train_clean["pickup_latitude"].between(*latitute_range)| \
    ~train_clean['dropoff_latitude'].between(*latitute_range)  | \
    ~train_clean['pickup_longitude'].between(*longitude_range) | \
    ~train_clean['dropoff_longitude'].between(*longitude_range)
print(f"""
        Filtering the langitute between Staten Island to Yonkers
        and longitude between New Jersey to JFK/Queens.
        Number of rows affected: {len(train_clean[coordinate_outliers])}
       """)
print("--- Removing thses outliers ---\n")
train_clean =train_clean[~coordinate_outliers]
```

```
        Filtering the langitute between Staten Island to Yonkers
        and longitude between New Jersey to JFK/Queens.
        Number of rows affected: 21799

--- Removing thses outliers ---
```

```
feature = train_clean[["passenger_count","year","month","hour","distance_km"]]
model = LinearRegression()

# 1. Spliting cleaned data by 80% train and 20% validation
X_train, X_val, y_train, y_val = train_test_split(
    feature, train_clean["fare_amount"], test_size=0.2, random_state=42
)
# 2. Train the model on the smaller training slice
model.fit(X_train, y_train)

# 3. Predict on the validation slice
val_predictions = model.predict(X_val)

# 4. Calculate RMSE
rmse = np.sqrt(mean_squared_error(y_val, val_predictions))
print(f"Local Validation RMSE: {rmse}")


# 5 Now for Kaglle submission

model.fit(X=feature,y=train_clean["fare_amount"])
test['pickup_datetime'] = pd.to_datetime(test['pickup_datetime'])
test['year'] = test['pickup_datetime'].dt.year
test['month'] = test['pickup_datetime'].dt.month
test['hour'] = test['pickup_datetime'].dt.hour
test["distance_km"]=haversign_distance(test['pickup_latitude'],
                                        test['dropoff_latitude'],
                                        test['pickup_longitude'],
                                        test['dropoff_longitude'])

# Select the same columns used during model.fit()
test_features = test[["passenger_count", "year", "month", "hour","distance_km"]]
test["fare_amount"] = model.predict(test_features)
test[["key","fare_amount"]].to_csv('submission.csv', index=False)
```

```
Local Validation RMSE: 4.601249846535166
```