

Capacitively-Coupled Chopper Instrumentation Amplifier for Hall Effect Sensor

IEEE SSCS Chipathon 2026

Team Chop

June 13, 2026

1 Introduction

- Discuss magnetic sensing application space
 - Current sensing
 - Tactile Sensing (robotics)
 - Position/Velocity Sensing (automotive)
 - Biosensors
- Discuss utility of building open-source Hall sensor readout
 - No existing data on n-well-based Hall sensors in open PDKs
 - Sensor evaluation gives future designers ability to integrate into their application
 - Readout circuit directly applicable to most bridge-type sensors

2 Conceptual Design

- Show high-level block diagram
- Table of pinouts with signal descriptions/directions

2.1 Sensor

- Vertical vs. Horizontal sensor design
- Horizontal sensor geometries
-

2.2 Readout Circuit

- Instrumentation Amplifier options/survey
- CCIA chosen due to large common-mode input range (sweepable bias current), stable gain (easy to integrate several gain options if needed)
- Hall sensor bias expected to dominate power consumption, but CCIA being low-power is great in other high-impedance sensor applications
- analog output reduces complexity and allows for easier characterization of CCIA

3 Design Specifications

- Table of specifications for full system

3.1 Sensor

3.2 Readout Circuit

4 Schematic Design

- Show top-level schematic

4.1 Subblock 1

4.2 Subblock N

5 Layout Design

- Show layout floorplan

5.1 Subblock 1

5.2 Subblock N

6 Simulation Results

- Verification Plan details (how is each specification tested?)

6.1 Simulation 1

6.2 Simulation M

References