

# Machine Learning - Block 01 Lab 2

*Agustín Valencia*

*12/5/2019*

## Assignment 2. Analysis of credit scoring

The data file `creditscoring.xls` contains data retrieved from a database in a private enterprise. Each row contains information about one customer. The variable `good/bad` indicates how the customers have managed their loans. The other features are potential predictors. Your task is to derive a prediction model that can be used to predict whether or not a new customer is likely to pay back the loan.

**1. Import the data to R and divide into training/validation/test as 50/25/25: use data partitioning code specified in Lecture 1e.**

```
## Data set size      : 1000 20
## Training set size   : 500 20
## Validation set size : 250 20
## Testing set size    : 250 20
```

**2. Fit a decision tree to the training data by using the following measures of impurity and report the misclassification rates for the training and test data. Choose the measure providing the better results for the following steps.**

**a. Deviance**

```
##
## Classification tree:
## tree(formula = f, data = train, split = "deviance")
## Variables actually used in tree construction:
## [1] "duration" "history" "age"      "property" "job"      "savings"  "amount"
## Number of terminal nodes: 12
## Residual mean deviance: 0.9879 = 476.2 / 482
## Misclassification error rate: 0.247 = 122 / 494

## Classification Performance : Tree. split = deviance
## [1] "Confusion Matrix"
##      predictions
## targets bad good
##   bad   22   43
##   good  44  141
## Rates details:
## TPR = 76.63043 % - TNR = 33.33333 % - FPR = 23.36957 % - FNR = 66.66667 %
## Misclassification Rate = 34.8 %
```

## b. Gini index

```
##
## Classification tree:
## tree(formula = f, data = train, split = "gini")
## Variables actually used in tree construction:
## [1] "foreign" "coapp" "depends" "existcr" "telephon" "savings"
## [7] "history" "property" "employed" "resident" "marital" "purpose"
## [13] "duration" "housing" "installp" "amount" "job" "age"
## Number of terminal nodes: 70
## Residual mean deviance: 1.059 = 449.1 / 424
## Misclassification error rate: 0.247 = 122 / 494

## Classification Performance : Tree. split = gini
## [1] "Confusion Matrix"
##      predictions
## targets bad good
##    bad   19   46
##    good  42  143
## Rates details:
## TPR = 75.66138 % - TNR = 31.14754 % - FPR = 24.33862 % - FNR = 68.85246 %
## Misclassification Rate = 35.2 %
```

In summary, the tree trained using deviance as split method performs slightly better than the one using gini index, because it gets better True Positive and Misclassification rates, also it is considerably smaller having 12 terminal nodes against the 70 from the Gini one.

**3. Use training and validation sets to choose the optimal tree depth. Present the graphs of the dependence of deviances for the training and the validation data on the number of leaves. Report the optimal tree, report its depth and the variables used by the tree. Interpret the information provided by the tree structure. Estimate the misclassification rate for the test data.**

**4. Use training data to perform classification using Naïve Bayes and report the confusion matrices and misclassification rates for the training and for the test data. Compare the results with those from step 3.**

**5. Use the optimal tree and the Naïve Bayes model to classify the test data by using the following principle:  $\hat{Y} = 1$  if  $p(Y = \text{good}|X) > \pi$ , otherwise  $\hat{Y} = 0$  where  $\pi = 0.05, 0.1, 0.15, \dots, 0.9, 0.95$ . Compute the TPR and FPR values for the two models and plot the corresponding ROC curves. Conclusion?**

**6. Repeat Naïve Bayes classification as it was in step 4 but use the following loss matrix.**

and report the confusion matrix for the training and test data. Compare the results with the results from step 4 and discuss how the rates have changed and why.

## Appendix A : Code

```
#### -----
####                               Setup
#### -----
knitr::opts_chunk$set(echo = TRUE)
library(readxl)
library(tree)
set.seed(12345)

#### -----
####                               Question 1
#### -----

## 1.1 Split data

data <- read_xls("data/creditscoring.xls")
n <- dim(data)[1]
data$good_bad <- as.factor(data$good_bad)

# training set
id <- sample(1:n, floor(n*0.5))
train <- data[id,]

# validation set
id1 <- setdiff(1:n, id)
id2 <- sample(id1, floor(n*0.25))
valid <- data[id2,]

# test set
id3 <- setdiff(id1, id2)
test <- data[id3,]

cat("Data set size \t\t:", dim(data))
cat("Training set size \t:", dim(train))
cat("Validation set size \t:", dim(valid))
cat("Testing set size \t:", dim(test))

## 1.2 Trees

f <- good_bad ~ .

# util function
get_performance <- function(targets, predictions, text) {
  cat("Classification Performance :", text, "\n")
  t <- table(targets, predictions)
  print("Confusion Matrix")
  print(t)
  tn <- t[1,1]
  tp <- t[2,2]
```

```

fp <- t[1,2]
fn <- t[2,1]
total <- dim(test)[1]
tpr <- tp/(tp+fp) * 100
tnr <- tn/(tn+fn) * 100
fpr <- fp/(tp+fp) * 100
fnr <- fn/(tn+fn) * 100

cat("Rates details:\n")
cat(" TPR =", tpr, "% -")
cat(" TNR =", tnr, "% -")
cat(" FPR =", fpr, "% -")
cat(" FNR =", fnr, "%")
cat("\n Misclassification Rate = ", (fp+fn)/total * 100, "%\n")
}

```

### ### 1.2.a Deviance Tree

```

devTree <- tree(formula = f, data = train, split = "deviance")
#plot(devTree)
#text(devTree)
summary(devTree)

```

```

true <- test$good_bad
predictions <- predict(devTree, newdata = test, type = "class")
get_performance(true, predictions, "Tree. split = deviance")

```

### ### 1.2.a Deviance Tree

```

giniTree <- tree(formula = f, data = train, split = "gini")
#plot(giniTree)
#text(giniTree)
summary(giniTree)

```

```

predictions <- predict(giniTree, newdata = test, type = "class")
get_performance(true, predictions, "Tree. split = gini")

```