MODULE 8: TOYOTA EDR SPECIFICS

Toyota

(includes Lexus and Scion)

- Toyota began phasing in EDR's in 2001 Lexus LS/GS – with precrash data
- Many early models have only longitudinal Delta V. By 2011 ALL have precrash data.
- Later models have 6 precrash data points, 5 at one second intervals, and a bonus point near TRG.
- In side impacts, some have side Delta V and in rollovers, some have roll angle

Toyota

(includes Lexus and Scion)

- Other manufacturers have all of their rules in the Data Limitations.
- Toyota is different. Some of the info found in other mfgr Data Limitations resides in the CDR Software's Glossary.
- For Toyotas, if you have a problem "**RTFG**" – **R**ead **T**he **F**riggin **G**lossary"

Toyota EDR Families

First Generation

- 00/02 MANY record only frontal events
- 00/02 A FEW record side data if side bag equipped, & roll

Second Generation

- 04/06 EDR – MOST have precrash, SOME have side data

Gen 1&2: Precrash data is not tied to a module family.


Third Generation

- 12 EDR 563-intent, but still **no** Lat DV in frontal events. If side event is triggered, only 70ms side data from B/C pillar
- 13 EDR, Adds ACM Lat ***accel*** to frontal events
- 15 EDR, adds side impact door pressure sensors

Fourth Generation

- 17 EDR (2018 models) with pop up hood feature

Toyota US CDR 17.9 Coverage 78%



Toyota Unique Help File Organization

Supported Toyota Vehicles

Use this section of the help file to determine if a vehicle is supported by the CDR tool and to look up the correct cable (and in some cases, adapter) to use for EDR data directly from the ACM. It is important to note that even if the vehicle is listed in this section, CDR must also support the part number on the ACM. Cli list of supported ACM part numbers.

Click here for tips on how to use this *Supported Vehicles* help topic

IMPORTANT: To prevent damage to Toyota ECUs when imaging EDR data directly from the ECU, you must always use the appropriate cable called out in this the help file.

General Toyota Application Notes:

The CDR Tool software will accept most Toyota VINs entered by the user and the *Collect Airbag Control Module Data* icon will no longer be grayed out. **This is n indicator that the vehicle is supported.** Only the vehicles listed in the help file below are supported as indicated by the list and any associated coverage not

All supported vehicles listed can be imaged through the vehicle's DLC connector using the CDR OBDII DLC Cable (F00K108287) unless otherwise stated.

All supported vehicles require the vehicle's ignition key to be switched on prior to and during EDR record imaging through the vehicle's DLC connector.

Vehicle Specific Application Notes:

Click here to view all vehicle specific Toyota coverage notes


Vehicles Are Listed Alphabetically
Not by Model Year

Toyota Models begin with: 4 8 9 A B C D E F H I K L M N P R S T V W X Y Z

4Runner (Toyota) 2003 and later Market: 7

Year	EDR Generation	CDR Cable & Adapter	Module	Module Location
2002 - 2008	Gen 1 (02EDR)	F00K108617 (no adapter)	ACM	Under Center Stack
2009 - 2011	Gen 2 (06EDR)	F00K108616 & F00K108387	ACM	Under Center Stack
2012 and later	Gen 3 (12EDR/13EDR)	F00K108616 & F00K108387	ACM	Under Center Stack

New Toyota Vehicle Lookup



Camry (Toyota) **2001 and later** **Market: 7**

All Markets the Vehicle is Sold

Year	EDR Generation	CDR Cable & Adapter	M
2001 - 2004 2005 (US/Canada)	Gen 1 (00EDR/02EDR)	F00K108615 (no adapter) F00K108617 (no adapter) Click here [?] to match the ACM part number to the correct cable	A
2005 - 2011	Gen 2 (04EDR/06EDR)	F00K108613 (no adapter) F00K108614 & F00K108387 F00K108615 (no adapter) F00K108616 & F00K108387 Click here [?] to match the ACM part number to the correct cable	A
2012 and later	Gen 3 (12EDR/13EDR)	F00K108616 & F00K108387	A

< Models

Many Different Cables for Same Model

Must Look up Cable for DTM by Part No

New Toyota Help File ***U.S.*** *Issues*

- Because the help file applies WORLDWIDE, it lists MANY models not found in the US/CAN.
- Toyotas internal records may be by ***CALENDAR*** YEAR, not ***MODEL*** YEAR. Help File may show EDR is first available in 2003, but that was 2004 Model Year in the US. MOST models are “one year off”.
- Avalon shows EDR in 02 but prior charts showed no EDR until 06 – do not assume EDR present in every vehicle listed in the help file

Unique to Toyota

- Delta V is recorded real time as it is occurring (GM waits until event is over to write anything). Even in older models with no backup power supply for recording, partially written Delta V is possible
- There are multiple “recording complete” entries:
- 1. Complete file
- 2. Crash Pulse subsection (Delta V), per event
- 3. Precrash subsection (Speed), per event


Toyota EDR Evolution

GEN 1 00,02 EDR	GEN 2 04,06 EDR	GEN 3 12,13,15 EDR	GEN 4 17 EDR
3 front 1 side 1 roll	2 front 2 side 2 roll	2 front 2 side 2 roll	4 front 4 side 6 precrash
Record on 2g wakeup	Record on 2g wakeup	Record on 5mph XDV, side 3.5g wake	Record on 5 X or Y DV
150ms XDV 5PC@1 + TRG	200ms XDV 5PC@1+TRG	250ms XDV 10PC@0.5 + TRG	250ms XY 10PC@0.5+TRG

Toyota EDR Evolution cont'd

GEN 1 00,02 EDR	GEN 2 04,06 EDR	GEN 3 12,13,15 EDR	GEN 4 17 EDR
70ms YDV@ACM +sats	70ms YDV@ACM +sats	12 YDV 70ms sats only 13 250ms ACM	250ms YDV
REFRESH 500 MS SPEED	REFRESH 500 MS SPEED	REFRESH 24 MS SPEED	REFRESH 24 MS SPEED
78 MPH TOP, 2kph res	75 MPH TOP. 2kph res	124 MPH TOP 1 kph res	124 MPH TOP, 1 kph res
Accel Pedal Volts	Accel Pedal Volts	Accel Pedal % & Throttle %	Accel Pedal % + Throttle

Toyota EDR Evolution cont'd



Unique to Toyota: Record Summary

Event Record Summary at Retrieval

Events Recorded	TRG Count	Crash Type	Time (msec)	Pre-Crash & DTC Data Recording Status	Event & Crash Pulse Data Recording Status
Most Recent Event	7	Side Crash	0	Complete (Page 0)	Complete (Side Page 0)
1st Prior Event	6	Front/Rear Crash	-20	Complete (Page 0)	Complete (Front/Rear Page 1)
2nd Prior Event	5	Side Crash	-228	Complete (Page 0)	Complete (Side Page 1)
3rd Prior Event	4	Front/Rear Crash	-282	Complete (Page 0)	Complete (Front/Rear Page 0)

- Events are TRG numbered & time stamped
- 7 events in the life of this vehicle. The Most recent 2 events per crash type are saved regardless of severity.
- For side recording equipped vehicles, in angular crashes, both front and side algorithms will wake up and record data separately. Look for front & side “pairs” with times close to one another. sequence.

02 EDR record summary

Front/Rear Event Record Summary at Retrieval

Events Recorded	TRG Count	Crash Type	Time (msec)	Event & Crash Pulse Data Recording Status
Most Recent Frontal/Rear Event	4	Front/Rear Crash	0	Complete (Front/Rear Page 1)
1st Prior Frontal/Rear Event	3	Front/Rear Crash	-5120 or greater	Complete (Front/Rear Page 2)
Prior Frontal/Rear Event	1	Front/Rear Crash	N/A	Complete (Front/Rear Page 0)

- Saves third front/rear event that came closest to deploying airbags (most negative DV).
- 1st prior event -5120ms ***or greater*** before most recent event, means ***NOT RELATED*** – nor is #1
- Event 2 was less important than Event 1 and was overwritten when #4 came in.

Finding PDOF in Toyota Gen1&2

- Toyota Gen 1&2 record frontal data when frontal algorithm wakes up, side data only when side algorithm wakes up.
- Many early Toyotas do not support side recording, you must estimate PDOF from visible crush damage.
- In later Toyotas with side recording, look for “pairs” of front and side recordings. Side recording duration is about 70ms, get PDOF by taking Y value at 70ms and X value from 70ms.

Unique to Toyota

- Toyota records ADDITIONAL precrash data point at TRG and the **time** from *last regular interval* recording to TRG (resolution to 0.1 sec, 0.0 to 0.9, truncated down)
- Last data may be WRITTEN at TRG, but could still be "old" as speed data in **Gen 1 & 2** was only transmitted every 0.5 sec. If speed data did not change from prior data point, it may be old by 0.5 sec. If the last reported value is different, it cannot be older than the time from last value to prior value.

Gen 1 & 2 Pre-Crash Data

- Accel Pedal Data in ***Voltage from sensor***
- Zero accel pedal is typically 0.78V, 100% is 3.79 V max seen to date but data limitations indicates the low and high could be different.
- You can calculate your own percentage if you want. %=(V-0.78)/(3.79-0.78) Update .5 sec
- RPM in 400 RPM increments, 400-799=400, 800-1199=800, etc. Updates every 24ms.
- Brake on/off updates immediately, no delay (accel pedal may as on when brake is on, but they are from different times)

Unique Toyota Memory Structure

- Toyota records pre-crash in a different memory section than Delta V. It gives records "page numbers" 0 and 1 and tells you which Precrash page goes with which Delta V page.
- If there are two or more events within 0.5 sec, all may be linked to the same precrash page. This is noted in the event record summary.

Event Record Summary at Retrieval

Events Recorded	TRG Count	Crash Type	Time (msec)	Pre-Crash & DTC Data Recording Status	Event & Crash Pulse Data Recording Status
Most Recent Event	7	Side Crash	0	Complete (Page 0)	Complete (Side Page 0)
1st Prior Event	6	Front/Rear Crash	-20	Complete (Page 0)	Complete (Front/Rear Page 1)
2nd Prior Event	5	Side Crash	-228	Complete (Page 0)	Complete (Side Page 1)
3rd Prior Event	4	Front/Rear Crash	-282	Complete (Page 0)	Complete (Front/Rear Page 0)

Un-linked precrash data

- The remaining precrash space is then known as “UNLINKED PRE CRASH” and was likely linked to a previous event. It is printed after the last linked precrash apg
- In multiple event scenarios, Unlinked precrash data overlaps linked precrash and shows driver behavior farther back in time. Always check for overlap between unlinked precrash data and linked precrash data.

Overlay Unlinked Data with Linked

Pre-Crash Data, -5 to 0 seconds (1st Prior Event, TRG 8)

Time (sec)	-4.1	-3.1	-2.1	-1.1	-0.1	0 (TRG)
Vehicle Speed (MPH [km/h])	74.6 [120]	70.8 [114]	70.8 [114]	69.6 [112]	36 [58]	36 [58]
Brake Switch	ON	OFF	OFF	OFF	OFF	OFF
Accelerator Rate (V)	0.78	0.78	1.05	1.45	0.78	0.78
Engine RPM (RPM)	2,400	2,400	3,200	3,200	1,200	800

Pre-Crash Data, -5 to 0 seconds (Unlinked, Page 1)

Time (sec)	-4.7	-3.7	-2.7	-1.7	-0.7	0 (TRG)
Vehicle Speed (MPH [km/h])	75.8 [122]	75.8 [122]	74.6 [120]	70.8 [114]	70.8 [114]	69.6 [112]
Brake Switch	ON	ON	ON	OFF	OFF	OFF
Accelerator Rate (V)	0.78	0.78	0.78	0.78	1.05	1.56
Engine RPM (RPM)	3,600	2,800	2,400	2,400	3,200	3,200

Delta V Data in Gen 2 models

- Longitudinal DV

  20 points @10ms intervals = 200ms duration starts at algorithm wake up - enough to get most crashes.
- Lateral DV (if equipped) for B pillar, C pillar and “Floor” (ACM) locations 25 points @4ms intervals – 100 ms duration starting 20ms before wakeup. Only use ACM (floor) location for recon.
- Roll Angle & Lateral Accel (if equipped).

  20 points @ 125 ms intervals beginning 625 ms before wake up

  Total duration 2.4 seconds
- Graph vs time, data table, and “Max” single value
- Same guidelines for use as GM/Ford

Other Useful Recon Data

- Front Pass Seat Belt Buckle status
- Passenger Weight Classification (Empty/Unoccupied, Child, AF05 (small adult), **AM 50 (midsize adult *or larger*).** (*Many others only have small adult or larger class*).
- Driver Seat Position (FW forward vs RW)
- Gearshift lever position (P-R-N-Drive)
- What safety devices deployed when, deploy time marked on Delta V graph.

Toyota Gen 2 Front Crash Report

BOSCH

CDR CRASH DATA RETRIEVAL SYSTEM

IMPORTANT NOTICE: Robert Bosch LLC and the manufacturers whose vehicles are accessible using the CDR System urge end users to use the latest production release of the Crash Data Retrieval system software when viewing, printing or exporting any retrieved data from within the CDR program. Using the latest version of the CDR software is the best way to ensure that retrieved data has been translated using the most current information provided by the manufacturers of the vehicles supported by this product.

CDR File Information

User Entered VIN	YOUR VIN HERE
User	NONE
Case Number	NONE
EDR Data Imaging Date	
Crash Date	
Filename	52690 POLICE 38.ROT.CDRX
Saved on	
Collected with CDR version	Crash Data Retrieval Tool 4.0
Reported with CDR version	Crash Data Retrieval Tool 4.0
EDR Device Type	airbag control module
Event(s) recovered	Front/Rear (2)

Events: Front/Rear vs Side vs Rollover - & how many

Comments

Data imported from: 52690 POLICE 38.ROT

Data Limitations

CDR Record Information:

- Due to limitations of the data recorded by the airbag ECU, such as the resolution, data range, sampling interval, time period of the recording, and the items recorded, the information provided by this data may not be sufficient to capture the entire crash
- Airbag ECU data should b
circumstances.
- If the airbags did not deplo called a Non-Deployment Event. D ecording threshold. If the airbag(s) deploy or the pretensioners are operated, it is called a Deployment Event. Deployment Event data cannot be overwritten or deleted by the airbag ECU following that event

P. 1 Same Look/Feel as others

Svstem Status at Retrieval

System Status at Time of Retrieval

ECU Part Number	89170-52690
ECU Generation	04EDR
Recording Status, All Pages	Complete
Freeze Signal	ON
Freeze Signal Factor	Front Airbag Deployment Front Pretenstioner Deployment
Diagnostic Codes Exist	No
Total number of Events	2
Time from Previous Pre Crash TRG (msec)	16381 or greater
Latest Pre-Crash Page	0
Contains Unlinked Pre-Crash Data	No

Event Record Summary at Retrieval

Events Recorded	TRG Count	Crash Type	Time (msec)	Pre-Crash & DTC Data Recording Status	Event & Crash Pulse Data Recording Status
Most Recent	2	Front/Rear Crash	0	Complete (Page 0)	Complete (Front/Rear Page 1)
1st Prior	1	Front/Rear Crash	-200	Complete (Page 0)	Complete (Front/Rear Page 0)

Back to back events

System Status at Event


System Status at Event (Most Recent, TRG 2)

Recording Status, Front/Rear Crash Info.	Complete
Event Type	Front/Rear Crash
TRG Count (times)	2
Previous Crash Type	Frontal/Rear
Time from Pre-Crash TRG (msec)	200
Linked Pre-Crash Page	0
Time to Deployment Command, Front Airbag, Driver (msec)	12
Time to Deployment Command, Front Airbag, Passenger (msec)	12
Event Severity Status, Driver	Level 3
Event Severity Status, Passenger	N/A
Time to Deployment Command, Pretensioner (msec)	12

Delta V Data Graph

Longitudinal Crash Pulse (Most Recent, TRG 2 - table 1 of 2)

Recording Status, Time Series Data	Complete
Max Longitudinal Delta-V (MPH[km/h])	-22.8 [-36.7]



Delta V Data Table

Longitudinal Crash Pulse (Most Recent, TRG 2

Time (msec)	Longitudinal Delta-V (MPH [km/h])
10	-1.7 [-2.7]
20	-3.6 [-5.8]
30	-5.7 [-9.2]
40	-8.2 [-13.2]
50	-11.1 [-17.9]
60	-13.9 [-22.4]
70	-17.0 [-27.4]
80	-20.1 [-32.3]
90	-21.9 [-35.2]
100	-22.6 [-36.4]
110	-22.8 [-36.7]
120	-22.5 [-36.2]
130	-21.3 [-34.3]
140	-19.0 [-30.6]
150	-16.6 [-26.7]
160	-15.1 [-24.3]
170	-14.6 [-23.5]
180	-14.9 [-24.0]
190	-15.6 [-25.1]
200	-15.9 [-25.6]

20 Data Points at 10ms intervals – start at wake-up

Pre Crash Data - Overview

DTCs Present at Time of Event (Most Recent, TRG 2)

Recording Status, Diagnostic	Complete
Ignition Cycle Since DTC was Set (times)	0
Airbag Warning Lamp ON Time Since DTC was Set (min)	0
Diagnostic Trouble Codes	None

Pre-Crash Data, 1 Sample (Most Recent, TRG 2)

Recording Status, Pre-Crash/Occupant	Complete
Time from Pre-Crash to TRG (msec)	200
Buckle Switch, Driver	Unbuckled
Buckle Switch, Passenger	Unbuckled
Occupancy Status, Passenger	Not Occupied
Seat Position, Driver	Rearward
Shift Position	Drive

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

Pre Crash Data Timing

Other Points a regular 1 sec intervals

6th point Sampled at TRG

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

Caution: Sampling at TRG could have un-refreshed data in buffer

New Pre Crash data will only be recorded if 500ms have passed since the last event.

Pre Crash Data - Overview

DTCs Present at Time of Event (Most Recent, TRG 2)

Recording Status, Diagnostic	Complete
Ignition Cycle Since DTC was Set (times)	0
Airbag Warning Lamp ON Time Since DTC was Set (min)	0
Diagnostic Trouble Codes	None


Pre-Crash Data, 1 Sample (Most Recent, TRG 2)

Recording Status, Pre-Crash/Occupant	Complete
Time from Pre-Crash to TRG (msec)	200
Buckle Switch, Driver	Unbuckled
Buckle Switch, Passenger	Unbuckled
Occupancy Status, Passenger	Not Occupied
Seat Position, Driver	Rearward
Shift Position	Drive

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

Toyota speed data transfer[34]



Pre Crash Data Timing

Other Points a 1 sec intervals

6th point Sampled at TRG

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

Caution: Sampling at TRG could have un-refreshed data in buffer

New Pre Crash data will only be recorded if 500ms have passed since the last event.

Pre Crash Speed Data

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

- Since the speed data buffer is only refreshed every 0.5 sec, the 0 and -0.2 data points may be from the same buffer value. If the time between TRG and the prior point is less than 0.5 sec and the values are identical, especially during precrash braking, do not assume the vehicle has stopped slowing down.
- Resolution 2km/hr (1.2 mph)
- Max Value 75 mph (121kph) on Gen 2 (04/06), (78.3mph in Gen 1 00/02 models)

Pre Crash Accel Pedal Data

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

- Only refreshed every 512 ms – held in buffer
- Volts not pedal percent
- Convert to % = (V-0.78)/(3.79-0.78)
- Data Limitations warns min & max may vary

Pre Crash RPM Data

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.2	-3.2	-2.2	-1.2	-0.2	0 (TRG)
Vehicle Speed (MPH [km/h])	12.4 [20]	8.7 [14]	5 [8]	2.5 [4]	1.2 [2]	1.2 [2]
Brake Switch	ON	ON	ON	ON	ON	ON
Accelerator Rate (V)	0.78	0.78	0.78	0.78	0.78	0.78
Engine RPM (RPM)	800	800	800	400	800	800

- Resolution to next lower 400 rpm
- If speed is reported at max 75 mph, can be used to calculate a higher min speed based on gear ratios.
- Speed in mph = RPM/trans ratio/final drive ratio/tire revs /mile*60

- Next Event

System Status at Event (1st Prior, TRG 1)

Recording Status, Front/Rear Crash Info.	Complete
Event Type	Front/Rear Crash
TRG Count (times)	1
Previous Crash Type	No Event
Time from Pre-Crash TRG (msec)	0
Linked Pre-Crash Page	0
Time to Deployment Command, Front Airbag, Driver (msec)	Not Commanded
Time to Deployment Command, Front Airbag, Passenger (msec)	Not Commanded
Event Severity Status, Driver	N/A
Event Severity Status, Passenger	N/A
Time to Deployment Command, Pretensioner (msec)	Not Commanded

RTFDL Caution

- In the 00 EDR, seat belt status in ND events is the status at time of READOUT, not the time of EVENT.
- This is duly noted in the data limitations, but has tripped some people up. A module was read in car that said unbelted, then re-read on the benchtop that gave the default value of belted.

- For Non-Deployment Event, "Buckle Switch", "Ignition Cycle Since DTC was Set" and "Airbag Warning Lamp ON Time Since DTC was Set" is the ACM parameter data at the time of retrieval, not the parameter data when the recording trigger was established. For Deployment Event, it is the information when the airbag deployment.

Toyota Gen 2 Side Crash Report

BOSCH

CDR CRASH DATA RETRIEVAL SYSTEM

IMPORTANT NOTICE: Robert Bosch LLC and the manufacturers whose vehicles are accessible using the CDR System urge end users to use the latest production release of the Crash Data Retrieval system software when viewing, printing or exporting any retrieved data from within the CDR program. Using the latest version of the CDR software is the best way to ensure that retrieved data has been translated using the most current information provided by the manufacturers of the vehicles supported by this product.

CDR File Information

User Entered VIN	4T1BF3EK4BU664098
User	Richard R. Ruth, P.E.
Case Number	Gazdick salvage yard find
EDR Data Imaging Date	06/01/2011
Crash Date	
Filename	4T1BF3EK4BU664098_ACM_GAZDICK_BODY_SHOP.CDRX
Saved on	Wednesday, June 1 2011 at 21:52:48
Collected with CDR version	Crash Data Retrieval Tool 4.0
Reported with CDR version	Crash Data Retrieval Tool 4.0
EDR Device Type	airbag control module
Event(s) recovered	Front/Rear (1), Side (1)

Comments

imaged direct to module with cable 614 and 387 adaptor

Data Limitations

CDR Record Information:

- Due to limitations of the data recorded by the airbag ECU, such as the resolution, data range, sampling interval, time period of the recording, and the items recorded, the information provided by this data may not be sufficient to capture the entire crash.
- Airbag ECU data should be used in conjunction with other physical evidence obtained from the vehicle and the surrounding circumstances.
- If the airbags did not deploy or the pretensioners did not operate during an event that meets a specified recording threshold, it is called a Non-Deployment Event. Data from a Non-Deployment Event can be overwritten by a succeeding event that meets the specified recording threshold. If the airbag(s) deploy or the pretensioners are operated, it is called a Deployment Event. Deployment Event data cannot be overwritten or deleted by the airbag ECU following that event

Events: Front/Rear vs Side vs Rollover - & how many

System Status **at Side Event**

System Status at Event (Most Recent, TRG 2)


Recording Status, Side Crash Info.	Complete
Event Type	Side Crash
TRG Count (times)	2
Recorded Side	Passenger's Side
Previous Crash type	Frontal/Rear
Time from Pre-Crash TRG (msec)	24
Linked Pre-Crash Page	0
Time to Deployment Command, Row 1 (msec)	Not Commanded
Time to Deployment Command, Row 2 (msec)	Not Commanded

- Side contacted is NOT determined by sign. Side that woke up algorithm is recorded. This alone gives you direction of impact.

Gen 1&2: Lateral Delta V Graph of ECU

Lateral Crash Pulse (Most Recent, TRG 2 - table 1 of 2)

Recording Status, Time Series Data	Complete
Time from TRG to Next Sample (msec)	3
Max Lateral Delta-V, Floor (MPH[km/h])	-0.9 [-1.4]
Max Lateral Delta-V, B-Pillar Sensor (MPH[km/h])	1.5 [2.4]
Max Lateral Delta-V, C-Pillar Sensor (MPH[km/h])	2.7 [4.3]



Gen 1&2: Use ECU Side Data Only

Lateral Crash Pulse (Most Recent, TRG 2 - table 2 of 2)

Time (msec)	Lateral Delta-V, Airbag ECU Sensor (MPH [km/h])	Lateral Delta-V, B-Pillar Sensor	Lateral Delta-V, C-Pillar Sensor
-21	0.0 [0.0]		
-17	0.2 [0.3]		
-13	0.3 [0.5]		
-9	0.3 [0.5]		
-5	0.2 [0.3]		
-1	0.2 [0.3]		
3	-0.1 [-0.2]		
7	-0.3 [-0.5]		
11	-0.3 [-0.5]		
15	-0.4 [-0.6]		
19	-0.7 [-1.1]		
23	-0.7 [-1.1]		
27	-0.8 [-1.3]		
31	-0.9 [-1.4]		
35	-0.9 [-1.4]		
39	-0.9 [-1.4]		
43	-0.9 [-1.4]		
47	-0.7 [-1.1]		
51	-0.5 [-0.8]	1.5 [2.4]	.6 [4.2]
55	-0.4 [-0.6]	1.5 [2.4]	2.7 [4.3]
59	-0.3 [-0.5]	1.5 [2.4]	2.7 [4.3]
63	-0.4 [-0.6]	1.4 [2.3]	2.7 [4.3]
67	-0.4 [-0.6]	1.4 [2.3]	2.7 [4.3]
71	-0.5 [-0.8]	1.5 [2.4]	2.7 [4.3]

Pre Crash Data Page Gen 1& 2 (looks same for side and frontal)

DTCs Present at Time of Event (Most Recent, TRG 2)

Recording Status, Diagnostic	Complete
Ignition Cycle Since DTC was Set (times)	0
Airbag Warning Lamp ON Time Since DTC was Set (min)	0
Diagnostic Trouble Codes	None

Pre-Crash Data, 1 Sample (Most Recent, TRG 2)

Recording Status, Pre-Crash/Occupant	Complete
Time from Pre-Crash to TRG (msec)	700
Buckle Switch, Driver	Buckled
Buckle Switch, Passenger	Unbuckled
Occupancy Status, Passenger	Not Occupied
Seat Position, Driver	Rearward
Shift Position	Drive

Pre-Crash Data, -5 to 0 seconds (Most Recent, TRG 2)

Time (sec)	-4.7	-3.7	-2.7	-1.7	-0.7	0 (TRG)
Vehicle Speed (MPH [km/h])	46 [74]	47.2 [76]	47.2 [76]	47.2 [76]	42.3 [68]	24.9 [40]
Brake Switch	OFF	OFF	OFF	OFF	ON	ON
Accelerator Rate (V)	1.25	1.09	0.98	0.98	0.78	0.78
Engine RPM (RPM)	1,600	1,200	1,200	1,200	800	800

Speed at Impact Worksheet GEN 1 & 2

TWO changes from 42 to 24?

PRE-CRASH DATA						
Time	-4.7	-3.7	-2.7	-1.7	-0.7	0
Speed	46 (74)	47.2 (76)	47.2 (76)	47.2 (76)	42.3 (68)	24.9 (40)
Brake	Off	Off	Off	Off	On	On
Time Range	-5.2 to -4.7	-4.2 to -3.7	-3.2 to -2.7	-2.2 to -1.7	-1.2 to -0.7	0.2 to 0.0

SPEED AT IMPACT WORKSHEET		English		Metric	
		MIN	MAX	MIN	MAX
Last Good Data Point mph (km/h)		24.9	24.9	40	40
Braking	-0.2 sec* 15 mph/sec	-3.0	0	-4.8	0
Slip +5%		1.2	1.2	2	2
Speedo +/-4%		-1	1	-1.6	1.6
Range		22.1	27.1	35.6	43.6

Age of TRG data sample Gen 1 & 2

Time Last Point to TRG	Changed twice	Changed once	Didn't change
0	n/a	0	0.5
0.1	n/a	0.1	0.5
0.2	n/a	0.2	0.5
0.3	n/a	0.3	0.5
0.4	n/a	0.4	0.5
0.5	0	0.5	n/a
0.6	0.1	0.5	n/a
0.7	0.2	0.5	n/a
0.8	0.3	0.5	n/a
0.9	0.4	0.5	n/a

- Data at TRG can be 0.5 sec old, but may be LESS than 0.5 sec if data has changed ONCE from prior sample within 0.5 sec (9 mph or less)
- Data at TRG can ALSO be LESS than 0.5 sec if data has changed TWICE from prior sample (10 mph or more)
- .
- Version 2.01 of the speed at impact worksheet excel program does this for you

Gen 3 -Part 563 Intent Toyota”12EDR”


- Phase in mid 2012 MY
- Adds key cycles, deploy times, longer ΔV (250ms), more pre-crash 5 sec @ 0.5 sec intervals, speed to 124 mph (200 KPH), Accel %.
- Lat ΔV only recorded in side events (Unique to Toyota) and ONLY FROM SIDE SATELLITES, not ACM
- Recording threshold 5mph ΔV min.
- Adds Throttle %, Steering, Yaw Rate, Brake Pressure, VSC Long Accel, Cruise, Gear, RPM @ 100 rpm resolution.


Gen 3 “12 EDR”

- Speed data updated more frequently now - every 20 to 24 ms – (64 ms on accel pedal)
- Toyota continues to sample data point at TRG
- Brake **pressure** data element added in MPa
- Accel pedal data comeS in % vs. volts
- Analyze the same as any other 563 intent module, except recognize that last data point is for all practical purposes at TRG now.

12 EDR "Pages"

00/02EDR (GEN 1)	04/06EDR (GEN 2) and **12EDR (GEN 3)**
▪Frontal Crash: **3** pages ▪Side and Rollover: 1page (no Pre-Crash)	▪Pre-Crash : **2** pages ▪Frontal Side Rollover :2 pages each





Reproduced with Permission from Toyota

Pre-Crash Parameter Comparison

Parameter	04/06 EDR		12 EDR	
Vehicle Speed (Part 563)	2 km/h /LSB	0~122 [km/h]	1 km/h /LSB	0 ~ 200 [km/h]
Accelerator Pedal (Part 563)	.039 V/LSB	0~5 [V]	0.5 %/LSB	0 ~ 100 [%]
Engine RPM (Part 563)	400 RPM/LSB	0~5200 [RPM]	100 RPM/LSB	0 ~ 12800 [RPM]
Service Brake (Part 563)	ON/OFF		ON/OFF	
Shift Position	R / N/ P / D		R / N / P / D / 5 / 4/ 3 / 2/ LO/ B/ Seq	
Percentage of Engine Throttle			0.5%/LSB	0 ~ 100 [%]
Motor RPM (Part 563)			100 RPM/LSB	-7500 ~ 17500 [RPM]
Brake Oil Pressure			0.048 MPa	0 ~ 12.144 [MPa]
Sequential Shift			1 / 2 / 3 /4 / 5 / 6 / 7 / 8	
Steering Input (Part 563)			3 deg/LSB	-375 ~ 375 [deg]
VSC Yaw Rate			0.488 deg/s/LSB	-61 ~ 61 [deg/s]
VSC Longitudinal Acceleration			0.07178 m/s^2/LSB	-8.9725~8.9725 [m/s^2]
Cruise Control Status			ON/OFF	
Drive Mode - Power Drive Mode – Eco Drive Mode - Sport Drive Mode - Snow Drive Mode - EV			ON/OFF	

Reproduced with Permission from Toyota

Gen 3 Longitudinal Stability Control Accel Data

- Units are in m/sec^2, divide by 9.8 to get G's (dividing by 10 gets you close)
- Data is like a Vericom, similar to Ford stability control system data, just not as frequent.
- It is not yet clear if the accel data is instantaneous or average over the interval, but if multiple consecutive data points are available averaging is recommended

Getting PDOF from 12 EDR

- 12 EDR records side Delta V ONLY if side algorithm wakes up, and ONLY from side satellites
- In Gen 1&2, we told you to IGNORE B and C pillar data and use ACM data only.
- With NO DATA from ACM recorded, your only choice is to use B pillar data (closest sensor to CG)
- Take side Delta V at end of trace (typically 70ms) and take arc tangent of Y over X at same time (70ms)

New “13 EDR” & “15 EDR”

- 13 EDR Adds lateral Accel data from ACM (“floor sensor”) in ***front/rear* events** (Fixes biggest drawback to 12 EDR), and lateral accel from ACM in ***side* events**.
- Lateral acceleration data table is in meters/sec^2, calculate Delta V from it yourself. For each point, take **(accel/9.81)*(32.2/1.466)*time interval**, and add them to get the cumulative value in **mph**.
- Metric, take accel*3.6*time interval, add them to get the cumulative value in kph.
- See **TEMPLATE** in student materials to do this math for you calculates both Delta V and PDOF.
- Remember side event recording duration recording is LESS than frontal direction –plot side vs front data to see if you got the WHOLE crash.
- 15 EDR adds side impact door pressure sensor models


13 EDR Long DV & Lat Accel

Longitudinal/Lateral Crash Pulse (3rd Prior Event, TRG 1 - table 2 of 2)

Time (msec)	Longitudinal Delta-V (MPH [km/h])	Lateral Acceleration for Frontal/Rear Crash, Floor Sensor (m/sec^2)	Power Supply Status
0	0.0 [0.0]	0.0	ON
10	-1.1 [-1.7]	4.6	ON
20	-2.0 [-3.3]	7.7	ON
30	-6.6 [-10.6]	41.4	ON
40	-7.8 [-12.5]	96.5	ON
50	-8.6 [-13.8]	19.9	ON
60	-9.1 [-14.7]	-79.7	ON
70	-9.8 [-15.8]	18.4	ON
80	-11.3 [-18.1]	-16.9	ON
90	-12.8 [-20.6]	64.4	ON
100	-13.8 [-22.2]	23.0	ON
110	-15.5 [-25.0]	30.6	ON
120	-17.6 [-28.3]	-49.0	ON
130	-19.8 [-31.8]	13.8	ON
140	-22.7 [-36.5]	24.5	ON
150	-22.3 [-35.9]	-76.6	ON
160	-23.3 [-37.5]	52.1	ON
170	-24.0 [-38.6]	6.1	ON
180	-24.7 [-39.8]	-13.8	ON
190	-25.6 [-41.2]	-12.3	ON
200	-26.1 [-42.1]	9.2	ON
210	-27.0 [-43.5]	29.1	ON
220	-27.5 [-44.2]	26.0	ON
230	-27.7 [-44.6]	19.9	ON
240	-27.9 [-44.9]	7.7	ON
250	-28.1 [-45.2]	4.6	ON

Integrate to get DV


13 EDR lat accel graph from 28 mph (big) longitudinal event



Deployment Time Marker Key

1	Driver Airbag Deployment Time
2	Passenger Airbag Deployment Time
3	Driver/Passenger Pretensioner
4	Driver 2nd Stage Airbag Deployment Time
5	Passenger 2nd Stage Airbag Deployment
6	Driver/Passenger AHR
7	Driver CSA
8	Passenger CSA
9	Rear Window Airbag Deployment Time

Toyota 15 EDR
side impact door PRESSURE sensors



New “17 EDR”

- “Front/Rear” events also triggered by 5mph Y DV or side deployment
- Y Delta V from ACM added to frontal events
- More precrash registers (6 vs 2 prior)
- More front/rear & side registers (4 vs 2)
- Separate side events still reported, but do NOT have precrash associated with them. Side events have detail of side satellite sensors (generally not used by Recons).
- Odometer data element added

New Look to Precrash Data (same stuff)

Pre-Crash Data -5 to 0 Seconds (1st Prior Event, TRG 2) - Table 1 of 4

Time (sec)	Vehicle Speed (MPH [km/h])	Accelerator Pedal, % Full (%)	Percentage of Engine Throttle (%)	Fuel Injection Quantity (mm^3/st)	Engine RPM (RPM)	Motor RPM (RPM)	Service Brake, ON/OFF
-5.00	29.8 [48]	49.5	24.5	Invalid	2,400	Invalid	OFF
-4.50	32.3 [52]	47.0	24.5	Invalid	2,500	Invalid	OFF
-4.00	34.2 [55]	38.0	20.0	Invalid	2,700	Invalid	OFF
-3.50	35.4 [57]	32.5	16.0	Invalid	2,800	Invalid	OFF
-3.00	36.7 [59]	26.5	13.5	Invalid	2,400	Invalid	OFF
-2.50	37.3 [60]	22.5	11.0	Invalid	2,400	Invalid	OFF
-2.00	37.3 [60]	19.0	8.5	Invalid	2,200	Invalid	OFF
-1.50	38.5 [62]	19.0	6.0	Invalid	1,900	Invalid	OFF
-1.00	37.9 [61]	18.0	5.5	Invalid	1,900	Invalid	OFF
-0.50	37.9 [61]	18.0	5.0	Invalid	1,800	Invalid	OFF
TRG(0)	36.0 [58]	100.0	26.0	Invalid	1,700	Invalid	OFF

Pre-Crash Data -5 to 0 Seconds (1st Prior Event, TRG 2) - Table 2 of 4

Time (sec)	ABS Control Status	BOS Control Status	Brake Oil Pressure (Mpa)	Longitudinal Acceleration , VSC Sensor (m/s^2)	Yaw Rate (deg/s)	Steering Input (degrees)	Shift Position
-5.00	OFF	OFF	0.00	1.579	-0.98	-4.5	D
-4.50	OFF	OFF	0.00	1.795	0.00	-1.5	D
-4.00	OFF	OFF	0.00	1.292	0.49	0.0	D
-3.50	OFF	OFF	0.00	0.861	0.00	-1.5	D
-3.00	OFF	OFF	0.00	0.718	0.00	-1.5	D
-2.50	OFF	OFF	0.00	-0.072	0.00	-1.5	D
-2.00	OFF	OFF	0.00	0.000	0.00	-1.5	D
-1.50	OFF	OFF	0.00	0.000	-0.49	-1.5	D
-1.00	OFF	OFF	0.00	0.287	0.00	-1.5	D
-0.50	OFF	OFF	0.00	-0.144	0.00	-1.5	D
TRG(0)	OFF	OFF	0.48	-1.507	61.00	-19.5	D

Pre-Crash Data -5 to 0 Seconds (1st Prior Event, TRG 2) - Table 3 of 4

Time (sec)	Sequential Shift Range	Cruise Control Status	VSC Control Status	READY Signal	Drive Mode, Power Train	Drive Mode, Snow	Drive Mode, EV
-5.00	Undetermined	OFF	ON (enable)	Invalid	Normal	OFF	Invalid

Pedestrian Protection Module EDR

System Status at Pedestrian Event (1st Prior Event, TRG 1)

TRG Count (times)	1
TRG Count not for Pedestrian (times)	SNA
Ignition Cycle, Crash (times)	353
Odometer signal (miles [km])	1,195 [1,923]
Trip count (times)	392
Time count (msec)	1,283,900
Time count input system	Normal
Airbag Warning Lamp, On/Off	OFF
Pedestrian Warning Lamp, On/Off	OFF
Time from Previous TRG (msec)	32767 or greater
Time from Pre-Crash to TRG (msec)	300
Time between TRG not for Pedestrian and TRG for Pedestrian (msec)	SNA
TRG Establishment not for Pedestrian, within 5 sec.	ON
Freeze Signal	ON
Recording Status, Pre-Crash	Complete
Recording Status, Crash Info.	Complete
Recording Status, EDR Correlation Info.	Complete

Deployment Command Data (1st Prior Event, TRG 1)

Front Pop-Up Hood, Time to Deploy (msec)	3.0
Rear Pop-Up Hood, Time to Deploy (msec)	3.0
Airbag for Pedestrian Deployment, Time to Deploy (msec)	SNA


DTCs Present at Time of Event (1st Prior Event, TRG 1)

Recording Status, Diagnostic	Complete
Ignition Cycle Since DTC was Set (times)	0
Warning ON Time Since DTC was Set, for Pedestrian (min)	0
Diagnostic Trouble Codes	None

Pedestrian Event Crash Pulse (1st Prior Event, TRG 1)

Recording Status, Time Series Data	Complete
Time from TRG to Next Sample (msec)	1

Data from L/R bumper pressure sensors




Pedestrian Event Crash Pulse (1st Prior Event, TRG 1)

Time (msec)	Rate of change of pressure, L (%)	Rate of change of pressure, R (%)	Calculated Value of Vehicle Speed (MPH [km/h])
-23	0.000	0.000	27.3 [44]
-19	0.000	0.000	27.3 [44]
-15	0.000	0.000	27.3 [44]
-11	0.000	0.000	27.3 [44]
-7	0.000	0.000	27.3 [44]
-3	0.000	0.000	27.3 [44]
1	-0.125	9.750	27.3 [44]
5	12.625	23.000	27.3 [44]
9	11.375	21.375	27.3 [44]
13	3.875	12.250	27.3 [44]
17	9.000	-1.500	27.3 [44]


New Freeze Frame Data

- New feature in 2013+ Rav 4 and 2014+ Highlander & Lexus IS, 2015+ Lexus NX & RC, “Vehicle Control History”
- Triggers EDR-style recording if accel pedal is rapidly depressed or other conditions that might occur during an alleged sudden or unintended acceleration or lane excursion
- Accessible only with Toyota Techstream service tool – not part of Bosch CDR system
- Data exports as CSV to Microsoft excel
- Space in memory for MANY events – can show a history of erratic driver behavior
- Access this whenever EDR data is either not available or insufficient for your investigation


Getting to Vehicle Control History Using Techstream Tool




Using Techstream to Access VCH data



VCH List of Recorded Events




Highlight Entry To Get Detail



Key Cycle	Elapsed Time	Clock Type	Time and Date	Trigger	ODO (km)	Number of Overwrite of the Recording Area
00334	00000:27:22.0	IG	-	Accelerator pedal opening angle signal is high during cruise control operation	6010	1
00349	00000:00:57.2	IG	-	Accelerator pedal opening angle is medium or higher immediately after shifting to R	6732	1
00353	00000:22:34.4	IG	-	Accelerator pedal opening angle is medium or higher immediately after shifting to forward position	6793	1
00354	00000:06:23.5	IG	-	Accelerator pedal opening angle signal is high immediately after brake pedal is released	6796	1
00354	00000:06:52.7	IG	-	Accelerator pedal opening angle signal is high immediately after brake pedal is released	6796	1
00369	00000:01:05.2	IG	-	Accelerator pedal opening angle is medium or higher immediately after shifting to R	7263	1
00376	00000:00:06.5	IG	-	Accelerator pedal opening angle is medium or higher immediately after shifting to forward position	7423	1
00382	00000:00:20.4	IG	-	Accelerator high position in mid to high speed	7553	2
00410	00000:05:49.5	IG	-	Accelerator high position in mid to high speed	8267	2
00439	00000:00:16.0	IG	-	ABS operation history	8819	31
00439	00000:02:27.2	IG	-	TRC operation history	8821	31
00439	00000:02:40.2	IG	-	ABS operation history	8821	32
00440	00000:06:42.5	IG	-	Accelerator pedal opening angle is medium or higher immediately after shifting to R	8825	1
00443	00000:00:49.8	IG	-	TRC operation history	8829	32
00443	00000:06:11.0	IG	-	ABS operation history	8832	32
00444	00000:12:01.1	IG	-	Accelerator pedal opening angle signal is high immediately after brake pedal is released	8836	1

Detailed VCH Data Per Event



Toyota EDR Accuracy

- Toyota stated up front that its first prototype readout tool was not validated –but that didn't mean it wasn't right.
- Because early Toyota EDR's (like many other manufacturers) that lost power at impact may not make a new recording at impact, there were examples of when the Toyota EDR's did not match the accident facts.
- Some claimed the Toyota EDR was unreliable - based on a lack of understanding of the not-yet-written data limitations.

Specific Toyota Validation

- Niehoff 2005: 3 barrier crashes: Delta V ranged -6.7% to +1.1%, only vehicle with speed data was -0.9% of reference instrument.
- Gabler 2008: 11 frontal/4 side barrier crashes: Delta V data ranged from -22% to +11%, avg -1.6%. Only one vehicle had speed data, it reported 35 mph in a 33.8 mph test or 3% high. Belt status was reported correctly in all 15 tests
- NHTSA 2011: 14 staged events, “No errors in measurement and storage or pre crash data” (within known accuracy and timing limitations). Vehicle speed within 1.5 mph, throttle voltage within 2.5%.

Additional Toyota Validation


- Ishikawa & Takubo 2009: 14 J-NCAP crashes EDR Delta V is from -14% to +0.5% of reference instrumentation, averaging -7.3%. Speed data within 4%, avg. 2%
- Ruth 2012: SAE 2012-01-0999 -Speed data within 3%
- Brown 2012: SAE 2012-01-0996 & 0998 (Actual speed -2.7%)
- Wilkinson 2013: SAE 2013-01-1268 (Gen 1 Delta V 1mph low in low speed frontal collisions, 1mph high in rear collisions)
- Webster 2014: SAE 2014-01-0505 **Accuracy of Recorded Driver Inputs in Toyota Part 563 EDR** (Only addressed accuracy of brake and accelerator pedal position).
- A new paper in peer review for 2016 suggests Gen 2 ACM Delta V may be under reported slightly in frontal collisions, and over reported slightly in rear collisions, similar Wilkinson's results on Gen 1's above.

CONCLUSION

When the recording is from the event of interest, and data limitations are understood, there is no reason to believe speed data is any less accurate than any other manufacturer's EDR based on 42 test events. Delta V may under report slightly in Gen 1 and Gen 2 ACM's in frontal collisions and over reported in rear collisions, but in barrier tests are still within the generally accepted +/-10%. Other than the 00 EDR seat belt reporting at time of readout and not event noted in the data limitations, there are no known issues with other data elements at this time.

Toyota Speed Data Accuracy Validated

SAE 2012-01-0999 2010/11 Camry



The Accuracy and Sensitivity of 2005 to 2008 Toyota Corolla Event Data Recorders in Low-Speed Collisions
SAE 2013-01-1268

- Induced a series of low speed events on vehicles and on a sled
- Verified 2G wakeup threshold thru testing
- Determined “offset” in Toyota accelerometers causing them to read 1.3 to 2.6 km/h low in frontal collisions and 0.6 to 2.2 km/h high in rear collisions.

Toyota EDR Summary

- Toyota began installing EDR's in 2001MY; many Gen 1 and some Gen 2 have Delta V data only, others have DV and precrash data. Gen 1 & 2 data is similar to GM but has added precrash data point sampled at TRG.
- Unique Gen 1 &2 issues (75/78 mph max speed, accel pedal in volts, & last data point up to 0.5 seconds old) require special attention.
- Toyota EDR data is as ***reliable*** as other manufacturers within the data limitations.
- Newer "12EDR" even better plus many additional data elements helpful to crash recon. "13EDR" better yet!
- New Vehicle Control History gives driving habits
- Newest 17 EDR has even better data